

3M™ Super Weatherstrip and Gasket Adhesive

Data Sheet

3M Part No.(s) **3M Part Descriptor (s)**
 08001 Super Weatherstrip and Gasket Adhesive

Detailed Product Description

3M™ Super Weatherstrip and Gasket Adhesive is a strong, flexible, rubbery adhesive that can withstand vibration and extreme temperature variations. It can be used to bond weatherstripping to car doors, trunks, T-tops, and sun roofs. It is an excellent adhesive for holding paper, cork, or rubber gaskets in place during installation. It provides the strength and rapid setting needed to hold weatherstripping, vinyl headliners, and side panels in place. If the weatherstripping is EPDM rubber 3M™ Super Weatherstrip, P.N. 08011 should be used.

Features, Advantages, Benefits

Features	High Strength Remains Flexible Adhesion To Many Substrates Easy to brush and spread Waterproof Resists oil, grease, and solvents
Advantages	Holds weatherstrip tightly to substrate One adhesive to bond a variety of materials Easy for technician to apply Not degraded by contact with most other chemicals
Benefits	Saves time in installation Highest quality job for customer satisfaction Save money by not needing to stock as many varieties of adhesive

Typical Physical Properties

Container	5 oz. Squeeze Tube	Packaged 1 tube to a box, 6 boxes to a case
Base	See package label	
Density lbs/Gallon (Appx.)	7.6	
Color	Yellow	
Flash Point - °F	-14	
Viscosity (CPS) Brookfield Viscometer	4,500 CPS	
Solids Content (Appx.)	39.0%	
Consistency	Heavy Liquid	
Service Temperature - °F	-20 to + 300°F	

Product Uses

For bonding weatherstripping to doors, trunks, T-tops, sun roofs and other areas of vehicles. It is an excellent adhesive for holding paper, cork, or rubber gaskets in place during installation. It provides the strength and rapid setting needed to hold weatherstripping, vinyl headliners, and side panels in place.

Performance Properties

Peel Adhesion

Peel adhesion tests were run using cloth to clear coat/base coat paint. Bonds were pulled at a rate of 2 inches per minute.

Tested @ 75°F	35.0 pounds per inch width (PIW)
Tested @ 120°F	32.5 PIW
Tested @ 160°F	22.0 PIW
Tested @ 180°F	16.0 PIW
Tested @ 200°F	18.0 PIW

Directions for Use

Thoroughly clean surfaces to be bonded. Wiping with 3M™ General Purpose Adhesive Cleaner, P.N. 08984, or 3M™ Gasket Prep and Parts Cleaner, P.N. 08901, will aid in removing oil and dirt from the surfaces to be bonded. Apply a thin uniform coat of adhesive on each surface. Allow adhesive to dry until tacky but will not transfer to your knuckle when touched. Assemble materials with sufficient pressure to ensure complete contact. Full cure may take as long as 24 hours at 70°F.

Applications

Weatherstripping and Gasketing Adhesive.
Cloth and supported vinyl bonding.
General rubber bonding.
Good adhesion to wood, metals, painted surfaces and some plastics.

Storage and Handling

Store at room temperature. Rotate stock on a "first-in-first-out" basis. When stored at the recommended conditions in original, unopened containers, this product has a shelf life of 24 months.

Precautionary Information

Refer to Product Label and Material Safety Data Sheet for Health and Safety Information before using this product .
NOTICE: This adhesive contains solvents that outgas while curing. These solvents may soften some paints or coatings and cause failure of the paint bond or coating bond. Test compatibility in an inconspicuous spot prior to use.

This product should not be put into a service application prior to achieving its full cure. Full cure may take as long as 24 hours at 70°F.

VOC REGULATED MATERIAL: Please consult State and Local Regulations. C.A.R.B. Category: Contact Adhesive - Special Purpose. See package label for VOC content.

Warranty and Limited Remedy

Technical Information : The technical information, recommendations and other statements contained in this document are based upon tests or experience that 3M believes are reliable, but the accuracy or completeness of such information is not guaranteed.

Product Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application.

Warranty, Limited Remedy, and Disclaimer : Unless an additional warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability : Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

For Additional Health and Safety Information

3M Automotive Aftermarket Division
3M Center, Building 223-6N-01
Saint Paul, MN 55144-1000
1-877-666-2277 (1-877-MMM-CARS)

This is the last page

<< End of Document >>