



Product Change Notice: 3M™ Round, Shielded/Jacketed, Discrete Wire, 28 AWG Stranded, Twisted Pair, PO/PVC, Series 3647B

Issue Number: 605
Date: July 15, 2005

To: 3M Electronic Solutions Division Global Copy List
3M Electronic Solutions Division Distribution List
3M Electronic Solutions Manufacturing Rep Firm List
Mara Guzman, 3M EMD

Product Change

Reference TS-0582 for available conductor counts and options.

Enhancement

3M is pleased to announce the 3M Round, Shielded/Jacketed Discrete Wire Series 3647B is now RoHS compliant*.

3M's intent is to offer products that allow our customers to be in compliance with European Union directive 2002/95/EC (Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment). 3M's determination of compliance is based on the current RoHS legislation and certification from 3M raw material suppliers. This change does not affect the form, fit or function of the cable, therefore product numbers and stock numbers will remain unchanged. The description, as well as the factory run number, will be updated to include "RC" for RoHS compliant.

The 3M Round, Shielded/Jacketed Discrete Wire, Series 3647B is available in standard lengths of 300 feet.

No new literature will be issued at this time. Please use the latest revision of TS-0582, which contains the notation.

**"RoHS compliant" means that the product or part does not contain any of the following substances in excess of the following maximum concentration values in any homogeneous material, unless the substance is in an application that is exempt under RoHS: (a) 0.1% (by weight) for lead, mercury, hexavalent chromium, polybrominated biphenyls or polybrominated diphenyl ethers; or (b) 0.01% (by weight) for cadmium. Unless otherwise stated by 3M in writing, this information represents 3M's knowledge and belief based on information provided by third party suppliers to 3M.*

Actions Required

- Please notify customers of this enhancement.

Thank you for your continued support of 3M products.

Please direct all correspondence on this matter to:

*Jeff Bullion
Copper Product Marketing
Phone: 512-984-5982
Email: jbullion@mmm.com*

3M is a trademark of 3M Company.

Important Notice

All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in 3M's current publications, or any contrary statements contained on your purchase order shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.

Warranty; Limited Remedy; Limited Liability.

This product will be free from defects in material and manufacture for a period of one year from the time of purchase. **3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. **Except where prohibited by law, 3M will not be liable for any indirect, special, incidental or consequential loss or damage arising from this 3M product, regardless of the legal theory asserted.**



Electronic Solutions Division
6801 River Place Blvd.
Austin, TX 78726-9000
www.3M.com/interconnects