



# Screen Printable Extended Life Vinyl Performance Label Products

## 7048 • 7051

Technical Data

August, 2010

**Product Description** 3M™ Screen Printable Extended Life Vinyl Performance Label Products are high performance materials that offer good conformability and moisture resistance. These vinyl label stocks utilize 3M™ Adhesive 350, which is designed to permanently bond to high and low surface energy plastics, textured and contoured surfaces, powder coatings, and slightly oily metals.

Construction	Product Number	Facestock	Adhesive	Liner
	<b>3M™ Screen Printable Extended Life Vinyl Performance Label Product 7048</b>	.0038 in. Soft White XL Vinyl TC9	350 1.1 mils	90# Polyctd. 7.0 mil bleached kraft sheet polyethylene coated on two sides
	<b>3M™ Screen Printable Extended Life Vinyl Performance Label Product 7051</b>	.0038 in. Soft White XL Vinyl NTC	350 1.1 mils	90# Polyctd. 7.0 mil bleached kraft sheet polyethylene coated on two sides

(Calipers are nominal values)

**Durability Statement** Based on 2000 hours Xenon arc test exposure, these materials are expected to have up to five year outdoor durability.

- Features**
- Outstanding durability. Designed for use up to five years outdoors.
  - Most universal adhesive for label applications.
  - 3M label product 7048 UL recognized (File MH11410). See the UL listings for details.
  - Adhesive offers excellent chemical resistance and holding strength, even at high temperatures.
  - Liner provides easy sheet processing and is designed for the ultimate in layflat. The backside of this liner is not printable.
  - Meets EU RoHS Directive (e.g.) means that the product or part does not contain any of the following substances in excess of the following maximum concentration values in any homogeneous material, unless the substance is in an application that is exempt under RoHS: (a) 0.1% (by weight) for lead, mercury, hexavalent chromium polybrominated biphenyls or polybrominated diphenyl ethers; or (b) 0.01% (by weight) for cadmium. Unless otherwise stated by 3M in writing, this information represents 3M's knowledge and belief based on information provided by third party suppliers to 3M.

# 3M™ Screen Printable Extended Life Vinyl Performance Label Products

7048 • 7051

## Application Ideas

- Nameplates and product ID labels.
- Rating plates.
- Property identification and asset labeling.
- Warning, instruction, and service labels for durable goods, equipment/machinery and lawn and garden.

## Typical Physical Properties

**Note: The following technical information and data should be considered representative or typical only and should not be used for specification purposes.**

Adhesion properties determined per TLMI Method using 1.0 mil polyester with 1.0 mil of adhesive on a polished stainless steel panel.

<b>Peel Adhesion to</b>		
<b>Stainless Steel</b>	5.0 lbs./in. (875 N/m)	TLMI Method, 180° Peel, 12"/min., 1" wide sample
<b>HDPE</b>	3.0 lbs./in. (528 N/m)	TLMI Method, 180° Peel, 12"/min., 1" wide sample
<b>Polypropylene</b>	4.0 lbs./in. (700 N/m)	TLMI Method, 180° Peel, 12"/min., 1" wide sample
<b>Polycarbonate</b>	4.5 lbs./in. (788 N/m)	TLMI Method, 180° Peel, 12"/min., 1" wide sample
<b>Shear</b>	> 100 hours	TLMI Method, 0.25 in. <sup>2</sup> x 500g
<b>Adhesive Coat Weight</b>	1.75 to 2.02 g/100 in. <sup>2</sup>	TM-2279
<b>Release Range</b>	5 to 70 g/2 in.	TLMI Method, 180° removal, 300 in./min.
<b>Service Temperature</b>	-20°F to 140°F (-29°C to 60°C)	
<b>Minimum Application Temperature</b>	50°F (10°C)	
<b>Convertability</b>	In order to capture the superior performance properties of 3M™ High Holding Acrylic Adhesive 350, thicker calipers are utilized for LSE or textured substrates. Its higher caliper, while desirable for the end use applications, may require extra care during processing. Please refer to the die cutting/converting section of this data page or the "Guide to Converting and Handling Label Products" technical bulletin for additional information.	

## Application Techniques

For maximum bond strength, the surface should be clean and dry. Typical cleaning solvents are heptane and isopropyl alcohol.\*

For best bonding conditions, application surface should be at room temperature or higher. Low temperature surfaces, below 40°F (5°C) can cause the adhesive to become so firm that it will not develop maximum contact with the substrate. Higher initial bonds can be achieved through increased rubdown pressure.

\*When using solvents, read and follow the manufacturer's precautions and directions for use.

# 3M™ Screen Printable Extended Life Vinyl Performance Label Products

7048 • 7051

---

<b>Printing</b>	<b>3M™ Screen Printable Extended Life Vinyl Performance Label Product 7048</b> <ul style="list-style-type: none"><li>• Clear high gloss topcoating designed to provide a printable surface for UV, solvent and water-based screen inks.</li></ul> <b>Solvent Screen Inks:</b> <p>Nazdar’s 7700 and System 2 Sericol’s Polyplast PY, GVYL, VYL, TMI and Techmark</p> <b>UV Screen Inks:</b> <p>ANI Printing Inks (formerly Akzo Nobel) Uvoscreen II Environmental UV III Screen Pro Nazdar 1600 Sericol’s Uviflex, 021 UV, UV and PEL</p> <b>Water-based Screen Inks:</b> <p>Nazdar 2700</p>	<b>3M™ Screen Printable Extended Life Vinyl Performance Label Product 7051</b> <ul style="list-style-type: none"><li>• A non-topcoated print surface designed for use with solvent screen ink systems.</li></ul> <b>Solvent Screen Inks:</b> <p>3M™ Screen Printing UV Ink Series 9800 Nazdar’s 7700 and System 2 Sericol’s Polyplast PY, GVYL, VYL, TMI and Techmark</p>
-----------------	---	---

Please be aware that our current production specifications for these materials are primarily qualified for printers who use flexographic, screen printing, and thermal transfer printing processes. 3M has neither done profile work with these products for printing by digital inkjet processes, nor engaged in any lot variation studies, nor taken any special measures in manufacturing or handling of these products with the intent of recommending these products for printing by digital inkjet methods.

---

<b>Die Cutting / Converting</b>	Die cut with steel rule or flatbed dies. The 90# lay-flat liner also allows kiss cutting and back splitting. The converter can cut through the vinyl facestock without cutting through the liner. Sheet label materials are not recommended for rotary die cutting and stripping operations.
---------------------------------	--

---

<b>Packaging</b>	Finished labels should be stored in plastic bags.
------------------	---

---

<b>Storage</b>	Store at room temperature conditions of 72°F (22°C) and 50% relative humidity.
----------------	--

---

<b>Shelf Life</b>	If stored under proper conditions, product retains its performance and properties for two years from date of manufacture.
-------------------	---

# 3M™ Screen Printable Extended Life Vinyl Performance Label Products

7048 • 7051

---

## Technical Information

The technical information, recommendations and other statements contained in this document are based upon tests or experience that 3M believes are reliable, but the accuracy or completeness of such information is not guaranteed.

---

## Product Use

Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application.

---

## Warranty, Limited Remedy, and Disclaimer

Unless an additional warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

---

## Limitation of Liability

Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

**ISO 9001:2000**

This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9001:2000 standards.

# 3M

Industrial Adhesives and Tapes Division  
Converter Markets

1030 Lake Road  
Medina, OH 44256-0428  
800-422-8116 • 877-722-5072 (fax)  
www.3M.com/converter



*Recycled Paper*  
40% pre-consumer  
10% post-consumer

3M is a trademark of 3M Company.  
Printed in U.S.A.  
©3M 2010 70-0713-4417-3 (8/10)