

3M™ Seam Sealer Tape is a directly paintable, self-adhering tape designed to duplicate factory appearance on hem flanges, door jams and trunk gutter applications.

Application:

1. Remove existing seam sealant and all residue. Clean surface with 3M™ General Purpose Adhesive Cleaner, N. 08984 or 08987.*
*3M™ General Purpose Adhesive Cleaner, (N.08984, 08985) has a VOC of 816 grams per liter (6.81 lbs. per gallon). 3M™ General Purpose Adhesive Cleaner (N. 08987-Aerosol) has a VOC of 736 grams per liter (6.16 lbs. per gallon). 3M™ Super Fast Adhesive Cleaner (N. 08215) has a VOC of 849 grams per liter (7.06 lbs. per gallon). Local air quality regulations may regulate or prohibit the use of surface preparation and cleanup materials based on VOC content. Consult your local air quality regulations.
2. Prime and seal surfaces according to paint manufacturer's recommendation. Do not use 3M™ Seam Sealer Tape over bare metal. For best results, apply 3M Seam Sealer Tape at temperatures above 65F.
3. Apply 3M Seam Sealer Tape over primed and sealed surfaces by removing liner and pressing tape firmly into place. Avoid stretching tape. Tape is conformable and pliable to best duplicate OEM appearances.
4. Avoid overlapping seam sealer tape and splicing in tight corners. 3M Seam Sealer Tape is repositionable; however, best results are obtained if tape is undisturbed after initial application. It is not necessary to apply heat during or after application of this tape as the solvents within the paint will activate the adhesive and provide a permanent bond.
5. 3M Seam Sealer Tape is immediately paintable. Follow your paint manufacturer's recommendations for pre-cleaning, priming, color coating and clear coating.

Other sizes available: 7/8" x 30' (22.2mm x 9.1m) roll - N. 08476, and 6" x 9" (15.2cm x 22.8cm) patches - N. 08477.

IMPORTANT NOTICE: 3M MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. User is responsible for determining whether this 3M product is fit for a particular purpose and suitable for user's method of application. LIMITATION OF REMEDIES AND LIABILITY: If this 3M product is proved to be defective, THE EXCLUSIVE REMEDY, AT 3M'S OPTION, SHALL BE TO REFUND THE PURCHASE PRICE OF OR TO REPAIR OR REPLACE THE DEFECTIVE 3M PRODUCT. 3M shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental, or consequential, regardless of the legal theory asserted, including negligence, warranty or strict liability.

3M I.D. No. 70-0062-8963-4

Additional Product Health and Safety

Information Source: Material Safety Data Sheet or:

3M Automotive Aftermarket Division

3M Center Bldg. 223-6N-01

St. Paul, MN 55144-1000

1-877-MMM-CARS (666-2277)

Copyright © 2000 3M IPC. All rights reserved.

34-7049-0200-5