



Mark Lanes

and Hazards to Help Keep Workplace Safe



3M™ Vinyl Tapes are durable and can be applied in minutes



3M™ Vinyl Tape Can outlast paint! Faster than masking and painting!

- **Durable Vinyl** – Tough vinyl tapes resist tearing, scuffing, moisture, weathering and most acids and alkaline.
- **Rubber Adhesive** – The rubber adhesive provides a strong adhesion to many surfaces for easier application and excellent holding strength.
- **Vivid, Long-Lasting Colors** – Tapes have pigment locked in throughout the vinyl (not printed on the surface) and can outlast paint.
- **Flexible and Stretchable** – 3M™ Vinyl Tapes make it easy to place attractive markings with straight, sharp lines, even around corners, curves and irregular surfaces.



Did you know...

- *Establishing a safety and health program to prevent occupational injuries and illnesses is not only the right thing to do, it is the profitable thing to do. Studies show a \$4 to \$6 return for every dollar invested in safety and health.*

(Source: Safety and Health News: Helpful Statistics. US Department of Labor)

vinyl tapes

	Product	UPC	Size	Description	Packaging
	3M™ Vinyl Tape 471 Green	00-021200-04313-0	2 in x 36 yds	3M™ Vinyl Tape 471 Green is OSHA compliant to identify safety areas.	24 / case
	3M™ Vinyl Tape 471 Red	00-021200-04305-5	2 in x 36 yds	3M™ Vinyl Tape 471 Red is OSHA compliant to identify fire safety areas.	24 / case
	3M™ Vinyl Tape 471 White	00-021200-04311-6	2 in x 36 yds	3M™ Vinyl Tape 471 White is OSHA compliant to mark traffic areas.	24 / case
	3M™ Vinyl Tape 471 Yellow	00-021200-04310-9	2 in x 36 yds	3M™ Vinyl Tape 471 Yellow is OSHA compliant to identify caution areas and traffic lanes.	24 / case
	3M™ Vinyl Tape 471 Orange	00-021200-04312-3	2 in x 36 yds	3M™ Vinyl Tape 471 Orange is OSHA compliant to identify equipment and physical hazards.	24 / case
	3M™ Safety Stripe Tape 5702 Black/Yellow, 5.4 mil	00-021200-04585-1	2 in x 36 yds	This black and yellow durable diagonally striped vinyl tape is used to identify and mark traffic areas and physical hazards.	24 / case
	3M™ Lane Marking Applicator M-77	00-021200-12951-3	applicator	3M™ Lane Marking Applicator M-77 dispenser on wheels applies tape while walking along the area to be marked.	1 / case
MSDS has been prepared to meet the US OSHA Hazards Communication Standard, 29 CFR 1910.1200. Available in additional colors, sizes and widths.					

Paint



3M™ Vinyl Tape 471



Fast, easy removal compared to paint. 3M™ Vinyl Tape simply peels off. Unlike paint, no messy solvents or heavy scraping are required for removal.

3M™ Vinyl Tape 471



Rugged abrasion resistance over paint. Paint versus 3M™ Vinyl Tape 471.

Paint

Competitive plastic tape



Rugged abrasion resistance over competitive tape. Competitive vinyl tape versus 3M™ Safety Stripe Tape 5702 (100 cycles with abrasive tet wheel).

3M™ Safety Strip Tape 5702



MRO Markets Maintenance Repair Operations

3M.com/MRO
Industrial 1-800-567-1639 Ext 4335
Electrical 1-800-245-3573

Product Use: All statements, technical information and recommendations contained in this document are based upon tests or experience that 3M believes are reliable. However, many factors beyond 3M's control can affect the use and performance of a 3M product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method of application.

Warranty and Limited Remedy: Unless stated otherwise in 3M's product literature, packaging inserts or product packaging for individual products, 3M warrants that each 3M product meets the applicable specifications at the time 3M ships the product. Individual products may have additional or different warranties as stated on product literature, package inserts or product packages. 3M MAKES NO OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's application. If the 3M product is defective within the warranty period, your exclusive remedy and 3M's and seller's sole obligation will be, at 3M's option, to replace the product or refund the purchase price.

Limitation of Liability: Except where prohibited by law, 3M and seller will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental, or consequential, regardless of the legal theory asserted, including warranty, contract, negligence, or strict liability.

3M is a trademark of 3M Company.

78-6901-2281-3 © 3M 2007