



Novec™

Brand

3M™ Novec™ Flux Remover

Introduction

3M™ Novec™ Flux Remover uses advanced 3M solvent technology to remove a wide variety of solder fluxes used in electronics manufacturing and repair – including rosin-based and many no-clean fluxes. Novec Flux Remover evaporates quickly, and leaves no residue. This industrial-strength cleaner is non-corrosive and compatible with most plastics, with the exception of sensitive plastics such as acrylics, polycarbonates, ABS and PS.

Novec Flux Remover is non-flammable, non-ozone depleting, has low global warming potential and does not contain any hydrochlorofluorocarbons (HCFCs), hydrofluorocarbons (HFCs), n-propyl bromide (nPB), or halogenated hazardous air pollutant (HAP) like trichloroethylene (TCE).

Plastics compatibility

Material	Compatibility	Material	Compatibility
ABS	Not Compatible	PMMA	Not Compatible
Nylon	Excellent	POM	Excellent
Lexan®/Polycarbonate	Not Compatible	PP	Excellent
HDPE	Excellent	PS	Not Compatible
CDPE	Excellent	PTFE	Excellent
C.E. Phenolic	Excellent	PVC	Excellent

Environmental, health and safety information

Not for specification purposes.

Properties	3M™ Novec™ Flux Remover
Ozone Depletion Potential ¹ (ODP)	0.0
Global Warming Potential ² (GWP)	107
Flashpoint ³	None
Exposure Guideline (ppmV, 8 hour time weighted average)	398 ⁴

¹ CFC-11 = 1.0

² GWP-100 year integration time horizon, CO₂ = 1.0

³ ASTM D3278

⁴ Please refer to Safety Data Sheet (SDS) for specifics

Key features and benefits

- Non-corrosive
- Fast drying, no residue
- Low odor
- Non-flammable
- Non-ozone depleting
- Low toxicity
- Low global warming potential

Regulatory information

RoHS/WEEE Compliant	Yes
Meets CA VOC Limits	No
Meets OTC VOC Limits	Yes - Electronic Cleaner
NSN (National Stock Number)	6850-01-534-2943

Physical properties

Not for specification purposes.

Properties	Values
Evaporation Rate (relative to n-Butyl Acetate)	>10X
Surface Tension (dynes/cm ²)	21
Specific Gravity (g/ml)	1.35
Dielectric Strength	>25 kV
Shelf Life	5 years*

* The shelf life of 3M™ Novec™ Flux Remover is 5 years from the date of manufacture when stored at general warehouse storage conditions, less than 27°C (80°F).

Safety and handling

3M™ Novec™ Flux Remover is nonflammable. When used as directed, in its intended applications, Novec flux remover has a wide margin of safety between anticipated exposures and the exposure guideline. Before using this product, be sure to read and follow all precautions and directions for use contained in the product label and Safety Data Sheet, which is available from your local 3M representative upon request. This product is for industrial use only. Not for consumer use or sale. Not for sale in California.

Transportation classification

Ground: Consumer Commodity ORM-D

Air: Aerosols, Nonflammable, 2.2, UN1950

Resources

For more information on 3M Novec products or to contact a 3M representative, visit 3M.com/Novec.

Smart. Safe. Sustainable.

The 3M™ Novec™ Brand Family

The Novec brand is the hallmark for a variety of proprietary 3M products. Although each has its own unique formula and performance properties, all Novec products are designed in common to address the need for smart, safe and sustainable solutions in industry-specific applications. These include precision and electronics cleaning, heat transfer, fire protection, protective coatings, immersion cooling, advanced insulation media replacement solutions and several specialty chemical applications.

3M™ Novec™ Engineered Fluids • 3M™ Novec™ Aerosol Cleaners • 3M™ Novec™ 1230 Fire Protection Fluid • 3M™ Novec™ Electronic Grade Coatings • 3M™ Novec™ Insulating Gases

Safety Data Sheet: Consult Safety Data Sheet before use.

Regulatory: For regulatory information about this product, contact your 3M representative.

Technical Information: The technical information, recommendations and other statements contained in this document are based upon tests or experience that 3M believes are reliable, but the accuracy or completeness of such information is not guaranteed.

Product Use: Many factors beyond 3M's control and uniquely within user's control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application.

Warranty, Limited Remedy, and Disclaimer: Unless an additional warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OR TRADE. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.



Electronics Materials Solutions Division

3M Center, Building 224-3N-11
St. Paul, MN 55144-1000 USA

Web www.3M.com/novec
Phone 1-800-810-8513

Please recycle. Printed in USA.
©3M 2021. All rights reserved.
Issued: 03/21 16695HB
60-5002-0348-8

Lexan is a registered trademark of SABIC Innovative
Plastics. 3M and Novec are trademarks of 3M Company.
Used under license by 3M subsidiaries and affiliates.