

3M™ Wind Tape and Residue Remover (TARR) W9900

Product Description

3M™ Tape and Residue Remover (TARR) W9900 is recommended for use in removing 3M™ Wind Protection Tapes and residue.

- Water based formulation
- Non-regulated material per the EPA's Hazardous Waste Numbering system
- Easy to use

Product	Package
16 oz. tub	6 tubs/case
Gallon	4 gallons/case

Typical Physical Properties

Properties	Typical Values
Container	Various
Color	Light tan
Flash Point	> 201°F
Viscosity (CPS) Brookfield Viscometer	>4000 cP
Consistency	Paste
Solvent	None
Odor	Sweet
Density	9.5 lb/gal
Boiling Point	>215°F (101.67°C)
Vapor Pressure	1 mmHg @ 68°F (20°C)
pH	8.1–8.7

Note: The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

Directions for Use

Warning: Test product compatibility with substrate prior to use. Not recommended for use on plastic or acrylic substrates. May cause paint softening or crazing.

3M Wind Protection Tape Removal

1. Masking the surrounding area is recommended.
2. Apply a uniform layer of 3M Wind Tape and Residue Remover approximately 1/8" thick to the entire tape surface being removed using a spreader. The product surface should look brown.
3. Cover residue remover using a clear plastic cellophane film to prevent evaporation.
4. Let stand until tape or rubber wrinkles, lifts or bubbles. Thinner tapes may take 2 to 6 hours while thicker tapes may take 12 hours or more.
5. Pull and remove tape. If any residue remains, remove using a rag moistened with residue remover.
6. Wipe surface and surrounding area using a clean cloth.
7. Clean surface using a damp cloth and final wipe using a substrate compatible solvent.

Tape Residue Removal

1. Masking the surrounding area is recommended.
2. Apply a uniform layer of 3M Wind Tape and Residue Remover approximately 1/8" thick to the entire tape surface being removed using a spreader. The product surface should look brown.
3. Let 3M Wind Tape and Residue Remover dwell for 1 to 15 minutes depending on residue type.
4. Wipe area with a clean cloth to remove residue.
5. Clean surface using a damp cloth and final wipe using a substrate compatible solvent

Note: The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

Storage and Handling

Storage

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water. Avoid breathing in vapors, mists or spray. Avoid contact with oxidizing agents. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below Occupational Exposure Limits. If ventilation is not adequate, use respiratory protection equipment.

Handling

Keep container in a well ventilated area. Store away from oxidizing agents. Keep from freezing. Use in a well-ventilated area.

Shelf Life

When stored in the original container at room temperature, shelf life is 36 months from manufacture date.

Precautionary Information

Refer to Product Label and Material Safety Data Sheet for Health and Safety Information before using this product.

Test product compatibility with substrate prior to use. Not recommended for use on plastic or acrylic substrates. May cause paint softening or crazing.

For additional health and safety information, call 1-800-364-3577 or (651) 737-6501.

For more information on our wind energy product line, contact 3M Renewable Energy at 800-755-2654 or visit us at www.3M.com/wind.

Technical Information: The technical information, recommendations and other statements contained in this document are based upon tests or experience that 3M believes are reliable, but the accuracy or completeness of such information is not guaranteed.

Product Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application.

Warranty, Limited Remedy, and Disclaimer: Unless an additional warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.



Renewable Energy Division

3M Center, Building 235-1S-67
St. Paul, MN 55144-1000
1-800-755-2654
www.3M.com/wind

Please recycle. Printed in USA.
Issued: 4/12 © 3M 2012.
All rights reserved. 8633HB
98-0150-0085-8

3M is a trademark of 3M Company.
Used under license by
3M subsidiaries and affiliates.