

# 3M™ Multi-Touch Display C2254PW

## Ruggedized Chassis for Next-Generation Multi-Touch Applications

The 22-inch **3M™ Multi-Touch Display C2254PW** combines a 3M Projected Capacitive touchscreen that delivers an ultra-fast, accurate, and precise 20 finger touch response, with a high-definition, wide viewing angle LCD, to create a multi-touch chassis for your next generation interactive application. The rugged all steel frame and a highly-durable glass front surface provide the durability needed for demanding public use environments.

### 3M Projected Capacitive Technology

The C2254PW display uses 3M Projected Capacitive Technology (3M PCT) to deliver “full multi-touch” capabilities. The ability to distinguish 20 touches at 6 millisecond touch response creates a user experience that is more natural, intuitive, and responsive compared to optical-based two touch systems. The design of the projected capacitive sensor has more than 3300 touch sensing points in close proximity, making it precise and extremely accurate across the entire touchscreen. 3M PCT’s durable glass touchscreen surface has a unique anti-stiction coating that greatly reduces surface friction and allows users fingers to effortlessly glide across the display for easy gesture functions. This fast, accurate, and easy to use multi-touch touchscreen enables customers to create, deliver and experience innovative and immersive user applications.

### Versatile Rugged Chassis Design

The C2254PW chassis was designed to meet the demanding needs of a public environment while being versatile enough to easily integrate into custom enclosures. The all steel construction provides a rugged metal frame to securely mount into enclosures. Multiple mounting methods (100mm VESA mount and side brackets) are offered to ensure a proper fit in both horizontal or vertical orientations. The compact form factor delivers a slim product designed to fit into tight kiosks and can be used to retrofit most 22” chassis in the marketplace.



### Recommended Multi-Touch Applications

- Kiosks
- Gaming and Amusement
- Point of Information
- Audio Visual
- Industrial Automation
- Digital Signage
- Self Service
- Security Monitoring Systems
- Media and Broadcast

### Optimal Display for Multi-Touch Interaction

The high-definition, high-contrast display provides impressive picture quality for vibrant, true-to-life graphics, dynamic HD video content and crisp, clear images. The C2254PW display delivers brilliant images from nearly every angle with its ultra-wide viewing angle (178 degree viewing in both vertical and horizontal directions). Since typical chassis mount applications are fixed, the ultra-wide viewing angle will help create an immersive experience regardless of a user’s height or position relative to the display. As multiple users interact with the multi-touch display, especially in a horizontal or table top position, the ultra-wide viewing angle will ensure that all users experience the same brilliant content.

Feature	Benefit
Full Multi-Touch Capabilities	<ul style="list-style-type: none"><li>• 20 finger multi-touch input</li><li>• Fast 6 millisecond touch response</li><li>• Enables next-generation interactive software applications well beyond two touch expectations</li><li>• Anti-stiction surface enhances the user experience for simple and advanced gestures</li><li>• Native multi-touch support with Windows 7</li><li>• Supports Windows XP and Linux Operating systems</li></ul>
Versatile Rugged Chassis Design	<ul style="list-style-type: none"><li>• All steel construction provides rugged frame for public use environments</li><li>• Slim profile for fit into compact enclosures</li><li>• Multiple mounting options (100mm VESA Mount and Side Brackets)</li><li>• Small form factor enables retrofit capabilities</li></ul>
Display Designed for Multi-Touch Applications	<ul style="list-style-type: none"><li>• 1680x1050 high definition resolution</li><li>• Ultra-wide horizontal/vertical viewing angle (178 degrees) allows outstanding off-axis viewing</li><li>• High contrast delivers sharp brilliant image quality</li></ul>



# 3M™ Multi-Touch Display C2254PW Specifications

## Functional Specifications

### Display Details

LCD Technology	P-MVA (wide angle viewing technology)
Display Colors	16.7 million
Pixel Pitch	.282 x .282mm
Brightness	300 cd/m <sup>2</sup> (nit) typical
with touch sensor (max.) <sup>1</sup>	270 cd/m <sup>2</sup> (nit) typical
Contrast Ratio	1000:1 typical
Viewing Angle <sup>2</sup>	Horizontal/Vertical: 178 degrees typical
Video Response Time <sup>3</sup>	8 ms typical
Control Type	OSD
Native Resolution	1680x1050

### Touch Details

Number of Touch Points	20 points
Touch Point Speed	6 milliseconds
Input Type	Finger, thin glove
Touch Communication	Auto detecting, USB and RS232 (Serial)
Operating System Support	Windows 7/Vista/XP, Linux

(1) Brightness measured on a display with 3M™ Projected Capacitive sensor.

(2) Measured at a contrast ratio of 10.

(3) Gray to Gray



Input Connections

## Physical Specifications

### Product Details

Operating Environment	0 to +40 degrees C Relative Humidity, non-condensing 90%
Storage Environment	-10 to +60 degrees C
Video Input	DVI and VGA
VESA Pattern	100mm x 100mm
Power Supply	12 VDC Power Supply (external)
Power Consumption	80 watts maximum
RoHS Compliant	Yes
Agency Approvals	FCC-B, CE, TUV, CCC
Warranty	1 Year

### Dimensions and Weight

Physical (WxHxD)	500.0 x 328.4 x 51.87 mm 19.7 x 12.9 x 2.0 inches
Display Area (WxH) (viewing area)	473.8 x 296.1 mm 18.7 x 11.7 inches
Packaging (WxHxD)	610 x 490 x 194 mm 24.0 x 19.3 x 7.6 inches
Display weight	7.0 kg / 15.4 lb
Packaging/Display weight	12.5 kg / 27.6 lb

Part Number 98-0003-3601-0



Slim Design



Optional Remote On-screen  
Display Module  
(Part number: 30114)

**3M Touch Systems**  
Subsidiary of 3M Company  
501 Griffin Brook Park Drive  
Methuen, MA 01844 U.S.A.  
1-888-659-1080  
[www.3M.com/touch](http://www.3M.com/touch)

**RoHS Directive compliant:** In accordance with European Directive 2002/95/EC, "RoHS Directive compliant" means that the product or part does not contain any of the following substances in excess of the following maximum concentration values in any homogeneous material, unless the substance is in an application that is exempt under RoHS: (a) 0.1% (by weight) for lead, mercury, hexavalent chromium, polybrominated biphenyls or polybrominated diphenyl ethers; or (b) 0.01% (by weight) for cadmium. Unless otherwise stated by 3M in writing, this information represents 3M's knowledge and belief based on information provided by third party suppliers to 3M. (9/06)

**IMPORTANT NOTICE TO PURCHASER:** Specifications are subject to change without notice. These 3M Touch Systems' Products and software are warranted to meet their published specifications from the date of shipment and for the period stated in the specification. 3M Touch Systems makes no additional warranties, express or implied, including but not limited to any implied warranties of merchantability or fitness for a particular purpose. User is responsible for determining whether the 3M Touch Systems Products and software are fit for User's particular purpose and suitable for its method of production, including intellectual property liability for User's application. If the Product, software or software media is proven not to have met 3M Touch Systems' warranty, then 3M Touch Systems' sole obligation and User's and Purchaser's exclusive remedy, will be, at 3M Touch Systems' option, to repair or replace that Product quantity or software mediator to refund its purchase price. 3M Touch Systems has no obligation under 3M Touch Systems' warranty for any Product, software or software media that has been modified or damaged through misuse, accident, neglect, or subsequent manufacturing operations or assemblies by anyone other than 3M Touch Systems. 3M Touch Systems shall not be liable in any action against it in any way related to the Products or software for any loss or damages, whether non-specified direct, indirect, special, incidental or consequential (including downtime, loss of profits or goodwill) regardless of the legal theory asserted. (7/02)

