



# Aluminum Foil Tape

## 3340

Technical Data

May 2017

**Product Description** 3M™ 3340 is a general purpose Aluminum Foil Tape offering an annealed aluminum foil backing combined with an acrylic pressure sensitive adhesive having an easy release PE coated Kraft liner.

Product Construction	Backing	Adhesive	Color	Liner
	Aluminum Foil	Acrylic	Silver	PE coated Kraft liner

**Typical Physical Properties**

Note: The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

		ASTM Test Method
Adhesion to Steel:	30 oz./in. width (43 N/100 mm width)	D-3330
Tensile Strength:	20 lbs./in. width (350 N/100 mm width)	D-3759
Elongation at Break:	4%	D-3759
Backing Thickness:	2.0 mils (0.05 mm)	D-3652
Liner Thickness:	3.1 mils (0.08 mm)	D-3652
Total Tape Thickness:	4.0 mils (0.10 mm)	D-3652

**Features**

- Meets requirements of UL 181A-P and UL 181 B-FX (file MH16587).
- Duct closure tape is specifically designed for use as a vapor seal on reinforced fiberglass duct board.
- Best adhesion results attained when applied to clean dry surfaces above 32°F (0°C).
- Foil backing printed with UL label approval.

**Application Ideas**

- For use with rigid glass fiber air duct board (181A-P) and flexible (non-metallic) air ducts and air connectors (181B-FX).

**Storage**

Store under normal conditions of 60° to 80°F (16° to 27°C) and 40 to 60% relative humidity in the original packaging material.

**Shelf Life**

To obtain best performance, use this product within 24 months from date of manufacture.

# 3M™ Aluminum Foil Tape

## 3340

---

### Technical Information

The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

---

### Product Selection and Use

Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

---

### Warranty, Limited Remedy, and Disclaimer

Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

---

### Limitation of Liability

Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

---

ISO 9001

This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9001 standards.



Industrial Adhesives and Tapes Division  
3M Center, Building 225-3S-06 St.  
Paul, MN 55144-1000  
800-362-3550 • 877-369-2923 (Fax)  
[www.3M.com/industrial](http://www.3M.com/industrial)

3M is a trademark of 3M  
Company. Printed in U.S.A.  
©3M 2017 E 70071616281 (5/17)