



3M Fire Protection Products

Technical Broadcast

BROADCAST NO.: T11-012

Date: December 30, 2011

Issued by: Kate Baker, Ted Colwell, Ernie Schmidt

TITLE: UPDATED SYSTEMS: ALL 3M TESTED AND LISTED UL SYSTEMS USING 3M™ FIRE BARRIER PILLOWS OR 3M™ FIRE BARRIER SELF-LOCKING PILLOWS

DESCRIPTION: All of 3M’s UL Systems using 3M™ Fire Barrier Pillows and / or 3M™ Fire Barrier Self-Locking Pillows were updated to reflect “tightly packed” pillows instead of defining a specific compression. The systems are:

C-AJ-0084	C-AJ-1611	C-AJ-4056
C-AJ-4078	C-AJ-6041	C-AJ-7110
C-AJ-8205	F-A-3053	F-B-3013
F-B-3016	F-B-3017	W-J-0021
W-J-1111	W-J-3169	W-J-4055
W-J-4062	W-J-4063	W-J-4069
W-J-8042	W-L-0011	W-L-0039
W-L-1255	W-L-3336	W-L-4037
W-L-4062	W-L-4066	W-L-4075
W-L-7197	W-L-8077	

TARGET MARKET & TYPICAL APPLICATIONS:

Used for new construction and retrofit applications. Great for large openings where re-enterability is desired. Cable trays, multiple metallic penetrants, cables, and HVAC ducts would be the primary use for 3M™ Fire Barrier Pillows. Don’t forget those blank openings waiting for penetrants. Pillows are ideal here. It’s the perfect product when temporary firestopping is required.

Our product data sheets state that 25% compression of the Pillows should achieve “tightly packed”.

Please let contractors, design professionals and inspectors know about this change.





3M Fire Protection Products

Technical Broadcast

BROADCAST RECIPIENTS:

3M Fire Protection Products Authorized L-1 Distributors
3M Fire Protection Products Authorized L-2 Distributors
3M Fire Protection Products Authorized National Distributors
3M Sales Representatives
3M Manufacturer's Agents
3M St. Paul Internal
3M International

Important Notice to User:

Technical Information: The technical information, recommendations and other statements contained in this document are based upon tests or experience that 3M believes are reliable, but the accuracy or completeness of such information is not guaranteed.

Product Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application.

Warranty and Limited Remedy: 3M warrants that each 3M Fire Protection Product will be free from defects in material and manufacture for 90 days from the date of purchase from 3M's authorized distributor. 3M MAKES NO OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. If a 3M product does not conform to this warranty, the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted.



Building and Commercial Services Division
St. Paul, MN 55144-1000
1-800-328-1687
www.3M.com/firestop

3M is a trademark of 3M.
© 3M 2011. All rights reserved.