


# 3M™ Wheel Weights

## Technical Data Sheet

### General Description

The 3M™ Wheel Weights PN55409, PN55428, PN61403, PN61405 and PN99473 and 3M™ Mechanical Replacement Weight PN99427 are provided as rolls and designed to be cut to weight to meet your precision wheel balancing requirements. Lead-free, 3M Wheel Weights are designed to provide an alternative to standard lead wheel weights and features the industry-leading 3M™ Attachment Tape Technology used in numerous tape-applied attachments of component parts to vehicles. 3M's tape expertise, combined with the conformable wheel balancing material, provides an all-in-one, securely attached wheel weight balancing system.



### Product Benefits


- Designed to be used with 3M™ Cutting Stand PN61480 and 3M™ Universal Cutter PN61479
- Corrosion-free feature improves wheel and overall vehicle appearance
- Manufactured with post-industrial recycled stainless steel (84.7% of product weight), this polymer/stainless steel/composite material is designed to replace lead wheel weights
- Elimination of clip-on weights improves wheel appearance by hiding weights
- Precision cut-to-length weights improve balance and vehicle ride quality
- Offered in multiple profiles and colors to fit customer design requirements
- Tire balance is retained with correctly located and attached weights
- Flexible product design enables one size to fit all wheel diameters

### Product Portfolio


Product Number	3M Stock Number	Roll Length	Profile Width x Height
99427 (TN4014P)	7100338495	10.4 M (11.37 yd)	14.0 mm (0.55 in) x 7.0 mm (0.28 in)
61403 (TN4715P)	7100338589	11.0 M (12.03 yd)	15.0 mm (0.59 in) x 7.0 mm (0.28 in)
61405 (TN4023P)	7100339232	20.8 M (22.75 yd)	23.0 mm (0.91 in) x 4.4 mm (0.17 in)
99473 (TN4029P)	7100338777	11.3 M (12.36 yd)	29.0 mm (1.14 in) x 6.0 mm (0.24 in)
55409 (TN4020P)	7100338877	14.5 M (15.86 yd)	20.0 mm (0.79 in) x 5.8 mm (0.23 in)
55428 (TN6020P)	7100339036	14.5 M (15.86 yd)	20.0 mm (0.79 in) x 5.8 mm (0.23 in)

## Product Construction


### TN4014P/PN99427




### TN4715P/PN61403




### TN4023P/PN61405




### TN4029P/PN99473



### TN4020P/PN55409



### TN6020P/PN55428



## Storage and Handling

Twelve months from date of manufacture, when stored at optimum storage conditions of 22°C (72°F) and 50% relative humidity.

## Regulatory Information

Please refer to the product label and Safety Data Sheet (SDS) for health and safety information before using. Observe proper handling precautions as outlined in the SDS, which is available on request or at [www.3M.com/msds](http://www.3M.com/msds). To obtain published IMDS ID numbers, email requests to [3M-IMDSrequest@mmm.com](mailto:3M-IMDSrequest@mmm.com).

## Contact Information

The information provided in this technical document is intended as a guide for these products. For more information or help in selecting a 3M product for an application, please contact your 3M technical service representative or call 1-800-328-1684.

**Technical Information:** The technical information, recommendations and other statements contained in this document are based upon tests or experience that 3M believes are reliable, but the accuracy or completeness of such information is not guaranteed. **Product Use:** Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application. **Warranty, Limited Remedy, and Disclaimer:** Unless an additional warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price. **Limitation of Liability:** Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.



### Automotive and Aerospace Solutions Division

3M Center  
St. Paul, MN 55144-1000  
Phone 1-800-328-1684  
Web [www.3M.com/autosolutions](http://www.3M.com/autosolutions)

3M is a trademark of 3M Company  
Please recycle.  
© 3M 2025. All rights reserved.