

3M Science.
Applied to Life.™

Nearly Invisible Protection

3M™ Paint Protection Film



Designed to protect vulnerable surfaces

- Durable, nearly invisible polyurethane film and protective clearcoat resist chipping, scratching, staining, and discoloration
- Pressure-sensitive adhesive makes for fast application without curing
- Pre-masked and die-cut parts make for a less complicated, more efficient application



Fender



Door Handle

Typical Applications:

Door handles	Door sills	Door edges
Bumpers	Door openings	Wheel flares
Fenders	Truck bed edges	Rocker panels



Wheel Flare



Bumper

Product Portfolio:

3M™ Paint Protection Films meet and exceed OEM appearance, performance and weathering requirements. Our films are available in a variety of thicknesses and stick to a multitude of substrates and surfaces.

Product	Thickness - Base Film	With Adhesive	Standard (No Clearcoat)	Premium (Clearcoat)
8591	12 mils (0.305 mm)	14 mils (0.356 mm)	X	
8592	6 mils (0.152 mm)	8 mils (0.203 mm)	X	
SPF12	12 mils (0.305 mm)	14 mils (0.356 mm)	X	
PUL2006	6 mils (0.152 mm)	8 mils (0.203 mm)		X
PUL2008	8 mils (0.203 mm)	10 mils (0.254 mm)		X
PUL2012	12 mils (0.305 mm)	14 mils (0.356 mm)		X

About 3M™ Paint Protection Film

3M Paint Protection Films are part of a global array of engineered solutions for automotive manufacturers, including research and development, application engineering resources and ongoing responsive manufacturing support. Like all 3M products for Automotive OEMs, these films simplify manufacturing, protect without altering the design of the vehicle, and meet OEM specifications.

Interested in Purchasing Paint Protection Films

- 3M Paint Protection Films are available direct from 3M or 3M-approved converters.
- Contact your 3M Automotive and Aerospace Solutions Division (AASD) account representative for roll sizes, minimum order quantities, prices, and terms and conditions of sale.
- If you do not have a 3M account representative, contact 3M AASD customer service at 800-328-1684.

Technical Information: The technical information, recommendations and other statements contained in this document are based upon tests or experience that 3M believes are reliable, but the accuracy or completeness of such information is not guaranteed.

Product Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application.

Warranty, Limited Remedy, and Disclaimer: Unless an additional warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.



3M Automotive and Aerospace
Solutions Division
3M Center
St. Paul, MN 55144 USA
mmm.com/autosolutions

3M is a trademark of 3M Company.
Please recycle.
© 3M 2017. All rights reserved.