

Feather 1010 Technical Data Sheet



Feather 1010 Full Body Harness

Universal size Feather 1010 Full Body Harnesses are designed for users with a maximum capacity up to 310 pounds (141 kg) including clothing, tools, etc.

Feather 1010 Full Body Harnesses sized XXL are designed for users with a maximum capacity up to 400 pounds (181 kg) including clothing, tools, etc.

All components of the Feather 1010 Full Body Harness meet the ANSI Z359.1-2007 standard and OSHA 29 CFR 1910.66 and 1926.502 requirements.



Attachment Points



- A** The dorsal (back) D-ring affixed to all 3M Full Body Harnesses is for fall arrest or restraint systems. The dorsal D-ring may also be used for rescue applications.



- L** A front D-ring is used for fall arrest in vertical systems that limit the free fall distance to 18 inches. The front D-ring may be used for restraint, and ladder climbing systems.



- D** The seat strap D-rings are to be used for rescue, and controlled descent applications. The front D-ring may also be used for rescue, and controlled descent.



- E** Shoulder D-rings may be used in rescue applications. Always use both shoulder D-rings simultaneously, utilizing the 3M M30-SBA Spreader Bar Assembly. **The shoulder D-rings are not for fall arrest or climbing applications.**



- P** Hip D-rings are used for positioning and restraint systems. Always use both hip D-ring connections when securing work positioning devices. **Hip D-rings are not for fall arrest or climbing applications.**

WARNING

Compliant fall protection and emergency rescue systems help prevent serious injury during fall arrest. Users must read and understand the User Instructions provided with the product and be properly trained by their employer prior to use per OSHA 29 CFR 1910.66 and 1926.503 or applicable local standards. **Misuse or failure to follow warnings and instructions may result in serious personal injury or death.** For proper use, see supervisor, User Instructions, or call Technical Service at 800-243-4630.



Feather 1010

Technical Data Sheet



Model 3M ID	Webbing Material	D-Rings	D-Ring Material	Leg Connection	Chest Connection	Capacity	CSA Class	Weight	Compliance Standards
1010 70071566387	Polyester	Back	Forged Steel	Pass Thru	Pass Thru	310 lbs (141 kg)	A	3.1 lbs (1.4 kg)	ANSI Z359.1-07 CSA Z259.10-06
1010-LOGO 70071566460	Polyester	Back	Forged Steel	Pass Thru	Pass Thru	310 lbs (141 kg)	A	3.1 lbs (1.4 kg)	ANSI Z359.1-07 CSA Z259.10-06
1010-XXL 70071566494	Polyester	Back	Forged Steel	Pass Thru	Pass Thru	400 lbs (181 kg)	A		ANSI Z359.1-07 CSA Z259.10-06
1010-XXL-LOGO 70071566502	Polyester	Back	Forged Steel	Pass Thru	Pass Thru	400 lbs (181 kg)	A		ANSI Z359.1-07 CSA Z259.10-06
1010E 70071596624	Polyester	Back, Extended Back D	Forged Steel	Pass Thru	Pass Thru	310 lbs (141 kg)	A		ANSI Z359.1-07 CSA Z259.10-06
1010E-LOGO 70071596707	Polyester	Back, Extended Back D	Forged Steel	Pass Thru	Pass Thru	310 lbs (141 kg)	A		ANSI Z359.1-07 CSA Z259.10-06
1010E-XXL 70071596731	Polyester	Back, Extended Back D	Forged Steel	Pass Thru	Pass Thru	400 lbs (181 kg)	A		ANSI Z359.1-07 CSA Z259.10-06
1010E-XXL-LOGO 70071596749	Polyester	Back, Extended Back D	Forged Steel	Pass Thru	Pass Thru	400 lbs (181 kg)	A		ANSI Z359.1-07 CSA Z259.10-06
1010EQ 70071596715	Polyester	Back, Extended Back D	Forged Steel	Quick Connect	Quick Connect	310 lbs (141 kg)	A		ANSI Z359.1-07 CSA Z259.10-06
1010EQ-LOGO 70071596723	Polyester	Back, Extended Back D	Forged Steel	Quick Connect	Quick Connect	310 lbs (141 kg)	A		ANSI Z359.1-07 CSA Z259.10-06
1010EQ-XXL 70071596756	Polyester	Back, Extended Back D	Forged Steel	Quick Connect	Quick Connect	400 lbs (181 kg)	A		ANSI Z359.1-07 CSA Z259.10-06
1010EQ-XXL-LOGO 70071596764	Polyester	Back, Extended Back D	Forged Steel	Quick Connect	Quick Connect	400 lbs (181 kg)	A		ANSI Z359.1-07 CSA Z259.10-06
1010F 70071596301	Polyester	Back, Front	Forged Steel	Pass Thru	Pass Thru	310 lbs (141 kg)	A, L		ANSI Z359.1-07 CSA Z259.10-06
1010F-LOGO 70071596343	Polyester	Back, Front	Forged Steel	Pass Thru	Pass Thru	310 lbs (141 kg)	A, L		ANSI Z359.1-07 CSA Z259.10-06
1010F-XXL 70071596376	Polyester	Back, Front	Forged Steel	Pass Thru	Pass Thru	400 lbs (181 kg)	A, L		ANSI Z359.1-07 CSA Z259.10-06
1010F-XXL-LOGO 70071596384	Polyester	Back, Front	Forged Steel	Pass Thru	Pass Thru	400 lbs (181 kg)	A, L		ANSI Z359.1-07 CSA Z259.10-06
1010FE 70071597564	Polyester	Back, Front, Extended Back D	Forged Steel	Pass Thru	Pass Thru	310 lbs (141 kg)	A, L		ANSI Z359.1-07 CSA Z259.10-06
1010FE-LOGO 70071597606	Polyester	Back, Front, Extended Back D	Forged Steel	Pass Thru	Pass Thru	310 lbs (141 kg)	A, L		ANSI Z359.1-07 CSA Z259.10-06
1010FE-XXL 70071597630	Polyester	Back, Front, Extended Back D	Forged Steel	Pass Thru	Pass Thru	400 lbs (181 kg)	A, L		ANSI Z359.1-07 CSA Z259.10-06
1010FE-XXL-LOGO 70071597648	Polyester	Back, Front, Extended Back D	Forged Steel	Pass Thru	Pass Thru	400 lbs (181 kg)	A, L		ANSI Z359.1-07 CSA Z259.10-06
1010FEQ 70071597614	Polyester	Back, Front, Extended Back D	Forged Steel	Quick Connect	Quick Connect	310 lbs (141 kg)	A, L		ANSI Z359.1-07 CSA Z259.10-06
1010FEQ-LOGO 70071597622	Polyester	Back, Front, Extended Back D	Forged Steel	Quick Connect	Quick Connect	310 lbs (141 kg)	A, L		ANSI Z359.1-07 CSA Z259.10-06
1010FEQ-XXL 70071597655	Polyester	Back, Front, Extended Back D	Forged Steel	Quick Connect	Quick Connect	400 lbs (181 kg)	A, L		ANSI Z359.1-07 CSA Z259.10-06
1010FEQ-XXL-LOGO 70071597663	Polyester	Back, Front, Extended Back D	Forged Steel	Quick Connect	Quick Connect	400 lbs (181 kg)	A, L		ANSI Z359.1-07 CSA Z259.10-06
1010FQ 70071596350	Polyester	Back, Front	Forged Steel	Quick Connect	Quick Connect	310 lbs (141 kg)	A, L		ANSI Z359.1-07 CSA Z259.10-06

F = Front D-Ring; E = Back D-Ring Extender; Q = Quick Connect; LOGO = Option to add custom logo; Weights and measurements are approximate.


Feather 1010

Technical Data Sheet



1010FQ-LOGO 70071596368	Polyester	Back, Front	Forged Steel	Quick Connect	Quick Connect	310 lbs (141 kg)	A, L	ANSI Z359.1-07 CSA Z259.10-06
1010FQ-XXL 70071596392	Polyester	Back, Front	Forged Steel	Quick Connect	Quick Connect	400 lbs (181 kg)	A, L	ANSI Z359.1-07 CSA Z259.10-06
1010FQ-XXL-LOGO 70071596400	Polyester	Back, Front	Forged Steel	Quick Connect	Quick Connect	400 lbs (181 kg)	A, L	ANSI Z359.1-07 CSA Z259.10-06
1010Q 70071566478	Polyester	Back	Forged Steel	Quick Connect	Quick Connect	310 lbs (141 kg)	A	ANSI Z359.1-07 CSA Z259.10-06
1010Q-LOGO 70071566486	Polyester	Back	Forged Steel	Quick Connect	Quick Connect	310 lbs (141 kg)	A	ANSI Z359.1-07 CSA Z259.10-06
1010Q-XXL 70071566510	Polyester	Back	Forged Steel	Quick Connect	Quick Connect	400 lbs (181 kg)	A	ANSI Z359.1-07 CSA Z259.10-06
1010Q-XXL-LOGO 70071566528	Polyester	Back	Forged Steel	Quick Connect	Quick Connect	400 lbs (181 kg)	A	ANSI Z359.1-07 CSA Z259.10-06

F = Front D-Ring; E = Back D-Ring Extender; Q = Quick Connect; LOGO = Option to add custom logo; Weights and measurements are approximate.



Product Warranty, Limited Remedy, and Limitation of Liability

WARRANTY: THE FOLLOWING IS MADE IN LIEU OF ALL WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OR CONDITIONS OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Equipment offered by 3M is warranted against factory defects in workmanship and materials for a period of one year from date of installation or first use by the original owner.

LIMITED REMEDY: Upon notice in writing, 3M will repair or replace all defective items at 3M's sole discretion. 3M reserves the right to require that the defective item be returned to its plant for inspection before determining the appropriate course of action. Warranty does not cover equipment damage resulting from wear, abuse, damage in transit, failure to maintain the product or other damage beyond the control of 3M. 3M shall be the sole judge of product condition and warranty options. This warranty applies only to original purchaser and is the only warranty applicable to this product. Please contact 3M technical service department at 800-243-4630 for assistance.

LIMITATION OF LIABILITY: IN NO EVENT WILL 3M BE LIABLE FOR ANY INDIRECT, INCIDENTAL, SPECIAL OR CONSEQUENTIAL DAMAGES INCLUDING, BUT NOT LIMITED TO LOSS OF PROFITS, IN ANY WAY RELATED TO THE PRODUCTS REGARDLESS OF THE LEGAL THEORY ASSERTED.

3M Occupational Health & Environmental Safety Division

3M Center Building 235-2W-70
Saint Paul, MN 55144-1000
USA

Technical Assistance: 1-800-243-4630 in U.S.
and 1-800-267-4414 in Canada
www.3M.com/FallProtection
www.3M.com/PPESafety



Please recycle.
© 3M 2012

3M is a trademark of 3M Company, used under license in Canada.
All rights reserved.
TS-00043 Rev A (06-2012)

