

Full Body Harness Inspection Sheet



Serial Number: _____

- Pass
 Remove From Service

Inspector Name: _____ Inspection Date: _____

Model Number: _____ Manufacture Date: _____ Date of First Use: _____

For more information, please see *User Instructions* sent with the product at the time of shipment.

Webbing

To inspect webbing, bend a portion of the webbing 6-8 inches into an upsidedown 'U' shape. Continue along all webbing inspecting for tears, cuts, fraying, abrasion, discoloration, burns, holes, mold, pulled or broken stitches, or other signs of wear and damage. Adjust all keepers, buckles, padding and D-ring to inspect webbing hidden by these components.

- Tears Cuts Fraying Abrasion Pass
 Discoloration Burns Holes Mold Remove From Service

Comments: _____

Hardware/Buckles/Grommets

All hardware must be free of cracks, sharp edges, deformation, corrosion, or any evidence of defect.

- Cracks Sharp Edges Deformation Corrosion Pass
 Chemical Attack Wear Alteration Excessive Heating Remove From Service

Comments: _____

Stitching

Sewn terminations must be secure, complete, and not visibly damaged.

- Broken Missing Load Indicator Warning Pass
 Remove From Service

Comments: _____

Labels

All markings must be legible and attached to the product.

- Illegible Missing Pass
 Remove From Service

Comments: _____

3M Personal Safety Division

3M Center Building 235-2W-70
Saint Paul, MN 55144-1000
USA
Technical Assistance: 800-243-4630 in U.S.
and 800-267-4414 in Canada
www.3M.com/FallProtection
www.3M.com/PPESafety



Please recycle.
© 3M 2013
3M is a trademark of 3M Company, used
under license in Canada.
All rights reserved.
IS-00001 Rev A (07-2013)

