

3M™ Aura™ Health Care Particulate Respirators 1883+

Technical Data Sheet

Description

The 3M™ Aura™ Health Care Particulate Respirator 1883+ provides effective respiratory protection for use in medical environments where health care workers will be exposed to airborne dust particles, non-volatile liquid particles and bio-aerosols. This respirator limits the transmission of infective agents from staff to patients and is suitable for use during surgical procedures and certain other medical procedures. This product also offers resistance to penetration of splashes of liquid.

- Tested to EN 14683:2019 + AC:2019 “Surgical masks – Requirements and test methods” and EN 149:2001+A1:2009 “Respiratory protective devices – Filtering half masks to protect against particles – Requirements, testing, marking”.
- CE approved to the Medical Device and PPE Regulation
- Foldable, patented 3-panel design allows for greater facial movement and comfort and easy storage when not in use.
- Low breathing resistance filter technology gives effective filtration with low breathing resistance for consistent high quality performance
- Sculpted nose panel helps conforms to the nose and contours of the face and helps to improve compatibility with 3M eyewear
- Innovative chin tab designed for ease of donning and adjustment to help achieve a comfortable fit
- Individual hygienic packaging protects the respirator from contamination before use
- Large, soft nosefoam is comfortable on the skin
- Even headband strap pressure improves comfort on the neck, face and head with a secure feel
- The shrouded 3M™ Cool Flow™ exhalation valve offers improved comfort in hot humid environments and/or where work is hard and physical whilst maintaining compliance with the requirements of EN 14683:2005.
- Outer cover and valve shroud provide resistance to fluid splashes.
- Coloured headbands for easy identification: red for FFP3

Materials

The following materials are used in the production of the Aura health care particulate respirator 1883+:

Component	Material
Straps	Polyisoprene
Staples	Steel
Nose Foam	Polyurethane
Nose Clip	Aluminium
Filter	Polypropylene
Valve	Polypropylene
Valve Diaphragm	Polyisoprene
Valve Shroud	Polypropylene

This product does not contain components made from natural rubber latex.

Maximum mass of product = 18 g

Standards

EN 149:2001+A1:2009

These products meet the requirements of European Standard EN 149:2001 + A1:2009, filtering facepiece respirators for use against particles. They should be used to protect the wearer from solid and non-volatile liquid particles only.

Products are classified by filtering efficiency and maximum total inward leakage performance (FFP1, FFP2 and FFP3), also by usability and clogging resistance.

Performance tests in this standard include filter penetration; extended exposure (loading) test; flammability; breathing resistance and total inward leakage. Reusable products are also subjected to cleaning, storage and mandatory clogging resistance tests (clogging is optional for non reusable products). A full copy of EN 149:2001+A1:2009 can be purchased from your national standards body.

Designations:

R = Reusable

NR = Non reusable (single shift use only)

D = Meets the clogging resistance requirements

EN 14683:2019 + AC:2019

This product meets the requirements of European Standard EN 14683:2019 + AC:2019, Surgical masks – requirements and test methods. It should be used to limit the transmission of infective agents exhaled by the wearer to the environment and patients. It also provides additional protection against the penetration of bodily fluids through the product.

Products are classified by bacterial filter efficiency and fluid resistance.

Performance tests in this standard include bacterial filter penetration; pressure drop and fluid resistance. According to clause 5.2.2 Breathability – if the product also provides respiratory protection the differential pressure requirements of this standard do not need to be met, provided that the requirements of the relevant PPE standard (in this case EN 149:2001+A1:2009 clause 7.16 Breathing Resistance) are met. A full copy of EN 14683:2019 + AC:2019 can be purchased from your national standards body.

Designations:

- I = Bacterial Filter Efficiency \geq 95%
- II = Bacterial Filter Efficiency \geq 98%
- R = Splash resistance pressure \geq 120mmHg

Approvals

These products are CE Marked to the requirements of European Regulation (EU) 2016/425. The applicable legislation can be determined by reviewing the Certificate and Declaration of Conformity at <http://www.3M.com/Respiratory/certs>

This product is classified per Rule 1, Annex VIII of the Medical Device Regulation (EU) 2017/745 as a Class 1 device. (See product DoC at above link for details.)

Applications

This respirator is suitable for use in concentrations of solid and non-volatile liquid particles up to the following limits:

Model	EN 14683 Classification	EN 149+A1 Classification	Exhalation Valve	APF*
1883+	IIR	FFP3 NR D	Shrouded valve	20

*APF + Assigned Protection Factor. Figures taken from EN 529:2005 for the UK. Other countries may use different protection factors. Please consult local legislation.

Respiratory protection is only effective if it is correctly selected, fitted and worn throughout the time when the wearer is exposed to hazards.

Storage and Transportation

3M™ Aura™ Health Care Particulate Respirators 1872V+ and 1873V+ have a shelf life of 5 years. End of shelf life is marked both on the product and on the product packaging. Before initial use, always check that the product is within the stated shelf life (use by date). Product should be stored in clean, dry conditions within the temperature range: -20°C to $+25^{\circ}\text{C}$ with a maximum relative humidity of $<80\%$. When storing or transporting this product use original packaging provided.

Disposal

Contaminated products should be disposed as hazardous waste in accordance with national regulations

Fitting Instructions

See figure 1.

Before fitting device, ensure hands are clean. All respirator components should be inspected for damage prior to each use.

1. With reverse side up, separate top and bottom panels to form a cup shape.
2. Ensure both panels are fully unfolded.
3. Cup respirator in one hand with open side towards face. Take both straps in other hand. Hold respirator under chin, with nosepiece up, and pull straps over head.
4. Locate the upper strap across the crown of the head and the lower strap below the ears. Straps must not be twisted. Adjust top and bottom panels for a comfortable fit, ensuring panels are not folded in.
5. Using both hands, mould noseclip to the shape of the lower part of the nose to ensure a close fit and good seal. Pinching the noseclip using only one hand may result in less effective respirator performance.
6. The seal of the respirator on the face should be fit-checked before entering the workplace.



Figure 1:

Product Range:



3M™ Aura™ Health Care Particulate Respirator 1883+

Seal Check

1. Cover the front of the respirator with both hands being careful not to disturb the fit of the respirator.
 - (a) UNVALVED respirator - EXHALE sharply;
 - (b) VALVED respirator - INHALE sharply.
2. If air leaks around the nose, re-adjust the noseclip to eliminate leakage. Repeat the above seal check.
3. If air leaks at the respirator edges, work the straps back along the sides of the head to eliminate leakage. Repeat the above seal check.

If you CANNOT achieve a proper seal DO NOT enter the hazardous area. See your supervisor.

3M recommends that users are face fit tested before using a respirator and that fit testing is repeated regularly as part of their occupational protection program.

For information regarding fit testing procedures, please contact 3M.

Warnings and Limitations

Always be sure that the complete product is:

- Suitable for the application;
- Fitted correctly;
- Worn during all periods of exposure;
- Replaced when necessary.
- Proper selection, training, use and appropriate maintenance are essential in order for the product to help protect the wearer from certain airborne contaminants.
- Failure to follow all instructions on the use of these respiratory protection products and/or failure to properly wear the complete product during all periods of exposure may adversely affect the wearer's health, lead to severe or life threatening illness or permanent disability.
- For suitability and proper use follow local regulations and refer to all information supplied. For more information contact a safety professional/3M representative.
- Before use, the wearer must be trained in use of the complete product in accordance with applicable Health and Safety standards/guidance.
- These product do not protect against gases/vapours such as glutaraldehyde.

- Do not use in atmospheres containing less than 19.5% oxygen. (3M definition. Individual countries may apply their own limits on oxygen deficiency. Seek advice if in doubt).
- Do not use for respiratory protection against atmospheric contaminants/concentrations which are unknown or immediately dangerous to life and health (IDLH).
- Do not use with beards or other facial hair that may inhibit contact between the face and the product thus preventing a good seal.
- These products do not eliminate the risk of contracting any disease or infection.
- Leave the contaminated area immediately if:
 - a. Breathing becomes difficult.
 - b. Dizziness or other distress occurs.
 - c. The respirator becomes damaged
 - d. You taste or smell contaminants, or an irritation occurs
- Discard and replace the respirator if it becomes contaminated with blood or other infectious material, damaged, breathing resistance becomes excessive or at the end of a shift.
- Do not alter, modify, clean or repair this respirator.
- In case of intended use in explosive atmospheres, contact 3M.
- Single use only. Do not reuse.

IMPORTANT NOTICE

The use of the 3M product described within this document assumes that the user has previous experience of this type of product and that it will be used by a competent professional. Before any use of this product it is recommended to complete some trials to validate the performance of the product within its expected application.

All information and specification details contained within this document are inherent to this specific 3M product and would not be applied to other products or environment. Any action or usage of this product made in violation of this document is at the risk of the user.

Personal Safety Division
3M United Kingdom PLC
3M Centre

Cain Road, Bracknell
Berkshire RG12 8HT
0870 60 800 60

www.3M.co.uk/safety

3M Ireland Limited
The Iveagh Building
The Park, Carrickmines
Dublin 18
T: 1 800 320 500

Please recycle. Printed in the UK. 3M is a trademark of the 3M company. Used under licence by 3M subsidiaries and affiliates. © 3M 2023. All rights reserved. 3M 2023. 1883+ V2

