

# 3M™ Peltor™ Technical Datasheet



PELTOR™

## 3M™ Peltor™ ComTac™ XP

MT17H682FB-\*\*

### Product description

The 3M™ Peltor™ ComTac™ XP is designed to help reduce exposure to hazardous levels of noise, improve situational awareness and at the same time enable two-way radio communication in noisy environments.

### Key Features:

- Designed for comfortable use with a ballistic helmet
- Hearing protection
- Level dependent function for situational awareness
- Easy to use and operate
- Foldable for easy storage and transport
- Configuration menu (hidden)
- Functions: release time, balance, external mute mode, EQ mode, plug mode (maintains situational awareness when used in combination with earplugs)
- SNR 39 dB when combined with earplugs
- Automatic switch off after two hours if no function is used
- No software loads or outside power required, complete self-contained headset with power fail safe
- Combat proven
- Tested to military standards

- (A:1) Headband wire
- (A:2) Headband
- (A:3) Headband padding
- (A:4) Microphone for level dep. function
- (A:5) Battery cover
- (A:6) On/off and volume +/- control
- (A:7) 2 x AAA batteries



# 3M™ Peltor™ Technical Datasheet

## Applications

Peltor ComTac XP is designed to be used by infantry soldiers and emergency response units within law enforcement.

## Standards and Approval:

PPE directive 89/686/EEC  
EMC directive 89/336/EEC  
MIL-STD-810F  
EMC-MIL-STD-461F

## Versions:

Description	3M art. no.	EAN/UPC	Colour
MT17H682FB-02 ComTac XP	XH001660584	7318640047297	Olive Green
MT17H682FB-08 SV ComTac XP	XH001660592	7318640047303	Black

## Accessories and Spare parts:

Description	3M art. no.	EAN
1079 SV Battery lid	11003065544	93045933242
HY68 Hygiene kit (attenuation cushions & foam)	XH001652482	7318640025615

## Attenuation

### MT17H682FB-\*\*

Frequency (Hz)	63	125	250	500	1000	2000	4000	8000
Mean attenuation (dB)		11.5	17.9	27.8	30.0	32.1	36.2	40.3
Std deviation (dB)		2.5	2.7	1.8	2.3	3.0	2.0	3.1
Assumed Protection Value (dB)		9.0	15.3	25.9	27.7	29.1	34.2	37.2

SNR=28 db H=31 db M=25 db L=16 db

### MT17H682FB-\*\* in combination with 3M EAR Classic earplug

Frequency (Hz)	63	125	250	500	1000	2000	4000	8000
Mean attenuation (dB)	33,6	35,5	40,8	51,4	44,7	37,0	48,1	44,8
Std deviation (dB)	4,4	5,8	5,0	6,6	4,8	3,6	4,9	4,8
Assumed Protection Value (dB)	29,1	29,7	35,8	44,9	40,0	33,5	43,3	40,0

SNR=39 db H=36 db M=38 db L=36 db

## Important Notice:

3M does not accept liability of any kind, be it direct or consequential (including, but not limited to, loss of profits, business and/or goodwill) arising from reliance upon any information herein provided by 3M. The user is responsible for determining the suitability of the products for their intended use. Nothing in this statement will be deemed to exclude or restrict 3M's liability for death or personal injury arising from its negligence.

## Warranty:

The warranty does not cover any damage caused by neglected maintenance or careless handling. For more information on maintenance, please see the user instruction. For complete warranty condition, contact your dealer or local 3M office

## In the Box:

1 x ComTac XP  
1 x User manual  
2 x AAA batteries

## Technical Data Specifications:

Power: Battery Type: 2 x AAA 1,2-1,5V batteries  
Operating time: ~ 500h (battery & temperature dependent)  
Net Weight: 285g (inc. batteries)  
Operating temperature: -40 °C to +55 °C (battery dependent)  
Storage Temperature: -50 °C to +70 °C



## 3M Personal Safety Division

3M Svenska AB, Box 2341  
SE-331 02 Värnamo  
Sweden  
Phone: +46 (0) 370 65 65 65  
Fax: +46 (0) 370 65 65 99  
Email: peltorcommunications@mmm.com  
Internet: www.3M.com/Peltorcomms

Please recycle. Printed in Sweden.  
© 3M 2014. All rights reserved.  
Bluetooth is a registered trademark of Bluetooth SIG Inc.