

3M™ Lane Marking Applicator M1

**Save time.
Save money.
Save your back.**



The 3M™ Lane Marking Applicator M1 helps you apply tape quickly and safely.

With the new 3M™ Lane Marking Applicator M1, tape application couldn't be easier or faster. An effective solution for marking warehouse traffic lanes and hazardous areas, it helps you easily apply tapes without crawling around on the floor.

3M Lane Marking Applicator M1 pairs perfectly with 3M™ Safety Stripe and Vinyl Tapes, which are a more durable solution for lane or hazard marking than other competitive tapes or painting. OSHA and ANSI approved, these versatile, abrasion- and wear-resistant tapes adhere to a wide variety of surfaces and are simpler to remove than paint.

Start striping smarter today and choose 3M.

When it comes to keeping the workplace safe, we've earned our stripes.



For more than 40 years, 3M™ Safety Stripe and Vinyl Tapes have been helping improve workplace safety with durable, easy-to-apply, easy-to-remove striping.



Competitive Safety Stripe Tape
After only 25 abrasion wear cycles, the black color is wearing away quickly.






3M™ Safety Stripe Tape 5702
After 25 abrasion wear cycles, the tape retains its original color stripes.



Competitive Safety Stripe Tape
After 1,000 abrasion wear cycles, the color black is worn away.



3M™ Safety Stripe Tape 5702
After 1,000 abrasion wear cycles, the black color is still visible.

Product	Size	Description
 6	2"-4" widths	A conformable, colored tape made from vinyl backing with rubber adhesive. Ideal for many lane and safety markings, color coding, abrasion protection, masking, sealing, splicing and other general purpose applications. Available in: Black, Blue, Brown, Green, Orange, Purple, Red, Transparent, White and Yellow.
 7	2"-4" widths	A black/white durable vinyl tape used to identify and mark traffic areas and physical hazards.
 8	2"-4" widths	A black/yellow durable vinyl tape used to identify and mark traffic areas and physical hazards.

For further information, contact your 3M sales representative or the 3M Customer Response Center at 800-362-3550.

Product Use: User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of application.

Warranty, Limited Remedy, and Disclaimer: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. User is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application. Unless an additional warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price. **Limitation of Liability:** Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.



Industrial Adhesives and Tapes Division

Building 225-3S-06
St. Paul, MN 55144-1000
1-800-362-3550
www.3M.com/IATD

3M is a trademark of 3M Company.
Please recycle. Printed in USA.
© 3M 2014. All rights reserved.
70-0716-1668-7