



Standard Abrasives™ Bristle Discs

Cleaning, General Maintenance and Repair (MRO)

Fast running. Consistent finishes.

Facility Maintenance. Automotive Repair. Engine Rebuild.

High-speed discs for most right angle tools.

4-1/2-inch Standard Abrasives Bristle Discs quickly and easily remove paint, stains, adhesives, weld burns, rust, heavy oxides and surface contaminant from large areas. Requires only light pressure, which helps reduce operator fatigue.

Fast running discs with standard TR attachment system.

Fast running 2-inch and 3-inch discs with a standard TR attachment efficiently clean or strip many substances from metal surfaces, without damaging the work piece. An operator quickly and easily achieves a quality, consistent finish with light pressure.





Standard Abrasives™ Bristle Discs

4-1/2-inch Bristle Discs:

- Remove a variety of surface contaminants from large areas
- Maximum operating speed suitable for most right angle tools

2-inch and 3-inch Bristle Discs with standard TR attachment:

- Clean or strip many substances from metal surfaces
- Require only light pressure
- Do not damage work piece
- Fast-running
- Consistent finishes

Standard Abrasives™ Bristle Discs — 4-1/2"

UPC No.	Part No.	Size	Grade	Color	Max. R.P.M.	Discs/Box
051141-43615-9	879702	4-1/2" x 5/8-11	36	Brown	12,000	10
051141-43613-5	879704	4-1/2" x 5/8-11	50	Green	12,000	10
051141-43614-2	879706	4-1/2" x 5/8-11	80	Yellow	12,000	10

Standard Abrasives™ Bristle Discs — 2" and 3"

UPC No.	Part No.	Size	Grade	Color	Trim	Max. R.P.M.	Discs/Box	Boxes/Case
TR Attachment								
051141-43607-4	879404	2"	50	Green	5/8" Tapered	25,000	10	4
051141-43608-1	879406	2"	80	Yellow	5/8" Tapered	25,000	10	4
051141-43609-8	879408	2"	120	White	5/8" Tapered	25,000	10	4
051141-43610-4	879504	3"	50	Green	5/8" Tapered	15,000	10	4
051141-43611-1	879506	3"	80	Yellow	5/8" Tapered	15,000	10	4
051141-43612-8	879508	3"	120	White	5/8" Tapered	15,000	10	4

Product Use: Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application.

Warranty, Limited Remedy and Disclaimer: Unless an additional warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.



3M Abrasive Systems Division
 3M Center
 Building 223-6S-03
 St. Paul, MN 55144-1000

phone 800-423-5444
 fax 800-947-8263
 web StandardAbrasives.com

3M and Standard Abrasives are trademarks of 3M Company. Please recycle. Printed in USA. © 3M 2017. All rights reserved. 61-5002-8356-1