

Woodgrain and Stripe Adhesive Remover 08908

Technical Data Sheet

July, 2014

3M Part No.(s)	3M Part Descriptor(s)
08908	3M [™] Woodgrain and Stripe Adhesive Remover

Product Description This product is designed to remove adhesive residue after the vinyl woodgrain or vinyl stripe has been removed. This product can be applied to baked on paints such as acrylic enamel and base-coat clear-coats.

Features

- Fast removal of adhesive on woodgrain films and stripes.
- Will not harm cured acrylic enamel or base-coat paints.

Typical Physical Properties

Note: The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

Container	24 fl. oz. Aerosol Can Contains 22-3/4 fl. oz.
Color	White
Flash Point - °F	Below -50°F
Consistency	Soft Gel
Solvent	Petroleum Distillates and Alcohol
Propellant	Hydrocarbon

Directions for Use

- 1. Shake well before using.
- 2. Apply in shade with the air temperature and can temperature are at least 60°F (16°C).
- **3.** Do not apply to surfaces above 90°F (32°C).
- **4.** Apply in a criss-cross slow application to adhesive residue.
- **5.** Allow solvent to work 1-2 minutes.
- **6.** Wipe adhesive away using a clean soft cloth.

Applications

To remove adhesive residue on baked on paints such as acrylic enamels, base-coat clear-coats etc. caused by the removal of vinyl woodgrain and stripes.

3M[™] Woodgrain and Stripe Adhesive Remover

08908

Storage and Handling

Store at room temperature. Rotate stock on a "first-in, first-out" basis. When stored at the recommended conditions in original, unopened containers, this product has a shelf life of 24 months.

Precautionary Information

Refer to Product Label and Material Safety Data Sheet for Health and Safety Information before using this product. See link below:

http://solutions.3m.com/wps/portal/3M/en_US/MSDS/Search/?gsaAction=msdsSRA&msdsLocate=en_US

Technical Information

The technical information, recommendations and other statements contained in this document are based upon tests or experience that 3M believes are reliable, but the accuracy or completeness of such information is not guaranteed.

Product Use

Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application.

Warranty, Limited Remedy, and Disclaimer

Unless an additional warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability

Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

For Additional Health and Safety Information



Automotive Aftermarket Division

3M Center, Building 223-6N-01 St. Paul, MN 55144-1000 1-877-666-2277 (1-877-MMM-CARS) www.3M.com/automotive