

3M™ Light Shielding Tape 601B

Product Description

3M™ Light Shielding Tape 601B is a special single coated black PET tape with excellent light shielding performance. This adhesive provides good adhesion on various surfaces and good convertability.

Features and Benefits

- Good adhesion to many kinds of materials including most plastics, glass and metals
- Good cleavage strength on PC at high temperature
- Excellent light insulation
- Easy converting by die-cut

Product Construction/Material Description

Product Number	3M™ Light Shielding Tape 601B
Color	Black
Adhesive / Carrier Type	High Performance Acrylic / PET
Thickness without liner	0.045 mm
Liner Thickness / Type	0.038 mm / PET
Roll Size	Standard: 1000 mm x 100 m log roll Custom size can be supplied by request

Applications

- Light insulating purpose of electronic devices
- General purpose joining and mounting application at indoor and outdoor use
- Holding and bonding of electronic devices
 - BLU bonding to LCD, BLU Module bonding, Appliance

Typical Physical Properties and Performance Characteristics

Note: The following technical information and data should be considered representative or typical only, and should not be used for specification purposes.

Properties of 3M™ Light Shielding Tape 601B

Product Number	3M™ Light Shielding Tape 601B			
	601B			
Adhesive	Acrylic			
Tape Thickness	0.045 mm			
Adhesion 30 min dwell @ RT Modified ASTM D-3330 180 degree peel 2 mil PET backing		oz/in	N/cm	kg/25.4mm
	SS	40	5.0	1.3
	PC	40	5.0	1.3
Adhesion 72 hrs dwell @ RT Modified ASTM D-3330 180 degree peel 2 mil PET backing		oz/in	N/cm	kg/25.4mm
	SS	50	5.5	1.4
	PC	50	5.5	1.4
Shear Strength at RT Modified ASTM D-3654 1000 grams (1x1")	10,000 minutes			
Shear Strength at 70°C (158°F) Modified ASTM D-3654 500 grams (1x1")	10,000 minutes			
Light Insulating Property	99.99%			

Application Techniques

Bond strength is dependent upon the amount of adhesive-to-surface contact developed. Firm application pressure helps develop better adhesive contact and improve bond strength. To obtain optimum adhesion, the bonding surfaces must be clean, dry and well unified. Some typical surface cleaning solvents are isopropyl alcohol or heptane.*

***Note:** Carefully read and follow the manufacturer's precautions and directions for use when using solvents. Ideal tape application temperature range is 21°C to 38°C (70°F to 100°F). Initial tape application to surfaces at temperatures below 10°C (50°F) is not recommended because the adhesive becomes too firm to adhere readily. However, once properly applied, low temperature holding is generally satisfactory.

Environmental Performance

Humidity Resistance:

No significant reduction in bond strength is observed after exposure for 7 days at 32°C (90°F) and 90% relative humidity.

UV Resistance:

When properly applied, nameplates and decorative trim parts are not adversely affected by exposure.

Water Resistance:

Immersion in water has no appreciable effect on the bond strength. After 100 hours at room temperature, the high bond strength is maintained.

Temperature Cycling Resistance:

High bond strength is maintained after cycling four times through:

- 4 hours at 70°C (158°F)
- 4 hours at -29°C (-20°F)
- 4 hours at 22°C (73°F)

Chemical Resistance:

When properly applied, nameplate and decorative trim parts will hold securely after exposure to numerous chemicals including oil, mild acids and alkalis.

Storage

Store in original cartons at 21°C (70°F) and 50% relative humidity.

Shelf Life

If stored under proper conditions, these products retain their performance and properties for two years from date of manufacture.

Safety Data Sheet

Consult Safety Data Sheet before use.

Regulatory

For regulatory information about this product, contact your 3M representative.

Technical Information

The technical information, recommendations and other statements contained in this document are based upon tests or experience that 3M believes are reliable, but the accuracy or completeness of such information is not guaranteed.

Product Use

Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application.

Warranty, Limited Remedy, and Disclaimer

Unless an additional warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability

Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.



Electronics Materials Solutions Division

3M Center, Building 225-3S-06
St. Paul, MN 55144-1000
1-800-251-8634 phone
651-778-4244 fax
www.3M.com/electronics

3M is a trademark of 3M Company.
Please recycle.
© 3M 2014. All rights reserved.
60-5002-0619-2

