

QS1000 Cold Shrink Inline Joint 92-AG6x3-1/C Series with mechanical connectors



Application

3M™ QS1000 Cold Shrink Series Kits are designed for inline splicing up to 12kV U_{max} voltage class, Single core polymeric power cable systems with lead sheath & armour, according to HD 620 (IEC 60502).

Kit Content

3M™ 92-AG6x3-1/C Inline Joint Series includes the Cold Shrink QS1000 silicone splice body with integrated stress control device, conductive electrode, silicone elastomeric insulation and outer semi-conductive layer. Also included are Copper Screen sleeve, Constant Force springs for metallic screen, armour connection components, mechanical connector, and thick walled EPDM rubber Cold Shrink outer tubes to re-build the cable outer jacket.

Product Features

- The versatile design of the prefabricated one-piece cold shrink splice body allows installation on a wide range of cable sizes and types and a fast and easy installation at temperatures ranging from - 20°C to + 50°C.
- No heat or flame is needed during splice body installation.
- Mechanical connector provides quick and easy connection, with no special tooling.
- Solderless earth connection by means of Copper Stocking and Constant Force springs.
- Thick walled, EPDM rubber Cold Shrink outer re-jacketing tubes provide mechanical protection and moisture sealing of the completed Inline joints.
- No special tools are needed during splice installation.

Installation

3M™ Cold Shrink technology ensures quick, easy and safe installation of the QS1000 Splice Body and outer protection tubes by pulling and unwinding the plastic support core in counter clockwise direction.

Detailed instructions for installing the 3M QS1000 Series Inline Joints are included in each kit.

Product Identification

3M™ QS1000 Series Inline Joint kits are marked with supplier name, cable cross section ranges, voltage class and cable type, storage conditions and manufacturing codes for product traceability.

Product Selection

Kit Reference	Diameter over Cable jacket max.(mm)	Diameter over Primary Insulation (mm)	Cross Section (mm ²) 6/10(12)kV & 6.35/11(12)kV
92-AG613-1/C	39	17.7 – 26.0	70 – 150
92-AG623-1/C	46	22.3 – 33.2	185 – 240
92-AG633-1/C	56	28.4 – 42.0	300 – 400

Storage

The shelf life of 3M™ QS1000 Series Inline Joints is specified as 3 years.
Temperature: - 40°C to +50°C.

Performance Tests

3M™ QS1000 Inline Joint Series meet the requirements of the European standard CENELEC HD 628/629. See Independent Test Reports TR-001383, TR-001898, and TR-001543

Product Stewardship

3M has a fundamental concern for all who make, distribute and use its products, and for the environment in which we live. This concern is the basis of our philosophy and policies by which we assess the health and environmental information on our products and then take the appropriate steps to protect employee, the public health and the environment.

Customer Notice

3M encourages its customers and potential users of 3M products to review their applications for such products from the standpoint of human health and environmental quality. To help ensure that 3M products are not used in ways for which they were not intended or tested. 3M personnel are available to assist customers in dealing with ecological and product safety considerations.

Regulatory Status

3M™ QS1000 Series Inline Joints are not subject of the European WEEE and RoHS Directives but meet their requirements



Electrical Markets Division
3M UK PLC, 3M Centre, Cain Rd,
Bracknell RG12 8HT, United Kingdom
0870 609 4639
www.3M.co.uk/electrical

Electrical Markets Division
3M Ireland Ltd, The Iveagh Building, The
Park, Carrickmines, Dublin 18, Ireland
1 800 812 732
www.3M.co.uk/electrical

3M and is a trademarks of the 3M
company.
© 3M 2021. All rights reserved.

Issue B
Document Reference AABCC93742