



Safety Data Sheet

Copyright,2021, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	16-4412-9	Version Number:	18.03
Issue Date:	08/04/21	Supersedes Date:	09/22/20

SECTION 1: Identification

1.1. Product identifier

3M ULTRATHON™ INSECT REPELLENT 8 (SPRAY)

Product Identification Numbers

70-0068-4906-4, 70-0068-4907-2, 70-1001-9373-2, 70-1001-9812-9, 70-1001-9813-7
7000042927, 7010315390, 7100024002, 7100145181, 7100144217

1.2. Recommended use and restrictions on use

Recommended use

INSECT REPELLENT

1.3. Supplier's details

MANUFACTURER:	3M
DIVISION:	Consumer Health and Safety Division
ADDRESS:	3M Center, St. Paul, MN 55144-1000, USA
Telephone:	1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

2.1. Hazard classification

Flammable Aerosol: Category 1.

Gas Under Pressure: Liquefied gas.

Serious Eye Damage/Irritation: Category 2A.

Simple Asphyxiant.

Specific Target Organ Toxicity (single exposure): Category 1.

Specific Target Organ Toxicity (single exposure): Category 3.

2.2. Label elements

Signal word

Danger

Symbols

Flame | Gas cylinder | Exclamation mark | Health Hazard |

Pictograms**Hazard Statements**

Extremely flammable aerosol.

Contains gas under pressure; may explode if heated.

Causes serious eye irritation.

May cause drowsiness or dizziness.

May displace oxygen and cause rapid suffocation.

Causes damage to organs:

cardiovascular system |

Precautionary Statements**General:**

Keep out of reach of children.

Prevention:

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not spray on an open flame or other ignition source.

Pressurized container: Do not pierce or burn, even after use.

Do not breathe dust/fume/gas/mist/vapors/spray.

Use only outdoors or in a well-ventilated area.

Wear eye/face protection.

Do not eat, drink or smoke when using this product.

Wash thoroughly after handling.

Response:

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

If eye irritation persists: Get medical advice/attention.

Specific treatment (see Notes to Physician on this label).

Call a POISON CENTER or doctor/physician if you feel unwell.

Storage:

Protect from sunlight. Do not expose to temperatures exceeding 50C/122F.

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

Notes to Physician:

Exposure may increase myocardial irritability. Do not administer sympathomimetic drugs unless absolutely necessary.

2.3. Hazards not otherwise classified

Repeated exposure may cause skin dryness or cracking.

Supplemental Information:

Intentional concentration and inhalation may be harmful or fatal.

7% of the mixture consists of ingredients of unknown acute oral toxicity.

12% of the mixture consists of ingredients of unknown acute dermal toxicity.

49% of the mixture consists of ingredients of unknown acute inhalation toxicity.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
ISOPROPYL ALCOHOL	67-63-0	20 - 40 Trade Secret *
ISOBUTANE (PROPELLENT)	75-28-5	10 - 30 Trade Secret *
1,1-DIFLUOROETHANE (PROPELLENT)	75-37-6	1 - 5 Trade Secret *
2-ETHYLHEXYL OXYSTEARATE	29710-25-6	1 - 5
ACRYLATE POLYMER	Trade Secret*	1 - 5
N,N-DIETHYL M-TOLUAMIDE	134-62-3	25

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. Get medical attention.

Skin Contact:

No need for first aid is anticipated.

Eye Contact:

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Central nervous system depression (headache, dizziness, drowsiness, incoordination, nausea, slurred speech, giddiness, and unconsciousness). Target organ effects. See Section 11 for additional details.

4.3. Indication of any immediate medical attention and special treatment required

Exposure may increase myocardial irritability. Do not administer sympathomimetic drugs unless absolutely necessary.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Use a fire fighting agent suitable for the surrounding fire.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

Substance

Carbon monoxide

Carbon dioxide

Condition

During Combustion

During Combustion

5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

If possible, seal leaking container. Place leaking containers in a well-ventilated area, preferably an operating exhaust hood, or if necessary outdoors on an impermeable surface until appropriate packaging for the leaking container or its contents is available. Contain spill. Cover spill area with a fire-extinguishing foam. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Avoid eye contact. Keep out of reach of children. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapors/spray. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Do not expose to temperatures exceeding 50C/122F. Store away from heat. Store away from acids. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
ISOPROPYL ALCOHOL	67-63-0	ACGIH	TWA:200 ppm;STEL:400 ppm	A4: Not class. as human carcin
ISOPROPYL ALCOHOL	67-63-0	OSHA	TWA:980 mg/m ³ (400 ppm)	
ISOBUTANE (PROPELLENT)	75-28-5	ACGIH	STEL:1000 ppm	

Natural gas	75-28-5	ACGIH	Limit value not established:	simple asphyxiant
1,1-DIFLUOROETHANE (PROPELLENT)	75-37-6	AIHA	TWA:2700 mg/m3(1000 ppm)	

ACGIH : American Conference of Governmental Industrial Hygienists
 AIHA : American Industrial Hygiene Association
 CMRG : Chemical Manufacturer's Recommended Guidelines
 OSHA : United States Department of Labor - Occupational Safety and Health Administration
 TWA: Time-Weighted-Average
 STEL: Short Term Exposure Limit
 CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Do not remain in area where available oxygen may be reduced. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended: Under normal use conditions, eye exposure is not expected to be significant enough to require eye protection.

- Full Face Shield
- Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Under normal use conditions, skin exposure is not expected to be significant enough to require skin protection. Gloves made from the following material(s) are recommended: Fluoroelastomer

Nitrile Rubber

Respiratory protection

Under normal use conditions, airborne exposures are not expected to be significant enough to require respiratory protection. An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece supplied-air respirator

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state

Liquid -Aerosol

Color

Light Yellow

Specific Physical Form:

Aerosol

Odor

Alcohol, DEET

Odor threshold	No Data Available
pH	4.6 [Details:1% water solution]
Melting point	Not Applicable
Boiling Point	No Data Available
Flash Point	-75 °F [Test Method:Tagliabue Closed Cup] [Details:Flammable Gas]
Evaporation rate	No Data Available
Flammability (solid, gas)	Not Applicable
Flammable Limits(LEL)	1.8 %
Flammable Limits(UEL)	12.7 %
Vapor Pressure	33 mmHg [@ 68 °F]
Vapor Density	No Data Available
Density	.867 g/ml [Details:(Liquid portion only)]
Specific Gravity	0.867 [Ref Std:WATER=1] [Details:(Liquid Portion Only)]
Solubility in Water	Negligible
Solubility- non-water	No Data Available
Partition coefficient: n-octanol/ water	No Data Available
Autoignition temperature	No Data Available
Decomposition temperature	No Data Available
Viscosity	11 centipoise [Test Method:ACS METHOD] [Details:(Liquid portion only)]
Volatile Organic Compounds	63.5 % [Test Method:calculated per CARB title 2]
VOC Less H2O & Exempt Solvents	63.5 % [Test Method:calculated per EPA method 24]

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat

Sparks and/or flames

10.5. Incompatible materials

None known.

10.6. Hazardous decomposition products

Substance

None known.

Condition

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be

relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

May be harmful if inhaled. Simple Asphyxiation: Signs/symptoms may include increased heart rate, rapid respirations, drowsiness, headache, incoordination, altered judgement, nausea, vomiting, lethargy, seizures, coma, and may be fatal.

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

Skin Contact:

Prolonged or repeated exposure may cause: Dermal Defatting: Signs/symptoms may include localized redness, itching, drying and cracking of skin.

Eye Contact:

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion:

May be harmful if swallowed.

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Single exposure, above recommended guidelines, may cause: Cardiac Sensitization: Signs/symptoms may include irregular heartbeat (arrhythmia), faintness, chest pain, and may be fatal.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Dust/Mist(4 hr)		No data available; calculated ATE5 - 12.5 mg/l
Overall product	Ingestion		No data available; calculated ATE2,000 - 5,000 mg/kg
ISOPROPYL ALCOHOL	Dermal	Rabbit	LD50 12,870 mg/kg
ISOPROPYL ALCOHOL	Inhalation-Vapor (4 hours)	Rat	LC50 72.6 mg/l
ISOPROPYL ALCOHOL	Ingestion	Rat	LD50 4,710 mg/kg
ISOBUTANE (PROPELLENT)	Inhalation-	Rat	LC50 276,000 ppm

	Gas (4 hours)		
N,N-DIETHYL M-TOLUAMIDE	Dermal	Rabbit	LD50 4,280 mg/kg
N,N-DIETHYL M-TOLUAMIDE	Inhalation-Dust/Mist (4 hours)	Rat	LC50 6 mg/l
N,N-DIETHYL M-TOLUAMIDE	Ingestion	Rat	LD50 1,892 mg/kg
1,1-DIFLUOROETHANE (PROPELLENT)	Inhalation-Gas (4 hours)	Rat	LC50 > 437,000 ppm
1,1-DIFLUOROETHANE (PROPELLENT)	Ingestion	Rat	LD50 > 1,500 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
ISOPROPYL ALCOHOL	Multiple animal species	No significant irritation
ISOBUTANE (PROPELLENT)	Professional judgement	No significant irritation
N,N-DIETHYL M-TOLUAMIDE	Rabbit	Minimal irritation

Serious Eye Damage/Irritation

Name	Species	Value
ISOPROPYL ALCOHOL	Rabbit	Severe irritant
ISOBUTANE (PROPELLENT)	Professional judgement	No significant irritation
N,N-DIETHYL M-TOLUAMIDE	Rabbit	Moderate irritant

Skin Sensitization

Name	Species	Value
ISOPROPYL ALCOHOL	Guinea pig	Not classified
N,N-DIETHYL M-TOLUAMIDE	Human	Not classified

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
ISOPROPYL ALCOHOL	In Vitro	Not mutagenic
ISOPROPYL ALCOHOL	In vivo	Not mutagenic
ISOBUTANE (PROPELLENT)	In Vitro	Not mutagenic
N,N-DIETHYL M-TOLUAMIDE	In Vitro	Not mutagenic
1,1-DIFLUOROETHANE (PROPELLENT)	In Vitro	Some positive data exist, but the data are not sufficient for classification
1,1-DIFLUOROETHANE (PROPELLENT)	In vivo	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
ISOPROPYL ALCOHOL	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification
N,N-DIETHYL M-TOLUAMIDE	Ingestion	Rat	Not carcinogenic
1,1-DIFLUOROETHANE (PROPELLENT)	Inhalation	Rat	Some positive data exist, but the data are not

sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
ISOPROPYL ALCOHOL	Ingestion	Not classified for development	Rat	NOAEL 400 mg/kg/day	during organogenesis
ISOPROPYL ALCOHOL	Inhalation	Not classified for development	Rat	LOAEL 9 mg/l	during gestation
N,N-DIETHYL M-TOLUAMIDE	Ingestion	Not classified for female reproduction	Rat	NOAEL 250 mg/kg/day	2 generation
N,N-DIETHYL M-TOLUAMIDE	Ingestion	Not classified for male reproduction	Rat	NOAEL 250 mg/kg/day	2 generation
N,N-DIETHYL M-TOLUAMIDE	Ingestion	Not classified for development	Rat	NOAEL 100 mg/kg/day	2 generation
1,1-DIFLUOROETHANE (PROPELLENT)	Inhalation	Not classified for development	Rat	NOAEL 50,000 ppm	during organogenesis

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
ISOPROPYL ALCOHOL	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
ISOPROPYL ALCOHOL	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
ISOPROPYL ALCOHOL	Inhalation	auditory system	Not classified	Guinea pig	NOAEL 13.4 mg/l	24 hours
ISOPROPYL ALCOHOL	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
ISOBUTANE (PROPELLENT)	Inhalation	cardiac sensitization	Causes damage to organs	Multiple animal species	NOAEL Not available	
ISOBUTANE (PROPELLENT)	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
ISOBUTANE (PROPELLENT)	Inhalation	respiratory irritation	Not classified	Mouse	NOAEL Not available	
1,1-DIFLUOROETHANE (PROPELLENT)	Inhalation	cardiac sensitization	Causes damage to organs	Human and animal	NOAEL Not available	poisoning and/or abuse
1,1-DIFLUOROETHANE (PROPELLENT)	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL 100,000 ppm	
1,1-DIFLUOROETHANE (PROPELLENT)	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Not available	NOAEL Not available	not available

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
ISOPROPYL ALCOHOL	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 12.3 mg/l	24 months
ISOPROPYL ALCOHOL	Inhalation	nervous system	Not classified	Rat	NOAEL 12 mg/l	13 weeks
ISOPROPYL ALCOHOL	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 400 mg/kg/day	12 weeks
ISOBUTANE (PROPELLENT)	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 4,500 ppm	13 weeks

N,N-DIETHYL M-TOLUAMIDE	Dermal	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
N,N-DIETHYL M-TOLUAMIDE	Ingestion	liver	Not classified	Rat	NOAEL 2,000 mg/kg/day	90 days
N,N-DIETHYL M-TOLUAMIDE	Ingestion	kidney and/or bladder	Not classified	Rat	LOAEL 100 mg/kg/day	90 days
N,N-DIETHYL M-TOLUAMIDE	Ingestion	nervous system	Not classified	Rat	NOAEL 100 mg/kg/day	2 generation
1,1-DIFLUOROETHANE (PROPELLENT)	Inhalation	hematopoietic system kidney and/or bladder respiratory system	Not classified	Rat	NOAEL 25,000 ppm	2 years

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information**Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations**13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. Facility must be capable of handling aerosol cans. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): D001 (Ignitable)

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information**15.1. US Federal Regulations**

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:**Physical Hazards**

Flammable (gases, aerosols, liquids, or solids)
Gas under pressure

Health Hazards
Hazard Not Otherwise Classified (HNOC)
Serious eye damage or eye irritation
Simple Asphyxiant
Specific target organ toxicity (single or repeated exposure)

FIFRA

Status
Registered

Registration Number
58007-7

This chemical is a pesticide product registered by the United States Environmental Protection Agency and is subject to certain labeling requirements under federal pesticide law. These requirements differ from the classification criteria and hazard information required for safety data sheets (SDS), and for workplace labels of non-pesticide chemicals. The hazard information required on the pesticide label is reproduced below. The pesticide label also includes other important information, including directions for use.
End user must read and follow all information as listed on the product container label according to US EPA regulations.

WARNING
Causes substantial but temporary eye injury.
Harmful if swallowed.
Use of this product may cause skin reactions in rare cases.
FLAMMABLE
Contents under pressure.
Exposure to temperatures above 120F may cause bursting.

15.2. State Regulations
Contact 3M for more information.

15.3. Chemical Inventories
Contact 3M for more information.

15.4. International Regulations
Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification
Health: 2 **Flammability:** 4 **Instability:** 0 **Special Hazards:** None
Aerosol Storage Code: 3

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

HMIS Hazard Classification
Health: 4 **Flammability:** 4 **Physical Hazard:** 0 **Personal Protection:** X - See PPE section.

Hazardous Material Identification System (HMIS® IV) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® IV ratings are to be used with a fully implemented HMIS® IV program. HMIS® is a registered mark of the American Coatings Association (ACA).

Document Group:	16-4412-9	Version Number:	18.03
Issue Date:	08/04/21	Supersedes Date:	09/22/20

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com