



## Safety Data Sheet

Copyright,2017,3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document Group:</b>	18-5336-5	<b>Version Number:</b>	13.01
<b>Issue Date:</b>	11/21/17	<b>Supersedes Date:</b>	11/20/17

### SECTION 1: Identification

#### 1.1. Product identifier

3M(TM) PERFORMANCE FINISH PN 38112, 39030, 06072, Performance Finish Synthetic Wax Protectant PN 39037, 3M(TM) Synthetic Wax PN 39030S

#### Product Identification Numbers

LB-K100-0318-6, LB-K100-0763-2, 60-4300-5031-4, 60-4300-5042-1, 60-4400-9659-6, 60-4400-9660-4, 60-4401-0048-9, 60-4401-0063-8, 60-4550-2922-7, 60-4550-2923-5, 60-4550-2924-3, 60-4550-2935-9, 60-4550-2999-5, 60-4550-3097-7, 60-4550-3306-2, 60-4550-3473-0, 60-4550-3475-5, 60-4550-5288-0, 60-4550-5289-8

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Automotive, Enhances and protects automotive painted surface.

#### 1.3. Supplier's details

<b>MANUFACTURER:</b>	3M
<b>DIVISION:</b>	Automotive Aftermarket
<b>ADDRESS:</b>	3M Center, St. Paul, MN 55144-1000, USA
<b>Telephone:</b>	1-888-3M HELPS (1-888-364-3577)

#### 1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

### SECTION 2: Hazard identification

The label elements below were prepared in accordance with OSHA Hazard Communication Standard, 29 CFR 1910.1200. This information may be different from the actual product label information for labels regulated by other agencies.

#### 2.1. Hazard classification

Flammable Liquid: Category 3.

Reproductive Toxicity: Category 2.

#### 2.2. Label elements

##### Signal word

Warning

**Symbols**

Flame | Health Hazard |

**Pictograms**



**Hazard Statements**

Flammable liquid and vapor.

Suspected of damaging fertility or the unborn child.

**Precautionary Statements**

**General:**

Keep out of reach of children.

**Prevention:**

- Obtain special instructions before use.
- Do not handle until all safety precautions have been read and understood.
- Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
- Ground/bond container and receiving equipment.
- Use only non-sparking tools.
- Take precautionary measures against static discharge.
- Keep container tightly closed.
- Use explosion-proof electrical/ventilating/lighting equipment.
- Wear protective gloves and eye/face protection.

**Response:**

- IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- IF exposed or concerned: Get medical advice/attention.
- In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

**Storage:**

- Store in a well-ventilated place. Keep cool.
- Store locked up.

**Disposal:**

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

4% of the mixture consists of ingredients of unknown acute dermal toxicity.  
9% of the mixture consists of ingredients of unknown acute inhalation toxicity.

**SECTION 3: Composition/information on ingredients**

Ingredient	C.A.S. No.	% by Wt
Water	7732-18-5	40 - 70 Trade Secret *
Dodecamethylcyclohexasiloxane	540-97-6	0 - 15 Trade Secret *
Decamethylcyclopentasiloxane	541-02-6	7 - 13 Trade Secret *
HYDROTREATED LIGHT PETROLEUM	64742-47-8	0 - 9 Trade Secret *

DISTILLATES		
Kaolin, calcined	92704-41-1	3 - 7 Trade Secret *
Isopropyl Alcohol	67-63-0	1 - 5 Trade Secret *
Siloxanes and Silicones, Di-Me, [[[3-[(2-Aminoethyl)Amino]Propyl]Dimethoxysilyl]Oxy]-Terminated	71750-80-6	1 - 5 Trade Secret *
Stoddard Solvent	8052-41-3	1 - 5 Trade Secret *
Siloxanes and Silicones, Di-Me, Hydroxy-Terminated, Reaction Products with Trimethoxymethylsilane and N-[3-(Trimethoxysilyl)Propyl]-1,2-Ethanediamine	69430-37-1	0.1 - 1.0 Trade Secret *
Methyl Alcohol	67-56-1	< 0.2 Trade Secret *

\*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

**Inhalation:**

Remove person to fresh air. If you feel unwell, get medical attention.

**Skin Contact:**

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

**Eye Contact:**

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

**If Swallowed:**

Rinse mouth. If you feel unwell, get medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

## SECTION 5: Fire-fighting measures

### 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

### 5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

### Hazardous Decomposition or By-Products

**Substance**

Formaldehyde  
Carbon monoxide  
Carbon dioxide

**Condition**

During Combustion  
During Combustion  
During Combustion

### 5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

### 6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

### 6.3. Methods and material for containment and cleaning up

Contain spill. Cover spill area with a fire-extinguishing foam. An appropriate aqueous film forming foam (AFFF) is recommended. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Do not use in a confined area with minimal air exchange. Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. Use personal protective equipment (gloves, respirators, etc.) as required. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapor accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

### 7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Protect from sunlight. Store away from heat. Store away from acids. Store away from oxidizing agents. Store away from areas where product may come into contact with food or pharmaceuticals.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

<b>Ingredient</b>	<b>C.A.S. No.</b>	<b>Agency</b>	<b>Limit type</b>	<b>Additional Comments</b>
Decamethylcyclpentasiloxane	541-02-6	AIHA	TWA:10 ppm	
Kerosine (petroleum)	64742-47-8	ACGIH	TWA(as total hydrocarbon vapor, non-aerosol):200 mg/m3	A3: Confirmed animal carcin., SKIN
Naphtha	64742-47-8	OSHA	TWA:400 mg/m3(100 ppm)	
Methyl Alcohol	67-56-1	ACGIH	TWA:200 ppm;STEL:250 ppm	SKIN
Methyl Alcohol	67-56-1	OSHA	TWA:260 mg/m3(200 ppm)	
Isopropyl Alcohol	67-63-0	OSHA	TWA:980 mg/m3(400 ppm)	
Isopropyl Alcohol	67-63-0	ACGIH	TWA:200 ppm;STEL:400 ppm	A4: Not class. as human carcin
Stoddard Solvent	8052-41-3	ACGIH	TWA:100 ppm	
Stoddard Solvent	8052-41-3	OSHA	TWA:2900 mg/m3(500 ppm)	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

## 8.2. Exposure controls

### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

### 8.2.2. Personal protective equipment (PPE)

#### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:  
Safety Glasses with side shields

#### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Butyl Rubber

Fluoroelastomer

Neoprene

#### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

Half facepiece or full facepiece supplied-air respirator

Organic vapor respirators may have short service life.

For questions about suitability for a specific application, consult with your respirator manufacturer.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

<b>General Physical Form:</b>	Liquid
<b>Odor, Color, Grade:</b>	Opaque, colored, viscous liquid; Slightly fragrant
<b>Odor threshold</b>	<i>No Data Available</i>
<b>pH</b>	7.5 - 8.5
<b>Melting point</b>	<i>No Data Available</i>
<b>Boiling Point</b>	212 °F
<b>Flash Point</b>	112 °F [ <i>Test Method</i> :Closed Cup]
<b>Evaporation rate</b>	<i>No Data Available</i>
<b>Flammability (solid, gas)</b>	Not Applicable
<b>Flammable Limits(LEL)</b>	None detected
<b>Flammable Limits(UEL)</b>	None detected
<b>Vapor Pressure</b>	<i>No Data Available</i>
<b>Vapor Density</b>	<i>No Data Available</i>
<b>Density</b>	1.024 g/ml
<b>Specific Gravity</b>	1.024 [ <i>Ref Std</i> :WATER=1]
<b>Solubility in Water</b>	Negligible
<b>Solubility- non-water</b>	<i>No Data Available</i>
<b>Partition coefficient: n-octanol/ water</b>	<i>No Data Available</i>
<b>Autoignition temperature</b>	<i>No Data Available</i>
<b>Decomposition temperature</b>	<i>No Data Available</i>
<b>Viscosity</b>	7,000 - 13,000 centipoise
<b>Hazardous Air Pollutants</b>	0.060 lb HAPS/lb solids [ <i>Test Method</i> :Calculated]
<b>Molecular weight</b>	<i>No Data Available</i>
<b>Volatile Organic Compounds</b>	138 g/l [ <i>Test Method</i> :calculated SCAQMD rule 443.1]
<b>Volatile Organic Compounds</b>	13.3 % weight [ <i>Test Method</i> :calculated per CARB title 2]
<b>Percent volatile</b>	73.4 % weight
<b>VOC Less H2O &amp; Exempt Solvents</b>	357 g/l [ <i>Test Method</i> :calculated SCAQMD rule 443.1]

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

This material is considered to be non reactive under normal use conditions.

### 10.2. Chemical stability

Stable.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

Heat  
Light  
Sparks and/or flames

### 10.5. Incompatible materials

Strong acids  
 Strong oxidizing agents

**10.6. Hazardous decomposition products**

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

**SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

**11.1. Information on Toxicological effects**

**Signs and Symptoms of Exposure**

**Based on test data and/or information on the components, this material may produce the following health effects:**

**Inhalation:**

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

**Skin Contact:**

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. May cause additional health effects (see below).

**Eye Contact:**

Contact with the eyes during product use is not expected to result in significant irritation.

**Ingestion:**

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

**Additional Health Effects:**

**Reproductive/Developmental Toxicity:**

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

**Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-		No data available; calculated ATE >50 mg/l

	Vapor(4 hr)		
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Decamethylcyclopentasiloxane	Dermal	Rabbit	LD50 > 15,000 mg/kg
Decamethylcyclopentasiloxane	Inhalation-Dust/Mist (4 hours)	Rat	LC50 8.7 mg/l
Decamethylcyclopentasiloxane	Ingestion	Rat	LD50 > 24,134 mg/kg
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Dermal	Rabbit	LD50 > 3,160 mg/kg
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 3 mg/l
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Ingestion	Rat	LD50 > 5,000 mg/kg
Dodecamethylcyclohexasiloxane	Dermal	Rat	LD50 > 2,000 mg/kg
Dodecamethylcyclohexasiloxane	Ingestion	Rat	LD50 > 50,000 mg/kg
Kaolin, calcined	Dermal		LD50 estimated to be 2,000 - 5,000 mg/kg
Kaolin, calcined	Ingestion	Rat	LD50 > 2,000 mg/kg
Stoddard Solvent	Inhalation-Vapor		LC50 estimated to be 20 - 50 mg/l
Stoddard Solvent	Dermal	Rabbit	LD50 > 3,000 mg/kg
Stoddard Solvent	Ingestion	Rat	LD50 > 5,000 mg/kg
Siloxanes and Silicones, Di-Me, [[[3-[(2-Aminoethyl)Amino]Propyl]Dimethoxysilyl]Oxy]-Terminated	Ingestion		LD50 estimated to be 300 - 2,000 mg/kg
Isopropyl Alcohol	Dermal	Rabbit	LD50 12,870 mg/kg
Isopropyl Alcohol	Inhalation-Vapor (4 hours)	Rat	LC50 72.6 mg/l
Isopropyl Alcohol	Ingestion	Rat	LD50 4,710 mg/kg
Siloxanes and Silicones, Di-Me, Hydroxy-Terminated, Reaction Products with Trimethoxymethylsilane and N-[3-(Trimethoxysilyl)Propyl]-1,2-Ethanediamine	Dermal		LD50 estimated to be 2,000 - 5,000 mg/kg
Siloxanes and Silicones, Di-Me, Hydroxy-Terminated, Reaction Products with Trimethoxymethylsilane and N-[3-(Trimethoxysilyl)Propyl]-1,2-Ethanediamine	Ingestion	Rat	LD50 > 2,000 mg/kg
Methyl Alcohol	Dermal		LD50 estimated to be 1,000 - 2,000 mg/kg
Methyl Alcohol	Inhalation-Vapor		LC50 estimated to be 10 - 20 mg/l
Methyl Alcohol	Ingestion		LD50 estimated to be 50 - 300 mg/kg

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

Name	Species	Value
Decamethylcyclopentasiloxane	Rabbit	No significant irritation
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Rabbit	Mild irritant
Dodecamethylcyclohexasiloxane	Rabbit	No significant irritation
Stoddard Solvent	Rabbit	Irritant
Isopropyl Alcohol	Multiple animal species	No significant irritation
Methyl Alcohol	Rabbit	Mild irritant

**Serious Eye Damage/Irritation**

Name	Species	Value
Decamethylcyclopentasiloxane	Rabbit	No significant irritation
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Rabbit	Mild irritant
Dodecamethylcyclohexasiloxane	Rabbit	No significant irritation
Stoddard Solvent	Rabbit	No significant irritation
Isopropyl Alcohol	Rabbit	Severe irritant
Methyl Alcohol	Rabbit	Moderate irritant

**Skin Sensitization**

Name	Species	Value
Decamethylcyclopentasiloxane	Mouse	Not classified
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Guinea pig	Not classified
Stoddard Solvent	Guinea pig	Not classified
Isopropyl Alcohol	Guinea pig	Not classified
Methyl Alcohol	Guinea pig	Not classified

**Respiratory Sensitization**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Germ Cell Mutagenicity**

Name	Route	Value
Decamethylcyclopentasiloxane	In Vitro	Not mutagenic
Decamethylcyclopentasiloxane	In vivo	Not mutagenic
HYDROTREATED LIGHT PETROLEUM DISTILLATES	In Vitro	Not mutagenic
Stoddard Solvent	In vivo	Not mutagenic
Stoddard Solvent	In Vitro	Some positive data exist, but the data are not sufficient for classification
Isopropyl Alcohol	In Vitro	Not mutagenic
Isopropyl Alcohol	In vivo	Not mutagenic
Methyl Alcohol	In Vitro	Some positive data exist, but the data are not sufficient for classification
Methyl Alcohol	In vivo	Some positive data exist, but the data are not sufficient for classification

**Carcinogenicity**

Name	Route	Species	Value
Decamethylcyclopentasiloxane	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Stoddard Solvent	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Stoddard Solvent	Inhalation	Human and animal	Some positive data exist, but the data are not sufficient for classification
Isopropyl Alcohol	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification
Methyl Alcohol	Inhalation	Multiple animal species	Not carcinogenic

**Reproductive Toxicity**

**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test Result	Exposure Duration
Decamethylcyclopentasiloxane	Inhalation	Not classified for reproduction and/or development	Rat	NOAEL 2.43 mg/l	2 generation
Decamethylcyclopentasiloxane	Inhalation	Not classified for female reproduction	Rat	NOAEL 2.43 mg/l	2 generation
Decamethylcyclopentasiloxane	Inhalation	Not classified for male reproduction	Rat	NOAEL 2.43 mg/l	2 generation
Dodecamethylcyclohexasiloxane	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	prematuring & during gestation
Dodecamethylcyclohexasiloxane	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	28 days

Dodecamethylcyclohexasiloxane	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	prematuring & during gestation
Stoddard Solvent	Inhalation	Not classified for development	Rat	NOAEL 2.4 mg/l	during organogenesis
Isopropyl Alcohol	Ingestion	Not classified for development	Rat	NOAEL 400 mg/kg/day	during organogenesis
Isopropyl Alcohol	Inhalation	Not classified for development	Rat	LOAEL 9 mg/l	during gestation
Methyl Alcohol	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,600 mg/kg/day	21 days
Methyl Alcohol	Ingestion	Toxic to development	Mouse	LOAEL 4,000 mg/kg/day	during organogenesis
Methyl Alcohol	Inhalation	Toxic to development	Mouse	NOAEL 1.3 mg/l	during organogenesis

**Target Organ(s)**

**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
Stoddard Solvent	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Stoddard Solvent	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Stoddard Solvent	Inhalation	nervous system	Not classified	Dog	NOAEL 6.5 mg/l	4 hours
Stoddard Solvent	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
Isopropyl Alcohol	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Isopropyl Alcohol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Isopropyl Alcohol	Inhalation	auditory system	Not classified	Guinea pig	NOAEL 13.4 mg/l	24 hours
Isopropyl Alcohol	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
Methyl Alcohol	Inhalation	blindness	Causes damage to organs	Human	NOAEL Not available	occupational exposure
Methyl Alcohol	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	not available
Methyl Alcohol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL Not available	6 hours
Methyl Alcohol	Ingestion	blindness	Causes damage to organs	Human	NOAEL Not available	poisoning and/or abuse

**3M(TM) PERFORMANCE FINISH PN 38112, 39030, 06072, Performance Finish Synthetic Wax Protectant PN 39037, 3M(TM) Synthetic Wax PN 39030S 11/21/17**

Methyl Alcohol	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
----------------	-----------	-----------------------------------	-----------------------------------	-------	---------------------	------------------------

**Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Decamethylcyclopentasiloxane	Dermal	hematopoietic system   eyes	Not classified	Rat	NOAEL 1,600 mg/kg/day	28 days
Decamethylcyclopentasiloxane	Inhalation	hematopoietic system   respiratory system   liver   eyes   kidney and/or bladder	Not classified	Rat	NOAEL 2.42 mg/l	2 years
Decamethylcyclopentasiloxane	Ingestion	liver   immune system   respiratory system   heart   hematopoietic system   kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	90 days
Dodecamethylcyclohexasiloxane	Ingestion	endocrine system   liver   respiratory system   nervous system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Stoddard Solvent	Inhalation	nervous system	Not classified	Rat	LOAEL 4.6 mg/l	6 months
Stoddard Solvent	Inhalation	kidney and/or bladder	Not classified	Rat	LOAEL 1.9 mg/l	13 weeks
Stoddard Solvent	Inhalation	respiratory system	Not classified	Multiple animal species	NOAEL 0.6 mg/l	90 days
Stoddard Solvent	Inhalation	bone, teeth, nails, and/or hair   blood   liver   muscles	Not classified	Rat	NOAEL 5.6 mg/l	12 weeks
Stoddard Solvent	Inhalation	heart	Not classified	Multiple animal species	NOAEL 1.3 mg/l	90 days
Isopropyl Alcohol	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 12.3 mg/l	24 months
Isopropyl Alcohol	Inhalation	nervous system	Not classified	Rat	NOAEL 12 mg/l	13 weeks
Isopropyl Alcohol	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 400 mg/kg/day	12 weeks
Methyl Alcohol	Inhalation	liver	Not classified	Rat	NOAEL 6.55 mg/l	4 weeks
Methyl Alcohol	Inhalation	respiratory system	Not classified	Rat	NOAEL 13.1 mg/l	6 weeks
Methyl Alcohol	Ingestion	liver   nervous system	Not classified	Rat	NOAEL 2,500 mg/kg/day	90 days

**Aspiration Hazard**

Name	Value
HYDROTREATED LIGHT PETROLEUM DISTILLATES	Aspiration hazard
Stoddard Solvent	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

**SECTION 12: Ecological information**

**Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

### Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

## SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

## SECTION 15: Regulatory information

### 15.1. US Federal Regulations

Contact 3M for more information.

#### 311/312 Hazard Categories:

Fire Hazard - Yes    Pressure Hazard - No    Reactivity Hazard - No    Immediate Hazard - Yes    Delayed Hazard - Yes

#### EPCRA 311/312 Hazard Classifications (effective January 1, 2018):

##### Physical Hazards

Flammable (gases, aerosols, liquids, or solids)

##### Health Hazards

Reproductive toxicity

### 15.2. State Regulations

Contact 3M for more information.

#### California Proposition 65

<u>Ingredient</u>	<u>C.A.S. No.</u>	<u>Classification</u>
Ethylbenzene	100-41-4	Carcinogen
Cumene	98-82-8	Carcinogen
Methyl Alcohol	67-56-1	Developmental Toxin

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

WARNING: This product contains a chemical known to the State of California to cause cancer.

### 15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA.

Contact 3M for more information.

### 15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

## SECTION 16: Other information

### NFPA Hazard Classification

Health: 1 Flammability: 2 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

### HMIS Hazard Classification

Health: \*1 Flammability: 2 Physical Hazard: 0 Personal Protection: X - See PPE section.

Hazardous Material Identification System (HMIS® IV) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® IV ratings are to be used with a fully implemented HMIS® IV program. HMIS® is a registered mark of the American Coatings Association (ACA).

<b>Document Group:</b>	18-5336-5	<b>Version Number:</b>	13.01
<b>Issue Date:</b>	11/21/17	<b>Supersedes Date:</b>	11/20/17

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at [www.3M.com](http://www.3M.com)