



Safety Data Sheet

Copyright, 2023, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

| | | | |
|------------------------|-----------|-------------------------|----------|
| Document Group: | 18-4660-9 | Version Number: | 9.01 |
| Issue Date: | 01/19/23 | Supersedes Date: | 05/21/18 |

SECTION 1: Identification

1.1. Product identifier

3M(TM) Scotch-Weld(TM) Control Joint Sealant Self-Leveling DP5106 Gray and Control Joint Sealant Self-Leveling 5106 Gray, Part A

Product Identification Numbers

62-3627-8535-4
7010310208

1.2. Recommended use and restrictions on use

Recommended use

Structural adhesive

1.3. Supplier's details

| | |
|----------------------|---|
| MANUFACTURER: | 3M |
| DIVISION: | Industrial Adhesives and Tapes Division |
| ADDRESS: | 3M Center, St. Paul, MN 55144-1000, USA |
| Telephone: | 1-888-3M HELPS (1-888-364-3577) |

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

2.1. Hazard classification

Serious Eye Damage/Irritation: Category 2A.
Skin Corrosion/Irritation: Category 2.
Respiratory Sensitizer: Category 1.
Skin Sensitizer: Category 1.
Specific Target Organ Toxicity (single exposure): Category 3.
Specific Target Organ Toxicity (repeated exposure): Category 1.

2.2. Label elements

Signal word

Danger

Symbols

Exclamation mark | Health Hazard |

Pictograms



Hazard Statements

Causes serious eye irritation.

Causes skin irritation.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

May cause respiratory irritation.

Causes damage to organs through prolonged or repeated exposure:
respiratory system |

Precautionary Statements

Prevention:

Do not breathe dust/fume/gas/mist/vapors/spray.

Use only outdoors or in a well-ventilated area.

In case of inadequate ventilation wear respiratory protection.

Wear protective gloves and eye/face protection.

Do not eat, drink or smoke when using this product.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Response:

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

IF ON SKIN: Wash with plenty of soap and water.

If skin irritation or rash occurs: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

Get medical advice/attention if you feel unwell.

Storage:

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

Supplemental Information:

Persons previously sensitized to isocyanates may develop a cross-sensitization reaction to other isocyanates.

SECTION 3: Composition/information on ingredients

| Ingredient | C.A.S. No. | % by Wt |
|------------|------------|---------|
|------------|------------|---------|

| | | |
|---|------------|------------------------|
| polyurethane prepolymer | 9042-82-4 | 50 - 80 Trade Secret * |
| dicyclohexylmethane-4,4'-diisocyanate (HMDI) | 5124-30-1 | 15 - 40 Trade Secret * |
| 1,1'-methylenebis(isocyanatobenzene) | 26447-40-5 | < 5 Trade Secret * |
| benzene, 1,1'-methylenebis[isocyanato-, homopolymer | 39310-05-9 | < 4 Trade Secret * |
| P,P'-Methylenebis(phenyl isocyanate) | 101-68-8 | < 4 Trade Secret * |
| amorphous silica | 68909-20-6 | <= 2 Trade Secret * |

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Irritating to the respiratory tract (coughing, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain). Allergic respiratory reaction (difficulty breathing, wheezing, cough, and tightness of chest). Allergic skin reaction (redness, swelling, blistering, and itching). Target organ effects following prolonged or repeated exposure. See Section 11 for additional details.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance

Carbon monoxide
Carbon dioxide
Hydrogen Cyanide
Oxides of Nitrogen
Toxic Vapor, Gas, Particulate

Condition

During Combustion
During Combustion
During Combustion
During Combustion
During Combustion

5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Pour isocyanate decontaminant solution (90% water, 8% concentrated ammonia, 2% detergent) on spill and allow to react for 10 minutes. Or pour water on spill and allow to react for more than 30 minutes. Cover with absorbent material. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a container approved for transportation by appropriate authorities, but do not seal the container for 48 hours to avoid pressure build-up. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed to prevent contamination with water or air. If contamination is suspected, do not reseal container. Store away from acids. Store away from strong bases.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

| Ingredient | C.A.S. No. | Agency | Limit type | Additional Comments |
|--|------------|--------|--|---------------------|
| P,P'-Methylenebis(phenyl isocyanate) | 101-68-8 | ACGIH | TWA:0.005 ppm | |
| P,P'-Methylenebis(phenyl isocyanate) | 101-68-8 | OSHA | CEIL:0.2 mg/m3(0.02 ppm) | |
| dicyclohexylmethane-4,4'-diisocyanate (HMDI) | 5124-30-1 | ACGIH | TWA:0.005 ppm | |
| SILICA, AMORPHOUS | 68909-20-6 | OSHA | TWA:20 millions of particles/cu. ft.;TWA concentration:0.8 mg/m3 | |

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average
STEL: Short Term Exposure Limit
CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields
Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state
Color

Liquid
Colorless

Specific Physical Form:

Viscous

Odor

Low Odor

Odor threshold

No Data Available

pH

Not Applicable

Melting point

No Data Available

Boiling Point

>=400 °F

Flash Point

>=290 °F [*Test Method:* Tagliabue Closed Cup]

Evaporation rate

<=1 [*Details:* Gels with exposure to humidity.]

| | |
|---|---|
| Flammability (solid, gas) | Not Applicable |
| Flammable Limits(LEL) | <i>Not Applicable</i> |
| Flammable Limits(UEL) | <i>Not Applicable</i> |
| Vapor Pressure | <=0.000004 mmHg [@ 68 °F] |
| Vapor Density | >=1 [Ref Std: AIR=1] |
| Density | 1.04 g/ml |
| Specific Gravity | 1.04 [Ref Std: WATER=1] |
| Solubility in Water | Negligible |
| Solubility- non-water | <i>No Data Available</i> |
| Partition coefficient: n-octanol/ water | <i>No Data Available</i> |
| Autoignition temperature | <i>Not Applicable</i> |
| Decomposition temperature | <i>No Data Available</i> |
| Viscosity | 1,300 - 2,000 centipoise |
| Hazardous Air Pollutants | <= 10 % weight [Test Method: Calculated] |
| Molecular weight | <i>No Data Available</i> |
| VOC Less H2O & Exempt Solvents | 1 g/l [Test Method: calculated SCAQMD rule 443.1] [Details: when used as intended with Part B] |
| VOC Less H2O & Exempt Solvents | 1 g/l [Test Method: calculated SCAQMD rule 443.1] [Details: as supplied] |
| VOC Less H2O & Exempt Solvents | 0.1 % [Test Method: calculated SCAQMD rule 443.1] [Details: when used as intended with Part B] |

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

Water

Strong acids

Strong bases

10.6. Hazardous decomposition products

Substance

None known.

Condition

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Allergic Respiratory Reaction: Signs/symptoms may include difficulty breathing, wheezing, cough, and tightness of chest.

May cause additional health effects (see below).

Skin Contact:

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain.

Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Additional Health Effects:

Prolonged or repeated exposure may cause target organ effects:

Respiratory Effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish colored skin (cyanosis), sputum production, changes in lung function tests, and/or respiratory failure.

Additional Information:

Persons previously sensitized to isocyanates may develop a cross-sensitization reaction to other isocyanates.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

| Name | Route | Species | Value |
|--|--------------------------------|---------|--|
| Overall product | Ingestion | | No data available; calculated ATE >5,000 mg/kg |
| dicyclohexylmethane-4,4'-diisocyanate (HMDI) | Dermal | Rat | LD50 > 7,000 mg/kg |
| dicyclohexylmethane-4,4'-diisocyanate (HMDI) | Inhalation-Dust/Mist (4 hours) | Rat | LC50 0.33 mg/l |
| dicyclohexylmethane-4,4'-diisocyanate (HMDI) | Ingestion | Rat | LD50 18,200 mg/kg |
| 1,1'-methylenebis(isocyanatobenzene) | Dermal | Rabbit | LD50 > 5,000 mg/kg |
| 1,1'-methylenebis(isocyanatobenzene) | Inhalation-Dust/Mist (4 hours) | Rat | LC50 0.368 mg/l |
| 1,1'-methylenebis(isocyanatobenzene) | Ingestion | Rat | LD50 31,600 mg/kg |
| P,P'-Methylenebis(phenyl isocyanate) | Dermal | Rabbit | LD50 > 5,000 mg/kg |
| P,P'-Methylenebis(phenyl isocyanate) | Inhalation-Dust/Mist (4 hours) | Rat | LC50 0.368 mg/l |
| P,P'-Methylenebis(phenyl isocyanate) | Ingestion | Rat | LD50 31,600 mg/kg |

| | | | |
|---|--------------------------------|--------|--------------------|
| benzene, 1,1'-methylenebis[isocyanato-, homopolymer | Dermal | Rabbit | LD50 > 5,000 mg/kg |
| benzene, 1,1'-methylenebis[isocyanato-, homopolymer | Inhalation-Dust/Mist (4 hours) | Rat | LC50 0.368 mg/l |
| benzene, 1,1'-methylenebis[isocyanato-, homopolymer | Ingestion | Rat | LD50 31,600 mg/kg |
| amorphous silica | Dermal | Rabbit | LD50 > 5,000 mg/kg |
| amorphous silica | Inhalation-Dust/Mist (4 hours) | Rat | LC50 > 0.691 mg/l |
| amorphous silica | Ingestion | Rat | LD50 > 5,110 mg/kg |

ATE = acute toxicity estimate

Skin Corrosion/Irritation

| Name | Species | Value |
|---|-------------------------|---------------------------|
| dicyclohexylmethane-4,4'-diisocyanate (HMDI) | Rabbit | Irritant |
| 1,1'-methylenebis(isocyanatobenzene) | official classification | Irritant |
| P,P'-Methylenebis(phenyl isocyanate) | official classification | Irritant |
| benzene, 1,1'-methylenebis[isocyanato-, homopolymer | official classification | Irritant |
| amorphous silica | Rabbit | No significant irritation |

Serious Eye Damage/Irritation

| Name | Species | Value |
|---|-------------------------|---------------------------|
| dicyclohexylmethane-4,4'-diisocyanate (HMDI) | Rabbit | Mild irritant |
| 1,1'-methylenebis(isocyanatobenzene) | official classification | Severe irritant |
| P,P'-Methylenebis(phenyl isocyanate) | official classification | Severe irritant |
| benzene, 1,1'-methylenebis[isocyanato-, homopolymer | official classification | Severe irritant |
| amorphous silica | Rabbit | No significant irritation |

Skin Sensitization

| Name | Species | Value |
|---|-------------------------|----------------|
| dicyclohexylmethane-4,4'-diisocyanate (HMDI) | Human and animal | Sensitizing |
| 1,1'-methylenebis(isocyanatobenzene) | official classification | Sensitizing |
| P,P'-Methylenebis(phenyl isocyanate) | official classification | Sensitizing |
| benzene, 1,1'-methylenebis[isocyanato-, homopolymer | official classification | Sensitizing |
| amorphous silica | Human and animal | Not classified |

Respiratory Sensitization

| Name | Species | Value |
|------|---------|-------|
|------|---------|-------|

| | | |
|---|-----------------------|-------------|
| dicyclohexylmethane-4,4'-diisocyanate (HMDI) | Professional judgment | Sensitizing |
| 1,1'-methylenebis(isocyanatobenzene) | Human | Sensitizing |
| P,P'-Methylenebis(phenyl isocyanate) | Human | Sensitizing |
| benzene, 1,1'-methylenebis[isocyanato-, homopolymer | Human | Sensitizing |

Germ Cell Mutagenicity

| Name | Route | Value |
|---|----------|--|
| dicyclohexylmethane-4,4'-diisocyanate (HMDI) | In Vitro | Not mutagenic |
| 1,1'-methylenebis(isocyanatobenzene) | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| P,P'-Methylenebis(phenyl isocyanate) | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| benzene, 1,1'-methylenebis[isocyanato-, homopolymer | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| amorphous silica | In Vitro | Not mutagenic |

Carcinogenicity

| Name | Route | Species | Value |
|---|---------------|---------|--|
| 1,1'-methylenebis(isocyanatobenzene) | Inhalation | Rat | Some positive data exist, but the data are not sufficient for classification |
| P,P'-Methylenebis(phenyl isocyanate) | Inhalation | Rat | Some positive data exist, but the data are not sufficient for classification |
| benzene, 1,1'-methylenebis[isocyanato-, homopolymer | Inhalation | Rat | Some positive data exist, but the data are not sufficient for classification |
| amorphous silica | Not Specified | Mouse | Some positive data exist, but the data are not sufficient for classification |

Reproductive Toxicity

Reproductive and/or Developmental Effects

| Name | Route | Value | Species | Test Result | Exposure Duration |
|---|------------|--|---------|-----------------------|--------------------------|
| dicyclohexylmethane-4,4'-diisocyanate (HMDI) | Inhalation | Not classified for female reproduction | Rat | NOAEL 6 mg/m3 | premating into lactation |
| dicyclohexylmethane-4,4'-diisocyanate (HMDI) | Inhalation | Not classified for male reproduction | Rat | NOAEL 6 mg/m3 | 28 days |
| dicyclohexylmethane-4,4'-diisocyanate (HMDI) | Inhalation | Not classified for development | Rat | NOAEL 6 mg/m3 | during gestation |
| 1,1'-methylenebis(isocyanatobenzene) | Inhalation | Not classified for development | Rat | NOAEL 0.004 mg/l | during organogenesis |
| P,P'-Methylenebis(phenyl isocyanate) | Inhalation | Not classified for development | Rat | NOAEL 0.004 mg/l | during organogenesis |
| benzene, 1,1'-methylenebis[isocyanato-, homopolymer | Inhalation | Not classified for development | Rat | NOAEL 0.004 mg/l | during organogenesis |
| amorphous silica | Ingestion | Not classified for female reproduction | Rat | NOAEL 509 mg/kg/day | 1 generation |
| amorphous silica | Ingestion | Not classified for male reproduction | Rat | NOAEL 497 mg/kg/day | 1 generation |
| amorphous silica | Ingestion | Not classified for development | Rat | NOAEL 1,350 mg/kg/day | during organogenesis |

Target Organ(s)

Specific Target Organ Toxicity - single exposure

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|---|------------|------------------------|----------------------------------|-------------------------|---------------------|-------------------|
| dicyclohexylmethane-4,4'-diisocyanate (HMDI) | Inhalation | respiratory irritation | May cause respiratory irritation | Rat | NOAEL not available | |
| 1,1'-methylenebis(isocyanatobenzene) | Inhalation | respiratory irritation | May cause respiratory irritation | official classification | NOAEL Not available | |
| P,P'-Methylenebis(phenyl isocyanate) | Inhalation | respiratory irritation | May cause respiratory irritation | official classification | NOAEL Not available | |
| benzene, 1,1'-methylenebis(isocyanato-, homopolymer | Inhalation | respiratory irritation | May cause respiratory irritation | official classification | NOAEL Not available | |

Specific Target Organ Toxicity - repeated exposure

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|---|------------|---|--|---------|---------------------|-----------------------|
| dicyclohexylmethane-4,4'-diisocyanate (HMDI) | Inhalation | respiratory system | Not classified | Rat | NOAEL 3 mg/m3 | 90 days |
| dicyclohexylmethane-4,4'-diisocyanate (HMDI) | Inhalation | heart skin endocrine system gastrointestinal tract bone, teeth, nails, and/or hair hematopoietic system liver immune system muscles nervous system eyes kidney and/or bladder vascular system | Not classified | Rat | NOAEL 18 mg/m3 | 90 days |
| 1,1'-methylenebis(isocyanatobenzene) | Inhalation | respiratory system | Causes damage to organs through prolonged or repeated exposure | Rat | LOAEL 0.004 mg/l | 13 weeks |
| P,P'-Methylenebis(phenyl isocyanate) | Inhalation | respiratory system | Causes damage to organs through prolonged or repeated exposure | Rat | LOAEL 0.004 mg/l | 13 weeks |
| benzene, 1,1'-methylenebis(isocyanato-, homopolymer | Inhalation | respiratory system | Causes damage to organs through prolonged or repeated exposure | Rat | LOAEL 0.004 mg/l | 13 weeks |
| amorphous silica | Inhalation | respiratory system silicosis | Not classified | Human | NOAEL Not available | occupational exposure |

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): Not regulated

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:

Physical Hazards

Not applicable

Health Hazards

Respiratory or Skin Sensitization

Serious eye damage or eye irritation

Skin Corrosion or Irritation

Specific target organ toxicity (single or repeated exposure)

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

| <u>Ingredient</u> | <u>C.A.S. No</u> | <u>% by Wt</u> |
|--|-------------------------|-----------------------|
| dicyclohexylmethane-4,4'-diisocyanate (HMDI) | 5124-30-1 | Trade Secret 15 - 40 |
| dicyclohexylmethane-4,4'-diisocyanate (HMDI) (DIISOCYANATES (CERTAIN CHEMICALS ONLY)) | 5124-30-1 | Trade Secret 15 - 40 |
| P,P'-Methylenebis(phenyl isocyanate) | 101-68-8 | Trade Secret < 4 |
| P,P'-Methylenebis(phenyl isocyanate) (Benzene, 1,1'-methylenebis[4-isocyanato-]) | 101-68-8 | Trade Secret < 4 |
| P,P'-Methylenebis(phenyl isocyanate) (DIISOCYANATES (CERTAIN CHEMICALS ONLY)) | 101-68-8 | Trade Secret < 4 |

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA. All required

components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 2 **Flammability:** 1 **Instability:** 1 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

| | | | |
|------------------------|-----------|-------------------------|----------|
| Document Group: | 18-4660-9 | Version Number: | 9.01 |
| Issue Date: | 01/19/23 | Supersedes Date: | 05/21/18 |

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com