



## Safety Data Sheet

Copyright,2018,3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document Group:</b>	11-2978-2	<b>Version Number:</b>	41.00
<b>Issue Date:</b>	05/21/18	<b>Supersedes Date:</b>	01/12/18

### SECTION 1: Identification

#### 1.1. Product identifier

3M(tm) Adhesion Promoter K-500

#### Product Identification Numbers

70-0704-5766-1, 70-0704-5854-5, 75-3472-0928-2, JT-2400-0079-7, JT-2400-1339-4

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Adhesion Promoter

#### 1.3. Supplier's details

<b>MANUFACTURER:</b>	3M
<b>DIVISION:</b>	3M Japan
	Automotive and Aerospace Solutions Division
<b>ADDRESS:</b>	3M Center, St. Paul, MN 55144-1000, USA
<b>Telephone:</b>	1-888-3M HELPS (1-888-364-3577)

#### 1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

### SECTION 2: Hazard identification

#### 2.1. Hazard classification

Flammable Liquid: Category 2.  
Serious Eye Damage/Irritation: Category 2A.  
Skin Corrosion/Irritation: Category 2.  
Respiratory Sensitizer: Category 1.  
Skin Sensitizer: Category 1.  
Aspiration Hazard: Category 1.  
Reproductive Toxicity: Category 1B.  
Specific Target Organ Toxicity (single exposure): Category 3.  
Specific Target Organ Toxicity (repeated exposure): Category 1.

#### 2.2. Label elements

Signal word

Danger

**Symbols**

Flame | Exclamation mark | Health Hazard |

**Pictograms****Hazard Statements**

Highly flammable liquid and vapor.

Causes serious eye irritation.

Causes skin irritation.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

May be fatal if swallowed and enters airways.

May cause drowsiness or dizziness.

May damage fertility or the unborn child.

Causes damage to organs through prolonged or repeated exposure:

nervous system |

respiratory system |

sensory organs |

**Precautionary Statements****Prevention:**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Keep container tightly closed.

Use explosion-proof electrical/ventilating/lighting equipment.

Do not breathe dust/fume/gas/mist/vapors/spray.

Use only outdoors or in a well-ventilated area.

In case of inadequate ventilation wear respiratory protection.

Wear protective gloves and eye/face protection.

Do not eat, drink or smoke when using this product.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

**Response:**

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

If eye irritation persists: Get medical advice/attention.

If skin irritation or rash occurs: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

Do NOT induce vomiting.

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

IF exposed or concerned: Get medical advice/attention.

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

**Storage:**

Store in a well-ventilated place. Keep container tightly closed.

Keep cool.

Store locked up.

**Disposal:**

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

5% of the mixture consists of ingredients of unknown acute oral toxicity.

5% of the mixture consists of ingredients of unknown acute dermal toxicity.

5% of the mixture consists of ingredients of unknown acute inhalation toxicity.

### SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
TOLUENE	108-88-3	85 - 95 Trade Secret *
CHLORINATED POLYPROPYLENE	68442-33-1	1 - 5
P,P'-Methylenebis(phenyl isocyanate)	101-68-8	1 - 5 Trade Secret *
POLYMETHYLENE POLYPHENYLENE ISOCYANATE	9016-87-9	1 - 5 Trade Secret *
EPICHLOROHYDRIN-TRIMETHYLOLPROPANE COPOLYMER	30499-70-8	0.1 - 1 Trade Secret *

\*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

**Inhalation:**

Remove person to fresh air. If you feel unwell, get medical attention.

**Skin Contact:**

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

**Eye Contact:**

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

**If Swallowed:**

Do not induce vomiting. Get immediate medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

**4.3. Indication of any immediate medical attention and special treatment required**

Not applicable

**SECTION 5: Fire-fighting measures****5.1. Suitable extinguishing media**

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

**5.2. Special hazards arising from the substance or mixture**

Closed containers exposed to heat from fire may build pressure and explode.

**Hazardous Decomposition or By-Products**

<u>Substance</u>	<u>Condition</u>
Isocyanates	During Combustion
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Hydrogen Chloride	During Combustion
Hydrogen Cyanide	During Combustion
Oxides of Nitrogen	During Combustion

**5.3. Special protective actions for fire-fighters**

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

**6.2. Environmental precautions**

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

**6.3. Methods and material for containment and cleaning up**

Contain spill. Cover spill area with a fire-extinguishing foam. An appropriate aqueous film forming foam (AFFF) is recommended. Pour isocyanate decontaminant solution (90% water, 8% concentrated ammonia, 2% detergent) on spill and allow to react for 10 minutes. Or pour water on spill and allow to react for more than 30 minutes. Cover with absorbent material. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a container approved for transportation by appropriate authorities, but do not seal the container for 48 hours to avoid pressure build-up. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

**SECTION 7: Handling and storage**

**7.1. Precautions for safe handling**

For industrial or professional use only. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. Use personal protective equipment (gloves, respirators, etc.) as required. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapor accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

**7.2. Conditions for safe storage including any incompatibilities**

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store away from heat. Store away from acids. Store away from oxidizing agents.

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters****Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

<b>Ingredient</b>	<b>C.A.S. No.</b>	<b>Agency</b>	<b>Limit type</b>	<b>Additional Comments</b>
P,P'-Methylenebis(phenyl isocyanate)	101-68-8	ACGIH	TWA:0.005 ppm	
P,P'-Methylenebis(phenyl isocyanate)	101-68-8	OSHA	CEIL:0.2 mg/m3(0.02 ppm)	
TOLUENE	108-88-3	ACGIH	TWA:20 ppm	A4: Not class. as human carcin
TOLUENE	108-88-3	OSHA	TWA:200 ppm;CEIL:300 ppm	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

**8.2. Exposure controls****8.2.1. Engineering controls**

Provide ventilated enclosure for heat curing. Curing enclosures must be exhausted to outdoors or to a suitable emission control device. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

**8.2.2. Personal protective equipment (PPE)****Eye/face protection**

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect Vented Goggles

**Skin/hand protection**

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Neoprene  
Nitrile Rubber  
Natural Rubber

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - Neoprene

Apron – Nitrile  
Apron - polymer laminate

**Respiratory protection**

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

<b>General Physical Form:</b>	Liquid
<b>Specific Physical Form:</b>	Liquid
<b>Odor, Color, Grade:</b>	Solvent odor, clear to amber.
<b>Odor threshold</b>	<i>No Data Available</i>
<b>pH</b>	<i>Not Applicable</i>
<b>Melting point</b>	<i>No Data Available</i>
<b>Boiling Point</b>	111 °C [ <i>Test Method:Estimated</i> ] [ <i>Details:Based On Toluene.</i> ]
<b>Flash Point</b>	4 °C [ <i>Test Method:Tagliabue Closed Cup</i> ] [ <i>Details:Based on Toluene</i> ]
<b>Evaporation rate</b>	Approximately 1 [ <i>Ref Std:TOLUENE=1</i> ]
<b>Flammability (solid, gas)</b>	Not Applicable
<b>Flammable Limits(LEL)</b>	1 % volume
<b>Flammable Limits(UEL)</b>	7.2 % volume
<b>Vapor Pressure</b>	22 mmHg [ <i>Details:@20 deg C</i> ]
<b>Vapor Density</b>	3.14 [ <i>Ref Std:AIR=1</i> ]
<b>Density</b>	0.88 g/cm <sup>3</sup>
<b>Specific Gravity</b>	0.88 [ <i>Ref Std:WATER=1</i> ]
<b>Solubility in Water</b>	Nil
<b>Solubility- non-water</b>	<i>No Data Available</i>
<b>Partition coefficient: n-octanol/ water</b>	<i>No Data Available</i>
<b>Autoignition temperature</b>	480 °C [ <i>Test Method:Estimated</i> ] [ <i>Details:Based On Toluene.</i> ]
<b>Decomposition temperature</b>	<i>No Data Available</i>
<b>Viscosity</b>	<=10 centipoise [ <i>Details:@23 deg C</i> ]
<b>Molecular weight</b>	<i>No Data Available</i>
<b>Volatile Organic Compounds</b>	810 g/l
<b>Percent volatile</b>	<=95 % weight
<b>VOC Less H<sub>2</sub>O &amp; Exempt Solvents</b>	< 836 g/l

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

This material is considered to be non reactive under normal use conditions.

### 10.2. Chemical stability

Stable.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

Heat  
Sparks and/or flames  
Temperatures above the boiling point

### 10.5. Incompatible materials

Strong oxidizing agents

### 10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

### 11.1. Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation:

May be harmful if inhaled.

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Allergic Respiratory Reaction: Signs/symptoms may include difficulty breathing, wheezing, cough, and tightness of chest.

May cause additional health effects (see below).

#### Skin Contact:

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain.

Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

**Eye Contact:**

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

**Ingestion:**

Chemical (Aspiration) Pneumonitis: Signs/symptoms may include coughing, gasping, choking, burning of the mouth, difficulty breathing, bluish colored skin (cyanosis), and may be fatal.

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

**Additional Health Effects:****Single exposure may cause target organ effects:**

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

**Prolonged or repeated exposure may cause target organ effects:**

Ocular Effects: Signs/symptoms may include blurred or significantly impaired vision.

Auditory Effects: Signs/symptoms may include hearing impairment, balance dysfunction and ringing in the ears.

Olfactory Effects: Signs/symptoms may include decreased ability to detect odors and/or complete loss of smell.

Neurological Effects: Signs/symptoms may include personality changes, lack of coordination, sensory loss, tingling or numbness of the extremities, weakness, tremors, and/or changes in blood pressure and heart rate.

Respiratory Effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish colored skin (cyanosis), sputum production, changes in lung function tests, and/or respiratory failure.

**Reproductive/Developmental Toxicity:**

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

**Additional Information:**

Persons previously sensitized to isocyanates may develop a cross-sensitization reaction to other isocyanates.

**Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Vapor(4 hr)		No data available; calculated ATE <sub>20</sub> - 50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
TOLUENE	Dermal	Rat	LD <sub>50</sub> 12,000 mg/kg
TOLUENE	Inhalation-Vapor (4 hours)	Rat	LC <sub>50</sub> 30 mg/l
TOLUENE	Ingestion	Rat	LD <sub>50</sub> 5,550 mg/kg
POLYMETHYLENE POLYPHENYLENE ISOCYANATE	Dermal	Rabbit	LD <sub>50</sub> > 5,000 mg/kg
POLYMETHYLENE POLYPHENYLENE ISOCYANATE	Inhalation-Dust/Mist (4 hours)	Rat	LC <sub>50</sub> 0.368 mg/l



POLYMETHYLENE POLYPHENYLENE ISOCYANATE	Ingestion	Rat	LD50 31,600 mg/kg
P,P'-Methylenebis(phenyl isocyanate)	Dermal	Rabbit	LD50 > 5,000 mg/kg
P,P'-Methylenebis(phenyl isocyanate)	Inhalation-Dust/Mist (4 hours)	Rat	LC50 0.368 mg/l
P,P'-Methylenebis(phenyl isocyanate)	Ingestion	Rat	LD50 31,600 mg/kg
EPICHLOROHYDRIN-TRIMETHYLOLPROPANE COPOLYMER	Dermal	Rat	LD50 > 2,000 mg/kg
EPICHLOROHYDRIN-TRIMETHYLOLPROPANE COPOLYMER	Ingestion	Rat	LD50 > 2,000 mg/kg

ATE = acute toxicity estimate

### Skin Corrosion/Irritation

Name	Species	Value
TOLUENE	Rabbit	Irritant
POLYMETHYLENE POLYPHENYLENE ISOCYANATE	official classification	Irritant
P,P'-Methylenebis(phenyl isocyanate)	official classification	Irritant

### Serious Eye Damage/Irritation

Name	Species	Value
TOLUENE	Rabbit	Moderate irritant
POLYMETHYLENE POLYPHENYLENE ISOCYANATE	official classification	Severe irritant
P,P'-Methylenebis(phenyl isocyanate)	official classification	Severe irritant

### Skin Sensitization

Name	Species	Value
TOLUENE	Guinea pig	Not classified
POLYMETHYLENE POLYPHENYLENE ISOCYANATE	official classification	Sensitizing
P,P'-Methylenebis(phenyl isocyanate)	official classification	Sensitizing

### Respiratory Sensitization

Name	Species	Value
POLYMETHYLENE POLYPHENYLENE ISOCYANATE	Human	Sensitizing
P,P'-Methylenebis(phenyl isocyanate)	Human	Sensitizing

### Germ Cell Mutagenicity

Name	Route	Value
TOLUENE	In Vitro	Not mutagenic
TOLUENE	In vivo	Not mutagenic
POLYMETHYLENE POLYPHENYLENE ISOCYANATE	In Vitro	Some positive data exist, but the data are not sufficient for classification
P,P'-Methylenebis(phenyl isocyanate)	In Vitro	Some positive data exist, but the data are not sufficient for classification

### Carcinogenicity

Name	Route	Species	Value
TOLUENE	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
TOLUENE	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification
TOLUENE	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification
POLYMETHYLENE POLYPHENYLENE ISOCYANATE	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification
P,P'-Methylenebis(phenyl isocyanate)	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification

## Reproductive Toxicity

### Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
TOLUENE	Inhalation	Not classified for female reproduction	Human	NOAEL Not available	occupational exposure
TOLUENE	Inhalation	Not classified for male reproduction	Rat	NOAEL 2.3 mg/l	1 generation
TOLUENE	Ingestion	Toxic to development	Rat	LOAEL 520 mg/kg/day	during gestation
TOLUENE	Inhalation	Toxic to development	Human	NOAEL Not available	poisoning and/or abuse
POLYMETHYLENE POLYPHENYLENE ISOCYANATE	Inhalation	Not classified for development	Rat	NOAEL 0.004 mg/l	during organogenesis
P,P'-Methylenebis(phenyl isocyanate)	Inhalation	Not classified for development	Rat	NOAEL 0.004 mg/l	during organogenesis

## Target Organ(s)

### Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
TOLUENE	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
TOLUENE	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
TOLUENE	Inhalation	immune system	Not classified	Mouse	NOAEL 0.004 mg/l	3 hours
TOLUENE	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
POLYMETHYLENE POLYPHENYLENE ISOCYANATE	Inhalation	respiratory irritation	May cause respiratory irritation	official classification	NOAEL Not available	
P,P'-Methylenebis(phenyl isocyanate)	Inhalation	respiratory irritation	May cause respiratory irritation	official classification	NOAEL Not available	

### Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
TOLUENE	Inhalation	auditory system   nervous system   eyes   olfactory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
TOLUENE	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 2.3 mg/l	15 months
TOLUENE	Inhalation	heart   liver   kidney and/or bladder	Not classified	Rat	NOAEL 11.3 mg/l	15 weeks

TOLUENE	Inhalation	endocrine system	Not classified	Rat	NOAEL 1.1 mg/l	4 weeks
TOLUENE	Inhalation	immune system	Not classified	Mouse	NOAEL Not available	20 days
TOLUENE	Inhalation	bone, teeth, nails, and/or hair	Not classified	Mouse	NOAEL 1.1 mg/l	8 weeks
TOLUENE	Inhalation	hematopoietic system   vascular system	Not classified	Human	NOAEL Not available	occupational exposure
TOLUENE	Inhalation	gastrointestinal tract	Not classified	Multiple animal species	NOAEL 11.3 mg/l	15 weeks
TOLUENE	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 625 mg/kg/day	13 weeks
TOLUENE	Ingestion	heart	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
TOLUENE	Ingestion	liver   kidney and/or bladder	Not classified	Multiple animal species	NOAEL 2,500 mg/kg/day	13 weeks
TOLUENE	Ingestion	hematopoietic system	Not classified	Mouse	NOAEL 600 mg/kg/day	14 days
TOLUENE	Ingestion	endocrine system	Not classified	Mouse	NOAEL 105 mg/kg/day	28 days
TOLUENE	Ingestion	immune system	Not classified	Mouse	NOAEL 105 mg/kg/day	4 weeks
POLYMETHYLENE POLYPHENYLENE ISOCYANATE	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.004 mg/l	13 weeks
P,P'-Methylenebis(phenyl isocyanate)	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.004 mg/l	13 weeks

### Aspiration Hazard

Name	Value
TOLUENE	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

## SECTION 12: Ecological information

### Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

### Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective

regulating authorities to determine the available treatment and disposal facilities.

**EPA Hazardous Waste Number (RCRA):** D001 (Ignitable), D022 (Chloroform)

**SECTION 14: Transport Information**

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

**SECTION 15: Regulatory information**

**15.1. US Federal Regulations**

Contact 3M for more information.

**EPCRA 311/312 Hazard Classifications:**

**Physical Hazards**

Flammable (gases, aerosols, liquids, or solids)

**Health Hazards**

Aspiration Hazard

Reproductive toxicity

Serious eye damage or eye irritation

Skin Corrosion or Irritation

Specific target organ toxicity (single or repeated exposure)

**Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):**

<u>Ingredient</u>	<u>C.A.S. No</u>	<u>% by Wt</u>
TOLUENE	108-88-3	Trade Secret 85 - 95
POLYMETHYLENE POLYPHENYLENE ISOCYANATE	9016-87-9	Trade Secret 1 - 5
P,P'-Methylenebis(phenyl isocyanate)	101-68-8	Trade Secret 1 - 5

**15.2. State Regulations**

Contact 3M for more information.

**15.3. Chemical Inventories**

The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information.

The components of this product are in compliance with the new substance notification requirements of CEPA.

The components of this material are in compliance with the China "Measures on Environmental Management of New Chemical Substance". Certain restrictions may apply. Contact the selling division for additional information.

The components of this material are in compliance with the provisions of Japan Industrial Safety and Health Law. Certain restrictions may apply. Contact the selling division for additional information.

The components of this material are in compliance with the provisions of the Korean Toxic Chemical Control Law. Certain restrictions may apply. Contact the selling division for additional information.

The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain

restrictions may apply. Contact the selling division for additional information.

The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information.

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

#### 15.4. International Regulations

Contact 3M for more information.

**This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.**

## SECTION 16: Other information

### NFPA Hazard Classification

**Health:** 2 **Flammability:** 3 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

### HMIS Hazard Classification

**Health:** \*3 **Flammability:** 3 **Physical Hazard:** 0 **Personal Protection:** X - See PPE section.

Hazardous Material Identification System (HMIS® IV) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® IV ratings are to be used with a fully implemented HMIS® IV program. HMIS® is a registered mark of the American Coatings Association (ACA).

<b>Document Group:</b>	11-2978-2	<b>Version Number:</b>	41.00
<b>Issue Date:</b>	05/21/18	<b>Supersedes Date:</b>	01/12/18

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

**3M USA SDSs are available at [www.3M.com](http://www.3M.com)**