



Safety Data Sheet

Copyright, 2016, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	26-7813-4	Version Number:	4.00
Issue Date:	10/10/16	Supersedes Date:	09/10/15

Product identifier

3M™ SMC/FRP Repair Adhesive-3 PN 08271

ID Number(s):

LB-K100-0711-3, 41-0003-6753-6, 41-0003-8003-4, 41-9103-0378-7, 60-4550-5026-4

Recommended use

Automotive

Supplier's details

MANUFACTURER: 3M
DIVISION: Automotive Aftermarket

ADDRESS: 3M Center, St. Paul, MN 55144-1000, USA
Telephone: 1-888-3M HELPS (1-888-364-3577)

Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet (SDS), Article Information Sheet (AIS), or Article Information Letter (AIL) for each of these components is included. Please do not separate the component documents from this cover page. The document numbers for components of this product are:

26-7812-6, 26-5887-0

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

3M USA SDSs are available at www.3M.com



Safety Data Sheet

Copyright,2023, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	26-5887-0	Version Number:	6.02
Issue Date:	04/13/23	Supersedes Date:	10/14/22

SECTION 1: Identification

1.1. Product identifier

3M™ SMC/Fiberglass Repair Adhesive-3 PN 08271 Part A

Product Identification Numbers

LB-K100-0680-6, LB-K100-0908-4

1.2. Recommended use and restrictions on use

Recommended use

Automotive, Adhesive used with Part B

1.3. Supplier's details

MANUFACTURER:	3M
DIVISION:	Automotive Aftermarket
ADDRESS:	3M Center, St. Paul, MN 55144-1000, USA
Telephone:	1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

The label elements below were prepared in accordance with OSHA Hazard Communication Standard, 29 CFR 1910.1200. This information may be different from the actual product label information for labels regulated by other agencies.

2.1. Hazard classification

Serious Eye Damage/Irritation: Category 2A.

Skin Corrosion/Irritation: Category 2.

Respiratory Sensitizer: Category 1.

Skin Sensitizer: Category 1.

Specific Target Organ Toxicity (single exposure): Category 3.

Specific Target Organ Toxicity (repeated exposure): Category 1.

2.2. Label elements

Signal word

Danger

Symbols

Exclamation mark | Health Hazard |

Pictograms



Hazard Statements

Causes serious eye irritation.

Causes skin irritation.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

May cause respiratory irritation.

Causes damage to organs through prolonged or repeated exposure:
respiratory system |

Precautionary Statements

Prevention:

Do not breathe dust/fume/gas/mist/vapors/spray.

Use only outdoors or in a well-ventilated area.

In case of inadequate ventilation wear respiratory protection.

Wear protective gloves and eye/face protection.

Do not eat, drink or smoke when using this product.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Response:

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

If eye irritation persists: Get medical advice/attention.

IF ON SKIN: Wash with plenty of soap and water.

If skin irritation or rash occurs: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

Get medical advice/attention if you feel unwell.

Storage:

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

Supplemental Information:

Persons previously sensitized to isocyanates may develop a cross-sensitization reaction to other isocyanates.

40% of the mixture consists of ingredients of unknown acute inhalation toxicity.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
Urethane Prepolymer (NJTSRN 04499600-7461)	Trade Secret*	30 - 60 Trade Secret *
Methylene Phenylene Isocyanate	101-68-8	15 - 40 Trade Secret *
4,4'-Diisocyanatodiphenylmethane Polymer	25686-28-6	10 - 30 Trade Secret *
Talc	14807-96-6	7 - 13 Trade Secret *
Aluminum Silicate (NJTSRN 04499600-6789)	Trade Secret*	7 - 13 Trade Secret *
Thickening Agent (NJTSRN 04499600-6784)	Trade Secret*	1 - 5 Trade Secret *

NJTS or NJTSRN: New Jersey Trade Secret Registry Number.

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Irritating to the respiratory tract (coughing, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain). Allergic respiratory reaction (difficulty breathing, wheezing, cough, and tightness of chest). Allergic skin reaction (redness, swelling, blistering, and itching). Target organ effects following prolonged or repeated exposure. See Section 11 for additional details.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

DO NOT USE WATER In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

Substance

Carbon monoxide
Carbon dioxide
Hydrogen Cyanide
Oxides of Nitrogen

Condition

During Combustion
During Combustion
During Combustion
During Combustion

5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Contain spill. Pour isocyanate decontaminant solution (90% water, 8% concentrated ammonia, 2% detergent) on spill and allow to react for 10 minutes. Or pour water on spill and allow to react for more than 30 minutes. Cover with absorbent material. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a container approved for transportation by appropriate authorities, but do not seal the container for 48 hours to avoid pressure build-up. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. Do not use in a confined area with minimal air exchange. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed to prevent loss of stabilizing materials. Keep container tightly closed to prevent contamination with water or air. If contamination is suspected, do not reseal container. Store away from heat. Store away from acids. Store away from strong bases.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Methylene Phenylene Isocyanate	101-68-8	ACGIH	TWA:0.005 ppm	
Methylene Phenylene Isocyanate	101-68-8	OSHA	CEIL:0.2 mg/m3(0.02 ppm)	
Talc	14807-96-6	ACGIH	TWA(respirable fraction):2 mg/m3	A4: Not class. as human carcin
Talc	14807-96-6	OSHA	TWA concentration(respirable):0.1 mg/m3(2.4 millions of particles/cu. ft.);TWA:20 millions of particles/cu. ft.	
Aluminum Silicate (NJTSRN)	Trade	ACGIH	TWA(respirable fraction):1	A4: Not class. as human

04499600-6789)	Secret		mg/m3	carcin
Thickening Agent (NJTSRN 04499600-6784)	Trade Secret	OSHA	TWA:20 millions of particles/cu. ft.;TWA concentration:0.8 mg/m3	

ACGIH : American Conference of Governmental Industrial Hygienists
 AIHA : American Industrial Hygiene Association
 CMRG : Chemical Manufacturer's Recommended Guidelines
 OSHA : United States Department of Labor - Occupational Safety and Health Administration
 TWA: Time-Weighted-Average
 STEL: Short Term Exposure Limit
 CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Provide ventilated enclosure for curing. Curing enclosures must be exhausted to outdoors or to a suitable emission control device. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

- Safety Glasses with side shields
- Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

- Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state
Color

Liquid
 White

Odor	Slight Isocyanate
Odor threshold	<i>No Data Available</i>
pH	<i>Not Applicable</i>
Melting point	<i>Not Applicable</i>
Boiling Point	<i>No Data Available</i>
Flash Point	> 383 °F [<i>Test Method</i> :Closed Cup]
Evaporation rate	< 1 [<i>Ref Std</i> :ETHER=1]
Flammability (solid, gas)	Not Applicable
Flammable Limits(LEL)	<i>No Data Available</i>
Flammable Limits(UEL)	<i>No Data Available</i>
Vapor Pressure	.010 mmHg [<i>Details</i> :@77.00 F for product]
Vapor Density	< 1 [<i>Ref Std</i> :AIR=1]
Density	10.72 lb/gal
Specific Gravity	1.288 [<i>Ref Std</i> :WATER=1]
Solubility In Water	<i>No Data Available</i>
Solubility- non-water	<i>No Data Available</i>
Partition coefficient: n-octanol/ water	<i>No Data Available</i>
Autoignition temperature	<i>No Data Available</i>
Decomposition temperature	<i>No Data Available</i>
Viscosity	<i>No Data Available</i>
Hazardous Air Pollutants	0.779 lb HAPS/lb solids [<i>Test Method</i> :Calculated]
Volatile Organic Compounds	0 g/l [<i>Test Method</i> :calculated SCAQMD rule 443.1]
Volatile Organic Compounds	0 % weight [<i>Test Method</i> :calculated per CARB title 2]
Percent volatile	0 % weight
VOC Less H2O & Exempt Solvents	0 g/l [<i>Test Method</i> :calculated SCAQMD rule 443.1]

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization may occur.

10.4. Conditions to avoid

Heat

Sparks and/or flames

10.5. Incompatible materials

Strong acids

Strong bases

Water

10.6. Hazardous decomposition products

Substance

None known.

Condition

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Allergic Respiratory Reaction: Signs/symptoms may include difficulty breathing, wheezing, cough, and tightness of chest.

May cause additional health effects (see below).

Skin Contact:

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain.

Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Additional Health Effects:

Prolonged or repeated exposure may cause target organ effects:

Pneumoconiosis: Sign/symptoms may include persistent cough, breathlessness, chest pain, increased amounts of sputum, and changes in lung function tests.

Respiratory Effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish colored skin (cyanosis), sputum production, changes in lung function tests, and/or respiratory failure.

Carcinogenicity:

Ingredient	CAS No.	Class Description	Regulation
Talc-based body powder (perineal use of)	14807-96-6	Grp. 2B: Possible human carc.	International Agency for Research on Cancer
Talc containing asbestiform fibres	14807-96-6	Grp. 1: Carcinogenic to humans	International Agency for Research on Cancer

Additional Information:

Persons previously sensitized to isocyanates may develop a cross-sensitization reaction to other isocyanates.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Inhalation-Dust/Mist(4 hr)		No data available; calculated ATE >12.5 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Methylene Phenylene Isocyanate	Dermal	Rabbit	LD50 > 5,000 mg/kg
Methylene Phenylene Isocyanate	Inhalation-Dust/Mist (4 hours)	Rat	LC50 0.368 mg/l
Methylene Phenylene Isocyanate	Ingestion	Rat	LD50 31,600 mg/kg
Urethane Prepolymer (NJTSRN 04499600-7461)	Dermal		LD50 estimated to be > 5,000 mg/kg
Urethane Prepolymer (NJTSRN 04499600-7461)	Ingestion	Rat	LD50 > 5,000 mg/kg
4,4'-Diisocyanatodiphenylmethane Polymer	Dermal	Rabbit	LD50 > 5,000 mg/kg
4,4'-Diisocyanatodiphenylmethane Polymer	Inhalation-Dust/Mist (4 hours)	Rat	LC50 0.368 mg/l
4,4'-Diisocyanatodiphenylmethane Polymer	Ingestion	Rat	LD50 31,600 mg/kg
Aluminum Silicate (NJTSRN 04499600-6789)	Dermal	Rabbit	LD50 > 2,000 mg/kg
Aluminum Silicate (NJTSRN 04499600-6789)	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 4.57 mg/l
Aluminum Silicate (NJTSRN 04499600-6789)	Ingestion	Rat	LD50 > 5,000 mg/kg
Talc	Dermal		LD50 estimated to be > 5,000 mg/kg
Talc	Ingestion		LD50 estimated to be > 5,000 mg/kg
Thickening Agent (NJTSRN 04499600-6784)	Dermal	Rabbit	LD50 > 5,000 mg/kg
Thickening Agent (NJTSRN 04499600-6784)	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Thickening Agent (NJTSRN 04499600-6784)	Ingestion	Rat	LD50 > 5,110 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Methylene Phenylene Isocyanate	official classification	Irritant
4,4'-Diisocyanatodiphenylmethane Polymer	official classification	Irritant
Aluminum Silicate (NJTSRN 04499600-6789)	Rabbit	No significant irritation
Talc	Rabbit	No significant irritation
Thickening Agent (NJTSRN 04499600-6784)	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Methylene Phenylene Isocyanate	official classification	Severe irritant
4,4'-Diisocyanatodiphenylmethane Polymer	official classification	Severe irritant
Aluminum Silicate (NJTSRN 04499600-6789)	Rabbit	Mild irritant
Talc	Rabbit	No significant irritation
Thickening Agent (NJTSRN 04499600-6784)	Rabbit	No significant irritation

Skin Sensitization

Name	Species	Value
Methylene Phenylene Isocyanate	official classification	Sensitizing
4,4'-Diisocyanatodiphenylmethane Polymer	official	Sensitizing

	classification	
Thickening Agent (NJTSRN 04499600-6784)	Human and animal	Not classified

Respiratory Sensitization

Name	Species	Value
Methylene Phenylene Isocyanate	Human	Sensitizing
4,4'-Diisocyanatodiphenylmethane Polymer	Human	Sensitizing
Talc	Human	Not classified

Germ Cell Mutagenicity

Name	Route	Value
Methylene Phenylene Isocyanate	In Vitro	Some positive data exist, but the data are not sufficient for classification
4,4'-Diisocyanatodiphenylmethane Polymer	In Vitro	Some positive data exist, but the data are not sufficient for classification
Talc	In Vitro	Not mutagenic
Talc	In vivo	Not mutagenic
Thickening Agent (NJTSRN 04499600-6784)	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Methylene Phenylene Isocyanate	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification
4,4'-Diisocyanatodiphenylmethane Polymer	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification
Talc	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification
Thickening Agent (NJTSRN 04499600-6784)	Not Specified	Mouse	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
Methylene Phenylene Isocyanate	Inhalation	Not classified for development	Rat	NOAEL 0.004 mg/l	during organogenesis
4,4'-Diisocyanatodiphenylmethane Polymer	Inhalation	Not classified for development	Rat	NOAEL 0.004 mg/l	during organogenesis
Talc	Ingestion	Not classified for development	Rat	NOAEL 1,600 mg/kg	during organogenesis
Thickening Agent (NJTSRN 04499600-6784)	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Thickening Agent (NJTSRN 04499600-6784)	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Thickening Agent (NJTSRN 04499600-6784)	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
------	-------	-----------------	-------	---------	-------------	-------------------

Methylene Phenylene Isocyanate	Inhalation	respiratory irritation	May cause respiratory irritation	official classification	NOAEL Not available	
4,4'-Diisocyanatodiphenylmethane Polymer	Inhalation	respiratory irritation	May cause respiratory irritation	official classification	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Methylene Phenylene Isocyanate	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.004 mg/l	13 weeks
4,4'-Diisocyanatodiphenylmethane Polymer	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.004 mg/l	13 weeks
Talc	Inhalation	pneumoconiosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
Talc	Inhalation	pulmonary fibrosis respiratory system	Not classified	Rat	NOAEL 18 mg/m3	113 weeks
Thickening Agent (NJTSRN 04499600-6784)	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:

Physical Hazards

Not applicable

Health Hazards

Respiratory or Skin Sensitization

Serious eye damage or eye irritation

Skin Corrosion or Irritation

Specific target organ toxicity (single or repeated exposure)

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

<u>Ingredient</u>	<u>C.A.S. No</u>	<u>% by Wt</u>
Methylene Phenylene Isocyanate	101-68-8	Trade Secret 15 - 40
Methylene Phenylene Isocyanate (Benzene, 1,1'-methylenebis[4-isocyanato-)	101-68-8	Trade Secret 15 - 40
Methylene Phenylene Isocyanate (DIISOCYANATES (CERTAIN CHEMICALS ONLY))	101-68-8	Trade Secret 15 - 40

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 2 **Flammability:** 1 **Instability:** 1 **Special Hazards:** Reacts with Water

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document Group:	26-5887-0	Version Number:	6.02
Issue Date:	04/13/23	Supersedes Date:	10/14/22

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY

OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com



Safety Data Sheet

Copyright, 2018, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	26-7812-6	Version Number:	4.04
Issue Date:	11/14/18	Supersedes Date:	07/26/18

SECTION 1: Identification

1.1. Product identifier

3M™ SMC/Fiberglass Repair Adhesive-3 PN 08271 Part B

Product Identification Numbers

LB-K100-0711-0, LB-K100-0909-9

1.2. Recommended use and restrictions on use

Recommended use

Automotive, Body and Structural Repair

1.3. Supplier's details

MANUFACTURER:	3M
DIVISION:	Automotive Aftermarket
ADDRESS:	3M Center, St. Paul, MN 55144-1000, USA
Telephone:	1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

The label elements below were prepared in accordance with OSHA Hazard Communication Standard, 29 CFR 1910.1200. This information may be different from the actual product label information for labels regulated by other agencies.

2.1. Hazard classification

Reproductive Toxicity: Category 2.

Specific Target Organ Toxicity (repeated exposure): Category 1.

2.2. Label elements

Signal word

Danger

Symbols

Health Hazard |

Pictograms**Hazard Statements**

Suspected of damaging fertility or the unborn child.

Causes damage to organs through prolonged or repeated exposure:
respiratory system |

Precautionary Statements**Prevention:**

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Do not breathe dust/fume/gas/mist/vapors/spray.
Wear protective gloves.
Do not eat, drink or smoke when using this product.
Wash thoroughly after handling.

Response:

Get medical advice/attention if you feel unwell.

Storage:

Store locked up.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2% of the mixture consists of ingredients of unknown acute oral toxicity.

2% of the mixture consists of ingredients of unknown acute dermal toxicity.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
Polyether Polyol (NJTSRN 04499600-6782)	Trade Secret*	30 - 60 Trade Secret *
Talc	14807-96-6	15 - 40 Trade Secret *
Polyol (NJTSRN 04499600-6783)	Trade Secret*	15 - 40 Trade Secret *
Urethane Prepolymer (NJTSRN 04499600-6781)	Trade Secret*	3 - 7 Trade Secret *
Clay	71011-24-0	1 - 5 Trade Secret *
Piperazine	110-85-0	0.1 - 1 Trade Secret *

NJTS or NJTSRN: New Jersey Trade Secret Registry Number.

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures**4.1. Description of first aid measures**

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Wash with soap and water. If signs/symptoms develop, get medical attention.

Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures**5.1. Suitable extinguishing media**

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products**Substance**

Hydrocarbons
Carbon monoxide
Carbon dioxide
Oxides of Nitrogen

Condition

During Combustion
During Combustion
During Combustion
During Combustion

5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate

solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. Do not use in a confined area with minimal air exchange. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (gloves, respirators, etc.) as required.

7.2. Conditions for safe storage including any incompatibilities

Store away from acids. Store away from strong bases. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Piperazine	110-85-0	ACGIH	TWA(as piperazine, inhalable fraction & vapor):0.03 ppm	A4: Not class. as human carcin, Dermal/Respiratory Sensitizer
Talc	14807-96-6	ACGIH	TWA(respirable fraction):2 mg/m3	A4: Not class. as human carcin
Talc	14807-96-6	OSHA	TWA:2 mg/m3	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the

substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Butyl Rubber

Neoprene

Nitrile Rubber

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

General Physical Form:	Liquid
Specific Physical Form:	Viscous
Odor, Color, Grade:	Slight ammonia like odor, dark green.
Odor threshold	<i>No Data Available</i>
pH	<i>Not Applicable</i>
Melting point	<i>Not Applicable</i>
Boiling Point	<i>No Data Available</i>
Flash Point	> 340 °F [<i>Test Method: Closed Cup</i>]
Evaporation rate	< 1 [<i>Ref Std: ETHER=1</i>]
Flammability (solid, gas)	Not Applicable
Flammable Limits(LEL)	<i>No Data Available</i>
Flammable Limits(UEL)	<i>No Data Available</i>
Vapor Pressure	<= 0.1 mmHg
Vapor Density	>= 1 [<i>Ref Std: AIR=1</i>]
Density	1.2 g/ml
Specific Gravity	1 - 1.2 [<i>Ref Std: WATER=1</i>]
Solubility In Water	<i>No Data Available</i>
Solubility- non-water	Negligible
Partition coefficient: n-octanol/ water	<i>No Data Available</i>
Autoignition temperature	<i>No Data Available</i>
Decomposition temperature	<i>No Data Available</i>
Viscosity	<i>No Data Available</i>
Hazardous Air Pollutants	0 lb HAPS/lb solids [<i>Test Method: Calculated</i>]
Volatile Organic Compounds	5 g/l [<i>Test Method: calculated SCAQMD rule 443.1</i>]
Volatile Organic Compounds	0.2 % weight [<i>Test Method: calculated per CARB title 2</i>]
Percent volatile	0.39 % weight
VOC Less H2O & Exempt Solvents	5 g/l [<i>Test Method: calculated SCAQMD rule 443.1</i>]

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

High shear and high temperature conditions

10.5. Incompatible materials

Strong acids

Strong bases

Strong oxidizing agents

Alcohols

10.6. Hazardous decomposition products**Substance****Condition**

Aldehydes

Not Specified

Hydrogen Cyanide

Not Specified

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects**Signs and Symptoms of Exposure**

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

Skin Contact:

Contact with the skin during product use is not expected to result in significant irritation. May cause additional health effects (see below).

Eye Contact:

Vapors released during curing may cause eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

Additional Health Effects:

Prolonged or repeated exposure may cause target organ effects:

Pneumoconiosis: Sign/symptoms may include persistent cough, breathlessness, chest pain, increased amounts of sputum, and changes in lung function tests.

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Polyether Polyol (NJTSRN 04499600-6782)	Dermal	Rat	LD50 > 2,000 mg/kg
Polyether Polyol (NJTSRN 04499600-6782)	Ingestion	Rat	LD50 > 2,500 mg/kg
Talc	Dermal		LD50 estimated to be > 5,000 mg/kg
Talc	Ingestion		LD50 estimated to be > 5,000 mg/kg
Polyol (NJTSRN 04499600-6783)	Dermal	Rabbit	LD50 > 5,000 mg/kg
Polyol (NJTSRN 04499600-6783)	Ingestion	Rat	LD50 > 10,000 mg/kg
Urethane Prepolymer (NJTSRN 04499600-6781)	Dermal		LD50 estimated to be > 5,000 mg/kg
Urethane Prepolymer (NJTSRN 04499600-6781)	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
Piperazine	Dermal		estimated to be > 5,000 mg/kg
Piperazine	Inhalation-Dust/Mist		estimated to be > 12.5 mg/l
Piperazine	Ingestion		estimated to be > 5,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Polyether Polyol (NJTSRN 04499600-6782)	Rabbit	No significant irritation
Talc	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Polyether Polyol (NJTSRN 04499600-6782)	Rabbit	Mild irritant
Talc	Rabbit	No significant irritation

Skin Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Respiratory Sensitization

Name	Species	Value
Talc	Human	Not classified

Germ Cell Mutagenicity

Name	Route	Value
Talc	In Vitro	Not mutagenic
Talc	In vivo	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Talc	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
Talc	Ingestion	Not classified for development	Rat	NOAEL 1,600 mg/kg	during organogenesis

Target Organ(s)

Specific Target Organ Toxicity - single exposure

For the component/components, either no data are currently available or the data are not sufficient for classification.

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Talc	Inhalation	pneumoconiosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
Talc	Inhalation	pulmonary fibrosis respiratory system	Not classified	Rat	NOAEL 18 mg/m ³	113 weeks

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:

Physical Hazards

Not applicable

Health Hazards

Reproductive toxicity

Specific target organ toxicity (single or repeated exposure)

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 1 **Flammability:** 1 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document Group: 26-7812-6 **Version Number:** 4.04
Issue Date: 11/14/18 **Supersedes Date:** 07/26/18

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com