

Safety Data Sheet

Copyright, 2021, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document Group:
 26-6753-3
 Version Number:
 4.01

 Issue Date:
 08/11/21
 Supercedes Date:
 03/25/20

SECTION 1: Identification

1.1. Product identifier

3MTM Scotch-WeldTM Structural Adhesive Film AF-325 White

Product Identification Numbers

87-2500-0364-4, 87-2500-0366-9 7010399423, 7010399424

1.2. Recommended use and restrictions on use

Recommended use

Surfacing Film, Industrial use

1.3. Supplier's details

MANUFACTURER: 3M

DIVISION: Automotive and Aerospace Solutions Division ADDRESS: 3M Center, St. Paul, MN 55144-1000, USA Telephone: 1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

2.1. Hazard classification

Skin Sensitizer: Category 1.

2.2. Label elements

Signal word

Warning

Symbols

Exclamation mark

Pictograms



Hazard Statements

May cause an allergic skin reaction.

Precautionary Statements

Prevention:

Avoid breathing dust/fume/gas/mist/vapors/spray.

Wear protective gloves.

Contaminated work clothing must not be allowed out of the workplace.

Response:

IF ON SKIN: Wash with plenty of soap and water.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
PHENOL-FORMALDEHYDE POLYMER GLYCIDYL	28064-14-4	35 - 55 Trade Secret *
ETHER		
GLASS BUBBLES	65997-17-3	10 - 30
4,4'-isopropylidenediphenol-epichlorohydrin polymer	25068-38-6	5 - 10 Trade Secret *
DICYANDIAMIDE	461-58-5	5 - 10
POLY(ETHYLENE TEREPHTHALATE)	25038-59-9	<= 10
PAPER	None	<= 10
EPOXY POLYMER	Trade Secret*	2 - 10
TALC	14807-96-6	3 - 7 Trade Secret *
1,1'-4(METHYL-M-PHENYLENE)BIS(3,3'-	17526-94-2	1 - 5
DIMETHYLUREA)		
NON-VOLATILE AMIDE	Trade Secret*	1 - 5
DIMETHYL TEREPHTHALATE-ETHYLENE	26006-30-4	<= 1.5
GLYCOL-ISOPHTHALIC ACID POLYMER		
ORGANOSILANE	2530-83-8	0.5 - 1.5 Trade Secret *

^{*}The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Page 2 of 11

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Aldehydes	During Combustion
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Hydrogen Chloride	During Combustion
Hydrogen Cyanide	During Combustion
Oxides of Nitrogen	During Combustion
Toxic Vapor, Gas, Particulate	During Combustion

5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. Avoid breathing dust/fume/gas/mist/vapors/spray.

Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage including any incompatibilities

No special storage requirements.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
TALC	14807-96-6	ACGIH	TWA(respirable fraction):2	A4: Not class. as human
			mg/m3	carcin
TALC	14807-96-6	OSHA	TWA - Use asbestos limits:	
TALC	14807-96-6	OSHA	TWA	
			concentration(respirable):0.1	
			mg/m3(2.4 millions of	
			particles/cu. ft.);TWA:20	
			millions of particles/cu. ft.	
GLASS BUBBLES	65997-17-3	Manufacturer	TWA(as non-fibrous,	
		determined	respirable)(8 hours):3	
			mg/m3;TWA(as non-fibrous,	
			inhalable fraction)(8 hours):10	
			mg/m3	

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CMRG: Chemical Manufacturer's Recommended Guidelines

OSHA: United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

None required.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then

use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state Solid film adhesive

Color White

Specific Physical Form: Film Odor Odorless

Odor threshold No Data Available pН Not Applicable Melting point No Data Available **Boiling Point** Not Applicable **Flash Point** No flash point **Evaporation rate** Not Applicable Not Classified Flammability (solid, gas) Flammable Limits(LEL) Not Applicable Flammable Limits(UEL) Not Applicable

Vapor PressureNilVapor DensityNil

 Density
 1.2 g/cm3 [@ 20 °C]

 Specific Gravity
 1.2 [Ref Std: WATER=1]

Solubility in Water Nil

Solubility- non-waterNo Data AvailablePartition coefficient: n-octanol/ waterNo Data AvailableAutoignition temperatureNo Data AvailableDecomposition temperatureNo Data AvailableViscosityNot ApplicableVolatile Organic CompoundsNot Applicable

Percent volatile Nil

VOC Less H2O & Exempt Solvents

Not Applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization may occur.

10.4. Conditions to avoid

Avoid curing large quantities of material to prevent a premature reaction (exotherm) with production of intense heat and smoke.

10.5. Incompatible materials

Not determined

10.6. Hazardous decomposition products

Substance

Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion:

Physical Blockage: Signs/symptoms may include cramping, abdominal pain, and constipation.

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Carcinogenicity:

Ingredient	CAS No.	Class Description	Regulation
Generic: TALC	14807-96-6	Grp. 1: Carcinogenic to humans	International Agency for Research on Cancer

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg

Page 6 of 11

Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
PHENOL-FORMALDEHYDE POLYMER GLYCIDYL ETHER	Dermal	Rabbit	LD50 > 6,000 mg/kg
PHENOL-FORMALDEHYDE POLYMER GLYCIDYL ETHER	Inhalation-	Rat	LC50 > 1.7 mg/l
	Dust/Mist		
	(4 hours)		
PHENOL-FORMALDEHYDE POLYMER GLYCIDYL ETHER	Ingestion	Rat	LD50 > 4,000 mg/kg
GLASS BUBBLES	Dermal		LD50 estimated to be > 5,000 mg/kg
GLASS BUBBLES	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
POLY(ETHYLENE TEREPHTHALATE)	Dermal		LD50 estimated to be > 5,000 mg/kg
POLY(ETHYLENE TEREPHTHALATE)	Ingestion	Rat	LD50 > 5,000 mg/kg
4,4'-isopropylidenediphenol-epichlorohydrin polymer	Dermal	Rat	LD50 > 1,600 mg/kg
4,4'-isopropylidenediphenol-epichlorohydrin polymer	Ingestion	Rat	LD50 > 1,000 mg/kg
EPOXY POLYMER	Dermal	Rabbit	LD50 > 3,000 mg/kg
EPOXY POLYMER	Ingestion	Rat	LD50 > 10,000 mg/kg
DICYANDIAMIDE	Dermal	Rabbit	LD50 > 10,000 mg/kg
DICYANDIAMIDE	Ingestion	Rat	LD50 > 30,000 mg/kg
TALC	Dermal		LD50 estimated to be > 5,000 mg/kg
TALC	Ingestion		LD50 estimated to be > 5,000 mg/kg
NON-VOLATILE AMIDE	Dermal		LD50 estimated to be > 5,000 mg/kg
1,1'-4(METHYL-M-PHENYLENE)BIS(3,3'-DIMETHYLUREA)	Dermal	Rat	LD50 > 2,000 mg/kg
1,1'-4(METHYL-M-PHENYLENE)BIS(3,3'-DIMETHYLUREA)	Ingestion	Rat	LD50 > 2,000 mg/kg
NON-VOLATILE AMIDE	Ingestion	Rat	LD50 > 5,000 mg/kg
ORGANOSILANE	Dermal	Rabbit	LD50 4,000 mg/kg
ORGANOSILANE	Inhalation-	Rat	LC50 > 5.3 mg/l
	Dust/Mist		
	(4 hours)		
ORGANOSILANE	Ingestion	Rat	LD50 7,010 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
PHENOL-FORMALDEHYDE POLYMER GLYCIDYL ETHER	Rabbit	Minimal irritation
GLASS BUBBLES	Professio	No significant irritation
	nal	
	judgeme	
	nt	
POLY(ETHYLENE TEREPHTHALATE)	In vitro	No significant irritation
	data	
4,4'-isopropylidenediphenol-epichlorohydrin polymer	Rabbit	Mild irritant
DICYANDIAMIDE	Human	Minimal irritation
	and	
	animal	
TALC	Rabbit	No significant irritation
1,1'-4(METHYL-M-PHENYLENE)BIS(3,3'-DIMETHYLUREA)	Rabbit	No significant irritation
NON-VOLATILE AMIDE	Rabbit	No significant irritation
ORGANOSILANE	Rabbit	Mild irritant

Serious Eve Damage/Irritation

Name	Species	Value
PHENOL-FORMALDEHYDE POLYMER GLYCIDYL ETHER	Rabbit	Mild irritant
GLASS BUBBLES	Professio	No significant irritation
	nal	
	judgeme	
	nt	
POLY(ETHYLENE TEREPHTHALATE)	Human	No significant irritation
4,4'-isopropylidenediphenol-epichlorohydrin polymer	Rabbit	Moderate irritant
DICYANDIAMIDE	Professio	Mild irritant
	nal	
	judgeme	
	nt	

Page 7 of 11

3MTM Scotch-WeldTM	A Structural Adhesiv	ve Film AF-325 White

TALC	Rabbit	No significant irritation
1,1'-4(METHYL-M-PHENYLENE)BIS(3,3'-DIMETHYLUREA)	Rabbit	No significant irritation
NON-VOLATILE AMIDE	Rabbit	Mild irritant
ORGANOSILANE	Rabbit	Corrosive

08/11/21

Skin Sensitization

Name	Species	Value
PHENOL-FORMALDEHYDE POLYMER GLYCIDYL ETHER	Human	Sensitizing
	and	
	animal	
POLY(ETHYLENE TEREPHTHALATE)	Human	Not classified
4,4'-isopropylidenediphenol-epichlorohydrin polymer	Human	Sensitizing
	and	
	animal	
DICYANDIAMIDE	Guinea	Not classified
	pig	
NON-VOLATILE AMIDE	Mouse	Not classified
ORGANOSILANE	Guinea	Not classified
	pig	

Respiratory Sensitization

p		
Name	Species	Value
4,4'-isopropylidenediphenol-epichlorohydrin polymer	Human	Not classified
TALC	Human	Not classified

Germ Cell Mutagenicity

Name	Route	Value		
PHENOL-FORMALDEHYDE POLYMER GLYCIDYL ETHER	In Vitro	Some positive data exist, but the data are not sufficient for classification		
GLASS BUBBLES	In Vitro	Some positive data exist, but the data are not sufficient for classification		
POLY(ETHYLENE TEREPHTHALATE)	In Vitro	Not mutagenic		
4,4'-isopropylidenediphenol-epichlorohydrin polymer	In vivo	Not mutagenic		
4,4'-isopropylidenediphenol-epichlorohydrin polymer	In Vitro	Some positive data exist, but the data are not sufficient for classification		
DICYANDIAMIDE	In Vitro	Not mutagenic		
TALC	In Vitro	Not mutagenic		
TALC	In vivo	Not mutagenic		
NON-VOLATILE AMIDE	In Vitro	Some positive data exist, but the data are not sufficient for classification		
ORGANOSILANE	In vivo	Not mutagenic		
ORGANOSILANE	In Vitro	Some positive data exist, but the data are not sufficient for classification		

Carcinogenicity

Name	Route	Species	Value
GLASS BUBBLES	Inhalation	Multiple animal species	Some positive data exist, but the data are not sufficient for classification
4,4'-isopropylidenediphenol-epichlorohydrin polymer	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
DICYANDIAMIDE	Ingestion	Rat	Not carcinogenic
TALC	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification
ORGANOSILANE	Dermal	Mouse	Not carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure
					Duration

Page 8 **of** 11

4,4'-isopropylidenediphenol- epichlorohydrin polymer	Ingestion	Not classified for female reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
4,4'-isopropylidenediphenol- epichlorohydrin polymer	Ingestion	Not classified for male reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
4,4'-isopropylidenediphenol- epichlorohydrin polymer	Dermal	Not classified for development	Rabbit	NOAEL 300 mg/kg/day	during organogenesi s
4,4'-isopropylidenediphenol- epichlorohydrin polymer	Ingestion	Not classified for development	Rat	NOAEL 750 mg/kg/day	2 generation
DICYANDIAMIDE	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	premating & during gestation
DICYANDIAMIDE	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	44 days
DICYANDIAMIDE	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	premating & during gestation
TALC	Ingestion	Not classified for development	Rat	NOAEL 1,600 mg/kg	during organogenesi s
ORGANOSILANE	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	1 generation
ORGANOSILANE	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	1 generation
ORGANOSILANE	Ingestion	Not classified for development	Rat	NOAEL 3,000 mg/kg/day	during organogenesi s

Target Organ(s)

Specific Target Organ Toxicity - single exposure

For the component/components, either no data are currently available or the data are not sufficient for classification.

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
GLASS BUBBLES	Inhalation	respiratory system	Not classified	Human	NOAEL not available	occupational exposure
POLY(ETHYLENE TEREPHTHALATE)	Ingestion	heart skin endocrine system bone, teeth, nails, and/or hair hematopoietic system liver immune system muscles nervous system eyes kidney and/or bladder respiratory system	Not classified	Rat	NOAEL Not available	13 weeks
4,4'- isopropylidenediphenol- epichlorohydrin polymer	Dermal	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	2 years
4,4'- isopropylidenediphenol- epichlorohydrin polymer	Dermal	nervous system	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
4,4'- isopropylidenediphenol- epichlorohydrin polymer	Ingestion	auditory system heart endocrine system hematopoietic system liver eyes kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
DICYANDIAMIDE	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 6,822 mg/kg/day	13 weeks

Page 9 **of** 11

TALC	Inhalation	pneumoconiosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
TALC	Inhalation	pulmonary fibrosis respiratory system	Not classified	Rat	NOAEL 18 mg/m3	113 weeks
ORGANOSILANE	Ingestion	heart endocrine system bone, teeth, nails, and/or hair hematopoietic system liver immune system nervous system kidney and/or bladder respiratory system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): Not regulated

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:

Physical Hazards

Not applicable

Health Hazards

Respiratory or Skin Sensitization

15.2. State Regulations

Contact 3M for more information.

California Proposition 65

IngredientC.A.S. No.ListingTalc containing asbestiform fibersNoneCarcinogen

15.3. Chemical Inventories

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 2 Flammability: 1 Instability: 1 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

 Document Group:
 26-6753-3
 Version Number:
 4.01

 Issue Date:
 08/11/21
 Supercedes Date:
 03/25/20

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com