



Safety Data Sheet

Copyright, 2021, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	26-0142-5	Version Number:	3.02
Issue Date:	05/03/21	Supersedes Date:	10/26/17

Product identifier

3M™ Scotchcast™ Electrical Resin 253 (A & B)

ID Number(s):

80-6116-2526-2, 80-7002-5302-6

7000058913, 7100151613

Recommended use

Electrical, Two part curing system for electrical insulation

Supplier's details

MANUFACTURER:	3M
DIVISION:	Electrical Markets Division

ADDRESS:	3M Center, St. Paul, MN 55144-1000, USA
Telephone:	1-888-3M HELPS (1-888-364-3577)

Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet (SDS), Article Information Sheet (AIS), or Article Information Letter (AIL) for each of these components is included. Please do not separate the component documents from this cover page. The document numbers for components of this product are:

24-9295-7, 24-9269-2

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com



Safety Data Sheet

Copyright, 2021, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	24-9269-2	Version Number:	1.06
Issue Date:	04/30/21	Supersedes Date:	12/11/17

SECTION 1: Identification

1.1. Product identifier

3M™ Scotchcast™ Electrical Resin 253 Part A

Product Identification Numbers

LH-A100-0613-1, LH-A100-2363-1, 80-7002-5304-2

1.2. Recommended use and restrictions on use

Recommended use

Electrical, Part A of two part electrical resin

1.3. Supplier's details

MANUFACTURER:	3M
DIVISION:	Electrical Markets Division
ADDRESS:	3M Center, St. Paul, MN 55144-1000, USA
Telephone:	1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

2.1. Hazard classification

Serious Eye Damage/Irritation: Category 2B.

Skin Sensitizer: Category 1.

2.2. Label elements

Signal word

Warning

Symbols

Exclamation mark |

Pictograms

**Hazard Statements**

Causes eye irritation.
May cause an allergic skin reaction.

Precautionary Statements**Prevention:**

Avoid breathing dust/fume/gas/mist/vapors/spray.
Wear protective gloves.
Wash thoroughly after handling.
Contaminated work clothing must not be allowed out of the workplace.

Response:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists: Get medical advice/attention.
IF ON SKIN: Wash with plenty of soap and water.
If skin irritation or rash occurs: Get medical advice/attention.
Wash contaminated clothing before reuse.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
BISPHENOL A - EPICHLOROHYDRIN COPOLYMER	25068-38-6	50 - 60 Trade Secret *
TALC	14807-96-6	40 - 50 Trade Secret *
CHLORITE (MINERAL)	1318-59-8	0 - 5 Trade Secret *
MAGNESIUM CARBONATE	546-93-0	0 - 5 Trade Secret *
DOLOMITE	16389-88-1	0 - 1 Trade Secret *
IRON OXIDE	1332-37-2	0 - 1 Trade Secret *

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures**4.1. Description of first aid measures****Inhalation:**

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products**Substance**

Aldehydes
Carbon monoxide
Carbon dioxide

Condition

During Combustion
During Combustion
During Combustion

5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after

handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage including any incompatibilities

Store away from heat.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
TALC	14807-96-6	ACGIH	TWA(respirable fraction):2 mg/m3	A4: Not class. as human carcin
TALC	14807-96-6	OSHA	TWA concentration(respirable):0.1 mg/m3(2.4 millions of particles/cu. ft.);TWA:20 millions of particles/cu. ft.	
MAGNESIUM CARBONATE	546-93-0	OSHA	TWA(as total dust):15 mg/m3;TWA(respirable fraction):5 mg/m3	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

No engineering controls required.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

None required.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties****Appearance****Physical state**

Liquid

Color

Buff

Specific Physical Form:

RESIN

Odor

Epoxy

Odor threshold*No Data Available***pH***No Data Available***Melting point***No Data Available***Boiling Point** $\geq 200\text{ }^{\circ}\text{F}$ **Flash Point** $\geq 200\text{ }^{\circ}\text{F}$ [Test Method: Closed Cup]**Evaporation rate***Not Applicable***Flammability (solid, gas)**

Not Applicable

Flammable Limits(LEL)*No Data Available***Flammable Limits(UEL)***No Data Available***Vapor Pressure** $\leq 27\text{ psia}$ [@ 131 $^{\circ}\text{F}$]**Vapor Density***No Data Available***Density**

1.66 g/ml

Specific Gravity

1.66 [Ref Std: WATER=1]

Solubility in Water

Slight (less than 10%)

Solubility- non-water*No Data Available***Partition coefficient: n-octanol/ water***No Data Available***Autoignition temperature***No Data Available***Decomposition temperature***No Data Available***Viscosity***No Data Available***Average particle size***No Data Available***Bulk density***No Data Available***Hazardous Air Pollutants***No Data Available***Molecular weight***No Data Available***Volatile Organic Compounds***No Data Available***Percent volatile***No Data Available***Softening point***No Data Available***VOC Less H₂O & Exempt Solvents***No Data Available***SECTION 10: Stability and reactivity****10.1. Reactivity**

This material is considered to be non reactive under normal use conditions.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat

10.5. Incompatible materials

None known.

No Data Available

10.6. Hazardous decomposition products**Substance****Condition**

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects**Signs and Symptoms of Exposure**

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

No health effects are expected.

Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
BISPHENOL A - EPICHLOROHYDRIN COPOLYMER	Dermal	Rat	LD50 > 1,600 mg/kg
BISPHENOL A - EPICHLOROHYDRIN COPOLYMER	Ingestion	Rat	LD50 > 1,000 mg/kg
TALC	Dermal		LD50 estimated to be > 5,000 mg/kg
TALC	Ingestion		LD50 estimated to be > 5,000 mg/kg
CHLORITE (MINERAL)	Dermal		LD50 estimated to be > 5,000 mg/kg
CHLORITE (MINERAL)	Ingestion		LD50 estimated to be > 5,000 mg/kg
MAGNESIUM CARBONATE	Dermal	Professional judgment	LD50 estimated to be 2,000 - 5,000 mg/kg
MAGNESIUM CARBONATE	Ingestion	Rat	LD50 > 2,000 mg/kg

DOLOMITE	Dermal		LD50 estimated to be 2,000 - 5,000 mg/kg
DOLOMITE	Ingestion	Rat	LD50 > 2,000 mg/kg
IRON OXIDE	Dermal	Not available	LD50 3,100 mg/kg
IRON OXIDE	Ingestion	Not available	LD50 3,700 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
BISPHENOL A - EPICHLOROHYDRIN COPOLYMER	Rabbit	Mild irritant
TALC	Rabbit	No significant irritation
CHLORITE (MINERAL)	Professional judgement	No significant irritation
MAGNESIUM CARBONATE	In vitro data	No significant irritation
DOLOMITE	Professional judgement	No significant irritation
IRON OXIDE	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
BISPHENOL A - EPICHLOROHYDRIN COPOLYMER	Rabbit	Moderate irritant
TALC	Rabbit	No significant irritation
CHLORITE (MINERAL)	Professional judgement	No significant irritation
MAGNESIUM CARBONATE	Rabbit	Mild irritant
DOLOMITE	Professional judgement	No significant irritation
IRON OXIDE	Rabbit	No significant irritation

Skin Sensitization

Name	Species	Value
BISPHENOL A - EPICHLOROHYDRIN COPOLYMER	Human and animal	Sensitizing
IRON OXIDE	Human	Not classified

Respiratory Sensitization

Name	Species	Value
BISPHENOL A - EPICHLOROHYDRIN COPOLYMER	Human	Not classified
TALC	Human	Not classified

Germ Cell Mutagenicity

Name	Route	Value
BISPHENOL A - EPICHLOROHYDRIN COPOLYMER	In vivo	Not mutagenic
BISPHENOL A - EPICHLOROHYDRIN COPOLYMER	In Vitro	Some positive data exist, but the data are not sufficient for classification
TALC	In Vitro	Not mutagenic
TALC	In vivo	Not mutagenic
IRON OXIDE	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
BISPHENOL A - EPICHLOROHYDRIN COPOLYMER	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
TALC	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification
IRON OXIDE	Inhalation	Human	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test Result	Exposure Duration
BISPHENOL A - EPICHLOROHYDRIN COPOLYMER	Ingestion	Not classified for female reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
BISPHENOL A - EPICHLOROHYDRIN COPOLYMER	Ingestion	Not classified for male reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
BISPHENOL A - EPICHLOROHYDRIN COPOLYMER	Dermal	Not classified for development	Rabbit	NOAEL 300 mg/kg/day	during organogenesis
BISPHENOL A - EPICHLOROHYDRIN COPOLYMER	Ingestion	Not classified for development	Rat	NOAEL 750 mg/kg/day	2 generation
TALC	Ingestion	Not classified for development	Rat	NOAEL 1,600 mg/kg	during organogenesis

Target Organ(s)**Specific Target Organ Toxicity - single exposure**

For the component/components, either no data are currently available or the data are not sufficient for classification.

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
BISPHENOL A - EPICHLOROHYDRIN COPOLYMER	Dermal	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	2 years
BISPHENOL A - EPICHLOROHYDRIN COPOLYMER	Dermal	nervous system	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
BISPHENOL A - EPICHLOROHYDRIN COPOLYMER	Ingestion	auditory system heart endocrine system hematopoietic system liver eyes kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
TALC	Inhalation	pneumoconiosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
TALC	Inhalation	pulmonary fibrosis respiratory system	Not classified	Rat	NOAEL 18 mg/m3	113 weeks
IRON OXIDE	Inhalation	pulmonary fibrosis pneumoconiosis	Not classified	Human	NOAEL Not available	occupational exposure

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. If no other disposal options are available, waste product that has been completely cured or polymerized may be placed in a landfill properly designed for industrial waste. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): Not regulated

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:

Physical Hazards
Not applicable

Health Hazards
Respiratory or Skin Sensitization
Serious eye damage or eye irritation

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information.

The components of this product are in compliance with the new substance notification requirements of CEPA.

The components of this material are in compliance with the China "Measures on Environmental Management of New Chemical Substance". Certain restrictions may apply. Contact the selling division for additional information.

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 2 **Flammability:** 1 **Instability:** 1 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document Group:	24-9269-2	Version Number:	1.06
Issue Date:	04/30/21	Supersedes Date:	12/11/17

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com



Safety Data Sheet

Copyright, 2021, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	24-9295-7	Version Number:	2.04
Issue Date:	09/13/21	Supersedes Date:	04/30/21

SECTION 1: Identification

1.1. Product identifier

3M™ Scotchcast™ Electrical Resin 253 Part B

Product Identification Numbers

LH-A100-0613-5, LH-A100-2363-2, 80-7002-5305-9

1.2. Recommended use and restrictions on use

Recommended use

Electrical, Part B of two part electrical resin

1.3. Supplier's details

MANUFACTURER:	3M
DIVISION:	Electrical Markets Division
ADDRESS:	3M Center, St. Paul, MN 55144-1000, USA
Telephone:	1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

2.1. Hazard classification

Serious Eye Damage/Irritation: Category 2B.

Respiratory Sensitizer: Category 1.

Skin Sensitizer: Category 1.

Carcinogenicity: Category 1A.

2.2. Label elements

Signal word

Danger

Symbols

Health Hazard |

Pictograms

**Hazard Statements**

Causes eye irritation.
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause an allergic skin reaction.
May cause cancer.

Precautionary Statements**Prevention:**

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Avoid breathing dust/fume/gas/mist/vapors/spray.
In case of inadequate ventilation wear respiratory protection.
Wear protective gloves.
Wash thoroughly after handling.
Contaminated work clothing must not be allowed out of the workplace.

Response:

IF INHALED: If breathing is difficult, remove person to fresh air and keep comfortable for breathing.
If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing.
If eye irritation persists: Get medical advice/attention.
IF ON SKIN: Wash with plenty of soap and water.
If skin irritation or rash occurs: Get medical advice/attention.
Wash contaminated clothing before reuse.
IF exposed or concerned: Get medical advice/attention.

Storage:

Store locked up.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
TALC	14807-96-6	40 - 50
DODECENYLSUCCINIC ANHYDRIDE	25377-73-5	20 - 30 Trade Secret *
MALEIC ANHYDRIDE-POLYPROPYLENE GLYCOL COPOLYMER	9016-60-8	15 - 25
CALCITE	13397-26-7	0 - 5
CHLORITE (MINERAL)	1318-59-8	0 - 5
DOLOMITE	16389-88-1	0 - 5
MAGNESIUM CARBONATE	546-93-0	0 - 5
QUARTZ SILICA	14808-60-7	0 - 1 Trade Secret *
QUINOLINE	91-22-5	0 - 1 Trade Secret *
MALEIC ANHYDRIDE	108-31-6	0 - 0.04

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Oxides of Nitrogen	During Combustion

5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

For industrial/occupational use only. Not for consumer sale or use. Do not use in a confined area with minimal air exchange. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Use personal protective equipment (gloves, respirators, etc.) as required.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Store away from heat. Keep from freezing.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
MALEIC ANHYDRIDE	108-31-6	ACGIH	TWA(inhalable fraction and vapor):0.01 mg/m3	A4: Not class. as human carcin, Dermal/Respiratory Sensitizer
MALEIC ANHYDRIDE	108-31-6	OSHA	TWA:1 mg/m3(0.25 ppm)	
TALC	14807-96-6	ACGIH	TWA(respirable fraction):2 mg/m3	A4: Not class. as human carcin
TALC	14807-96-6	OSHA	TWA - Use asbestos limits:	
TALC	14807-96-6	OSHA	TWA concentration(respirable):0.1 mg/m3(2.4 millions of particles/cu. ft.);TWA:20 millions of particles/cu. ft.	
QUARTZ SILICA	14808-60-7	ACGIH	TWA(respirable fraction):0.025 mg/m3	A2: Suspected human carcin.
QUARTZ SILICA	14808-60-7	OSHA	TWA Table Z-1(respirable):0.05 mg/m3;TWA Table Z-3(respirable):0.1 mg/m3;TWA concentration(respirable):0.1 mg/m3(2.4 millions of particles/cu. ft.)	
CAS NO SEQ117921	16389-88-1	ACGIH	TWA(inhalable particulates):10 mg/m3	

CAS NO SEQ117922	16389-88-1	ACGIH	TWA(respirable particles):3 mg/m3	
CAS NO SEQ126498	16389-88-1	OSHA	TWA(as total dust):15 mg/m3	
CAS NO SEQ126499	16389-88-1	OSHA	TWA(respirable fraction):5 mg/m3	
DUST, INERT OR NUISANCE	16389-88-1	OSHA	TWA(as total dust):15 mg/m3;TWA(as total dust):50 millions of particles/cu. ft.(15 mg/m3);TWA(respirable fraction):5 mg/m3;TWA(respirable fraction):15 millions of particles/cu. ft.(5 mg/m3)	
CAS NO SEQ117921	546-93-0	ACGIH	TWA(inhalable particulates):10 mg/m3	
CAS NO SEQ117922	546-93-0	ACGIH	TWA(respirable particles):3 mg/m3	
MAGNESIUM CARBONATE	546-93-0	OSHA	TWA(as total dust):15 mg/m3;TWA(respirable fraction):5 mg/m3	
QUINOLINE	91-22-5	AIHA	TWA:0.005 mg/m3(0.001 ppm)	SKIN

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state

Liquid

Color

Dark Gray

Specific Physical Form:

RESIN

Odor

Maleic Anhydride

Odor threshold

No Data Available

pH

Not Applicable

Melting point

No Data Available

Boiling Point

>= 395 °F

Flash Point

>= 218 °F [Test Method: Closed Cup]

Evaporation rate

No Data Available

Flammability (solid, gas)

Not Applicable

Flammable Limits(LEL)

1.4 %

Flammable Limits(UEL)

7.1 %

Vapor Pressure

<= 27 psia [@ 131 °F]

Vapor Density

No Data Available

Density

1.44 g/ml

Specific Gravity

1.44 [Ref Std: WATER=1]

Solubility in Water

Nil

Solubility- non-water

No Data Available

Partition coefficient: n-octanol/ water

No Data Available

Autoignition temperature

No Data Available

Decomposition temperature

No Data Available

Viscosity

No Data Available

Average particle size

No Data Available

Bulk density

No Data Available

Hazardous Air Pollutants

No Data Available

Molecular weight

No Data Available

Volatile Organic Compounds

No Data Available

Percent volatile

No Data Available

Softening point

No Data Available

VOC Less H2O & Exempt Solvents

No Data Available

SECTION 10: Stability and reactivity

10.1. Reactivity

This material is considered to be non reactive under normal use conditions.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

None known.

No Data Available

10.6. Hazardous decomposition products

Substance

Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Allergic Respiratory Reaction: Signs/symptoms may include difficulty breathing, wheezing, cough, and tightness of chest.

Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion:

May be harmful if swallowed.

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Additional Health Effects:

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Ingredient	CAS No.	Class Description	Regulation
SILICA, CRYSTALLINE	14808-60-7	Known human carcinogen	National Toxicology Program Carcinogens
Generic: CAS NO S14807966D	14807-96-6	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

Generic: COAL GASSIFICATION	91-22-5	Grp. 1: Carcinogenic to humans	International Agency for Research on Cancer
Generic: COKE PRODUCTION	91-22-5	Grp. 1: Carcinogenic to humans	International Agency for Research on Cancer
Generic: SOOTS	91-22-5	Grp. 1: Carcinogenic to humans	International Agency for Research on Cancer
Generic: SOOTS	91-22-5	Known human carcinogen	National Toxicology Program Carcinogens
Generic: TALC	14807-96-6	Grp. 1: Carcinogenic to humans	International Agency for Research on Cancer
QUARTZ SILICA	14808-60-7	Grp. 1: Carcinogenic to humans	International Agency for Research on Cancer
QUINOLINE	91-22-5	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE 2,000 - 5,000 mg/kg
TALC	Dermal		LD50 estimated to be > 5,000 mg/kg
TALC	Ingestion		LD50 estimated to be > 5,000 mg/kg
DODECENYLSUCCINIC ANHYDRIDE	Dermal	Rabbit	LD50 6,200 mg/kg
DODECENYLSUCCINIC ANHYDRIDE	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 1.2 mg/l
DODECENYLSUCCINIC ANHYDRIDE	Ingestion	Rat	LD50 > 2,000 mg/kg
MALEIC ANHYDRIDE-POLYPROPYLENE GLYCOL COPOLYMER	Dermal		LD50 estimated to be > 5,000 mg/kg
MALEIC ANHYDRIDE-POLYPROPYLENE GLYCOL COPOLYMER	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
MAGNESIUM CARBONATE	Dermal	Professional judgement	LD50 estimated to be 2,000 - 5,000 mg/kg
MAGNESIUM CARBONATE	Ingestion	Rat	LD50 > 2,000 mg/kg
CHLORITE (MINERAL)	Dermal		LD50 estimated to be > 5,000 mg/kg
CHLORITE (MINERAL)	Ingestion		LD50 estimated to be > 5,000 mg/kg
DOLOMITE	Dermal		LD50 estimated to be 2,000 - 5,000 mg/kg
CALCITE	Dermal	Rat	LD50 > 2,000 mg/kg
CALCITE	Inhalation-Dust/Mist (4 hours)	Rat	LC50 3 mg/l
CALCITE	Ingestion	Rat	LD50 6,450 mg/kg
DOLOMITE	Ingestion	Rat	LD50 > 2,000 mg/kg
QUARTZ SILICA	Dermal		LD50 estimated to be > 5,000 mg/kg
QUARTZ SILICA	Ingestion		LD50 estimated to be > 5,000 mg/kg
QUINOLINE	Dermal	Rat	LD50 1,377 mg/kg
QUINOLINE	Ingestion	Rat	LD50 262 mg/kg
MALEIC ANHYDRIDE	Dermal	Rabbit	LD50 2,620 mg/kg
MALEIC ANHYDRIDE	Ingestion	Rat	LD50 1,030 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
TALC	Rabbit	No significant irritation
DODECENYLSUCCINIC ANHYDRIDE	Rabbit	Mild irritant
MAGNESIUM CARBONATE	In vitro data	No significant irritation
CALCITE	Rabbit	No significant irritation
CHLORITE (MINERAL)	Professional judgement	No significant irritation

DOLOMITE	Professional judgement	No significant irritation
QUARTZ SILICA	Professional judgement	No significant irritation
MALEIC ANHYDRIDE	Human and animal	Corrosive

Serious Eye Damage/Irritation

Name	Species	Value
TALC	Rabbit	No significant irritation
DODECENYLSUCCINIC ANHYDRIDE	Rabbit	Moderate irritant
MAGNESIUM CARBONATE	Rabbit	Mild irritant
CALCITE	Rabbit	No significant irritation
CHLORITE (MINERAL)	Professional judgement	No significant irritation
DOLOMITE	Professional judgement	No significant irritation
MALEIC ANHYDRIDE	Rabbit	Corrosive

Skin Sensitization

Name	Species	Value
DODECENYLSUCCINIC ANHYDRIDE	Human	Sensitizing
MALEIC ANHYDRIDE	Multiple animal species	Sensitizing

Respiratory Sensitization

Name	Species	Value
TALC	Human	Not classified
DODECENYLSUCCINIC ANHYDRIDE	similar compounds	Sensitizing
MALEIC ANHYDRIDE	Human	Sensitizing

Germ Cell Mutagenicity

Name	Route	Value
TALC	In Vitro	Not mutagenic
TALC	In vivo	Not mutagenic
DODECENYLSUCCINIC ANHYDRIDE	In Vitro	Not mutagenic
QUARTZ SILICA	In Vitro	Some positive data exist, but the data are not sufficient for classification
QUARTZ SILICA	In vivo	Some positive data exist, but the data are not sufficient for classification
MALEIC ANHYDRIDE	In vivo	Not mutagenic
MALEIC ANHYDRIDE	In Vitro	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
TALC	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification

QUARTZ SILICA	Inhalation	Human and animal	Carcinogenic
QUINOLINE	Ingestion	Multiple animal species	Carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
TALC	Ingestion	Not classified for development	Rat	NOAEL 1,600 mg/kg	during organogenesis
CALCITE	Ingestion	Not classified for development	Rat	NOAEL 625 mg/kg/day	premating & during gestation
MALEIC ANHYDRIDE	Ingestion	Not classified for female reproduction	Rat	NOAEL 55 mg/kg/day	2 generation
MALEIC ANHYDRIDE	Ingestion	Not classified for male reproduction	Rat	NOAEL 55 mg/kg/day	2 generation
MALEIC ANHYDRIDE	Ingestion	Not classified for development	Rat	NOAEL 140 mg/kg/day	during organogenesis

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
DODECENYLSUCCINIC ANHYDRIDE	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar compounds	NOAEL Not available	
CALCITE	Inhalation	respiratory system	Not classified	Rat	NOAEL 0.812 mg/l	90 minutes
MALEIC ANHYDRIDE	Inhalation	respiratory irritation	May cause respiratory irritation	Human	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
TALC	Inhalation	pneumoconiosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
TALC	Inhalation	pulmonary fibrosis respiratory system	Not classified	Rat	NOAEL 18 mg/m3	113 weeks
CALCITE	Inhalation	respiratory system	Not classified	Human	NOAEL Not available	occupational exposure
QUARTZ SILICA	Inhalation	silicosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
MALEIC ANHYDRIDE	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.0011 mg/l	6 months
MALEIC ANHYDRIDE	Inhalation	endocrine system hematopoietic system nervous system kidney and/or bladder heart liver eyes	Not classified	Rat	NOAEL 0.0098 mg/l	6 months
MALEIC ANHYDRIDE	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 55 mg/kg/day	80 days
MALEIC ANHYDRIDE	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 250 mg/kg/day	183 days
MALEIC ANHYDRIDE	Ingestion	heart nervous	Not classified	Rat	NOAEL 600	183 days

		system			mg/kg/day	
MALEIC ANHYDRIDE	Ingestion	gastrointestinal tract	Not classified	Rat	NOAEL 150 mg/kg/day	80 days
MALEIC ANHYDRIDE	Ingestion	hematopoietic system	Not classified	Dog	NOAEL 60 mg/kg/day	90 days
MALEIC ANHYDRIDE	Ingestion	skin endocrine system immune system eyes respiratory system	Not classified	Rat	NOAEL 150 mg/kg/day	80 days

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information**Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations**13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): Not regulated

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information**15.1. US Federal Regulations**

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:**Physical Hazards**

Not applicable

Health Hazards

Carcinogenicity

Serious eye damage or eye irritation

15.2. State Regulations

Contact 3M for more information.

California Proposition 65**Ingredient**

Talc containing asbestiform fibers

C.A.S. No.

None

Listing

Carcinogen

15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information**NFPA Hazard Classification****Health: 2 Flammability: 1 Instability: 0 Special Hazards: None**

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

HMIS Hazard Classification**Health: *2 Flammability: 1 Physical Hazard: 0 Personal Protection: X - See PPE section.**

Hazardous Material Identification System (HMIS® IV) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® IV ratings are to be used with a fully implemented HMIS® IV program. HMIS® is a registered mark of the American Coatings Association (ACA).

Document Group: 24-9295-7**Issue Date:** 09/13/21**Version Number:** 2.04**Supersedes Date:** 04/30/21

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer

may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com