



## Safety Data Sheet

Copyright,2018,3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document Group:</b>	25-7019-0	<b>Version Number:</b>	3.00
<b>Issue Date:</b>	01/12/18	<b>Supersedes Date:</b>	05/14/15

### SECTION 1: Identification

#### 1.1. Product identifier

3M(TM) Screen Printing Ink 1991 Magenta Half-Tone Concentrate

#### Product Identification Numbers

75-3469-4438-4

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Ink

#### 1.3. Supplier's details

<b>MANUFACTURER:</b>	3M
<b>DIVISION:</b>	Commercial Solutions Division
<b>ADDRESS:</b>	3M Center, St. Paul, MN 55144-1000, USA
<b>Telephone:</b>	1-888-3M HELPS (1-888-364-3577)

#### 1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

### SECTION 2: Hazard identification

#### 2.1. Hazard classification

Flammable Liquid: Category 4.

Acute Toxicity (inhalation): Category 4.

Serious Eye Damage/Irritation: Category 1.

Skin Sensitizer: Category 1A.

Reproductive Toxicity: Category 1B.

Specific Target Organ Toxicity (repeated exposure): Category 2.

#### 2.2. Label elements

##### Signal word

Danger

##### Symbols

Corrosion | Exclamation mark | Health Hazard |

**Pictograms****Hazard Statements**

Combustible liquid.

Causes serious eye damage.

May cause an allergic skin reaction.

Harmful if inhaled.

May damage fertility or the unborn child.

May cause damage to organs through prolonged or repeated exposure:  
blood or blood-forming organs |

**Precautionary Statements****Prevention:**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not breathe dust/fume/gas/mist/vapors/spray.

Use only outdoors or in a well-ventilated area.

Wear protective gloves and eye/face protection.

Contaminated work clothing must not be allowed out of the workplace.

**Response:**

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF ON SKIN: Wash with plenty of soap and water.

Immediately call a POISON CENTER or doctor/physician.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

IF exposed or concerned: Get medical advice/attention.

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

**Storage:**

Keep cool.

Keep container tightly closed.

Store locked up in a well-ventilated place.

**Disposal:**

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

17% of the mixture consists of ingredients of unknown acute oral toxicity.

17% of the mixture consists of ingredients of unknown acute dermal toxicity.

35% of the mixture consists of ingredients of unknown acute inhalation toxicity.

**SECTION 3: Composition/information on ingredients**

Ingredient	C.A.S. No.	% by Wt
2-BUTOXYETHYL ACETATE	112-07-2	30 - 40 Trade Secret *
C.I. PIGMENT RED 122	980-26-7	10 - 20 Trade Secret *
VINYL ACETATE-VINYL ALCOHOL-VINYL CHLORIDE POLYMER	25086-48-0	10 - 20 Trade Secret *
GAMMA-BUTYROLACTONE	96-48-0	10 - 19 Trade Secret *
ACRYLIC POLYMER	Trade Secret*	5 - 15 Trade Secret *
POLYMERIC PLASTICIZER	Trade Secret*	5 - 10 Trade Secret *
EPOXIDIZED SOYBEAN OIL	8013-07-8	0.1 - 5 Trade Secret *
Poly(oxy-1,2-ethanediyl), .alpha.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-.omega.-hydroxy-	104810-48-2	< 1 Trade Secret *
Polymeric Benzotriazole	104810-47-1	< 1 Trade Secret *
2-Butoxyethanol	111-76-2	< 0.5 Trade Secret *
Bis(1,2,2,6,6-pentamethyl-4-piperidiny) sebacate	41556-26-7	< 0.5 Trade Secret *
CALCIUM 2-ETHYLHEXANOATE	136-51-6	< 0.5 Trade Secret *
HEAVY AROMATIC SOLVENT NAPHTHA (PETROLEUM)	64742-94-5	< 0.5 Trade Secret *
Light aromatic solvent naphtha (petroleum)	64742-95-6	< 0.5 Trade Secret *
Methyl Methacrylate	80-62-6	< 0.5 Trade Secret *
TOLUENE	108-88-3	< 0.5 Trade Secret *
ZINC 2-ETHYLHEXANOATE	136-53-8	< 0.5 Trade Secret *
Triphenyl Phosphite	101-02-0	< 0.1 Trade Secret *

\*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

#### Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

#### Eye Contact:

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

#### If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable.

## SECTION 5: Fire-fighting measures

### 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

### 5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

### Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Hydrogen Chloride	During Combustion
Oxides of Nitrogen	During Combustion

### 5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

### 6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

### 6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with detergent and water. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

For industrial or professional use only. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (gloves, respirators, etc.) as required.

### 7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Protect from sunlight. Store away from heat. Store away from acids. Store away from oxidizing agents.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
TOLUENE	108-88-3	ACGIH	TWA:20 ppm	A4: Not class. as human carcin
TOLUENE	108-88-3	OSHA	TWA:200 ppm;CEIL:300 ppm	
2-Butoxyethanol	111-76-2	OSHA	TWA:240 mg/m3(50 ppm)	SKIN
2-Butoxyethanol	111-76-2	ACGIH	TWA:20 ppm	A3: Confirmed animal carcin.
2-BUTOXYETHYL ACETATE	112-07-2	ACGIH	TWA:20 ppm	A3: Confirmed animal carcin.
Naphtha	64742-94-5	OSHA	TWA:400 mg/m3(100 ppm)	
Naphtha	64742-95-6	OSHA	TWA:400 mg/m3(100 ppm)	
Methyl Methacrylate	80-62-6	OSHA	TWA:410 mg/m3(100 ppm)	
Methyl Methacrylate	80-62-6	ACGIH	TWA:50 ppm;STEL:100 ppm	Dermal Sensitizer, A4: Not class. as human carcin

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

### 8.2. Exposure controls

#### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

#### 8.2.2. Personal protective equipment (PPE)

##### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full Face Shield

Indirect Vented Goggles

##### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an

exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

General Physical Form:	Liquid
Specific Physical Form:	Liquid
Odor, Color, Grade:	Solvent Odor, Magenta Color
Odor threshold	<i>No Data Available</i>
pH	<i>Not Applicable</i>
Melting point	<i>Not Applicable</i>
Boiling Point	>=367 °F
Flash Point	160 °F [ <i>Test Method</i> :Closed Cup]
Evaporation rate	<i>No Data Available</i>
Flammability (solid, gas)	Not Applicable
Flammable Limits(LEL)	0.5 %
Flammable Limits(UEL)	6.9 %
Vapor Pressure	<=0.26 mmHg [ <i>@ 20 °C</i> ]
Vapor Density	> 1 [ <i>Ref Std</i> :AIR=1]
Density	1.1 g/ml
Specific Gravity	1.1 [ <i>Ref Std</i> :WATER=1]
Solubility in Water	Moderate
Solubility- non-water	<i>No Data Available</i>
Partition coefficient: n-octanol/ water	<i>No Data Available</i>
Autoignition temperature	> 640 °F
Decomposition temperature	<i>No Data Available</i>
Viscosity	11,000 - 13,000 centipoise [ <i>Test Method</i> :Tested per ASTM protocol]
Volatile Organic Compounds	562 g/l [ <i>Details</i> :As formulated]
Volatile Organic Compounds	611 g/l [ <i>Details</i> :After manufacturing thinning]
Percent volatile	45.0 - 55.0 %
VOC Less H2O & Exempt Solvents	562 g/l [ <i>Details</i> :As formulated]
VOC Less H2O & Exempt Solvents	611 g/l [ <i>Details</i> :After manufacturing thinning]

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

### 10.2. Chemical stability

Stable.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

**10.4. Conditions to avoid**

Heat  
Sparks and/or flames

**10.5. Incompatible materials**

Strong oxidizing agents

**10.6. Hazardous decomposition products**

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

**SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

**11.1. Information on Toxicological effects****Signs and Symptoms of Exposure**

Based on test data and/or information on the components, this material may produce the following health effects:

**Inhalation:**

Harmful if inhaled.

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

**Skin Contact:**

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

**Eye Contact:**

Corrosive (Eye Burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

**Ingestion:**

May be harmful if swallowed.

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

**Additional Health Effects:****Prolonged or repeated exposure may cause target organ effects:**

Blood Effects: Signs/symptoms may include generalized weakness and fatigue, skin pallor, changes in blood clotting time, internal bleeding, and/or hemoglobinemia.

**Reproductive/Developmental Toxicity:**

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

**Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Vapor(4 hr)		No data available; calculated ATE20 - 50 mg/l
Overall product	Ingestion		No data available; calculated ATE2,000 - 5,000 mg/kg
2-BUTOXYETHYL ACETATE	Inhalation-Vapor	official classification	LC50 estimated to be 10 - 20 mg/l
2-BUTOXYETHYL ACETATE	Dermal	Rabbit	LD50 > 4,766 mg/kg
2-BUTOXYETHYL ACETATE	Ingestion	Rat	LD50 2,400 mg/kg
GAMMA-BUTYROLACTONE	Dermal	Rabbit	LD50 > 5,000 mg/kg
GAMMA-BUTYROLACTONE	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 5.1 mg/l
GAMMA-BUTYROLACTONE	Ingestion	Rat	LD50 1,920 mg/kg
C.I. PIGMENT RED 122	Dermal	Rat	LD50 > 3,000 mg/kg
C.I. PIGMENT RED 122	Ingestion	Rat	LD50 > 2,000 mg/kg
VINYL ACETATE-VINYL ALCOHOL-VINYL CHLORIDE POLYMER	Dermal	Rabbit	LD50 > 8,000 mg/kg
VINYL ACETATE-VINYL ALCOHOL-VINYL CHLORIDE POLYMER	Ingestion	Rat	LD50 > 8,000 mg/kg
EPOXIDIZED SOYBEAN OIL	Dermal	Rabbit	LD50 > 20,000 mg/kg
EPOXIDIZED SOYBEAN OIL	Ingestion	Rat	LD50 > 5,000 mg/kg
Poly(oxy-1,2-ethanediyl), .alpha.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-.omega.-hydroxy-	Dermal	Rat	LD50 > 2,000 mg/kg
Poly(oxy-1,2-ethanediyl), .alpha.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-.omega.-hydroxy-	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 5.8 mg/l
Poly(oxy-1,2-ethanediyl), .alpha.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-.omega.-hydroxy-	Ingestion	Rat	LD50 > 5,000 mg/kg
Polymeric Benzotriazole	Dermal	Rat	LD50 > 2,000 mg/kg
Polymeric Benzotriazole	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 5.8 mg/l
Polymeric Benzotriazole	Ingestion	Rat	LD50 > 5,000 mg/kg
2-Butoxyethanol	Dermal	Guinea pig	LD50 > 2,000 mg/kg
2-Butoxyethanol	Inhalation-Vapor (4 hours)	Guinea pig	LC50 > 2.6 mg/l
2-Butoxyethanol	Ingestion	Guinea pig	LD50 1,414 mg/kg
HEAVY AROMATIC SOLVENT NAPHTHA (PETROLEUM)	Dermal	Rabbit	LD50 > 2,000 mg/kg
HEAVY AROMATIC SOLVENT NAPHTHA (PETROLEUM)	Ingestion	Rat	LD50 > 5,000 mg/kg
Bis(1,2,2,6,6-pentamethyl-4-piperidiny)l) sebacate	Dermal		LD50 estimated to be 2,000 - 5,000 mg/kg
Bis(1,2,2,6,6-pentamethyl-4-piperidiny)l) sebacate	Ingestion	Rat	LD50 3,125 mg/kg
TOLUENE	Dermal	Rat	LD50 12,000 mg/kg
TOLUENE	Inhalation-Vapor (4 hours)	Rat	LC50 30 mg/l
TOLUENE	Ingestion	Rat	LD50 5,550 mg/kg
Methyl Methacrylate	Dermal	Rabbit	LD50 > 5,000 mg/kg
Methyl Methacrylate	Inhalation-	Rat	LC50 29 mg/l



	Vapor (4 hours)		
Methyl Methacrylate	Ingestion	Rat	LD50 7,900 mg/kg
ZINC 2-ETHYLHEXANOATE	Dermal		LD50 estimated to be > 5,000 mg/kg
ZINC 2-ETHYLHEXANOATE	Ingestion	Rat	LD50 > 5,000 mg/kg
CALCIUM 2-ETHYLHEXANOATE	Dermal	Rabbit	LD50 > 5,000 mg/kg
CALCIUM 2-ETHYLHEXANOATE	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 1.2 mg/l
CALCIUM 2-ETHYLHEXANOATE	Ingestion	Rat	LD50 > 5,000 mg/kg
Light aromatic solvent naphtha (petroleum)	Dermal	Rabbit	LD50 > 2,000 mg/kg
Light aromatic solvent naphtha (petroleum)	Inhalation-Vapor (4 hours)	Rat	LC50 > 5.2 mg/l
Light aromatic solvent naphtha (petroleum)	Ingestion	Rat	LD50 > 5,000 mg/kg
Triphenyl Phosphite	Dermal	Rabbit	LD50 > 2,000 mg/kg
Triphenyl Phosphite	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 1.7 mg/l
Triphenyl Phosphite	Ingestion	Rat	LD50 1,590 mg/kg

ATE = acute toxicity estimate

### Skin Corrosion/Irritation

Name	Species	Value
2-BUTOXYETHYL ACETATE	Rabbit	Minimal irritation
GAMMA-BUTYROLACTONE	Rabbit	No significant irritation
C.I. PIGMENT RED 122	Rabbit	No significant irritation
VINYL ACETATE-VINYL ALCOHOL-VINYL CHLORIDE POLYMER	Professional judgment	No significant irritation
EPOXIDIZED SOYBEAN OIL	Rabbit	No significant irritation
Poly(oxy-1,2-ethanediyl), alpha.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-.omega.-hydroxy-	Rabbit	No significant irritation
Polymeric Benzotriazole	Rabbit	No significant irritation
2-Butoxyethanol	Rabbit	Irritant
HEAVY AROMATIC SOLVENT NAPHTHA (PETROLEUM)	Rabbit	Irritant
Bis(1,2,2,6,6-pentamethyl-4-piperidiny) sebacate	Rabbit	No significant irritation
TOLUENE	Rabbit	Irritant
Methyl Methacrylate	Human and animal	Mild irritant
ZINC 2-ETHYLHEXANOATE	Rabbit	Mild irritant
CALCIUM 2-ETHYLHEXANOATE	Rabbit	No significant irritation
Light aromatic solvent naphtha (petroleum)	Rabbit	Irritant
Triphenyl Phosphite	Rabbit	Irritant

### Serious Eye Damage/Irritation

Name	Species	Value
2-BUTOXYETHYL ACETATE	Rabbit	Mild irritant
GAMMA-BUTYROLACTONE	Rabbit	Corrosive
C.I. PIGMENT RED 122	Rabbit	No significant irritation
VINYL ACETATE-VINYL ALCOHOL-VINYL CHLORIDE POLYMER	Professional judgment	No significant irritation
EPOXIDIZED SOYBEAN OIL	Rabbit	No significant irritation
Poly(oxy-1,2-ethanediyl), alpha.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-.omega.-hydroxy-	Rabbit	No significant irritation
Polymeric Benzotriazole	Rabbit	No significant irritation
2-Butoxyethanol	Rabbit	Severe irritant
HEAVY AROMATIC SOLVENT NAPHTHA (PETROLEUM)	Rabbit	Mild irritant

Bis(1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate	Rabbit	No significant irritation
TOLUENE	Rabbit	Moderate irritant
Methyl Methacrylate	Rabbit	Moderate irritant
ZINC 2-ETHYLHEXANOATE	Rabbit	Severe irritant
CALCIUM 2-ETHYLHEXANOATE	Rabbit	Corrosive
Light aromatic solvent naphtha (petroleum)	Rabbit	Mild irritant
Triphenyl Phosphite	Rabbit	Moderate irritant

### Skin Sensitization

Name	Species	Value
C.I. PIGMENT RED 122	Not available	Not classified
EPOXIDIZED SOYBEAN OIL	Guinea pig	Not classified
Poly(oxy-1,2-ethanediyl), .alpha.-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-.omega.-hydroxy-	Guinea pig	Sensitizing
Polymeric Benzotriazole	Guinea pig	Sensitizing
2-Butoxyethanol	Guinea pig	Not classified
HEAVY AROMATIC SOLVENT NAPHTHA (PETROLEUM)	Guinea pig	Not classified
Bis(1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate	Guinea pig	Sensitizing
TOLUENE	Guinea pig	Not classified
Methyl Methacrylate	Human and animal	Sensitizing
Light aromatic solvent naphtha (petroleum)	Guinea pig	Not classified
Triphenyl Phosphite	Mouse	Sensitizing

### Respiratory Sensitization

Name	Species	Value
Methyl Methacrylate	Human	Not classified

### Germ Cell Mutagenicity

Name	Route	Value
EPOXIDIZED SOYBEAN OIL	In Vitro	Not mutagenic
2-Butoxyethanol	In Vitro	Some positive data exist, but the data are not sufficient for classification
Bis(1,2,2,6,6-pentamethyl-4-piperidinyl) sebacate	In Vitro	Not mutagenic
TOLUENE	In Vitro	Not mutagenic
TOLUENE	In vivo	Not mutagenic
Methyl Methacrylate	In vivo	Not mutagenic
Methyl Methacrylate	In Vitro	Some positive data exist, but the data are not sufficient for classification
CALCIUM 2-ETHYLHEXANOATE	In Vitro	Not mutagenic

### Carcinogenicity

Name	Route	Species	Value
EPOXIDIZED SOYBEAN OIL	Ingestion	Rat	Not carcinogenic
2-Butoxyethanol	Inhalation	Multiple animal species	Some positive data exist, but the data are not sufficient for classification
HEAVY AROMATIC SOLVENT NAPHTHA (PETROLEUM)	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
TOLUENE	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
TOLUENE	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification

TOLUENE	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification
Methyl Methacrylate	Ingestion	Rat	Not carcinogenic
Methyl Methacrylate	Inhalation	Human and animal	Not carcinogenic
Light aromatic solvent naphtha (petroleum)	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification

**Reproductive Toxicity**

**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test Result	Exposure Duration
EPOXIDIZED SOYBEAN OIL	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	1 generation
EPOXIDIZED SOYBEAN OIL	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	1 generation
EPOXIDIZED SOYBEAN OIL	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	1 generation
2-Butoxyethanol	Dermal	Not classified for development	Rat	NOAEL 1,760 mg/kg/day	during gestation
2-Butoxyethanol	Ingestion	Not classified for development	Rat	NOAEL 100 mg/kg/day	during organogenesis
2-Butoxyethanol	Inhalation	Not classified for development	Multiple animal species	NOAEL 0.48 mg/l	during organogenesis
TOLUENE	Inhalation	Not classified for female reproduction	Human	NOAEL Not available	occupational exposure
TOLUENE	Inhalation	Not classified for male reproduction	Rat	NOAEL 2.3 mg/l	1 generation
TOLUENE	Ingestion	Toxic to development	Rat	LOAEL 520 mg/kg/day	during gestation
TOLUENE	Inhalation	Toxic to development	Human	NOAEL Not available	poisoning and/or abuse
Methyl Methacrylate	Inhalation	Not classified for male reproduction	Mouse	NOAEL 36.9 mg/l	
Methyl Methacrylate	Inhalation	Not classified for development	Rat	NOAEL 8.3 mg/l	during organogenesis
ZINC 2-ETHYLHEXANOATE	Ingestion	Toxic to female reproduction	Rat	NOAEL 300 mg/kg/day	1 generation
ZINC 2-ETHYLHEXANOATE	Ingestion	Toxic to male reproduction	Rat	NOAEL 300 mg/kg/day	1 generation
ZINC 2-ETHYLHEXANOATE	Ingestion	Toxic to development	Rat	NOAEL 100 mg/kg/day	1 generation
CALCIUM 2-ETHYLHEXANOATE	Ingestion	Toxic to female reproduction	Rat	NOAEL 300 mg/kg/day	1 generation
CALCIUM 2-ETHYLHEXANOATE	Ingestion	Toxic to male reproduction	Rat	NOAEL 300 mg/kg/day	1 generation
CALCIUM 2-ETHYLHEXANOATE	Ingestion	Toxic to development	Rat	NOAEL 100 mg/kg/day	1 generation
Light aromatic solvent naphtha (petroleum)	Inhalation	Not classified for female reproduction	Rat	NOAEL 1,500 ppm	2 generation
Light aromatic solvent naphtha (petroleum)	Inhalation	Not classified for male reproduction	Rat	NOAEL 1,500 ppm	2 generation
Light aromatic solvent naphtha (petroleum)	Inhalation	Not classified for development	Rat	NOAEL 500 ppm	2 generation

**Target Organ(s)**

**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
------	-------	-----------------	-------	---------	-------------	-------------------

2-BUTOXYETHYL ACETATE	Dermal	kidney and/or bladder	Not classified	Rabbit	NOAEL Not available	24 hours
2-BUTOXYETHYL ACETATE	Dermal	blood	Not classified	Rabbit	LOAEL 3,191 mg/kg	24 hours
2-BUTOXYETHYL ACETATE	Dermal	heart   endocrine system   hematopoietic system   liver   nervous system	Not classified	Rabbit	NOAEL 10,000 mg/kg	24 hours
2-BUTOXYETHYL ACETATE	Inhalation	central nervous system depression	Some positive data exist, but the data are not sufficient for classification	similar compounds	NOAEL Not available	
2-BUTOXYETHYL ACETATE	Inhalation	blood   heart   endocrine system   hematopoietic system   liver   nervous system   kidney and/or bladder   respiratory system	Not classified	Multiple animal species	NOAEL 2.6 mg/l	4 hours
2-BUTOXYETHYL ACETATE	Ingestion	blood	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 2,400 mg/kg	not applicable
2-BUTOXYETHYL ACETATE	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 2,400 mg/kg	not applicable
2-BUTOXYETHYL ACETATE	Ingestion	kidney and/or bladder	Not classified	Rat	LOAEL 2,400 mg/kg	not applicable
2-BUTOXYETHYL ACETATE	Ingestion	heart   liver   nervous system	Not classified	Rat	NOAEL 3,000 mg/kg	not applicable
GAMMA-BUTYROLACTONE	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Rat	NOAEL Not available	4 hours
GAMMA-BUTYROLACTONE	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
2-Butoxyethanol	Dermal	endocrine system	Not classified	Rabbit	NOAEL 902 mg/kg	6 hours
2-Butoxyethanol	Dermal	liver	Not classified	Rabbit	LOAEL 72 mg/kg	not available
2-Butoxyethanol	Dermal	kidney and/or bladder	Not classified	Rabbit	LOAEL 451 mg/kg	6 hours
2-Butoxyethanol	Dermal	blood	Not classified	Multiple animal species	NOAEL Not available	
2-Butoxyethanol	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
2-Butoxyethanol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
2-Butoxyethanol	Inhalation	blood	Not classified	Multiple animal species	NOAEL Not available	
2-Butoxyethanol	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
2-Butoxyethanol	Ingestion	blood	Not classified	Multiple animal species	NOAEL Not available	
2-Butoxyethanol	Ingestion	kidney and/or bladder	Not classified	Human	NOAEL Not available	poisoning and/or abuse
HEAVY AROMATIC SOLVENT NAPHTHA (PETROLEUM)	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
HEAVY AROMATIC SOLVENT NAPHTHA (PETROLEUM)	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Professional judgement	NOAEL Not available	
HEAVY AROMATIC	Ingestion	central nervous	May cause drowsiness or	Professional	NOAEL Not	

SOLVENT NAPHTHA (PETROLEUM)		system depression	dizziness	nal judgement	available	
TOLUENE	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
TOLUENE	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
TOLUENE	Inhalation	immune system	Not classified	Mouse	NOAEL 0.004 mg/l	3 hours
TOLUENE	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
Methyl Methacrylate	Inhalation	respiratory irritation	May cause respiratory irritation	Human	NOAEL Not available	occupational exposure
ZINC 2-ETHYLHEXANOATE	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL not available	
CALCIUM 2-ETHYLHEXANOATE	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL not available	
Light aromatic solvent naphtha (petroleum)	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
Light aromatic solvent naphtha (petroleum)	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Professional judgement	NOAEL Not available	
Light aromatic solvent naphtha (petroleum)	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	

**Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
2-BUTOXYETHYL ACETATE	Inhalation	blood	May cause damage to organs though prolonged or repeated exposure	Multiple animal species	NOAEL 0.7 mg/l	10 months
2-BUTOXYETHYL ACETATE	Inhalation	kidney and/or bladder	Not classified	Multiple animal species	LOAEL 0.7 mg/l	10 months
2-BUTOXYETHYL ACETATE	Inhalation	heart   endocrine system   hematopoietic system   liver   nervous system   respiratory system	Not classified	Multiple animal species	NOAEL 0.7 mg/l	10 months
EPOXIDIZED SOYBEAN OIL	Ingestion	liver   kidney and/or bladder	Not classified	Rat	NOAEL 1,250 mg/kg/day	2 years
2-Butoxyethanol	Dermal	blood	Not classified	Multiple animal species	NOAEL Not available	not available
2-Butoxyethanol	Dermal	endocrine system	Not classified	Rabbit	NOAEL 150 mg/kg/day	90 days
2-Butoxyethanol	Inhalation	liver	Not classified	Rat	NOAEL 2.4 mg/l	14 weeks
2-Butoxyethanol	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 0.15 mg/l	14 weeks
2-Butoxyethanol	Inhalation	blood	Not classified	Rat	LOAEL 0.15 mg/l	6 months
2-Butoxyethanol	Inhalation	endocrine system	Not classified	Dog	LOAEL 1.9 mg/l	8 days
2-Butoxyethanol	Ingestion	blood	Not classified	Rat	LOAEL 69 mg/kg/day	13 weeks
2-Butoxyethanol	Ingestion	kidney and/or	Not classified	Multiple	NOAEL Not	not available

		bladder		animal species	available	
TOLUENE	Inhalation	auditory system   nervous system   eyes   olfactory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
TOLUENE	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 2.3 mg/l	15 months
TOLUENE	Inhalation	heart   liver   kidney and/or bladder	Not classified	Rat	NOAEL 11.3 mg/l	15 weeks
TOLUENE	Inhalation	endocrine system	Not classified	Rat	NOAEL 1.1 mg/l	4 weeks
TOLUENE	Inhalation	immune system	Not classified	Mouse	NOAEL Not available	20 days
TOLUENE	Inhalation	bone, teeth, nails, and/or hair	Not classified	Mouse	NOAEL 1.1 mg/l	8 weeks
TOLUENE	Inhalation	hematopoietic system   vascular system	Not classified	Human	NOAEL Not available	occupational exposure
TOLUENE	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 625 mg/kg/day	13 weeks
TOLUENE	Ingestion	heart	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
TOLUENE	Ingestion	liver   kidney and/or bladder	Not classified	Multiple animal species	NOAEL 2,500 mg/kg/day	13 weeks
TOLUENE	Ingestion	hematopoietic system	Not classified	Mouse	NOAEL 600 mg/kg/day	14 days
TOLUENE	Ingestion	endocrine system	Not classified	Mouse	NOAEL 105 mg/kg/day	28 days
TOLUENE	Ingestion	immune system	Not classified	Mouse	NOAEL 105 mg/kg/day	4 weeks
Methyl Methacrylate	Dermal	peripheral nervous system	Not classified	Human	NOAEL Not available	occupational exposure
Methyl Methacrylate	Inhalation	olfactory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
Methyl Methacrylate	Inhalation	kidney and/or bladder	Not classified	Multiple animal species	NOAEL Not available	14 weeks
Methyl Methacrylate	Inhalation	liver	Not classified	Mouse	NOAEL 12.3 mg/l	14 weeks
Methyl Methacrylate	Inhalation	respiratory system	Not classified	Human	NOAEL Not available	occupational exposure
Triphenyl Phosphite	Ingestion	nervous system	May cause damage to organs though prolonged or repeated exposure	Rat	NOAEL 15 mg/kg/day	28 days

### Aspiration Hazard

Name	Value
HEAVY AROMATIC SOLVENT NAPHTHA (PETROLEUM)	Aspiration hazard
TOLUENE	Aspiration hazard
Light aromatic solvent naphtha (petroleum)	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

## SECTION 12: Ecological information

### Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material

and/or its components.

### Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

**EPA Hazardous Waste Number (RCRA):** D006 (Cadmium), D009 (Mercury), D010 (Selenium), D018 (Benzene)

## SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

## SECTION 15: Regulatory information

### 15.1. US Federal Regulations

Contact 3M for more information.

#### EPCRA 311/312 Hazard Classifications:

##### Physical Hazards

Flammable (gases, aerosols, liquids, or solids)

##### Health Hazards

Acute toxicity

Reproductive toxicity

Respiratory or Skin Sensitization

Serious eye damage or eye irritation

Specific target organ toxicity (single or repeated exposure)

#### Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

<u>Ingredient</u>	<u>C.A.S. No</u>	<u>% by Wt</u>
2-BUTOXYETHYL ACETATE (GLYCOL ETHERS)	112-07-2	30 - 40
2-Butoxyethanol (GLYCOL ETHERS)	111-76-2	< 0.5

### 15.2. State Regulations

Contact 3M for more information.

**15.3. Chemical Inventories**

The components of this product are in compliance with the chemical notification requirements of TSCA.

Contact 3M for more information.

**15.4. International Regulations**

Contact 3M for more information.

**This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.**

**SECTION 16: Other information**

**NFPA Hazard Classification**

**Health: 3 Flammability: 2 Instability: 0 Special Hazards: None**

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

<b>Document Group:</b>	25-7019-0	<b>Version Number:</b>	3.00
<b>Issue Date:</b>	01/12/18	<b>Supersedes Date:</b>	05/14/15

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

**3M USA SDSs are available at [www.3M.com](http://www.3M.com)**