



Safety Data Sheet

Copyright, 2023, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	25-2752-1	Version Number:	4.02
Issue Date:	03/16/23	Supersedes Date:	12/11/19

SECTION 1: Identification

1.1. Product identifier

3M™ Scotch-Weld™ Epoxy Adhesive EC-3501 B/A Gray, Part A

Product Identification Numbers

LA-T100-2867-7, LC-B100-0585-4, LC-B100-0585-5, LC-B100-0605-3, LC-B100-0913-1, LC-B100-1243-5, LC-B100-1807-4, 41-3588-1673-8, 62-3601-8540-9
7010330239

1.2. Recommended use and restrictions on use

Recommended use

Accelerator component (Part A) of 2-part epoxy adhesive

1.3. Supplier's details

MANUFACTURER:	3M
DIVISION:	Automotive and Aerospace Solutions Division
ADDRESS:	3M Center, St. Paul, MN 55144-1000, USA
Telephone:	1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

2.1. Hazard classification

Serious Eye Damage/Irritation: Category 1.

Skin Corrosion/Irritation: Category 2.

Skin Sensitizer: Category 1A.

2.2. Label elements

Signal word

Danger

Symbols

Corrosion | Exclamation mark |

Pictograms

**Hazard Statements**

Causes serious eye damage.
 Causes skin irritation.
 May cause an allergic skin reaction.

Precautionary Statements**Prevention:**

Avoid breathing dust/fume/gas/mist/vapors/spray.
 Wear protective gloves and eye/face protection.
 Wash thoroughly after handling.
 Contaminated work clothing must not be allowed out of the workplace.

Response:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 IF ON SKIN: Wash with plenty of soap and water.
 Immediately call a POISON CENTER or doctor/physician.
 If skin irritation or rash occurs: Get medical advice/attention.
 Take off contaminated clothing and wash it before reuse.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

Supplemental Information:

Persons previously sensitized to amines may develop a cross-sensitization reaction to certain other amines.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
Mercaptan Polymer	72244-98-5	40 - 60 Trade Secret *
Talc	14807-96-6	15 - 40 Trade Secret *
Fatty acids, tall-oil, polymers with C18-unsatd. fatty acid dimers and triethylenetetramine	68082-29-1	5 - 15 Trade Secret *
Amorphous Silica	112945-52-5	1 - 5
2,4,6-Tris((dimethylamino)methyl)phenol	90-72-2	0.5 - 2.5 Trade Secret *
Carbon Black	1333-86-4	< 0.5 Trade Secret *
TRIETHYLENETETRAMINE	112-24-3	< 0.5 Trade Secret *

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures**Inhalation:**

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance

Aldehydes
 Hydrocarbons
 Carbon monoxide
 Carbon dioxide
 Ketones
 Oxides of Nitrogen
 Oxides of Sulfur
 Toxic Vapor, Gas, Particulate

Condition

During Combustion
 During Combustion
 During Combustion
 During Combustion
 During Combustion
 During Combustion
 During Combustion
 During Combustion

5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible.

Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid skin contact with hot material. For industrial/occupational use only. Not for consumer sale or use. Do not use in a confined area with minimal air exchange. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Store away from heat. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
TRIETHYLENETETRAMINE	112-24-3	AIHA	TWA:6 mg/m ³ (1 ppm)	SKIN
SILICA, AMORPHOUS	112945-52-5	OSHA	TWA:20 millions of particles/cu. ft.;TWA concentration:0.8 mg/m ³	
Carbon Black	1333-86-4	ACGIH	TWA(inhalable fraction):3 mg/m ³	A3: Confirmed animal carcin.
Carbon Black	1333-86-4	OSHA	TWA:3.5 mg/m ³	
Talc	14807-96-6	ACGIH	TWA(respirable fraction):2 mg/m ³	A4: Not class. as human carcin
Talc	14807-96-6	OSHA	TWA concentration(respirable):0.1 mg/m ³ (2.4 millions of particles/cu. ft.);TWA:20 millions of particles/cu. ft.	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full Face Shield

Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

When only incidental contact is anticipated, alternative glove material(s) may be used. If contact with the glove does occur, remove immediately and replace with a set of new gloves. For incidental contact, gloves made of the following material(s) may be used: Nitrile Rubber

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Thermal hazards

Wear heat insulating gloves, indirect vented goggles, and a full face shield when handling hot material to prevent thermal burns.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state

Liquid

Color

Black

Specific Physical Form:

Viscous Liquid

Odor

Strong Mercaptan

Odor threshold

No Data Available

pH

Not Applicable

Melting point

No Data Available

Boiling Point

≥ 250 °F [*Test Method: Estimated*]

Flash Point

≥ 200 °F [*Test Method: Closed Cup*]

Evaporation rate

Not Applicable

Flammability (solid, gas)

Not Applicable

Flammable Limits(LEL)

No Data Available

Flammable Limits(UEL)

No Data Available

Vapor Pressure

≤ 27 psia [*@ 131 °F*] [*Details: MITS data*]

Vapor Density

Not Applicable

Density	1.4 g/ml
Specific Gravity	1.4 [Ref Std: WATER=1]
Solubility in Water	No Data Available
Solubility- non-water	No Data Available
Partition coefficient: n-octanol/ water	No Data Available
Autoignition temperature	No Data Available
Decomposition temperature	No Data Available
Viscosity	No Data Available
Hazardous Air Pollutants	< 1 % weight [Test Method: Calculated]
Molecular weight	No Data Available
Volatile Organic Compounds	< 7 g/l [Test Method: calculated SCAQMD rule 443.1]
VOC Less H2O & Exempt Solvents	< 7 g/l [Test Method: calculated SCAQMD rule 443.1]

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat

Heat is generated during cure. Do not cure a mass larger than 50 grams in a confined space to prevent a premature exothermic reaction with production of intense heat and smoke.

10.5. Incompatible materials

Strong oxidizing agents

10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin Contact:

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain.
Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

Corrosive (Eye Burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

Ingestion:

May be harmful if swallowed.

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Carcinogenicity:

Ingredient	CAS No.	Class Description	Regulation
Carbon black	1333-86-4	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

Additional Information:

Persons previously sensitized to amines may develop a cross-sensitization reaction to certain other amines.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >2,000 - =5,000 mg/kg
Mercaptan Polymer	Dermal	Rabbit	LD50 > 10,200 mg/kg
Mercaptan Polymer	Ingestion	Rat	LD50 2,600 mg/kg
Talc	Dermal		LD50 estimated to be > 5,000 mg/kg
Talc	Ingestion		LD50 estimated to be > 5,000 mg/kg
Fatty acids, tall-oil, polymers with C18-unsatd. fatty acid dimers and triethylenetetramine	Dermal	Rat	LD50 > 2,000 mg/kg
Fatty acids, tall-oil, polymers with C18-unsatd. fatty acid dimers and triethylenetetramine	Ingestion	Rat	LD50 > 5,000 mg/kg
2,4,6-Tris((dimethylamino)methyl)phenol	Dermal	Rat	LD50 1,280 mg/kg
2,4,6-Tris((dimethylamino)methyl)phenol	Ingestion	Rat	LD50 1,000 mg/kg
Amorphous Silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
Amorphous Silica	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Amorphous Silica	Ingestion	Rat	LD50 > 5,110 mg/kg
TRIETHYLENETETRAMINE	Dermal	Rabbit	LD50 550 mg/kg
TRIETHYLENETETRAMINE	Ingestion	Rat	LD50 2,500 mg/kg
Carbon Black	Dermal	Rabbit	LD50 > 3,000 mg/kg
Carbon Black	Ingestion	Rat	LD50 > 8,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Mercaptan Polymer	Rabbit	No significant irritation
Talc	Rabbit	No significant irritation
Fatty acids, tall-oil, polymers with C18-unsatd. fatty acid dimers and triethylenetetramine	In vitro data	Irritant
2,4,6-Tris((dimethylamino)methyl)phenol	Rabbit	Corrosive

Amorphous Silica	Rabbit	No significant irritation
TRIETHYLENETETRAMINE	Rabbit	Corrosive
Carbon Black	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Mercaptan Polymer	Rabbit	Mild irritant
Talc	Rabbit	No significant irritation
Fatty acids, tall-oil, polymers with C18-unsatd. fatty acid dimers and triethylenetetramine	Rabbit	Corrosive
2,4,6-Tris((dimethylamino)methyl)phenol	Rabbit	Corrosive
Amorphous Silica	Rabbit	No significant irritation
TRIETHYLENETETRAMINE	Rabbit	Corrosive
Carbon Black	Rabbit	No significant irritation

Skin Sensitization

Name	Species	Value
Mercaptan Polymer	Mouse	Sensitizing
Fatty acids, tall-oil, polymers with C18-unsatd. fatty acid dimers and triethylenetetramine	Mouse	Sensitizing
2,4,6-Tris((dimethylamino)methyl)phenol	Guinea pig	Not classified
Amorphous Silica	Human and animal	Not classified
TRIETHYLENETETRAMINE	Guinea pig	Sensitizing

Respiratory Sensitization

Name	Species	Value
Talc	Human	Not classified

Germ Cell Mutagenicity

Name	Route	Value
Mercaptan Polymer	In Vitro	Not mutagenic
Talc	In Vitro	Not mutagenic
Talc	In vivo	Not mutagenic
2,4,6-Tris((dimethylamino)methyl)phenol	In Vitro	Not mutagenic
Amorphous Silica	In Vitro	Not mutagenic
Carbon Black	In Vitro	Not mutagenic
Carbon Black	In vivo	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
Talc	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification
Amorphous Silica	Not Specified	Mouse	Some positive data exist, but the data are not sufficient for classification
Carbon Black	Dermal	Mouse	Not carcinogenic
Carbon Black	Ingestion	Mouse	Not carcinogenic
Carbon Black	Inhalation	Rat	Carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
------	-------	-------	---------	-------------	-------------------

Talc	Ingestion	Not classified for development	Rat	NOAEL 1,600 mg/kg	during organogenesis
Amorphous Silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Amorphous Silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Amorphous Silica	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
2,4,6-Tris((dimethylamino)methyl)phenol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Mercaptan Polymer	Ingestion	hematopoietic system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 75 mg/kg/day	90 days
Mercaptan Polymer	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 250 mg/kg/day	90 days
Mercaptan Polymer	Ingestion	endocrine system heart skin immune system nervous system eyes kidney and/or bladder respiratory system vascular system	Not classified	Rat	NOAEL 1,000 mg/kg/day	90 days
Talc	Inhalation	pneumoconiosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
Talc	Inhalation	pulmonary fibrosis respiratory system	Not classified	Rat	NOAEL 18 mg/m ³	113 weeks
2,4,6-Tris((dimethylamino)methyl)phenol	Dermal	skin liver nervous system auditory system hematopoietic system eyes	Not classified	Rat	NOAEL 125 mg/kg/day	28 days
Amorphous Silica	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
Carbon Black	Inhalation	pneumoconiosis	Not classified	Human	NOAEL Not available	occupational exposure

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations**13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): Not regulated

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information**15.1. US Federal Regulations**

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:**Physical Hazards**

Not applicable

Health Hazards

Respiratory or Skin Sensitization

Serious eye damage or eye irritation

Skin Corrosion or Irritation

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information**NFPA Hazard Classification****Health:** 3 **Flammability:** 1 **Instability:** 1 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document Group:	25-2752-1	Version Number:	4.02
Issue Date:	03/16/23	Supersedes Date:	12/11/19

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com