



Safety Data Sheet

Copyright,2019,3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

| | | | |
|------------------------|-----------|-------------------------|----------|
| Document Group: | 29-3088-1 | Version Number: | 4.01 |
| Issue Date: | 10/14/19 | Supersedes Date: | 05/22/18 |

SECTION 1: Identification

1.1. Product identifier

3M(TM) Foam Fast 74 25% VOC Spray Adhesive (orange)

Product Identification Numbers

62-4879-4930-7, 62-4879-4935-6
7100014104, 7010329911

1.2. Recommended use and restrictions on use

Recommended use

Aerosol Spray Adhesive

1.3. Supplier's details

| | |
|----------------------|---|
| MANUFACTURER: | 3M |
| DIVISION: | Industrial Adhesives and Tapes Division |
| ADDRESS: | 3M Center, St. Paul, MN 55144-1000, USA |
| Telephone: | 1-888-3M HELPS (1-888-364-3577) |

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

2.1. Hazard classification

Flammable Aerosol: Category 1.
Gas Under Pressure: Dissolved gas.
Serious Eye Damage/Irritation: Category 2B.
Skin Sensitizer: Category 1B.
Carcinogenicity: Category 1B.
Simple Asphyxiant.
Specific Target Organ Toxicity (single exposure): Category 1.
Specific Target Organ Toxicity (single exposure): Category 3.

2.2. Label elements

Signal word

Danger

Symbols

Flame | Gas cylinder | Exclamation mark | Health Hazard |

Pictograms**Hazard Statements**

Extremely flammable aerosol.

Contains gas under pressure; may explode if heated.

Causes eye irritation.

May cause an allergic skin reaction.

May cause drowsiness or dizziness.

May cause cancer.

May displace oxygen and cause rapid suffocation.

Causes damage to organs:
cardiovascular system |May cause damage to organs:
respiratory system |**Precautionary Statements****General:**

Keep out of reach of children.

Prevention:

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not spray on an open flame or other ignition source.

Pressurized container: Do not pierce or burn, even after use.

Do not breathe dust/fume/gas/mist/vapors/spray.

Use only outdoors or in a well-ventilated area.

Wear protective gloves and eye/face protection.

Do not eat, drink or smoke when using this product.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Response:

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

IF ON SKIN: Wash with plenty of soap and water.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see Notes to Physician on this label).

Storage:

Protect from sunlight. Do not expose to temperatures exceeding 50C/122F.
Keep container tightly closed.
Store locked up in a well-ventilated place.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

Notes to Physician:

Exposure may increase myocardial irritability. Do not administer sympathomimetic drugs unless absolutely necessary.

2.3. Hazards not otherwise classified

Repeated exposure may cause skin dryness or cracking.

Supplemental Information:

Intentional concentration and inhalation may be harmful or fatal.

SECTION 3: Composition/information on ingredients

| Ingredient | C.A.S. No. | % by Wt |
|---|---------------|------------------------|
| Methyl acetate | 79-20-9 | 35 - 45 Trade Secret * |
| Non-hazardous components (N.J.T.S. Reg No. 0449960-6448P) | Trade Secret* | 25 - 35 Trade Secret * |
| Dimethyl ether | 115-10-6 | 5 - 15 Trade Secret * |
| Propane | 74-98-6 | 5 - 15 Trade Secret * |
| 1,1-Difluoroethane | 75-37-6 | 3 - 10 Trade Secret * |
| Hexmethyldisiloxane | 107-46-0 | 3 - 10 Trade Secret * |
| Cyclohexane | 110-82-7 | 1 - 5 Trade Secret * |
| 4-Chlorobenzotrifluoride | 98-56-6 | < 2 Trade Secret * |
| N-Butyl acetate | 123-86-4 | < 2 Trade Secret * |

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures**4.1. Description of first aid measures****Inhalation:**

Remove person to fresh air. Get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Exposure may increase myocardial irritability. Do not administer sympathomimetic drugs unless absolutely necessary.

SECTION 5: Fire-fighting measures**5.1. Suitable extinguishing media**

Use a fire fighting agent suitable for the surrounding fire.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

| <u>Substance</u> | <u>Condition</u> |
|-------------------------------|-------------------|
| Acetic Acid | During Combustion |
| Aldehydes | During Combustion |
| Hydrocarbons | During Combustion |
| Formaldehyde | During Combustion |
| Methane | During Combustion |
| Carbon monoxide | During Combustion |
| Carbon dioxide | During Combustion |
| Hydrogen Chloride | During Combustion |
| Hydrogen Fluoride | During Combustion |
| Ketones | During Combustion |
| Toxic Vapor, Gas, Particulate | During Combustion |

5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. When fire fighting conditions are severe and total thermal decomposition of the product is possible, wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

If possible, seal leaking container. Place leaking containers in a well-ventilated area, preferably an operating exhaust hood, or if necessary outdoors on an impermeable surface until appropriate packaging for the leaking container or its contents is available. Place in a metal container approved for transportation by appropriate authorities. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Do not breathe thermal decomposition products. Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (gloves, respirators, etc.) as required.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Do not expose to temperatures exceeding 50C/122F. Store away from heat. Store away from acids. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

| Ingredient | C.A.S. No. | Agency | Limit type | Additional Comments |
|--------------------|------------|--------|------------------------------|---------------------|
| Cyclohexane | 110-82-7 | ACGIH | TWA:100 ppm | |
| Cyclohexane | 110-82-7 | OSHA | TWA:1050 mg/m3(300 ppm) | |
| Dimethyl ether | 115-10-6 | AIHA | TWA:1880 mg/m3(1000 ppm) | |
| N-Butyl acetate | 123-86-4 | OSHA | TWA:710 mg/m3(150 ppm) | |
| N-Butyl acetate | 123-86-4 | ACGIH | TWA:50 ppm;STEL:150 ppm | |
| Propane | 74-98-6 | ACGIH | Limit value not established: | simple asphyxiant |
| Propane | 74-98-6 | OSHA | TWA:1800 mg/m3(1000 ppm) | |
| 1,1-Difluoroethane | 75-37-6 | AIHA | TWA:2700 mg/m3(1000 ppm) | |
| Methyl acetate | 79-20-9 | ACGIH | TWA:200 ppm;STEL:250 ppm | |
| Methyl acetate | 79-20-9 | OSHA | TWA:610 mg/m3(200 ppm) | |

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Provide appropriate local exhaust when product is heated. Do not remain in area where available oxygen may be reduced. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full Face Shield

Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the

results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

During heating:

Use a positive pressure supplied-air respirator if there is a potential for over exposure from an uncontrolled release, exposure levels are not known, or under any other circumstances where air-purifying respirators may not provide adequate protection.

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

Half facepiece or full facepiece supplied-air respirator

Organic vapor respirators may have short service life.

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state

Liquid

Color

Amber

Specific Physical Form:

Aerosol

Odor

Mild Solvent

Odor threshold

No Data Available

pH

Not Applicable

Melting point

No Data Available

Boiling Point

Approximately 140 °F

Flash Point

Approximately -40 °F

Evaporation rate

1

Flammability (solid, gas)

Not Applicable

Flammable Limits(LEL)

No Data Available

Flammable Limits(UEL)

No Data Available

Vapor Pressure

<=4137 mmHg

Vapor Density

2

Density

0.853 g/cm³

Specific Gravity

Approximately 0.88 Units not avail. or not appl. [Ref Std: WATER=1]

Solubility in Water

Nil

Solubility- non-water

No Data Available

Partition coefficient: n-octanol/ water

No Data Available

Autoignition temperature

No Data Available

Decomposition temperature

No Data Available

Viscosity

Approximately 500 centipoise

Hazardous Air Pollutants

0 % weight

Volatile Organic Compounds<=24.5 % [*Test Method*:calculated per CARB title 2]**Volatile Organic Compounds**<=208.7 g/l [*Test Method*:calculated SCAQMD rule 443.1][*Details*:Material VOC]**SECTION 10: Stability and reactivity****10.1. Reactivity**

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat

10.5. Incompatible materials

Strong oxidizing agents

10.6. Hazardous decomposition products**Substance****Condition**

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

Extreme heat arising from situations such as misuse or equipment failure can generate hydrogen fluoride as a decomposition product.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects**Signs and Symptoms of Exposure**

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Simple Asphyxiation: Signs/symptoms may include increased heart rate, rapid respirations, drowsiness, headache, incoordination, altered judgement, nausea, vomiting, lethargy, seizures, coma, and may be fatal.

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

Skin Contact:

Prolonged or repeated exposure may cause:

Dermal Defatting: Signs/symptoms may include localized redness, itching, drying and cracking of skin.

Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Respiratory Effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish colored skin (cyanosis), sputum production, changes in lung function tests, and/or respiratory failure.

Single exposure, above recommended guidelines, may cause:

Cardiac Sensitization: Signs/symptoms may include irregular heartbeat (arrhythmia), faintness, chest pain, and may be fatal.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

| Name | Route | Species | Value |
|---|----------------------------|---------------|--|
| Overall product | Dermal | | No data available; calculated ATE >5,000 mg/kg |
| Overall product | Inhalation-Vapor(4 hr) | | No data available; calculated ATE >50 mg/l |
| Overall product | Ingestion | | No data available; calculated ATE >5,000 mg/kg |
| Methyl acetate | Dermal | Rat | LD50 > 2,000 mg/kg |
| Methyl acetate | Inhalation-Vapor (4 hours) | Rat | LC50 > 49 mg/l |
| Methyl acetate | Ingestion | Rat | LD50 > 5,000 mg/kg |
| Propane | Inhalation-Gas (4 hours) | Rat | LC50 > 200,000 ppm |
| Non-hazardous components (N.J.T.S. Reg No. 0449960-6448P) | Dermal | Not available | LD50 > 2,000 mg/kg |
| Non-hazardous components (N.J.T.S. Reg No. 0449960-6448P) | Ingestion | Not available | LD50 > 2,000 mg/kg |
| Dimethyl ether | Inhalation-Gas (4 hours) | Rat | LC50 164,000 ppm |
| Hexmethyldisiloxane | Dermal | Rabbit | LD50 > 2,000 mg/kg |
| Hexmethyldisiloxane | Inhalation-Vapor (4 | Rat | LC50 106 mg/l |

| | | | |
|--------------------------|--------------------------------|--------|--------------------|
| | hours) | | |
| Hexmethyldisiloxane | Ingestion | Rat | LD50 > 5,000 mg/kg |
| 1,1-Difluoroethane | Inhalation-Gas (4 hours) | Rat | LC50 > 437,000 ppm |
| 1,1-Difluoroethane | Ingestion | Rat | LD50 > 1,500 mg/kg |
| Cyclohexane | Dermal | Rat | LD50 > 2,000 mg/kg |
| Cyclohexane | Inhalation-Vapor (4 hours) | Rat | LC50 > 32.9 mg/l |
| Cyclohexane | Ingestion | Rat | LD50 6,200 mg/kg |
| N-Butyl acetate | Dermal | Rabbit | LD50 > 5,000 mg/kg |
| N-Butyl acetate | Inhalation-Dust/Mist (4 hours) | Rat | LC50 1.4 mg/l |
| N-Butyl acetate | Inhalation-Vapor (4 hours) | Rat | LC50 > 20 mg/l |
| N-Butyl acetate | Ingestion | Rat | LD50 > 8,800 mg/kg |
| 4-Chlorobenzotrifluoride | Dermal | Rabbit | LD50 > 2,700 mg/kg |
| 4-Chlorobenzotrifluoride | Inhalation-Dust/Mist (4 hours) | Rat | LC50 > 32 mg/l |
| 4-Chlorobenzotrifluoride | Inhalation-Vapor (4 hours) | Rat | LC50 33 mg/l |
| 4-Chlorobenzotrifluoride | Ingestion | Rat | LD50 5,546 mg/kg |

ATE = acute toxicity estimate

Skin Corrosion/Irritation

| Name | Species | Value |
|---|------------------------|---------------------------|
| Methyl acetate | Rabbit | No significant irritation |
| Propane | Rabbit | Minimal irritation |
| Non-hazardous components (N.J.T.S. Reg No. 0449960-6448P) | Professional judgement | No significant irritation |
| Hexmethyldisiloxane | Rabbit | No significant irritation |
| Cyclohexane | Rabbit | Mild irritant |
| N-Butyl acetate | Rabbit | Minimal irritation |
| 4-Chlorobenzotrifluoride | Rabbit | Minimal irritation |

Serious Eye Damage/Irritation

| Name | Species | Value |
|---|------------------------|---------------------------|
| Methyl acetate | Rabbit | Moderate irritant |
| Propane | Rabbit | Mild irritant |
| Non-hazardous components (N.J.T.S. Reg No. 0449960-6448P) | Professional judgement | No significant irritation |
| Hexmethyldisiloxane | Rabbit | Mild irritant |
| Cyclohexane | Rabbit | Mild irritant |
| N-Butyl acetate | Rabbit | Moderate irritant |
| 4-Chlorobenzotrifluoride | Rabbit | No significant irritation |

Skin Sensitization

| Name | Species | Value |
|---|------------|----------------|
| Methyl acetate | Human | Not classified |
| Non-hazardous components (N.J.T.S. Reg No. 0449960-6448P) | | Not classified |
| Hexmethyldisiloxane | Guinea pig | Not classified |
| N-Butyl acetate | Multiple | Not classified |

| | | |
|--------------------------|----------------|-------------|
| | animal species | |
| 4-Chlorobenzotrifluoride | Mouse | Sensitizing |

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

| Name | Route | Value |
|--------------------------|----------|--|
| Methyl acetate | In Vitro | Not mutagenic |
| Methyl acetate | In vivo | Not mutagenic |
| Propane | In Vitro | Not mutagenic |
| Dimethyl ether | In Vitro | Not mutagenic |
| Dimethyl ether | In vivo | Not mutagenic |
| Hexmethylsiloxane | In Vitro | Not mutagenic |
| Hexmethylsiloxane | In vivo | Not mutagenic |
| 1,1-Difluoroethane | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| 1,1-Difluoroethane | In vivo | Some positive data exist, but the data are not sufficient for classification |
| Cyclohexane | In Vitro | Not mutagenic |
| Cyclohexane | In vivo | Some positive data exist, but the data are not sufficient for classification |
| N-Butyl acetate | In Vitro | Not mutagenic |
| 4-Chlorobenzotrifluoride | In Vitro | Not mutagenic |
| 4-Chlorobenzotrifluoride | In vivo | Some positive data exist, but the data are not sufficient for classification |

Carcinogenicity

| Name | Route | Species | Value |
|--------------------------|------------|-------------------------|--|
| Dimethyl ether | Inhalation | Rat | Not carcinogenic |
| Hexmethylsiloxane | Inhalation | Rat | Some positive data exist, but the data are not sufficient for classification |
| 1,1-Difluoroethane | Inhalation | Rat | Some positive data exist, but the data are not sufficient for classification |
| 4-Chlorobenzotrifluoride | Inhalation | Multiple animal species | Carcinogenic |

Reproductive Toxicity

Reproductive and/or Developmental Effects

| Name | Route | Value | Species | Test Result | Exposure Duration |
|--------------------|------------|--|---------|------------------|--------------------------------|
| Dimethyl ether | Inhalation | Not classified for development | Rat | NOAEL 40,000 ppm | during organogenesis |
| Hexmethylsiloxane | Inhalation | Not classified for male reproduction | Rat | NOAEL 33 mg/l | 13 weeks |
| 1,1-Difluoroethane | Inhalation | Not classified for development | Rat | NOAEL 50,000 ppm | during organogenesis |
| Cyclohexane | Inhalation | Not classified for female reproduction | Rat | NOAEL 24 mg/l | 2 generation |
| Cyclohexane | Inhalation | Not classified for male reproduction | Rat | NOAEL 24 mg/l | 2 generation |
| Cyclohexane | Inhalation | Not classified for development | Rat | NOAEL 6.9 mg/l | 2 generation |
| N-Butyl acetate | Inhalation | Not classified for female reproduction | Rat | NOAEL 7.1 mg/l | prematuring & during gestation |
| N-Butyl acetate | Inhalation | Not classified for development | Rat | NOAEL 7.1 mg/l | prematuring & during |

| | | | | | |
|--------------------------|------------|--|-------------------------|--------------------|--------------|
| | | | | | gestation |
| 4-Chlorobenzotrifluoride | Ingestion | Not classified for female reproduction | Rat | NOAEL 45 mg/kg/day | 1 generation |
| 4-Chlorobenzotrifluoride | Ingestion | Not classified for male reproduction | Rat | NOAEL 45 mg/kg/day | 1 generation |
| 4-Chlorobenzotrifluoride | Ingestion | Not classified for development | Rat | NOAEL 45 mg/kg/day | 1 generation |
| 4-Chlorobenzotrifluoride | Inhalation | Not classified for female reproduction | Multiple animal species | NOAEL 3.7 mg/l | 3 months |
| 4-Chlorobenzotrifluoride | Inhalation | Not classified for male reproduction | Multiple animal species | NOAEL 1.8 mg/l | 3 months |

Target Organ(s)

Specific Target Organ Toxicity - single exposure

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|----------------------|------------|-----------------------------------|--|------------------------|---------------------|------------------------|
| Methyl acetate | Inhalation | central nervous system depression | May cause drowsiness or dizziness | Human and animal | NOAEL Not available | |
| Methyl acetate | Inhalation | respiratory irritation | May cause respiratory irritation | Human and animal | NOAEL Not available | |
| Methyl acetate | Inhalation | blindness | Not classified | | NOAEL Not available | |
| Methyl acetate | Ingestion | central nervous system depression | May cause drowsiness or dizziness | | NOAEL Not available | |
| Propane | Inhalation | cardiac sensitization | Causes damage to organs | Human | NOAEL Not available | |
| Propane | Inhalation | central nervous system depression | May cause drowsiness or dizziness | Human | NOAEL Not available | |
| Propane | Inhalation | respiratory irritation | Not classified | Human | NOAEL Not available | |
| Dimethyl ether | Inhalation | central nervous system depression | May cause drowsiness or dizziness | Rat | LOAEL 10,000 ppm | 30 minutes |
| Dimethyl ether | Inhalation | cardiac sensitization | Some positive data exist, but the data are not sufficient for classification | Dog | NOAEL 100,000 ppm | 5 minutes |
| Hexmethylidisiloxane | Inhalation | respiratory irritation | Not classified | Rat | NOAEL 33 mg/l | 6 hours |
| Hexmethylidisiloxane | Ingestion | central nervous system depression | Not classified | Guinea pig | LOAEL 22,900 mg/kg | not applicable |
| 1,1-Difluoroethane | Inhalation | cardiac sensitization | Causes damage to organs | Human and animal | NOAEL Not available | poisoning and/or abuse |
| 1,1-Difluoroethane | Inhalation | central nervous system depression | May cause drowsiness or dizziness | Human and animal | NOAEL 100,000 ppm | |
| 1,1-Difluoroethane | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | Not available | NOAEL Not available | not available |
| Cyclohexane | Inhalation | central nervous system depression | May cause drowsiness or dizziness | Human and animal | NOAEL Not available | |
| Cyclohexane | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | Human and animal | NOAEL Not available | |
| Cyclohexane | Ingestion | central nervous system depression | May cause drowsiness or dizziness | Professional judgement | NOAEL Not available | |
| N-Butyl acetate | Inhalation | respiratory system | May cause damage to organs | Rat | LOAEL 2.6 mg/l | 4 hours |
| N-Butyl acetate | Inhalation | central nervous | May cause drowsiness or | Human | NOAEL Not | not available |

| | | | | | | |
|-----------------|------------|-----------------------------------|-----------------------------------|-----------------------|---------------------|---------------|
| | | system depression | dizziness | | available | |
| N-Butyl acetate | Inhalation | respiratory irritation | May cause respiratory irritation | Human | NOAEL Not available | not available |
| N-Butyl acetate | Ingestion | central nervous system depression | May cause drowsiness or dizziness | Professional judgment | NOAEL Not available | |

Specific Target Organ Toxicity - repeated exposure

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|--------------------------|------------|---|--|-------------------------|-----------------------|-------------------|
| Methyl acetate | Inhalation | respiratory system | Some positive data exist, but the data are not sufficient for classification | Rat | NOAEL 1.1 mg/l | 28 days |
| Methyl acetate | Inhalation | endocrine system hematopoietic system liver immune system kidney and/or bladder | Not classified | Rat | NOAEL 6.1 mg/l | 28 days |
| Dimethyl ether | Inhalation | hematopoietic system | Not classified | Rat | NOAEL 25,000 ppm | 2 years |
| Dimethyl ether | Inhalation | liver | Not classified | Rat | NOAEL 20,000 ppm | 30 weeks |
| Hexmethylsiloxane | Dermal | liver kidney and/or bladder | Not classified | Rat | NOAEL 1,000 mg/kg/day | 28 days |
| Hexmethylsiloxane | Inhalation | kidney and/or bladder | Not classified | Rat | NOAEL 4 mg/l | 13 weeks |
| Hexmethylsiloxane | Inhalation | hematopoietic system | Not classified | Rat | NOAEL 33 mg/l | 13 weeks |
| Hexmethylsiloxane | Inhalation | liver | Not classified | Multiple animal species | NOAEL 29 mg/l | 15 days |
| Hexmethylsiloxane | Inhalation | heart endocrine system immune system nervous system respiratory system | Not classified | Rat | NOAEL 33 mg/l | 13 weeks |
| 1,1-Difluoroethane | Inhalation | hematopoietic system kidney and/or bladder respiratory system | Not classified | Rat | NOAEL 25,000 ppm | 2 years |
| Cyclohexane | Inhalation | liver | Not classified | Rat | NOAEL 24 mg/l | 90 days |
| Cyclohexane | Inhalation | auditory system | Not classified | Rat | NOAEL 1.7 mg/l | 90 days |
| Cyclohexane | Inhalation | kidney and/or bladder | Not classified | Rabbit | NOAEL 2.7 mg/l | 10 weeks |
| Cyclohexane | Inhalation | hematopoietic system | Not classified | Mouse | NOAEL 24 mg/l | 14 weeks |
| Cyclohexane | Inhalation | peripheral nervous system | Not classified | Rat | NOAEL 8.6 mg/l | 30 weeks |
| N-Butyl acetate | Inhalation | olfactory system | Not classified | Rat | NOAEL 2.4 mg/l | 14 weeks |
| N-Butyl acetate | Inhalation | liver kidney and/or bladder | Not classified | Rabbit | NOAEL 7.26 mg/l | 13 days |
| 4-Chlorobenzotrifluoride | Inhalation | liver | Some positive data exist, but the data are not sufficient for classification | Multiple animal species | NOAEL 1.8 mg/l | 3 months |
| 4-Chlorobenzotrifluoride | Inhalation | heart | Not classified | Multiple animal species | LOAEL 15 mg/l | 3 months |
| 4-Chlorobenzotrifluoride | Inhalation | endocrine system gastrointestinal tract hematopoietic system | Not classified | Multiple animal species | NOAEL 15 mg/l | 3 months |

| | | | | | | |
|--------------------------|------------|--|----------------|-------------------------|---------------------|----------|
| 4-Chlorobenzotrifluoride | Inhalation | immune system | Not classified | Multiple animal species | LOAEL 15 mg/l | 3 months |
| 4-Chlorobenzotrifluoride | Inhalation | nervous system | Not classified | Multiple animal species | NOAEL 15 mg/l | 3 months |
| 4-Chlorobenzotrifluoride | Inhalation | kidney and/or bladder | Not classified | Multiple animal species | LOAEL 15 mg/l | 3 months |
| 4-Chlorobenzotrifluoride | Inhalation | respiratory system vascular system bone, teeth, nails, and/or hair eyes | Not classified | Multiple animal species | NOAEL 15 mg/l | 3 months |
| 4-Chlorobenzotrifluoride | Ingestion | hematopoietic system liver kidney and/or bladder heart endocrine system eyes | Not classified | Rat | NOAEL 500 mg/kg/day | 90 days |

Aspiration Hazard

| Name | Value |
|-------------|-------------------|
| Cyclohexane | Aspiration hazard |

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Facility must be capable of handling aerosol cans. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): D001 (Ignitable)

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:

Physical Hazards

Flammable (gases, aerosols, liquids, or solids)

Gas under pressure

Health Hazards

Carcinogenicity

Hazard Not Otherwise Classified (HNOC)

Respiratory or Skin Sensitization

Serious eye damage or eye irritation

Simple Asphyxiant

Specific target organ toxicity (single or repeated exposure)

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

| <u>Ingredient</u> | <u>C.A.S. No</u> | <u>% by Wt</u> |
|-------------------|------------------|--------------------|
| Cyclohexane | 110-82-7 | Trade Secret 1 - 5 |

This material contains a chemical which requires export notification under TSCA Section 12[b]:

| <u>Ingredient (Category if applicable)</u> | <u>C.A.S. No</u> | <u>Regulation</u> | <u>Status</u> |
|--|------------------|--|---------------|
| 4-Chlorobenzotrifluoride | 98-56-6 | Toxic Substances Control Act (TSCA) 4 Test Rule Chemicals | Applicable |

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 3 **Flammability:** 4 **Instability:** 0 **Special Hazards:** None
Aerosol Storage Code: 3

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar

emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

The NFPA Health code of 3 is due to emergency situations where the material may thermally decompose and release Hydrogen Fluoride. During normal use conditions, please reference Section 2 and Section 11 of the SDS for additional health hazard information.

| | | | |
|------------------------|-----------|-------------------------|----------|
| Document Group: | 29-3088-1 | Version Number: | 4.01 |
| Issue Date: | 10/14/19 | Supersedes Date: | 05/22/18 |

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com