



Safety Data Sheet

Copyright,2018,3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	28-1488-7	Version Number:	4.03
Issue Date:	01/12/18	Supersedes Date:	06/16/15

SECTION 1: Identification

1.1. Product identifier

3M Scotchkote WB Epoxy Primer EA9WB, Grey (Part A)

Product Identification Numbers

ID Number	UPC	ID Number	UPC
GR-2001-0277-4			

1.2. Recommended use and restrictions on use

Recommended use

Coating, Primer for steel surfaces.

1.3. Supplier's details

MANUFACTURER:	3M
DIVISION:	3M United Kingdom Electrical Markets Division
ADDRESS:	3M Center, St. Paul, MN 55144-1000, USA
Telephone:	1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

2.1. Hazard classification

Carcinogenicity: Category 2.

2.2. Label elements

Signal word

Warning

Symbols

Health Hazard |

Pictograms

**Hazard Statements**

Suspected of causing cancer.

Precautionary Statements**Prevention:**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Wear protective gloves.

Response:

IF exposed or concerned: Get medical advice/attention.

Storage:

Store locked up.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

23% of the mixture consists of ingredients of unknown acute oral toxicity.

23% of the mixture consists of ingredients of unknown acute dermal toxicity.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
NON-HAZARDOUS INGREDIENTS	Mixture	60 - 70
BARIUM SULFATE	7727-43-7	1 - 10 Trade Secret *
TITANIUM DIOXIDE	13463-67-7	1 - 10 Trade Secret *
ZINC PHOSPHATE	7779-90-0	1 - 10 Trade Secret *
1,3-BENZENEDICARBOXYLIC ACID, 5-NITRO-, ZINC SALT	60580-61-2	1 - 5 Trade Secret *
ALUMINUM PHOSPHATE	7784-30-7	1 - 5 Trade Secret *
ETHYLENE GLYCOL MONOPROPYL ETHER	2807-30-9	1 - 5 Trade Secret *
2,4,7,9-TETRAMETHYL-5-DECYNE-4,7-DIOL	126-86-3	< 0.5 Trade Secret *
SODIUM NITRITE	7632-00-0	< 0.5 Trade Secret *
TALC	14807-96-6	< 0.5 Trade Secret *
ZINC OXIDE	1314-13-2	< 0.5 Trade Secret *
1,2-BENZISOTHIAZOLIN-3-ONE	2634-33-5	< 0.05 Trade Secret *
3(2H)-ISOTHIAZOLONE, 5-CHLORO-2-METHYL-, mixt. with 2-METHYL-3(2H)-ISOTHIAZOLONE	55965-84-9	< 0.001 Trade Secret *

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you are concerned, get medical advice.

Skin Contact:

Wash with soap and water. If signs/symptoms develop, get medical attention.

Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance

Carbon monoxide
Carbon dioxide

Condition

During Combustion
During Combustion

5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with detergent and water.

Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial or professional use only. Do not use in a confined area with minimal air exchange. Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (gloves, respirators, etc.) as required.

7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidizing agents. Store away from amines.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
ZINC OXIDE	1314-13-2	ACGIH	TWA(respirable fraction):2 mg/m ³ ;STEL(respirable fraction):10 mg/m ³	
ZINC OXIDE	1314-13-2	OSHA	TWA(as fume):5 mg/m ³ ;TWA(as total dust):15 mg/m ³ ;TWA(respirable fraction):5 mg/m ³	
TITANIUM DIOXIDE	13463-67-7	ACGIH	TWA:10 mg/m ³	A4: Not class. as human carcin
TITANIUM DIOXIDE	13463-67-7	OSHA	TWA(as total dust):15 mg/m ³	
TALC	14807-96-6	ACGIH	TWA(respirable fraction):2 mg/m ³	A4: Not class. as human carcin
TALC	14807-96-6	OSHA	TWA:2 mg/m ³	
BARIUM SULFATE	7727-43-7	ACGIH	TWA(inhalable fraction):5 mg/m ³	
BARIUM SULFATE	7727-43-7	OSHA	TWA(as total dust):15 mg/m ³ ;TWA(respirable fraction):5 mg/m ³	
Aluminum, insoluble compounds	7784-30-7	ACGIH	TWA(respirable fraction):1 mg/m ³	A4: Not class. as human carcin

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment. Curing enclosures must be exhausted to outdoors or to a suitable emission control device.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

None required.

Skin/hand protection

No chemical protective gloves are required.

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

General Physical Form:	Liquid
Specific Physical Form:	Liquid
Odor, Color, Grade:	Faint odor; Grey color
Odor threshold	<i>No Data Available</i>
pH	8
Melting point	<i>Not Applicable</i>
Boiling Point	≥ 100 °C
Flash Point	≥ 100 °C [<i>Test Method</i> :Closed Cup]
Evaporation rate	<i>No Data Available</i>
Flammability (solid, gas)	Not Applicable
Flammable Limits(LEL)	<i>No Data Available</i>
Flammable Limits(UEL)	<i>No Data Available</i>
Vapor Pressure	<i>No Data Available</i>
Vapor Density	<i>No Data Available</i>
Density	1.360 g/ml
Specific Gravity	1.360 [<i>Ref Std</i> :WATER=1]
Solubility in Water	Moderate
Solubility- non-water	Moderate
Partition coefficient: n-octanol/ water	<i>No Data Available</i>
Autoignition temperature	≥ 230 °C
Decomposition temperature	<i>No Data Available</i>
Viscosity	<i>No Data Available</i>
Molecular weight	<i>Not Applicable</i>
Volatile Organic Compounds	76 g/l [<i>Test Method</i> :Estimated] [<i>Details</i> :EU Definition (Part A and B mix)]
Volatile Organic Compounds	68 g/l [<i>Test Method</i> :Estimated] [<i>Details</i> :EU Definition (Part A and B mix thinned 10%)]
Percent volatile	44 % weight

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Temperatures above the boiling point

10.5. Incompatible materials

Accelerators

Amines

Strong acids

Strong bases

Strong oxidizing agents

10.6. Hazardous decomposition products**Substance****Condition**

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects**Signs and Symptoms of Exposure**

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Vapors released during curing may cause irritation of the respiratory system. Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin Contact:

Contact with the skin during product use is not expected to result in significant irritation.

Eye Contact:

Contact with the eyes during product use is not expected to result in significant irritation. Vapors released during curing may cause eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Additional Health Effects:**Carcinogenicity:**

Contains a chemical or chemicals which can cause cancer.

Ingredient	CAS No.	Class Description	Regulation
TITANIUM DIOXIDE	13463-67-7	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Vapor(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
BARIUM SULFATE	Dermal		LD50 estimated to be > 5,000 mg/kg
BARIUM SULFATE	Ingestion	Rat	LD50 > 15,000 mg/kg
ZINC PHOSPHATE	Dermal		LD50 estimated to be > 5,000 mg/kg
ZINC PHOSPHATE	Ingestion	Rat	LD50 > 5,000 mg/kg
TITANIUM DIOXIDE	Dermal	Rabbit	LD50 > 10,000 mg/kg
TITANIUM DIOXIDE	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 6.82 mg/l
TITANIUM DIOXIDE	Ingestion	Rat	LD50 > 10,000 mg/kg
ALUMINUM PHOSPHATE	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
ALUMINUM PHOSPHATE	Dermal	Rabbit	LD50 > 4,640 mg/kg
ETHYLENE GLYCOL MONOPROPYL ETHER	Dermal	Rabbit	LD50 1,337 mg/kg
ETHYLENE GLYCOL MONOPROPYL ETHER	Inhalation-Vapor (4 hours)	Rat	LC50 > 11.1 mg/l
ETHYLENE GLYCOL MONOPROPYL ETHER	Ingestion	Rat	LD50 3,089 mg/kg
TALC	Dermal		LD50 estimated to be > 5,000 mg/kg
TALC	Ingestion		LD50 estimated to be > 5,000 mg/kg
ZINC OXIDE	Dermal		LD50 estimated to be > 5,000 mg/kg
ZINC OXIDE	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 5.7 mg/l
ZINC OXIDE	Ingestion	Rat	LD50 > 5,000 mg/kg
2,4,7,9-TETRAMETHYL-5-DECYNE-4,7-DIOL	Dermal	Rat	LD50 > 2,000 mg/kg
2,4,7,9-TETRAMETHYL-5-DECYNE-4,7-DIOL	Ingestion	Rat	LD50 > 500 mg/kg
3(2H)-ISOTHIAZOLONE, 5-CHLORO-2-METHYL-, mixt. with 2-METHYL-3(2H)-ISOTHIAZOLONE	Dermal	Rabbit	LD50 87 mg/kg
3(2H)-ISOTHIAZOLONE, 5-CHLORO-2-METHYL-, mixt. with 2-METHYL-3(2H)-ISOTHIAZOLONE	Inhalation-Dust/Mist (4 hours)	Rat	LC50 0.33 mg/l
3(2H)-ISOTHIAZOLONE, 5-CHLORO-2-METHYL-, mixt. with 2-METHYL-3(2H)-ISOTHIAZOLONE	Ingestion	Rat	LD50 40 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
TITANIUM DIOXIDE	Rabbit	No significant irritation
TALC	Rabbit	No significant irritation
ZINC OXIDE	Human and animal	No significant irritation

2,4,7,9-TETRAMETHYL-5-DECYNE-4,7-DIOL	Rabbit	No significant irritation
3(2H)-ISOTHIAZOLONE, 5-CHLORO-2-METHYL-, mixt. with 2-METHYL-3(2H)-ISOTHIAZOLONE	Rabbit	Corrosive

Serious Eye Damage/Irritation

Name	Species	Value
BARIUM SULFATE	Rabbit	No significant irritation
TITANIUM DIOXIDE	Rabbit	No significant irritation
TALC	Rabbit	No significant irritation
ZINC OXIDE	Rabbit	Mild irritant
2,4,7,9-TETRAMETHYL-5-DECYNE-4,7-DIOL	Rabbit	Corrosive
3(2H)-ISOTHIAZOLONE, 5-CHLORO-2-METHYL-, mixt. with 2-METHYL-3(2H)-ISOTHIAZOLONE	Rabbit	Corrosive

Skin Sensitization

Name	Species	Value
TITANIUM DIOXIDE	Human and animal	Not classified
ZINC OXIDE	Guinea pig	Not classified
2,4,7,9-TETRAMETHYL-5-DECYNE-4,7-DIOL	Mouse	Sensitizing
3(2H)-ISOTHIAZOLONE, 5-CHLORO-2-METHYL-, mixt. with 2-METHYL-3(2H)-ISOTHIAZOLONE	Human and animal	Sensitizing

Photosensitization

Name	Species	Value
3(2H)-ISOTHIAZOLONE, 5-CHLORO-2-METHYL-, mixt. with 2-METHYL-3(2H)-ISOTHIAZOLONE	Human and animal	Not sensitizing

Respiratory Sensitization

Name	Species	Value
TALC	Human	Not classified

Germ Cell Mutagenicity

Name	Route	Value
TITANIUM DIOXIDE	In Vitro	Not mutagenic
TITANIUM DIOXIDE	In vivo	Not mutagenic
TALC	In Vitro	Not mutagenic
TALC	In vivo	Not mutagenic
ZINC OXIDE	In Vitro	Some positive data exist, but the data are not sufficient for classification
ZINC OXIDE	In vivo	Some positive data exist, but the data are not sufficient for classification
3(2H)-ISOTHIAZOLONE, 5-CHLORO-2-METHYL-, mixt. with 2-METHYL-3(2H)-ISOTHIAZOLONE	In vivo	Not mutagenic
3(2H)-ISOTHIAZOLONE, 5-CHLORO-2-METHYL-, mixt. with 2-METHYL-3(2H)-ISOTHIAZOLONE	In Vitro	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
TITANIUM DIOXIDE	Ingestion	Multiple animal species	Not carcinogenic
TITANIUM DIOXIDE	Inhalation	Rat	Carcinogenic
TALC	Inhalation	Rat	Some positive data exist, but the data are not

			sufficient for classification
3(2H)-ISOTHIAZOLONE, 5-CHLORO-2-METHYL-, mixt. with 2-METHYL-3(2H)-ISOTHIAZOLONE	Dermal	Mouse	Not carcinogenic
3(2H)-ISOTHIAZOLONE, 5-CHLORO-2-METHYL-, mixt. with 2-METHYL-3(2H)-ISOTHIAZOLONE	Ingestion	Rat	Not carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
TALC	Ingestion	Not classified for development	Rat	NOAEL 1,600 mg/kg	during organogenesis
ZINC OXIDE	Ingestion	Not classified for reproduction and/or development	Multiple animal species	NOAEL 125 mg/kg/day	prematuring & during gestation
3(2H)-ISOTHIAZOLONE, 5-CHLORO-2-METHYL-, mixt. with 2-METHYL-3(2H)-ISOTHIAZOLONE	Ingestion	Not classified for female reproduction	Rat	NOAEL 10 mg/kg/day	2 generation
3(2H)-ISOTHIAZOLONE, 5-CHLORO-2-METHYL-, mixt. with 2-METHYL-3(2H)-ISOTHIAZOLONE	Ingestion	Not classified for male reproduction	Rat	NOAEL 10 mg/kg/day	2 generation
3(2H)-ISOTHIAZOLONE, 5-CHLORO-2-METHYL-, mixt. with 2-METHYL-3(2H)-ISOTHIAZOLONE	Ingestion	Not classified for development	Rat	NOAEL 15 mg/kg/day	during organogenesis

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
3(2H)-ISOTHIAZOLONE, 5-CHLORO-2-METHYL-, mixt. with 2-METHYL-3(2H)-ISOTHIAZOLONE	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
BARIUM SULFATE	Inhalation	pneumoconiosis	Not classified	Human	NOAEL Not available	occupational exposure
TITANIUM DIOXIDE	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.01 mg/l	2 years
TITANIUM DIOXIDE	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure
TALC	Inhalation	pneumoconiosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
TALC	Inhalation	pulmonary fibrosis respiratory system	Not classified	Rat	NOAEL 18 mg/m3	113 weeks
ZINC OXIDE	Ingestion	nervous system	Not classified	Rat	NOAEL 600 mg/kg/day	10 days
ZINC OXIDE	Ingestion	endocrine system hematopoietic system kidney and/or bladder	Not classified	Other	NOAEL 500 mg/kg/day	6 months

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): D005 (Barium), D006 (Cadmium), D007 (Chromium), D008 (Lead), D009 (Mercury)

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:

Physical Hazards

Not applicable

Health Hazards

Carcinogenicity

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

Ingredient	C.A.S. No	% by Wt
ZINC PHOSPHATE (ZINC COMPOUNDS)	7779-90-0	1 - 10
ETHYLENE GLYCOL MONOPROPYL ETHER (GLYCOL ETHERS)	2807-30-9	1 - 5
1,3-BENZENEDICARBOXYLIC ACID, 5-NITRO-, ZINC SALT (ZINC COMPOUNDS)	60580-61-2	1 - 5
ZINC OXIDE (ZINC COMPOUNDS)	1314-13-2	< 0.5

This material contains a chemical which requires export notification under TSCA Section 12[b]:

<u>Ingredient (Category if applicable)</u>	<u>C.A.S. No</u>	<u>Regulation</u>	<u>Status</u>
SODIUM NITRITE (ALKALI METAL NITRITES FOR USE IN METALWORKING FLUIDS CONTAINING AMINES)	7632-00-0	Toxic Substances Control Act (TSCA) 5 SNUR or Consent Order Chemicals	Applicable
SODIUM NITRITE	7632-00-0	Toxic Substances Control Act (TSCA) 5 SNUR or Consent Order Chemicals	Applicable

This material contains a chemical regulated by an EPA Significant New Use Rule (TSCA Section 5)

<u>Ingredient (Category if applicable)</u>	<u>C.A.S. No</u>	<u>Reference</u>
SODIUM NITRITE	7632-00-0	40CFR721.4740

15.2. State Regulations

Contact 3M for more information.

California Proposition 65

<u>Ingredient</u>	<u>C.A.S. No.</u>	<u>Listing</u>
Ethylene Glycol	107-21-1	Developmental Toxin
Mercury	7439-97-6	Developmental Toxin
Cobalt	7440-48-4	Carcinogen

15.3. Chemical Inventories

The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information.

The components of this product are in compliance with the new substance notification requirements of CEPA.

The components of this material are in compliance with the provisions of the Korean Toxic Chemical Control Law. Certain restrictions may apply. Contact the selling division for additional information.

The components of this product are in compliance with the chemical notification requirements of TSCA.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 2 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include

the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document Group:	28-1488-7	Version Number:	4.03
Issue Date:	01/12/18	Supersedes Date:	06/16/15

Reason for Reissue

Conversion to GHS format SDS.

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com