



Safety Data Sheet

Copyright, 2022, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	22-1636-4	Version Number:	8.01
Issue Date:	07/28/22	Supersedes Date:	08/11/21

SECTION 1: Identification

1.1. Product identifier

3M™ Hi-Strength Laminating 92 Cylinder Spray Adhesive (Clear or Red)

Product Identification Numbers

62-4956-8030-8, 62-4956-8150-4, 62-4956-8300-5, 62-4958-8030-4, 62-4958-8150-0, 62-4958-8300-1
7100138900, 7100139493, 7010366494, 7100138899, 7100139492

1.2. Recommended use and restrictions on use

Recommended use

Industrial use

Restrictions on use

Adhesive

This chemical/product is not and cannot be distributed in commerce (as defined in TSCA section 3(5)) or processed (as defined in TSCA section 3(13)) for consumer paint or coating removal.

1.3. Supplier's details

MANUFACTURER:	3M
DIVISION:	Industrial Adhesives and Tapes Division
ADDRESS:	3M Center, St. Paul, MN 55144-1000, USA
Telephone:	1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

2.1. Hazard classification

Flammable Liquid: Category 1.

Serious Eye Damage/Irritation: Category 2A.

Skin Corrosion/Irritation: Category 2.

Reproductive Toxicity: Category 1B.

Simple Asphyxiant.

Specific Target Organ Toxicity (single exposure): Category 1.

Specific Target Organ Toxicity (single exposure): Category 3.

2.2. Label elements

Signal word

Danger

Symbols

Flame | Exclamation mark | Health Hazard |

Pictograms



Hazard Statements

Extremely flammable liquid and vapor.

Causes serious eye irritation.

Causes skin irritation.

May cause drowsiness or dizziness.

May damage fertility or the unborn child.

May displace oxygen and cause rapid suffocation.

Causes damage to organs:

cardiovascular system |

Precautionary Statements

Prevention:

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Keep container tightly closed.

Use explosion-proof electrical/ventilating/lighting equipment.

Do not breathe dust/fume/gas/mist/vapors/spray.

Use only outdoors or in a well-ventilated area.

Wear protective gloves and eye/face protection.

Do not eat, drink or smoke when using this product.

Wash thoroughly after handling.

Response:

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

If eye irritation persists: Get medical advice/attention.

If skin irritation occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see Notes to Physician on this label).

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

Storage:

Keep cool.
Keep container tightly closed.
Store locked up in a well-ventilated place.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

Notes to Physician:

Exposure may increase myocardial irritability. Do not administer sympathomimetic drugs unless absolutely necessary.

Supplemental Information:

Intentional concentration and inhalation may be harmful or fatal.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
Non-Hazardous Components	Trade Secret*	20 - 30 Trade Secret *
Dimethyl Ether	115-10-6	15 - 25 Trade Secret *
Acetone	67-64-1	10 - 20 Trade Secret *
Heptane, branched, cyclic and linear	426260-76-6	5 - 20 Trade Secret *
Methyl Acetate	79-20-9	5 - 15 Trade Secret *
Heptane	142-82-5	1 - 10 Trade Secret *
Isobutane	75-28-5	5 - 10 Trade Secret *
Propane	74-98-6	5 - 10 Trade Secret *
Toluene	108-88-3	< 1 Trade Secret *
Methylene Chloride	75-09-2	< 0.01 Trade Secret *

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures**4.1. Description of first aid measures****Inhalation:**

Remove person to fresh air. Get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Central nervous system depression (headache, dizziness, drowsiness, incoordination, nausea, slurred speech, giddiness, and unconsciousness). Target organ effects. See Section 11 for additional details.

4.3. Indication of any immediate medical attention and special treatment required

Exposure may increase myocardial irritability. Do not administer sympathomimetic drugs unless absolutely necessary.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

Substance

Aldehydes
Hydrocarbons
Methane
Carbon monoxide
Carbon dioxide
Ketones
Toxic Vapor, Gas, Particulate

Condition

During Combustion
During Combustion
During Combustion
During Combustion
During Combustion
During Combustion
During Combustion

5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Cover spill area with a fire-extinguishing foam. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes,

on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. Use personal protective equipment (gloves, respirators, etc.) as required. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapor accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store away from acids. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Toluene	108-88-3	ACGIH	TWA:20 ppm	A4: Not class. as human carcin, Ototoxicant
Toluene	108-88-3	OSHA	TWA:200 ppm;CEIL:300 ppm	
Dimethyl Ether	115-10-6	AIHA	TWA:1880 mg/m3(1000 ppm)	
Heptane	142-82-5	ACGIH	TWA:400 ppm;STEL:500 ppm	
Heptane	142-82-5	OSHA	TWA:2000 mg/m3(500 ppm)	
Acetone	67-64-1	ACGIH	TWA:250 ppm;STEL:500 ppm	A4: Not class. as human carcin
Acetone	67-64-1	OSHA	TWA:2400 mg/m3(1000 ppm)	
Propane	74-98-6	ACGIH	Limit value not established:	simple asphyxiant
Propane	74-98-6	OSHA	TWA:1800 mg/m3(1000 ppm)	
Methylene Chloride	75-09-2	ACGIH	TWA:50 ppm	A3: Confirmed animal carcin.
Methylene Chloride	75-09-2	OSHA	TWA:25 ppm;STEL:125 ppm	29 CFR 1910.1052, SKIN
Isobutane	75-28-5	ACGIH	STEL:1000 ppm	
Methyl Acetate	79-20-9	ACGIH	TWA:200 ppm;STEL:250 ppm	
Methyl Acetate	79-20-9	OSHA	TWA:610 mg/m3(200 ppm)	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Do not remain in area where available oxygen may be reduced. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

Half facepiece or full facepiece supplied-air respirator

Organic vapor respirators may have short service life.

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state

Liquid

Color

Multicolor

Odor

Solvent

Odor threshold

No Data Available

pH

No Data Available

Melting point

No Data Available

Boiling Point

No Data Available

Flash Point

8 °F

Evaporation rate

No Data Available

Flammability (solid, gas)

Not Applicable

Flammable Limits(LEL)

3.1 %

Flammable Limits(UEL)

16 %

Vapor Pressure

No Data Available

Vapor Density

2.8 [Ref Std: AIR=1]

Density

0.8 - 0.85 g/ml

Specific Gravity

0.85

Solubility in Water

Nil

Solubility- non-water

No Data Available

Partition coefficient: n-octanol/ water

No Data Available

Autoignition temperature

No Data Available

Decomposition temperature

Not Applicable

Viscosity

No Data Available

Hazardous Air Pollutants

<=1 % weight [Test Method: Calculated]

VOC Less H2O & Exempt Solvents

<=599 g/l [Test Method: calculated SCAQMD rule 443.1]

Solids Content

20 - 30 %

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Sparks and/or flames

10.5. Incompatible materials

Strong oxidizing agents

10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
Formaldehyde	During Storage

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects**Signs and Symptoms of Exposure**

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Simple Asphyxiation: Signs/symptoms may include increased heart rate, rapid respirations, drowsiness, headache, incoordination, altered judgement, nausea, vomiting, lethargy, seizures, coma, and may be fatal.

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

Skin Contact:

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain.

Eye Contact:

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Single exposure, above recommended guidelines, may cause: Cardiac Sensitization: Signs/symptoms may include irregular heartbeat (arrhythmia), faintness, chest pain, and may be fatal.

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Carcinogenicity:

Ingredient	CAS No.	Class Description	Regulation
Dichloromethane (methylene chloride)	75-09-2	Grp. 2A: Probable human carc.	International Agency for Research on Cancer
Dichloromethane (Methylene Chloride)	75-09-2	Anticipated human carcinogen	National Toxicology Program Carcinogens
METHYLENE CHLORIDE	75-09-2	Cancer hazard	OSHA Carcinogens

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Vapor(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Dimethyl Ether	Inhalation-Gas (4 hours)	Rat	LC50 164,000 ppm
Acetone	Dermal	Rabbit	LD50 > 15,688 mg/kg
Acetone	Inhalation-Vapor (4 hours)	Rat	LC50 76 mg/l
Acetone	Ingestion	Rat	LD50 5,800 mg/kg
Heptane, branched, cyclic and linear	Dermal	Rabbit	LD50 > 2,920 mg/kg
Heptane, branched, cyclic and linear	Inhalation-Vapor (4 hours)	Rat	LC50 > 23.3 mg/l
Heptane, branched, cyclic and linear	Ingestion	Rat	LD50 > 5,840 mg/kg
Isobutane	Inhalation-Gas (4 hours)	Rat	LC50 276,000 ppm
Methyl Acetate	Dermal	Rat	LD50 > 2,000 mg/kg
Methyl Acetate	Inhalation-Vapor (4 hours)	Rat	LC50 > 49 mg/l
Methyl Acetate	Ingestion	Rat	LD50 > 5,000 mg/kg
Non-Hazardous Components	Dermal	Not available	LD50 > 2,000 mg/kg
Non-Hazardous Components	Ingestion	Not available	LD50 > 2,000 mg/kg
Propane	Inhalation-Gas (4 hours)	Rat	LC50 > 200,000 ppm
Heptane	Dermal	Rabbit	LD50 3,000 mg/kg
Heptane	Inhalation-	Rat	LC50 103 mg/l

	Vapor (4 hours)		
Heptane	Ingestion	Rat	LD50 > 15,000 mg/kg
Toluene	Dermal	Rat	LD50 12,000 mg/kg
Toluene	Inhalation-Vapor (4 hours)	Rat	LC50 30 mg/l
Toluene	Ingestion	Rat	LD50 5,550 mg/kg
Methylene Chloride	Dermal	Rat	LD50 > 2,000 mg/kg
Methylene Chloride	Inhalation-Vapor (4 hours)	Rat	LC50 63.7 mg/l
Methylene Chloride	Ingestion	Rat	LD50 1,410 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Acetone	Mouse	Minimal irritation
Heptane, branched, cyclic and linear	Rabbit	Irritant
Isobutane	Professional judgement	No significant irritation
Methyl Acetate	Rabbit	No significant irritation
Non-Hazardous Components	Professional judgement	No significant irritation
Propane	Rabbit	Minimal irritation
Heptane	Human	Mild irritant
Toluene	Rabbit	Irritant
Methylene Chloride	Rabbit	Irritant

Serious Eye Damage/Irritation

Name	Species	Value
Acetone	Rabbit	Severe irritant
Heptane, branched, cyclic and linear	Rabbit	Mild irritant
Isobutane	Professional judgement	No significant irritation
Methyl Acetate	Rabbit	Moderate irritant
Non-Hazardous Components	Professional judgement	No significant irritation
Propane	Rabbit	Mild irritant
Heptane	Professional judgement	Moderate irritant
Toluene	Rabbit	Moderate irritant
Methylene Chloride	Rabbit	Severe irritant

Skin Sensitization

Name	Species	Value
Heptane, branched, cyclic and linear	Guinea pig	Not classified
Methyl Acetate	Human	Not classified
Non-Hazardous Components		Not classified
Toluene	Guinea pig	Not classified

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Dimethyl Ether	In Vitro	Not mutagenic
Dimethyl Ether	In vivo	Not mutagenic
Acetone	In vivo	Not mutagenic
Acetone	In Vitro	Some positive data exist, but the data are not sufficient for classification
Heptane, branched, cyclic and linear	In Vitro	Not mutagenic
Isobutane	In Vitro	Not mutagenic
Methyl Acetate	In Vitro	Not mutagenic
Methyl Acetate	In vivo	Not mutagenic
Propane	In Vitro	Not mutagenic
Heptane	In Vitro	Not mutagenic
Toluene	In Vitro	Not mutagenic
Toluene	In vivo	Not mutagenic
Methylene Chloride	In vivo	Not mutagenic
Methylene Chloride	In Vitro	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
Dimethyl Ether	Inhalation	Rat	Not carcinogenic
Acetone	Not Specified	Multiple animal species	Not carcinogenic
Toluene	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Toluene	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification
Toluene	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification
Methylene Chloride	Inhalation	Multiple animal species	Carcinogenic

Reproductive Toxicity**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test Result	Exposure Duration
Dimethyl Ether	Inhalation	Not classified for development	Rat	NOAEL 40,000 ppm	during organogenesis
Acetone	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,700 mg/kg/day	13 weeks
Acetone	Inhalation	Not classified for development	Rat	NOAEL 5.2 mg/l	during organogenesis
Heptane, branched, cyclic and linear	Not Specified	Not classified for female reproduction	Rat	NOAEL Not available	2 generation
Heptane, branched, cyclic and linear	Not Specified	Not classified for male reproduction	Rat	NOAEL Not available	2 generation
Heptane, branched, cyclic and linear	Not Specified	Not classified for development	Rat	NOAEL Not available	2 generation
Toluene	Inhalation	Not classified for female reproduction	Human	NOAEL Not available	occupational exposure
Toluene	Inhalation	Not classified for male reproduction	Rat	NOAEL 2.3 mg/l	1 generation
Toluene	Ingestion	Toxic to development	Rat	LOAEL 520	during

				mg/kg/day	gestation
Toluene	Inhalation	Toxic to development	Human	NOAEL Not available	poisoning and/or abuse
Methylene Chloride	Inhalation	Not classified for female reproduction	Rat	NOAEL 5.2 mg/l	2 generation
Methylene Chloride	Inhalation	Not classified for male reproduction	Rat	NOAEL 5.2 mg/l	2 generation
Methylene Chloride	Inhalation	Not classified for development	Multiple animal species	NOAEL 4.3 mg/l	during gestation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Dimethyl Ether	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Rat	LOAEL 10,000 ppm	30 minutes
Dimethyl Ether	Inhalation	cardiac sensitization	Some positive data exist, but the data are not sufficient for classification	Dog	NOAEL 100,000 ppm	5 minutes
Acetone	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Acetone	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Acetone	Inhalation	immune system	Not classified	Human	NOAEL 1.19 mg/l	6 hours
Acetone	Inhalation	liver	Not classified	Guinea pig	NOAEL Not available	
Acetone	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
Heptane, branched, cyclic and linear	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Isobutane	Inhalation	cardiac sensitization	Causes damage to organs	Multiple animal species	NOAEL Not available	
Isobutane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Isobutane	Inhalation	respiratory irritation	Not classified	Mouse	NOAEL Not available	
Methyl Acetate	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Methyl Acetate	Inhalation	respiratory irritation	May cause respiratory irritation	Human and animal	NOAEL Not available	
Methyl Acetate	Inhalation	blindness	Not classified		NOAEL Not available	
Methyl Acetate	Ingestion	central nervous system depression	May cause drowsiness or dizziness		NOAEL Not available	
Propane	Inhalation	cardiac sensitization	Causes damage to organs	Human	NOAEL Not available	
Propane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Propane	Inhalation	respiratory irritation	Not classified	Human	NOAEL Not available	
Heptane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Heptane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Heptane	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	

Toluene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Toluene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Toluene	Inhalation	immune system	Not classified	Mouse	NOAEL 0.004 mg/l	3 hours
Toluene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
Methylene Chloride	Dermal	blood	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL Not available	4 hours
Methylene Chloride	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	occupational exposure
Methylene Chloride	Inhalation	blood	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Methylene Chloride	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Dimethyl Ether	Inhalation	hematopoietic system	Not classified	Rat	NOAEL 25,000 ppm	2 years
Dimethyl Ether	Inhalation	liver	Not classified	Rat	NOAEL 20,000 ppm	30 weeks
Acetone	Dermal	eyes	Not classified	Guinea pig	NOAEL Not available	3 weeks
Acetone	Inhalation	hematopoietic system	Not classified	Human	NOAEL 3 mg/l	6 weeks
Acetone	Inhalation	immune system	Not classified	Human	NOAEL 1.19 mg/l	6 days
Acetone	Inhalation	kidney and/or bladder	Not classified	Guinea pig	NOAEL 119 mg/l	not available
Acetone	Inhalation	heart liver	Not classified	Rat	NOAEL 45 mg/l	8 weeks
Acetone	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 900 mg/kg/day	13 weeks
Acetone	Ingestion	heart	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
Acetone	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 200 mg/kg/day	13 weeks
Acetone	Ingestion	liver	Not classified	Mouse	NOAEL 3,896 mg/kg/day	14 days
Acetone	Ingestion	eyes	Not classified	Rat	NOAEL 3,400 mg/kg/day	13 weeks
Acetone	Ingestion	respiratory system	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
Acetone	Ingestion	muscles	Not classified	Rat	NOAEL 2,500 mg/kg	13 weeks
Acetone	Ingestion	skin bone, teeth, nails, and/or hair	Not classified	Mouse	NOAEL 11,298 mg/kg/day	13 weeks
Isobutane	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 4,500 ppm	13 weeks
Methyl Acetate	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1.1 mg/l	28 days
Methyl Acetate	Inhalation	endocrine system hematopoietic system liver	Not classified	Rat	NOAEL 6.1 mg/l	28 days

		immune system kidney and/or bladder				
Heptane	Inhalation	liver nervous system kidney and/or bladder	Not classified	Rat	NOAEL 12 mg/l	26 weeks
Toluene	Inhalation	auditory system eyes olfactory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
Toluene	Inhalation	nervous system	May cause damage to organs though prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
Toluene	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 2.3 mg/l	15 months
Toluene	Inhalation	heart liver kidney and/or bladder	Not classified	Rat	NOAEL 11.3 mg/l	15 weeks
Toluene	Inhalation	endocrine system	Not classified	Rat	NOAEL 1.1 mg/l	4 weeks
Toluene	Inhalation	immune system	Not classified	Mouse	NOAEL Not available	20 days
Toluene	Inhalation	bone, teeth, nails, and/or hair	Not classified	Mouse	NOAEL 1.1 mg/l	8 weeks
Toluene	Inhalation	hematopoietic system vascular system	Not classified	Human	NOAEL Not available	occupational exposure
Toluene	Inhalation	gastrointestinal tract	Not classified	Multiple animal species	NOAEL 11.3 mg/l	15 weeks
Toluene	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 625 mg/kg/day	13 weeks
Toluene	Ingestion	heart	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
Toluene	Ingestion	liver kidney and/or bladder	Not classified	Multiple animal species	NOAEL 2,500 mg/kg/day	13 weeks
Toluene	Ingestion	hematopoietic system	Not classified	Mouse	NOAEL 600 mg/kg/day	14 days
Toluene	Ingestion	endocrine system	Not classified	Mouse	NOAEL 105 mg/kg/day	28 days
Toluene	Ingestion	immune system	Not classified	Mouse	NOAEL 105 mg/kg/day	4 weeks
Methylene Chloride	Inhalation	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 6.95 mg/l	2 years
Methylene Chloride	Inhalation	liver	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 0.17 mg/l	2 years
Methylene Chloride	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Multiple animal species	LOAEL 35 mg/l	8 weeks
Methylene Chloride	Inhalation	heart	Not classified	Human	NOAEL Not available	
Methylene Chloride	Inhalation	immune system	Not classified	Rat	NOAEL 18 mg/l	28 days
Methylene Chloride	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 1,200 mg/kg/day	3 months
Methylene Chloride	Ingestion	blood	Not classified	Rat	NOAEL 249 mg/kg/day	2 years
Methylene Chloride	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 1,469 mg/kg/day	3 months
Methylene Chloride	Ingestion	eyes	Not classified	Rat	NOAEL 249 mg/kg/day	104 weeks

Aspiration Hazard

Name	Value
Heptane, branched, cyclic and linear	Aspiration hazard
Heptane	Aspiration hazard
Toluene	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information**Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations**13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): D001 (Ignitable)

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information**15.1. US Federal Regulations**

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:**Physical Hazards**

Flammable (gases, aerosols, liquids, or solids)

Health Hazards

Reproductive toxicity

Serious eye damage or eye irritation

Simple Asphyxiant

Skin Corrosion or Irritation

Specific target organ toxicity (single or repeated exposure)

This material contains a chemical which requires export notification under TSCA Section 12[b]:

<u>Ingredient (Category if applicable)</u>	<u>C.A.S. No</u>	<u>Regulation</u>	<u>Status</u>
Methylene Chloride	75-09-2	Toxic Substances Control Act (TSCA) 6 Banned or Restricted Use Chemicals	Applicable

Additional TSCA Information

This chemical/product is not and cannot be distributed in commerce (as defined in TSCA section 3(5)) or processed (as defined in TSCA section 3(13)) for consumer paint or coating removal.

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 2 **Flammability:** 4 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document Group:	22-1636-4	Version Number:	8.01
Issue Date:	07/28/22	Supersedes Date:	08/11/21

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com