



## Safety Data Sheet

Copyright, 2019, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

|                        |           |                         |          |
|------------------------|-----------|-------------------------|----------|
| <b>Document Group:</b> | 22-3592-7 | <b>Version Number:</b>  | 5.04     |
| <b>Issue Date:</b>     | 04/22/19  | <b>Supersedes Date:</b> | 12/13/18 |

### SECTION 1: Identification

#### 1.1. Product identifier

3M™ Urethane Seam Sealer, Beige, PN 08364, 08365

#### Product Identification Numbers

| ID Number              | UPC              | ID Number      | UPC              |
|------------------------|------------------|----------------|------------------|
| 60-4550-3091-0         | 00-51135-08364-2 | 60-4550-5461-3 | 00-51135-08365-9 |
| 7100049259, 7100024963 |                  |                |                  |

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Used for unpainted seams to closely match factory sealed seams, Sealant

#### 1.3. Supplier's details

|                      |   |
|----------------------|---|
| <b>MANUFACTURER:</b> | 3M                                      |
| <b>DIVISION:</b>     | Automotive Aftermarket                  |
| <b>ADDRESS:</b>      | 3M Center, St. Paul, MN 55144-1000, USA |
| <b>Telephone:</b>    | 1-888-3M HELPS (1-888-364-3577)         |

#### 1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

### SECTION 2: Hazard identification

The label elements below were prepared in accordance with OSHA Hazard Communication Standard, 29 CFR 1910.1200. This information may be different from the actual product label information for labels regulated by other agencies.

#### 2.1. Hazard classification

Respiratory Sensitizer: Category 1.

Skin Sensitizer: Category 1.

Carcinogenicity: Category 2.

Specific Target Organ Toxicity (single exposure): Category 1.

Specific Target Organ Toxicity (repeated exposure): Category 1.

#### 2.2. Label elements

**Signal word**

Danger

**Symbols**

Health Hazard |

**Pictograms****Hazard Statements**

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

Suspected of causing cancer.

Causes damage to organs:

sensory organs |

Causes damage to organs through prolonged or repeated exposure:

nervous system |

May cause damage to organs through prolonged or repeated exposure:

sensory organs |

**Precautionary Statements****General:**

Keep out of reach of children.

**Prevention:**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Do not breathe dust/fume/gas/mist/vapors/spray.

In case of inadequate ventilation wear respiratory protection.

Wear protective gloves.

Do not eat, drink or smoke when using this product.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

**Response:**

IF INHALED: If breathing is difficult, remove person to fresh air and keep comfortable for breathing.

If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.

IF ON SKIN: Wash with plenty of soap and water.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

Get medical advice/attention if you feel unwell.

**Storage:**

Store locked up.

**Disposal:**

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

**Supplemental Information:**

Persons previously sensitized to isocyanates may develop a cross-sensitization reaction to other isocyanates.

1% of the mixture consists of ingredients of unknown acute dermal toxicity.

1% of the mixture consists of ingredients of unknown acute inhalation toxicity.

**SECTION 3: Composition/information on ingredients**

| Ingredient                               | C.A.S. No. | % by Wt                |
|--|------------|------------------------|
| Urethane Polymer                         | 68130-40-5 | 15 - 40 Trade Secret * |
| Poly(Vinyl Chloride)                     | 9002-86-2  | 10 - 30 Trade Secret * |
| Sulfonic Acids, C10-18-Alkane, Ph Esters | 70775-94-9 | 10 - 30 Trade Secret * |
| Sulfonic Acids, C10-21-Alkane, PH Esters | 91082-17-6 | 10 - 30 Trade Secret * |
| Xylene                                   | 1330-20-7  | 5 - 10 Trade Secret *  |
| Calcium Oxide                            | 1305-78-8  | 1 - 5 Trade Secret *   |
| Ethylbenzene                             | 100-41-4   | 1 - 5 Trade Secret *   |
| Hydrotreated Light Petroleum Distillates | 64742-47-8 | 1 - 5 Trade Secret *   |
| Titanium Dioxide                         | 13463-67-7 | 1 - 5 Trade Secret *   |
| P,P'-Methylenebis(phenyl isocyanate)     | 101-68-8   | 0.1 - 1 Trade Secret * |

\*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

**SECTION 4: First aid measures****4.1. Description of first aid measures****Inhalation:**

Remove person to fresh air. If you feel unwell, get medical attention.

**Skin Contact:**

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

**Eye Contact:**

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

**If Swallowed:**

Rinse mouth. If you feel unwell, get medical attention.

**4.2. Most important symptoms and effects, both acute and delayed**

See Section 11.1. Information on toxicological effects.

**4.3. Indication of any immediate medical attention and special treatment required**

Not applicable

**SECTION 5: Fire-fighting measures****5.1. Suitable extinguishing media**

In case of fire: Use a carbon dioxide or dry chemical extinguisher to extinguish.

**5.2. Special hazards arising from the substance or mixture**

None inherent in this product.

#### Hazardous Decomposition or By-Products

##### Substance

Carbon monoxide  
Carbon dioxide

##### Condition

During Combustion  
During Combustion

#### 5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

## SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

#### 6.2. Environmental precautions

Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a container approved for transportation by appropriate authorities, but do not seal the container for 48 hours to avoid pressure build-up. Clean up residue. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

## SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Do not use in a confined area with minimal air exchange. Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Keep away from reactive metals (eg. Aluminum, zinc etc.) to avoid the formation of hydrogen gas that could create an explosion hazard. Use personal protective equipment (gloves, respirators, etc.) as required.

#### 7.2. Conditions for safe storage including any incompatibilities

Keep container tightly closed to prevent contamination with water or air. If contamination is suspected, do not reseal container. Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidizing agents. Store away from amines.

## SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

| Ingredient               | C.A.S. No. | Agency | Limit type                          | Additional Comments          |
|--------------------------|------------|--------|-------------------------------------|------------------------------|
| Ethylbenzene             | 100-41-4   | ACGIH  | TWA:20 ppm                          | A3: Confirmed animal carcin. |
| Ethylbenzene             | 100-41-4   | OSHA   | TWA:435 mg/m <sup>3</sup> (100 ppm) |                              |
| P,P'-Methylenebis(phenyl | 101-68-8   | ACGIH  | TWA:0.005 ppm                       |                              |

|                                      |            |       |  |                                    |
|--------------------------------------|------------|-------|--|------------------------------------|
| isocyanate)                          |            |       |  |                                    |
| P,P'-Methylenebis(phenyl isocyanate) | 101-68-8   | OSHA  | CEIL:0.2 mg/m <sup>3</sup> (0.02 ppm)  |                                    |
| Calcium Oxide                        | 1305-78-8  | ACGIH | TWA:2 mg/m <sup>3</sup>  |                                    |
| Calcium Oxide                        | 1305-78-8  | OSHA  | TWA:5 mg/m <sup>3</sup>  |                                    |
| Xylene                               | 1330-20-7  | ACGIH | TWA:100 ppm;STEL:150 ppm   | A4: Not class. as human carcin     |
| Xylene                               | 1330-20-7  | OSHA  | TWA:435 mg/m <sup>3</sup> (100 ppm)  |                                    |
| Titanium Dioxide                     | 13463-67-7 | ACGIH | TWA:10 mg/m <sup>3</sup>   | A4: Not class. as human carcin     |
| Titanium Dioxide                     | 13463-67-7 | OSHA  | TWA(as total dust):15 mg/m <sup>3</sup>  |                                    |
| Kerosine (petroleum)                 | 64742-47-8 | ACGIH | TWA(as total hydrocarbon vapor, non-aerosol):200 mg/m <sup>3</sup>   | A3: Confirmed animal carcin., SKIN |
| DUST, INERT OR NUISANCE              | 9002-86-2  | OSHA  | TWA(as total dust):15 mg/m <sup>3</sup> ;TWA(as total dust):50 millions of particles/cu. ft.(15 mg/m <sup>3</sup> );TWA(respirable fraction):15 millions of particles/cu. ft.(5 mg/m <sup>3</sup> );TWA(respirable fraction):5 mg/m <sup>3</sup> |                                    |
| Poly(Vinyl Chloride)                 | 9002-86-2  | ACGIH | TWA(respirable fraction):1 mg/m <sup>3</sup>   | A4: Not class. as human carcin     |

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

## 8.2. Exposure controls

### 8.2.1. Engineering controls

Provide ventilated enclosure for heat curing. Curing enclosures must be exhausted to outdoors or to a suitable emission control device. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

### 8.2.2. Personal protective equipment (PPE)

#### Eye/face protection

None required.

#### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Neoprene

Nitrile Rubber

Polyvinyl Chloride

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then

use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - Neoprene  
Apron – Nitrile

### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

|  |  |
|--|--|
| <b>General Physical Form:</b>                  | Solid  |
| <b>Specific Physical Form:</b>                 | Paste  |
| <b>Odor, Color, Grade:</b>                     | Solvent odor, white paste.                                       |
| <b>Odor threshold</b>                          | <i>No Data Available</i>   |
| <b>pH</b>                                      | <i>Not Applicable</i>  |
| <b>Melting point</b>                           | <i>Not Applicable</i>  |
| <b>Boiling Point</b>                           | 137 °C   |
| <b>Flash Point</b>                             | No flash point   |
| <b>Evaporation rate</b>                        | <i>Not Applicable</i>  |
| <b>Flammability (solid, gas)</b>               | Not Classified   |
| <b>Flammable Limits(LEL)</b>                   | 0.6 % volume   |
| <b>Flammable Limits(UEL)</b>                   | 7 % volume   |
| <b>Vapor Pressure</b>                          | 11 mbar [ <i>Ref Std: AIR=1</i> ]                                |
| <b>Vapor Density</b>                           | 4 [ <i>Ref Std: AIR=1</i> ]                                      |
| <b>Density</b>                                 | 1.17 g/ml  |
| <b>Specific Gravity</b>                        | 1.17 [ <i>Ref Std: WATER=1</i> ]                                 |
| <b>Solubility In Water</b>                     | <i>Not Applicable</i>  |
| <b>Solubility in Water</b>                     | Negligible   |
| <b>Solubility- non-water</b>                   | <i>No Data Available</i>   |
| <b>Partition coefficient: n-octanol/ water</b> | <i>No Data Available</i>   |
| <b>Autoignition temperature</b>                | > 200 °C   |
| <b>Decomposition temperature</b>               | <i>No Data Available</i>   |
| <b>Viscosity</b>                               | <i>No Data Available</i>   |
| <b>Hazardous Air Pollutants</b>                | 7.11 % weight [ <i>Test Method: Calculated</i> ]                 |
| <b>Hazardous Air Pollutants</b>                | 0.69 lb HAPS/gal [ <i>Test Method: Calculated</i> ]              |
| <b>Hazardous Air Pollutants</b>                | 0.11 lb HAPS/lb solids [ <i>Test Method: Calculated</i> ]        |
| <b>Volatile Organic Compounds</b>              | 108 g/l [ <i>Test Method: calculated SCAQMD rule 443.1</i> ]     |
| <b>Volatile Organic Compounds</b>              | 9.3 % weight [ <i>Test Method: calculated per CARB title 2</i> ] |
| <b>Percent volatile</b>                        | 9.3 % weight [ <i>Details: Excluding exempt compounds</i> ]      |
| <b>VOC Less H2O &amp; Exempt Solvents</b>      | 108 g/l [ <i>Test Method: calculated SCAQMD rule 443.1</i> ]     |

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

### 10.2. Chemical stability

Stable.

**10.3. Possibility of hazardous reactions**

Hazardous polymerization will not occur.

**10.4. Conditions to avoid**

Heat

High shear and high temperature conditions

Sparks and/or flames

Temperatures above the boiling point

**10.5. Incompatible materials**

Amines

Alcohols

Water

Reaction with water, alcohols, and amines is not hazardous if container can vent to the atmosphere to prevent pressure buildup.

Accelerators

Al or Mg powder and high/shear temperature conditions

Alkali and alkaline earth metals

Reactive metals

Strong acids

Strong bases

Finely divided active metals

Combustibles

Strong oxidizing agents

**10.6. Hazardous decomposition products****Substance****Condition**

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

**SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

**11.1. Information on Toxicological effects****Signs and Symptoms of Exposure**

Based on test data and/or information on the components, this material may produce the following health effects:

**Inhalation:**

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Allergic Respiratory Reaction: Signs/symptoms may include difficulty breathing, wheezing, cough, and tightness of chest.

May cause additional health effects (see below).

**Skin Contact:**

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

**Eye Contact:**

Vapors released during curing may cause eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

**Ingestion:**

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

**Additional Health Effects:****Single exposure may cause target organ effects:**

Auditory Effects: Signs/symptoms may include hearing impairment, balance dysfunction and ringing in the ears.

**Prolonged or repeated exposure may cause target organ effects:**

Auditory Effects: Signs/symptoms may include hearing impairment, balance dysfunction and ringing in the ears.

Neurological Effects: Signs/symptoms may include personality changes, lack of coordination, sensory loss, tingling or numbness of the extremities, weakness, tremors, and/or changes in blood pressure and heart rate.

**Carcinogenicity:**

Contains a chemical or chemicals which can cause cancer.

| Ingredient       | CAS No.    | Class Description             | Regulation                                  |
|------------------|------------|-------------------------------|---|
| Ethylbenzene     | 100-41-4   | Grp. 2B: Possible human carc. | International Agency for Research on Cancer |
| Titanium Dioxide | 13463-67-7 | Grp. 2B: Possible human carc. | International Agency for Research on Cancer |

**Additional Information:**

Persons previously sensitized to isocyanates may develop a cross-sensitization reaction to other isocyanates.

**Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

| Name                                     | Route                      | Species | Value  |
|--|----------------------------|---------|--|
| Overall product                          | Dermal                     |         | No data available; calculated ATE >5,000 mg/kg |
| Overall product                          | Inhalation-Vapor(4 hr)     |         | No data available; calculated ATE >50 mg/l     |
| Overall product                          | Ingestion                  |         | No data available; calculated ATE >5,000 mg/kg |
| Urethane Polymer                         | Dermal                     |         | LD50 estimated to be > 5,000 mg/kg             |
| Urethane Polymer                         | Ingestion                  |         | LD50 estimated to be 2,000 - 5,000 mg/kg       |
| Poly(Vinyl Chloride)                     | Dermal                     |         | LD50 estimated to be > 5,000 mg/kg             |
| Poly(Vinyl Chloride)                     | Ingestion                  |         | LD50 estimated to be > 5,000 mg/kg             |
| Sulfonic Acids, C10-18-Alkane, Ph Esters | Dermal                     | Rat     | LD50 > 1,000 mg/kg                             |
| Sulfonic Acids, C10-18-Alkane, Ph Esters | Ingestion                  | Rat     | LD50 > 5,000 mg/kg                             |
| Sulfonic Acids, C10-21-Alkane, PH Esters | Dermal                     | Rat     | LD50 > 1,055 mg/kg                             |
| Sulfonic Acids, C10-21-Alkane, PH Esters | Ingestion                  | Rat     | LD50 > 15,825 mg/kg                            |
| Xylene                                   | Dermal                     | Rabbit  | LD50 > 4,200 mg/kg                             |
| Xylene                                   | Inhalation-Vapor (4 hours) | Rat     | LC50 29 mg/l                                   |
| Xylene                                   | Ingestion                  | Rat     | LD50 3,523 mg/kg                               |



|  |                                |        |                     |
|--|--------------------------------|--------|---------------------|
| Titanium Dioxide                         | Dermal                         | Rabbit | LD50 > 10,000 mg/kg |
| Titanium Dioxide                         | Inhalation-Dust/Mist (4 hours) | Rat    | LC50 > 6.82 mg/l    |
| Titanium Dioxide                         | Ingestion                      | Rat    | LD50 > 10,000 mg/kg |
| Ethylbenzene                             | Dermal                         | Rabbit | LD50 15,433 mg/kg   |
| Ethylbenzene                             | Inhalation-Vapor (4 hours)     | Rat    | LC50 17.4 mg/l      |
| Ethylbenzene                             | Ingestion                      | Rat    | LD50 4,769 mg/kg    |
| Calcium Oxide                            | Ingestion                      | Rat    | LD50 > 2,500 mg/kg  |
| Hydrotreated Light Petroleum Distillates | Dermal                         | Rabbit | LD50 > 3,160 mg/kg  |
| Hydrotreated Light Petroleum Distillates | Inhalation-Dust/Mist (4 hours) | Rat    | LC50 > 3 mg/l       |
| Hydrotreated Light Petroleum Distillates | Ingestion                      | Rat    | LD50 > 5,000 mg/kg  |
| P,P'-Methylenebis(phenyl isocyanate)     | Dermal                         | Rabbit | LD50 > 5,000 mg/kg  |
| P,P'-Methylenebis(phenyl isocyanate)     | Inhalation-Dust/Mist (4 hours) | Rat    | LC50 0.368 mg/l     |
| P,P'-Methylenebis(phenyl isocyanate)     | Ingestion                      | Rat    | LD50 31,600 mg/kg   |

ATE = acute toxicity estimate

#### Skin Corrosion/Irritation

| Name                                     | Species                 | Value                     |
|--|-------------------------|---------------------------|
| Poly(Vinyl Chloride)                     | Professional judgment   | No significant irritation |
| Sulfonic Acids, C10-21-Alkane, PH Esters | Human and animal        | No significant irritation |
| Xylene                                   | Rabbit                  | Mild irritant             |
| Titanium Dioxide                         | Rabbit                  | No significant irritation |
| Ethylbenzene                             | Rabbit                  | Mild irritant             |
| Calcium Oxide                            | Human                   | Corrosive                 |
| Hydrotreated Light Petroleum Distillates | Rabbit                  | Mild irritant             |
| P,P'-Methylenebis(phenyl isocyanate)     | official classification | Irritant                  |

#### Serious Eye Damage/Irritation

| Name                                     | Species                 | Value                     |
|--|-------------------------|---------------------------|
| Overall product                          | Rabbit                  | Mild irritant             |
| Sulfonic Acids, C10-21-Alkane, PH Esters | Rabbit                  | No significant irritation |
| Xylene                                   | Rabbit                  | Mild irritant             |
| Titanium Dioxide                         | Rabbit                  | No significant irritation |
| Ethylbenzene                             | Rabbit                  | Moderate irritant         |
| Calcium Oxide                            | Rabbit                  | Corrosive                 |
| Hydrotreated Light Petroleum Distillates | Rabbit                  | Mild irritant             |
| P,P'-Methylenebis(phenyl isocyanate)     | official classification | Severe irritant           |

#### Skin Sensitization

| Name                                     | Species          | Value          |
|--|------------------|----------------|
| Titanium Dioxide                         | Human and animal | Not classified |
| Ethylbenzene                             | Human            | Not classified |
| Hydrotreated Light Petroleum Distillates | Guinea pig       | Not classified |

|                                      |                         |             |
|--------------------------------------|-------------------------|-------------|
| P,P'-Methylenebis(phenyl isocyanate) | official classification | Sensitizing |
|--------------------------------------|-------------------------|-------------|

### Respiratory Sensitization

| Name                                 | Species | Value       |
|--------------------------------------|---------|-------------|
| P,P'-Methylenebis(phenyl isocyanate) | Human   | Sensitizing |

### Germ Cell Mutagenicity

| Name                                     | Route    | Value  |
|--|----------|--|
| Poly(Vinyl Chloride)                     | In Vitro | Not mutagenic  |
| Sulfonic Acids, C10-21-Alkane, PH Esters | In Vitro | Not mutagenic  |
| Xylene                                   | In Vitro | Not mutagenic  |
| Xylene                                   | In vivo  | Not mutagenic  |
| Titanium Dioxide                         | In Vitro | Not mutagenic  |
| Titanium Dioxide                         | In vivo  | Not mutagenic  |
| Ethylbenzene                             | In vivo  | Not mutagenic  |
| Ethylbenzene                             | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| Calcium Oxide                            | In Vitro | Not mutagenic  |
| Hydrotreated Light Petroleum Distillates | In Vitro | Not mutagenic  |
| P,P'-Methylenebis(phenyl isocyanate)     | In Vitro | Some positive data exist, but the data are not sufficient for classification |

### Carcinogenicity

| Name                                     | Route         | Species                 | Value  |
|--|---------------|-------------------------|--|
| Poly(Vinyl Chloride)                     | Not Specified | Rat                     | Some positive data exist, but the data are not sufficient for classification |
| Xylene                                   | Dermal        | Rat                     | Not carcinogenic   |
| Xylene                                   | Ingestion     | Multiple animal species | Not carcinogenic   |
| Xylene                                   | Inhalation    | Human                   | Some positive data exist, but the data are not sufficient for classification |
| Titanium Dioxide                         | Ingestion     | Multiple animal species | Not carcinogenic   |
| Titanium Dioxide                         | Inhalation    | Rat                     | Carcinogenic   |
| Ethylbenzene                             | Inhalation    | Multiple animal species | Carcinogenic   |
| Hydrotreated Light Petroleum Distillates | Dermal        | Mouse                   | Some positive data exist, but the data are not sufficient for classification |
| P,P'-Methylenebis(phenyl isocyanate)     | Inhalation    | Rat                     | Some positive data exist, but the data are not sufficient for classification |

### Reproductive Toxicity

#### Reproductive and/or Developmental Effects

| Name                                     | Route         | Value                                  | Species | Test Result         | Exposure Duration     |
|--|---------------|--|---------|---------------------|-----------------------|
| Poly(Vinyl Chloride)                     | Not Specified | Not classified for development         | Mouse   | NOAEL Not available | during gestation      |
| Sulfonic Acids, C10-21-Alkane, PH Esters | Ingestion     | Not classified for female reproduction | Rat     | NOAEL 530 mg/kg/day | 1 generation          |
| Sulfonic Acids, C10-21-Alkane, PH Esters | Ingestion     | Not classified for development         | Rat     | NOAEL 530 mg/kg/day | 1 generation          |
| Xylene                                   | Inhalation    | Not classified for female reproduction | Human   | NOAEL Not available | occupational exposure |
| Xylene                                   | Ingestion     | Not classified for development         | Mouse   | NOAEL Not available | during organogenesis  |

|                                      |            |                                |                         |                     |                                |
|--------------------------------------|------------|--------------------------------|-------------------------|---------------------|--------------------------------|
| Xylene                               | Inhalation | Not classified for development | Multiple animal species | NOAEL Not available | during gestation               |
| Ethylbenzene                         | Inhalation | Not classified for development | Rat                     | NOAEL 4.3 mg/l      | prematuring & during gestation |
| P,P'-Methylenebis(phenyl isocyanate) | Inhalation | Not classified for development | Rat                     | NOAEL 0.004 mg/l    | during organogenesis           |

### Lactation

| Name   | Route     | Species | Value  |
|--------|-----------|---------|--|
| Xylene | Ingestion | Mouse   | Not classified for effects on or via lactation |

### Target Organ(s)

#### Specific Target Organ Toxicity - single exposure

| Name                                     | Route      | Target Organ(s)                   | Value  | Species                 | Test Result         | Exposure Duration     |
|--|------------|-----------------------------------|--|-------------------------|---------------------|-----------------------|
| Xylene                                   | Inhalation | auditory system                   | Causes damage to organs  | Rat                     | LOAEL 6.3 mg/l      | 8 hours               |
| Xylene                                   | Inhalation | central nervous system depression | May cause drowsiness or dizziness  | Human                   | NOAEL Not available |                       |
| Xylene                                   | Inhalation | respiratory irritation            | Some positive data exist, but the data are not sufficient for classification | Human                   | NOAEL Not available |                       |
| Xylene                                   | Inhalation | eyes                              | Not classified   | Rat                     | NOAEL 3.5 mg/l      | not available         |
| Xylene                                   | Inhalation | liver                             | Not classified   | Multiple animal species | NOAEL Not available |                       |
| Xylene                                   | Ingestion  | central nervous system depression | May cause drowsiness or dizziness  | Multiple animal species | NOAEL Not available |                       |
| Xylene                                   | Ingestion  | eyes                              | Not classified   | Rat                     | NOAEL 250 mg/kg     | not applicable        |
| Ethylbenzene                             | Inhalation | central nervous system depression | May cause drowsiness or dizziness  | Human                   | NOAEL Not available |                       |
| Ethylbenzene                             | Inhalation | respiratory irritation            | Some positive data exist, but the data are not sufficient for classification | Human and animal        | NOAEL Not available |                       |
| Ethylbenzene                             | Ingestion  | central nervous system depression | May cause drowsiness or dizziness  | Professional judgement  | NOAEL Not available |                       |
| Calcium Oxide                            | Inhalation | respiratory irritation            | May cause respiratory irritation   | Not available           | NOAEL Not available | occupational exposure |
| Hydrotreated Light Petroleum Distillates | Inhalation | central nervous system depression | May cause drowsiness or dizziness  | Human and animal        | NOAEL Not available |                       |
| Hydrotreated Light Petroleum Distillates | Inhalation | respiratory irritation            | Some positive data exist, but the data are not sufficient for classification |                         | NOAEL Not available |                       |
| Hydrotreated Light Petroleum Distillates | Ingestion  | central nervous system depression | May cause drowsiness or dizziness  | Professional judgement  | NOAEL Not available |                       |
| P,P'-Methylenebis(phenyl isocyanate)     | Inhalation | respiratory irritation            | May cause respiratory irritation   | official classification | NOAEL Not available |                       |

#### Specific Target Organ Toxicity - repeated exposure

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|------|-------|-----------------|-------|---------|-------------|-------------------|
|------|-------|-----------------|-------|---------|-------------|-------------------|

|  |            |  |  |                         |                       |                       |
|--|------------|--|--|-------------------------|-----------------------|-----------------------|
| Poly(Vinyl Chloride)                     | Inhalation | respiratory system   | Not classified   | Multiple animal species | NOAEL 0.013 mg/l      | 22 months             |
| Sulfonic Acids, C10-21-Alkane, PH Esters | Ingestion  | liver   kidney and/or bladder  | Not classified   | Rat                     | NOAEL 1,490 mg/kg/day | 90 days               |
| Xylene                                   | Inhalation | nervous system   | Causes damage to organs through prolonged or repeated exposure               | Rat                     | LOAEL 0.4 mg/l        | 4 weeks               |
| Xylene                                   | Inhalation | auditory system  | May cause damage to organs through prolonged or repeated exposure            | Rat                     | LOAEL 7.8 mg/l        | 5 days                |
| Xylene                                   | Inhalation | liver  | Not classified   | Multiple animal species | NOAEL Not available   |                       |
| Xylene                                   | Inhalation | heart   endocrine system   gastrointestinal tract   hematopoietic system   muscles   kidney and/or bladder   respiratory system                | Not classified   | Multiple animal species | NOAEL 3.5 mg/l        | 13 weeks              |
| Xylene                                   | Ingestion  | auditory system  | Not classified   | Rat                     | NOAEL 900 mg/kg/day   | 2 weeks               |
| Xylene                                   | Ingestion  | kidney and/or bladder  | Not classified   | Rat                     | NOAEL 1,500 mg/kg/day | 90 days               |
| Xylene                                   | Ingestion  | liver  | Not classified   | Multiple animal species | NOAEL Not available   |                       |
| Xylene                                   | Ingestion  | heart   skin   endocrine system   bone, teeth, nails, and/or hair   hematopoietic system   immune system   nervous system   respiratory system | Not classified   | Mouse                   | NOAEL 1,000 mg/kg/day | 103 weeks             |
| Titanium Dioxide                         | Inhalation | respiratory system   | Some positive data exist, but the data are not sufficient for classification | Rat                     | LOAEL 0.01 mg/l       | 2 years               |
| Titanium Dioxide                         | Inhalation | pulmonary fibrosis   | Not classified   | Human                   | NOAEL Not available   | occupational exposure |
| Ethylbenzene                             | Inhalation | kidney and/or bladder  | Some positive data exist, but the data are not sufficient for classification | Rat                     | NOAEL 1.1 mg/l        | 2 years               |
| Ethylbenzene                             | Inhalation | liver  | Some positive data exist, but the data are not sufficient for classification | Mouse                   | NOAEL 1.1 mg/l        | 103 weeks             |
| Ethylbenzene                             | Inhalation | hematopoietic system   | Not classified   | Rat                     | NOAEL 3.4 mg/l        | 28 days               |
| Ethylbenzene                             | Inhalation | auditory system  | Not classified   | Rat                     | NOAEL 2.4 mg/l        | 5 days                |
| Ethylbenzene                             | Inhalation | endocrine system   | Not classified   | Mouse                   | NOAEL 3.3 mg/l        | 103 weeks             |
| Ethylbenzene                             | Inhalation | gastrointestinal tract   | Not classified   | Rat                     | NOAEL 3.3 mg/l        | 2 years               |
| Ethylbenzene                             | Inhalation | bone, teeth, nails, and/or hair   muscles  | Not classified   | Multiple animal species | NOAEL 4.2 mg/l        | 90 days               |
| Ethylbenzene                             | Inhalation | heart   immune system   respiratory system   | Not classified   | Multiple animal species | NOAEL 3.3 mg/l        | 2 years               |
| Ethylbenzene                             | Ingestion  | liver   kidney and/or bladder  | Not classified   | Rat                     | NOAEL 680 mg/kg/day   | 6 months              |
| P,P'-Methylenebis(phenyl isocyanate)     | Inhalation | respiratory system   | Causes damage to organs through prolonged or repeated exposure               | Rat                     | LOAEL 0.004 mg/l      | 13 weeks              |

**Aspiration Hazard**

| Name                                     | Value             |
|--|-------------------|
| Xylene                                   | Aspiration hazard |
| Ethylbenzene                             | Aspiration hazard |
| Hydrotreated Light Petroleum Distillates | Aspiration hazard |

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

**SECTION 12: Ecological information****Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

**Chemical fate information**

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

**SECTION 13: Disposal considerations****13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

**SECTION 14: Transport Information**

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

**SECTION 15: Regulatory information****15.1. US Federal Regulations**

Contact 3M for more information.

**EPCRA 311/312 Hazard Classifications:****Physical Hazards**

Not applicable

**Health Hazards**

Carcinogenicity

Respiratory or Skin Sensitization

Specific target organ toxicity (single or repeated exposure)

**Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):**

| <u>Ingredient</u>           | <u>C.A.S. No</u> | <u>% by Wt</u>      |
|-----------------------------|------------------|---------------------|
| Xylene                      | 1330-20-7        | Trade Secret 5 - 10 |
| Xylene (Benzene, dimethyl-) | 1330-20-7        | 5 - 10              |
| Ethylbenzene                | 100-41-4         | Trade Secret 1 - 5  |

## 15.2. State Regulations

Contact 3M for more information.

### California Proposition 65

| <u>Ingredient</u>   | <u>C.A.S. No.</u> | <u>Listing</u> |
|---|-------------------|----------------|
| ETHYLBENZENE  | 100-41-4          | Carcinogen     |
| TITANIUM DIOXIDE (AIRBORNE, UNBOUND PARTICLES OF RESPIRABLE SIZE) | 13463-67-7        | Carcinogen     |

## 15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

## 15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

## SECTION 16: Other information

### NFPA Hazard Classification

**Health:** 2 **Flammability:** 1 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

|                        |           |                         |          |
|------------------------|-----------|-------------------------|----------|
| <b>Document Group:</b> | 22-3592-7 | <b>Version Number:</b>  | 5.04     |
| <b>Issue Date:</b>     | 04/22/19  | <b>Supersedes Date:</b> | 12/13/18 |

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at [www.3M.com](http://www.3M.com)