



## Safety Data Sheet

Copyright,2020, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document Group:</b>	23-8876-7	<b>Version Number:</b>	1.04
<b>Issue Date:</b>	02/05/20	<b>Supersedes Date:</b>	05/04/17

### Product identifier

3M™Scotch-Weld™ Epoxy Adhesive EC-2615 B/A Charcoal

### ID Number(s):

87-2500-0287-7, 87-2500-0288-5, 87-2500-0291-9, 87-2500-0322-2, 87-2500-0334-7, 87-3300-0190-7

7010399415, 7010351962

### Recommended use

Structural adhesive

### Supplier's details

<b>MANUFACTURER:</b>	3M
<b>DIVISION:</b>	Automotive and Aerospace Solutions Division

<b>ADDRESS:</b>	3M Center, St. Paul, MN 55144-1000, USA
<b>Telephone:</b>	1-888-3M HELPS (1-888-364-3577)

### Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

**This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet (SDS), Article Information Sheet (AIS), or Article Information Letter (AIL) for each of these components is included. Please do not separate the component documents from this cover page. The document numbers for components of this product are:**

23-9079-7, 23-9078-9

**DISCLAIMER:** The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at [www.3M.com](http://www.3M.com)



## Safety Data Sheet

Copyright, 2023, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document Group:</b>	23-9078-9	<b>Version Number:</b>	4.02
<b>Issue Date:</b>	03/10/23	<b>Supersedes Date:</b>	02/15/23

### SECTION 1: Identification

#### 1.1. Product identifier

3M™ Scotch-Weld™ Epoxy Adhesive EC-2615 B/A Charcoal, Part B

#### Product Identification Numbers

41-0001-5457-9, 41-3588-1660-5, 87-2500-0308-1  
7010321063

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Base for 2 part adhesive

#### 1.3. Supplier's details

<b>MANUFACTURER:</b>	3M
<b>DIVISION:</b>	Automotive and Aerospace Solutions Division
<b>ADDRESS:</b>	3M Center, St. Paul, MN 55144-1000, USA
<b>Telephone:</b>	1-888-3M HELPS (1-888-364-3577)

#### 1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

### SECTION 2: Hazard identification

#### 2.1. Hazard classification

Serious Eye Damage/Irritation: Category 2B.

Skin Sensitizer: Category 1.

Reproductive Toxicity: Category 1B.

#### 2.2. Label elements

##### Signal word

Danger

##### Symbols

Exclamation mark | Health Hazard |

##### Pictograms

**Hazard Statements**

Causes eye irritation.  
 May cause an allergic skin reaction.  
 May damage fertility or the unborn child.

**Precautionary Statements****Prevention:**

Obtain special instructions before use.  
 Do not handle until all safety precautions have been read and understood.  
 Avoid breathing dust/fume/gas/mist/vapors/spray.  
 Wear protective gloves.  
 Wash thoroughly after handling.  
 Contaminated work clothing must not be allowed out of the workplace.

**Response:**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 If eye irritation persists: Get medical advice/attention.  
 IF ON SKIN: Wash with plenty of soap and water.  
 If skin irritation or rash occurs: Get medical advice/attention.  
 Wash contaminated clothing before reuse.  
 IF exposed or concerned: Get medical advice/attention.

**Storage:**

Store locked up.

**Disposal:**

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

### SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
EPOXY RESIN	25068-38-6	60 - 90 Trade Secret *
ACRYLIC POLYMER (N.J. TRADE SECRET REG. NO 04499600-5018P)	Trade Secret*	10 - 30
SILICA	67762-90-7	1 - 5
SILANE	2530-83-8	< 1
TITANIUM DIOXIDE	13463-67-7	< 1 Trade Secret *
Toluene	108-88-3	<= 0.99 Trade Secret *

\*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

**Inhalation:**

Remove person to fresh air. If you feel unwell, get medical attention.

**Skin Contact:**

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

**Eye Contact:**

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

**If Swallowed:**

Rinse mouth. If you feel unwell, get medical attention.

**4.2. Most important symptoms and effects, both acute and delayed**

Allergic skin reaction (redness, swelling, blistering, and itching).

**4.3. Indication of any immediate medical attention and special treatment required**

Not applicable

**SECTION 5: Fire-fighting measures****5.1. Suitable extinguishing media**

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

**5.2. Special hazards arising from the substance or mixture**

None inherent in this product.

**Hazardous Decomposition or By-Products****Substance**

Aldehydes

Carbon monoxide

Carbon dioxide

Hydrogen Chloride

Oxides of Nitrogen

Toxic Vapor, Gas, Particulate

**Condition**

During Combustion

During Combustion

During Combustion

During Combustion

During Combustion

During Combustion

**5.3. Special protective actions for fire-fighters**

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

**6.2. Environmental precautions**

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

**6.3. Methods and material for containment and cleaning up**

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible.

Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Use personal protective equipment (gloves, respirators, etc.) as required.

### 7.2. Conditions for safe storage including any incompatibilities

No special storage requirements.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Toluene	108-88-3	ACGIH	TWA:20 ppm	A4: Not class. as human carcin, Ototoxicant
Toluene	108-88-3	OSHA	TWA:200 ppm;CEIL:300 ppm	
TITANIUM DIOXIDE	13463-67-7	ACGIH	TWA(Respirable nanoscale particles):0.2 mg/m <sup>3</sup> ;TWA(Respirable finescale particles):2.5 mg/m <sup>3</sup>	A3: Confirmed animal carcin.
TITANIUM DIOXIDE	13463-67-7	OSHA	TWA(as total dust):15 mg/m <sup>3</sup>	
SILICA, AMORPHOUS	67762-90-7	OSHA	TWA:20 millions of particles/cu. ft.;TWA concentration:0.8 mg/m <sup>3</sup>	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

### 8.2. Exposure controls

#### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

#### 8.2.2. Personal protective equipment (PPE)

##### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect Vented Goggles

### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

#### Appearance

Physical state

Liquid

Color

Dark Gray, White

Odor

Mild Odor

Odor threshold

*No Data Available*

pH

*Not Applicable*

Melting point

*No Data Available*

Boiling Point

*Not Applicable*

Flash Point

$\geq 340$  °F [*Test Method: Closed Cup*]

Evaporation rate

*Not Applicable*

Flammability (solid, gas)

Not Applicable

Flammable Limits(LEL)

*No Data Available*

Flammable Limits(UEL)

*No Data Available*

Vapor Pressure

$\leq 27$  psia [*@ 131 °F*]

Vapor Density

Nil

Density

9.5 lb/gal

Specific Gravity

1.14 [*Ref Std: WATER=1*]

Solubility in Water

Nil

Solubility- non-water

*No Data Available*

Partition coefficient: n-octanol/ water

*No Data Available*

Autoignition temperature

*No Data Available*

Decomposition temperature

*No Data Available*

Viscosity

100,000 centipoise [*@ 68 °F*]

Molecular weight

*No Data Available*

Volatile Organic Compounds

11.3 g/l

Percent volatile

1 %

Percent volatile

Negligible

VOC Less H<sub>2</sub>O & Exempt Solvents

11.7 g/l

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

This material is considered to be non reactive under normal use conditions.

### 10.2. Chemical stability

Stable.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

None known.

### 10.5. Incompatible materials

None known.

### 10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

### 11.1. Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

#### Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

#### Eye Contact:

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

#### Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).



**Additional Health Effects:****Reproductive/Developmental Toxicity:**

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

**Carcinogenicity:**

Ingredient	CAS No.	Class Description	Regulation
Titanium dioxide	13463-67-7	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

**Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
EPOXY RESIN	Dermal	Rat	LD50 > 1,600 mg/kg
EPOXY RESIN	Ingestion	Rat	LD50 > 1,000 mg/kg
ACRYLIC POLYMER (N.J. TRADE SECRET REG. NO 04499600-5018P)	Dermal		LD50 estimated to be > 5,000 mg/kg
ACRYLIC POLYMER (N.J. TRADE SECRET REG. NO 04499600-5018P)	Ingestion	Rat	LD50 > 5,000 mg/kg
SILICA	Dermal	Rabbit	LD50 > 5,000 mg/kg
SILICA	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
SILICA	Ingestion	Rat	LD50 > 5,110 mg/kg
Toluene	Dermal	Rat	LD50 12,000 mg/kg
Toluene	Inhalation-Vapor (4 hours)	Rat	LC50 30 mg/l
Toluene	Ingestion	Rat	LD50 5,550 mg/kg
TITANIUM DIOXIDE	Dermal	Rabbit	LD50 > 10,000 mg/kg
TITANIUM DIOXIDE	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 6.82 mg/l
TITANIUM DIOXIDE	Ingestion	Rat	LD50 > 10,000 mg/kg
SILANE	Dermal	Rabbit	LD50 4,000 mg/kg
SILANE	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 5.3 mg/l
SILANE	Ingestion	Rat	LD50 7,010 mg/kg

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

Name	Species	Value
EPOXY RESIN	Rabbit	Mild irritant
SILICA	Rabbit	No significant irritation
Toluene	Rabbit	Irritant
TITANIUM DIOXIDE	Rabbit	No significant irritation
SILANE	Rabbit	Mild irritant

**Serious Eye Damage/Irritation**

Name	Species	Value
EPOXY RESIN	Rabbit	Moderate irritant
SILICA	Rabbit	No significant irritation
Toluene	Rabbit	Moderate irritant

TITANIUM DIOXIDE	Rabbit	No significant irritation
SILANE	Rabbit	Corrosive

### Skin Sensitization

Name	Species	Value
EPOXY RESIN	Human and animal	Sensitizing
SILICA	Human and animal	Not classified
Toluene	Guinea pig	Not classified
TITANIUM DIOXIDE	Human and animal	Not classified
SILANE	Guinea pig	Not classified

### Respiratory Sensitization

Name	Species	Value
EPOXY RESIN	Human	Not classified

### Germ Cell Mutagenicity

Name	Route	Value
EPOXY RESIN	In vivo	Not mutagenic
EPOXY RESIN	In Vitro	Some positive data exist, but the data are not sufficient for classification
SILICA	In Vitro	Not mutagenic
Toluene	In Vitro	Not mutagenic
Toluene	In vivo	Not mutagenic
TITANIUM DIOXIDE	In Vitro	Not mutagenic
TITANIUM DIOXIDE	In vivo	Not mutagenic
SILANE	In vivo	Not mutagenic
SILANE	In Vitro	Some positive data exist, but the data are not sufficient for classification

### Carcinogenicity

Name	Route	Species	Value
EPOXY RESIN	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
SILICA	Not Specified	Mouse	Some positive data exist, but the data are not sufficient for classification
Toluene	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Toluene	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification
Toluene	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification
TITANIUM DIOXIDE	Ingestion	Multiple animal species	Not carcinogenic
TITANIUM DIOXIDE	Inhalation	Rat	Carcinogenic
SILANE	Dermal	Mouse	Not carcinogenic

### Reproductive Toxicity

#### Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
EPOXY RESIN	Ingestion	Not classified for female reproduction	Rat	NOAEL 750	2 generation

				mg/kg/day	
EPOXY RESIN	Ingestion	Not classified for male reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
EPOXY RESIN	Dermal	Not classified for development	Rabbit	NOAEL 300 mg/kg/day	during organogenesis
EPOXY RESIN	Ingestion	Not classified for development	Rat	NOAEL 750 mg/kg/day	2 generation
SILICA	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
SILICA	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
SILICA	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
Toluene	Inhalation	Not classified for female reproduction	Human	NOAEL Not available	occupational exposure
Toluene	Inhalation	Not classified for male reproduction	Rat	NOAEL 2.3 mg/l	1 generation
Toluene	Ingestion	Toxic to development	Rat	LOAEL 520 mg/kg/day	during gestation
Toluene	Inhalation	Toxic to development	Human	NOAEL Not available	poisoning and/or abuse
SILANE	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	1 generation
SILANE	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	1 generation
SILANE	Ingestion	Not classified for development	Rat	NOAEL 3,000 mg/kg/day	during organogenesis

### Target Organ(s)

#### Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Toluene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Toluene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Toluene	Inhalation	immune system	Not classified	Mouse	NOAEL 0.004 mg/l	3 hours
Toluene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse

#### Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
EPOXY RESIN	Dermal	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	2 years
EPOXY RESIN	Dermal	nervous system	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
EPOXY RESIN	Ingestion	auditory system   heart   endocrine system   hematopoietic system   liver   eyes   kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
SILICA	Inhalation	respiratory system   silicosis	Not classified	Human	NOAEL Not available	occupational exposure
Toluene	Inhalation	auditory system	Causes damage to organs through	Human	NOAEL Not	poisoning

		eyes   olfactory system	prolonged or repeated exposure		available	and/or abuse
Toluene	Inhalation	nervous system	May cause damage to organs though prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
Toluene	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 2.3 mg/l	15 months
Toluene	Inhalation	heart   liver   kidney and/or bladder	Not classified	Rat	NOAEL 11.3 mg/l	15 weeks
Toluene	Inhalation	endocrine system	Not classified	Rat	NOAEL 1.1 mg/l	4 weeks
Toluene	Inhalation	immune system	Not classified	Mouse	NOAEL Not available	20 days
Toluene	Inhalation	bone, teeth, nails, and/or hair	Not classified	Mouse	NOAEL 1.1 mg/l	8 weeks
Toluene	Inhalation	hematopoietic system   vascular system	Not classified	Human	NOAEL Not available	occupational exposure
Toluene	Inhalation	gastrointestinal tract	Not classified	Multiple animal species	NOAEL 11.3 mg/l	15 weeks
Toluene	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 625 mg/kg/day	13 weeks
Toluene	Ingestion	heart	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
Toluene	Ingestion	liver   kidney and/or bladder	Not classified	Multiple animal species	NOAEL 2,500 mg/kg/day	13 weeks
Toluene	Ingestion	hematopoietic system	Not classified	Mouse	NOAEL 600 mg/kg/day	14 days
Toluene	Ingestion	endocrine system	Not classified	Mouse	NOAEL 105 mg/kg/day	28 days
Toluene	Ingestion	immune system	Not classified	Mouse	NOAEL 105 mg/kg/day	4 weeks
TITANIUM DIOXIDE	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.01 mg/l	2 years
TITANIUM DIOXIDE	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure
SILANE	Ingestion	heart   endocrine system   bone, teeth, nails, and/or hair   hematopoietic system   liver   immune system   nervous system   kidney and/or bladder   respiratory system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days

### Aspiration Hazard

Name	Value
Toluene	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

## SECTION 12: Ecological information

### Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material

and/or its components.

### Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

**EPA Hazardous Waste Number (RCRA):** Not regulated

## SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

## SECTION 15: Regulatory information

### 15.1. US Federal Regulations

Contact 3M for more information.

#### EPCRA 311/312 Hazard Classifications:

##### Physical Hazards

Not applicable

##### Health Hazards

Reproductive toxicity

Respiratory or Skin Sensitization

Serious eye damage or eye irritation

### 15.2. State Regulations

Contact 3M for more information.

### 15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

### 15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

**SECTION 16: Other information****NFPA Hazard Classification****Health:** 2 **Flammability:** 1 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

<b>Document Group:</b>	23-9078-9	<b>Version Number:</b>	4.02
<b>Issue Date:</b>	03/10/23	<b>Supersedes Date:</b>	02/15/23

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

**3M USA SDSs are available at [www.3M.com](http://www.3M.com)**



## Safety Data Sheet

Copyright, 2023, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document Group:</b>	23-9079-7	<b>Version Number:</b>	5.03
<b>Issue Date:</b>	03/10/23	<b>Supersedes Date:</b>	08/04/21

### SECTION 1: Identification

#### 1.1. Product identifier

3M™ Scotch-Weld™ Epoxy Adhesive EC-2615 B/A Charcoal Part A

#### Product Identification Numbers

LC-B100-0393-0, LC-B100-0393-1, LC-B100-0398-0, LC-B100-0596-8, LC-B100-0596-9, 41-3588-1678-7, 87-2500-0309-9  
7010399412

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Accelerator for 2-Part Adhesive

#### 1.3. Supplier's details

<b>MANUFACTURER:</b>	3M
<b>DIVISION:</b>	Automotive and Aerospace Solutions Division
<b>ADDRESS:</b>	3M Center, St. Paul, MN 55144-1000, USA
<b>Telephone:</b>	1-888-3M HELPS (1-888-364-3577)

#### 1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

### SECTION 2: Hazard identification

#### 2.1. Hazard classification

Corrosive to metal: Category 1.

Serious Eye Damage/Irritation: Category 1.

Skin Corrosion/Irritation: Category 1B.

Skin Sensitizer: Category 1.

#### 2.2. Label elements

##### Signal word

Danger

##### Symbols

Corrosion | Exclamation mark |

##### Pictograms

**Hazard Statements**

May be corrosive to metals.

Causes severe skin burns and eye damage.  
May cause an allergic skin reaction.

**Precautionary Statements****Prevention:**

Keep only in original container.  
Do not breathe dust/fume/gas/mist/vapors/spray.  
Wear protective gloves, protective clothing, and eye/face protection.  
Wash thoroughly after handling.  
Contaminated work clothing must not be allowed out of the workplace.

**Response:**

IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
Immediately call a POISON CENTER or doctor/physician.  
If skin irritation or rash occurs: Get medical advice/attention.  
Wash contaminated clothing before reuse.  
IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.  
Absorb spillage to prevent material damage.

**Storage:**

Store in a corrosive resistant container with a resistant inner liner.  
Store locked up.

**Disposal:**

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

**2.3. Hazards not otherwise classified**

May cause chemical gastrointestinal burns.

**SECTION 3: Composition/information on ingredients**

Ingredient	C.A.S. No.	% by Wt
4,7,10-TRIOXATRIDECANE-1,13-DIAMINE	4246-51-9	40 - 70 Trade Secret *
MODIFIED EPOXY RESIN	68610-41-3	20 - 30 Trade Secret *
4,4'-isopropylidenediphenol-epichlorohydrin polymer	25068-38-6	3 - 10
AMORPHOUS SILICA	67762-90-7	3 - 7
CATALYST	55120-75-7	1 - 5 Trade Secret *
TRIS(2,4,6-DIMETHYLAMINOMONOMETHYL)PHENOL	90-72-2	1 - 5 Trade Secret *

\*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade



secret.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

#### Skin Contact:

Immediately flush with large amounts of water for at least 15 minutes. Remove contaminated clothing. Get immediate medical attention. Wash clothing before reuse.

#### Eye Contact:

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

#### If Swallowed:

Rinse mouth. Do not induce vomiting. Get immediate medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

Skin burns (localized redness, swelling, itching, intense pain, blistering, and tissue destruction). Allergic skin reaction (redness, swelling, blistering, and itching). Serious damage to the eyes (corneal cloudiness, severe pain, tearing, ulcerations, and significantly impaired or loss of vision).

### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

## SECTION 5: Fire-fighting measures

### 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

### 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

### Hazardous Decomposition or By-Products

#### Substance

Aldehydes  
Carbon monoxide  
Carbon dioxide  
Hydrogen Chloride  
Hydrogen Cyanide  
Oxides of Nitrogen  
Oxides of Sulfur  
Toxic Vapor, Gas, Particulate

#### Condition

During Combustion  
During Combustion  
During Combustion  
During Combustion  
During Combustion  
During Combustion  
During Combustion  
During Combustion

### 5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for

information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

### 6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

### 6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a metal container approved for use in transportation by appropriate authorities. The container must be lined with polyethylene plastic or contain a plastic drum liner made of polyethylene. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Cover, but do not seal for 48 hours. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse.

### 7.2. Conditions for safe storage including any incompatibilities

Keep only in original container. Store in a corrosive resistant container with a resistant inner liner. Store away from acids.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
SILICA, AMORPHOUS	67762-90-7	OSHA	TWA:20 millions of particles/cu. ft.;TWA concentration:0.8 mg/m3	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

### 8.2. Exposure controls

#### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

#### 8.2.2. Personal protective equipment (PPE)

##### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full Face Shield

Indirect Vented Goggles

#### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

#### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

#### Appearance

Physical state

Liquid

Color

Orange-Amber

Odor

Mild Odor

Odor threshold

*No Data Available*

pH

*Not Applicable*

Melting point

*No Data Available*

Boiling Point

$\geq 340$  °F

Flash Point

$\geq 340$  °F [*Test Method*: Closed Cup]

Evaporation rate

*Not Applicable*

Flammability (solid, gas)

Not Applicable

Flammable Limits(LEL)

*No Data Available*

Flammable Limits(UEL)

*No Data Available*

Vapor Pressure

$\leq 0.01$  mmHg [*@* 68 °F]

Vapor Density

3.72 [*Ref.Std*: AIR=1]

Density

1.12 g/ml [*@* 20 °C]

Specific Gravity

1.12 [*Ref.Std*: WATER=1]

Solubility in Water

Slight (less than 10%)

Solubility- non-water

*No Data Available*

Partition coefficient: n-octanol/ water

*No Data Available*

Autoignition temperature

*No Data Available*

Decomposition temperature

*No Data Available*

Viscosity

8,000 centipoise

Molecular weight

*No Data Available*

Volatile Organic Compounds

*Not Applicable*

Percent volatile  
VOC Less H<sub>2</sub>O & Exempt Solvents

Negligible  
*Not Applicable*

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

This material is considered to be non reactive under normal use conditions.

### 10.2. Chemical stability

Stable.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

None known.

### 10.5. Incompatible materials

None known.

### 10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

### 11.1. Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

#### Skin Contact:

May be harmful in contact with skin.

Corrosive (Skin Burns): Signs/symptoms may include localized redness, swelling, itching, intense pain, blistering, ulceration, and tissue destruction.

Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

#### Eye Contact:

Corrosive (Eye Burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

**Ingestion:**

May be harmful if swallowed.

Gastrointestinal Corrosion: Signs/symptoms may include severe mouth, throat and abdominal pain; nausea; vomiting; and diarrhea; blood in the feces and/or vomitus may also be seen.

**Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >2,000 - =5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >2,000 - =5,000 mg/kg
4,7,10-TRIOXATRIDECANE-1,13-DIAMINE	Dermal	Rabbit	LD50 2,525 mg/kg
4,7,10-TRIOXATRIDECANE-1,13-DIAMINE	Ingestion	Rat	LD50 2,850 mg/kg
MODIFIED EPOXY RESIN	Dermal	Not available	LD50 3,000 mg/kg
MODIFIED EPOXY RESIN	Ingestion	Not available	LD50 > 34,000 mg/kg
4,4'-isopropylidenediphenol-epichlorohydrin polymer	Dermal	Rat	LD50 > 1,600 mg/kg
4,4'-isopropylidenediphenol-epichlorohydrin polymer	Ingestion	Rat	LD50 > 1,000 mg/kg
AMORPHOUS SILICA	Dermal	Rabbit	LD50 > 5,000 mg/kg
AMORPHOUS SILICA	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
AMORPHOUS SILICA	Ingestion	Rat	LD50 > 5,110 mg/kg
TRIS(2,4,6-DIMETHYLAMINOMONOMETHYL)PHENOL	Dermal	Rat	LD50 1,280 mg/kg
TRIS(2,4,6-DIMETHYLAMINOMONOMETHYL)PHENOL	Ingestion	Rat	LD50 1,000 mg/kg
CATALYST	Dermal	Professional judgment	LD50 estimated to be 2,000 - 5,000 mg/kg
CATALYST	Ingestion	Rat	LD50 > 2,000 mg/kg

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

Name	Species	Value
4,7,10-TRIOXATRIDECANE-1,13-DIAMINE	Rabbit	Corrosive
MODIFIED EPOXY RESIN	similar compounds	Irritant
4,4'-isopropylidenediphenol-epichlorohydrin polymer	Rabbit	Mild irritant
AMORPHOUS SILICA	Rabbit	No significant irritation
TRIS(2,4,6-DIMETHYLAMINOMONOMETHYL)PHENOL	Rabbit	Corrosive
CATALYST	Rabbit	Minimal irritation

**Serious Eye Damage/Irritation**

Name	Species	Value
4,7,10-TRIOXATRIDECANE-1,13-DIAMINE	Rabbit	Corrosive
MODIFIED EPOXY RESIN	similar compounds	Severe irritant
4,4'-isopropylidenediphenol-epichlorohydrin polymer	Rabbit	Moderate irritant
AMORPHOUS SILICA	Rabbit	No significant irritation
TRIS(2,4,6-DIMETHYLAMINOMONOMETHYL)PHENOL	Rabbit	Corrosive
CATALYST	Rabbit	Corrosive

**Skin Sensitization**

Name	Species	Value
4,7,10-TRIOXATRIDECANE-1,13-DIAMINE	Professional judgment	Sensitizing
MODIFIED EPOXY RESIN	similar compounds	Sensitizing
4,4'-isopropylidenediphenol-epichlorohydrin polymer	Human and animal	Sensitizing
AMORPHOUS SILICA	Human and animal	Not classified
TRIS(2,4,6-DIMETHYLAMINOMONOMETHYL)PHENOL	Guinea pig	Not classified
CATALYST	Guinea pig	Not classified

### Respiratory Sensitization

Name	Species	Value
4,4'-isopropylidenediphenol-epichlorohydrin polymer	Human	Not classified

### Germ Cell Mutagenicity

Name	Route	Value
4,7,10-TRIOXATRIDECANE-1,13-DIAMINE	In Vitro	Not mutagenic
4,4'-isopropylidenediphenol-epichlorohydrin polymer	In vivo	Not mutagenic
4,4'-isopropylidenediphenol-epichlorohydrin polymer	In Vitro	Some positive data exist, but the data are not sufficient for classification
AMORPHOUS SILICA	In Vitro	Not mutagenic
TRIS(2,4,6-DIMETHYLAMINOMONOMETHYL)PHENOL	In Vitro	Not mutagenic
CATALYST	In Vitro	Not mutagenic

### Carcinogenicity

Name	Route	Species	Value
4,4'-isopropylidenediphenol-epichlorohydrin polymer	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
AMORPHOUS SILICA	Not Specified	Mouse	Some positive data exist, but the data are not sufficient for classification

### Reproductive Toxicity

#### Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
4,7,10-TRIOXATRIDECANE-1,13-DIAMINE	Ingestion	Not classified for female reproduction	Rat	NOAEL 600 mg/kg/day	prematuring into lactation
4,7,10-TRIOXATRIDECANE-1,13-DIAMINE	Ingestion	Not classified for male reproduction	Rat	NOAEL 600 mg/kg/day	59 days
4,7,10-TRIOXATRIDECANE-1,13-DIAMINE	Ingestion	Not classified for development	Rat	NOAEL 600 mg/kg/day	prematuring into lactation
4,4'-isopropylidenediphenol-epichlorohydrin polymer	Ingestion	Not classified for female reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
4,4'-isopropylidenediphenol-epichlorohydrin polymer	Ingestion	Not classified for male reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
4,4'-isopropylidenediphenol-epichlorohydrin polymer	Dermal	Not classified for development	Rabbit	NOAEL 300 mg/kg/day	during organogenesis
4,4'-isopropylidenediphenol-epichlorohydrin polymer	Ingestion	Not classified for development	Rat	NOAEL 750 mg/kg/day	2 generation
AMORPHOUS SILICA	Ingestion	Not classified for female reproduction	Rat	NOAEL 509	1 generation

				mg/kg/day	
AMORPHOUS SILICA	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
AMORPHOUS SILICA	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis

### Target Organ(s)

#### Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
4,7,10-TRIOXATRIDECANE-1,13-DIAMINE	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
TRIS(2,4,6-DIMETHYLAMINOMETHYL)PHENOL	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
CATALYST	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL not available	

#### Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
4,7,10-TRIOXATRIDECANE-1,13-DIAMINE	Ingestion	gastrointestinal tract   heart   endocrine system   bone, teeth, nails, and/or hair   hematopoietic system   liver   immune system   muscles   nervous system   eyes   kidney and/or bladder   respiratory system   vascular system	Not classified	Rat	NOAEL 600 mg/kg/day	59 days
4,4'-isopropylidenediphenol-epichlorohydrin polymer	Dermal	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	2 years
4,4'-isopropylidenediphenol-epichlorohydrin polymer	Dermal	nervous system	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
4,4'-isopropylidenediphenol-epichlorohydrin polymer	Ingestion	auditory system   heart   endocrine system   hematopoietic system   liver   eyes   kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
AMORPHOUS SILICA	Inhalation	respiratory system   silicosis	Not classified	Human	NOAEL Not available	occupational exposure
TRIS(2,4,6-DIMETHYLAMINOMETHYL)PHENOL	Dermal	skin   liver   nervous system   auditory system   hematopoietic system   eyes	Not classified	Rat	NOAEL 125 mg/kg/day	28 days

### Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

**SECTION 12: Ecological information****Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

**Chemical fate information**

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

**SECTION 13: Disposal considerations****13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

**EPA Hazardous Waste Number (RCRA):** D002 (Corrosive)

**SECTION 14: Transport Information**

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

**SECTION 15: Regulatory information****15.1. US Federal Regulations**

Contact 3M for more information.

**EPCRA 311/312 Hazard Classifications:****Physical Hazards**

Corrosive to metal

**Health Hazards**

Hazard Not Otherwise Classified (HNOC)

Respiratory or Skin Sensitization

Serious eye damage or eye irritation

Skin Corrosion or Irritation

**15.2. State Regulations**

Contact 3M for more information.

**15.3. Chemical Inventories**

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.



Contact 3M for more information.

#### 15.4. International Regulations

Contact 3M for more information.

**This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.**

### SECTION 16: Other information

#### NFPA Hazard Classification

**Health:** 3 **Flammability:** 1 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

<b>Document Group:</b>	23-9079-7	<b>Version Number:</b>	5.03
<b>Issue Date:</b>	03/10/23	<b>Supersedes Date:</b>	08/04/21

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

**3M USA SDSs are available at [www.3M.com](http://www.3M.com)**