



Safety Data Sheet

Copyright,2019,3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	20-7386-4	Version Number:	4.05
Issue Date:	05/21/19	Supersedes Date:	05/21/19

SECTION 1: Identification

1.1. Product identifier

3M™ Screen Printing UV Ink 9891 Blue Violet

Product Identification Numbers

75-3470-6914-0
7000056121

1.2. Recommended use and restrictions on use

Recommended use

Screen Printing Ink, Ink

1.3. Supplier's details

MANUFACTURER:	3M
DIVISION:	Commercial Solutions Division
ADDRESS:	3M Center, St. Paul, MN 55144-1000, USA
Telephone:	1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

2.1. Hazard classification

Serious Eye Damage/Irritation: Category 2A.
Skin Sensitizer: Category 1.
Reproductive Toxicity: Category 1B.
Carcinogenicity: Category 2.
Specific Target Organ Toxicity (repeated exposure): Category 1.

2.2. Label elements

Signal word

Danger

Symbols

Exclamation mark | Health Hazard |

Pictograms**Hazard Statements**

Causes serious eye irritation.
 May cause an allergic skin reaction.
 May damage fertility or the unborn child.
 Suspected of causing cancer.

Causes damage to organs through prolonged or repeated exposure:
 respiratory system |

Precautionary Statements**Prevention:**

Obtain special instructions before use.
 Do not handle until all safety precautions have been read and understood.
 Do not breathe dust/fume/gas/mist/vapors/spray.
 Wear protective gloves and eye/face protection.
 Do not eat, drink or smoke when using this product.
 Wash thoroughly after handling.
 Contaminated work clothing must not be allowed out of the workplace.

Response:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 If eye irritation persists: Get medical advice/attention.
 IF ON SKIN: Wash with plenty of soap and water.
 If skin irritation or rash occurs: Get medical advice/attention.
 Wash contaminated clothing before reuse.
 IF exposed or concerned: Get medical advice/attention.
 Get medical advice/attention if you feel unwell.

Storage:

Keep container tightly closed.
 Keep cool.
 Store locked up in a well-ventilated place.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

10% of the mixture consists of ingredients of unknown acute oral toxicity.
 10% of the mixture consists of ingredients of unknown acute dermal toxicity.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
PHENOXY ETHYL ACRYLATE	48145-04-6	30 - 40 Trade Secret *
VINYLCAPROLACTAM	2235-00-9	10 - 20 Trade Secret *
METHACRYLATE POLYMER	Trade Secret*	10 - 20 Trade Secret *

ALIPHATIC URETHANE ACRYLATE	Trade Secret*	7 - 13 Trade Secret *
1-BUTANONE, 2-(DIMETHYLAMINO)-1-[4-(4-MORPHOLINYL)PHENYL]-2-(PHENYLMETHYL)-	119313-12-1	1 - 5 Trade Secret *
1-PROPANONE, 2-METHYL-1-[4-(METHYLTHIO)PHENYL]-2-(4-MORPHOLINYL)-	71868-10-5	1 - 5 Trade Secret *
2-PHENOXYETHANOL	122-99-6	1 - 5 Trade Secret *
DIETHYLENE GLYCOL ETHYL ETHER ACRYLATE	7328-17-8	1 - 5 Trade Secret *
DIOXAZINE VIOLET	6358-30-1	1 - 5 Trade Secret *
SYNTHETIC AMORPHOUS SILICA, FUMED, CRYSTALLINE FREE	112945-52-5	1 - 5 Trade Secret *
.ALPHA.,.ALPHA.',.ALPHA."-1,2,3-PROPANETRIYLTRIS[POLYPROPYLENE GLYCOL ACRYLATE]	52408-84-1	0.1 - 1.0
ETHYLBENZENE	100-41-4	0.1 - 1.0 Trade Secret *
OCTAMETHYLCYCLOTETRASILOXANE	556-67-2	0.1 - 1.0 Trade Secret *
TRIMETHYLOLPROPANE ETHOXYLATE TRIACRYLATE	28961-43-5	< 1 Trade Secret *

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products**Substance**

Formaldehyde
Carbon monoxide
Carbon dioxide

Condition

During Combustion
During Combustion
During Combustion

5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (gloves, respirators, etc.) as required.

7.2. Conditions for safe storage including any incompatibilities

Keep cool. Protect from sunlight. Store away from heat. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
ETHYLBENZENE	100-41-4	ACGIH	TWA:20 ppm	A3: Confirmed animal

				carcin.
ETHYLBENZENE	100-41-4	OSHA	TWA:435 mg/m3(100 ppm)	
SILICA, AMORPHOUS	112945-52-5	OSHA	TWA concentration:0.8 mg/m3;TWA:20 millions of particles/cu. ft.	
VINYLCAPROLACTAM	2235-00-9	Manufacturer determined	TWA:0.1 ppm(0.57 mg/m3)	
OCTAMETHYLCYCLOTETRA SILOXANE	556-67-2	AIHA	TWA:10 ppm	

ACGIH : American Conference of Governmental Industrial Hygienists
 AIHA : American Industrial Hygiene Association
 CMRG : Chemical Manufacturer's Recommended Guidelines
 OSHA : United States Department of Labor - Occupational Safety and Health Administration
 TWA: Time-Weighted-Average
 STEL: Short Term Exposure Limit
 CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:
 Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:
 Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

General Physical Form: Liquid

Specific Physical Form:	Liquid
Odor, Color, Grade:	Blue color, acrylate odor
Odor threshold	<i>No Data Available</i>
pH	<i>Not Applicable</i>
Melting point	<i>Not Applicable</i>
Boiling Point	> 300 °F
Flash Point	> 200 °F [Test Method:Pensky-Martens Closed Cup]
Evaporation rate	< 1 [Ref Std:BUOAC=1]
Flammability (solid, gas)	Not Applicable
Flammable Limits(LEL)	<i>No Data Available</i>
Flammable Limits(UEL)	<i>No Data Available</i>
Vapor Pressure	< 1.2 mmHg [@ 20 °C]
Vapor Density	<i>No Data Available</i>
Density	Approximately 1.3 g/ml
Specific Gravity	Approximately 1.3 [Ref Std:WATER=1]
Solubility in Water	Negligible
Solubility- non-water	<i>No Data Available</i>
Partition coefficient: n-octanol/ water	<i>No Data Available</i>
Autoignition temperature	<i>No Data Available</i>
Decomposition temperature	<i>No Data Available</i>
Viscosity	<i>No Data Available</i>
Volatile Organic Compounds	7 g/l
Percent volatile	1 - 5 % weight
VOC Less H2O & Exempt Solvents	7 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization may occur. Upon loss of initiator or with exposure to heat.

10.4. Conditions to avoid

Sparks and/or flames

Heat

10.5. Incompatible materials

Strong oxidizing agents

10.6. Hazardous decomposition products

Substance

None known.

Condition

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient

classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion:

May be harmful if swallowed.

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

Additional Health Effects:

Prolonged or repeated exposure may cause target organ effects:

Respiratory Effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish colored skin (cyanosis), sputum production, changes in lung function tests, and/or respiratory failure.

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Ingredient	CAS No.	Class Description	Regulation
ETHYLBENZENE	100-41-4	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE 2,000 - 5,000 mg/kg
PHENOXY ETHYL ACRYLATE	Dermal	Rat	LD50 > 2,000 mg/kg
PHENOXY ETHYL ACRYLATE	Ingestion	Rat	LD50 > 5,000 mg/kg

METHACRYLATE POLYMER	Dermal		LD50 estimated to be > 5,000 mg/kg
METHACRYLATE POLYMER	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
VINYLCAPROLACTAM	Dermal	Rabbit	LD50 1,700 mg/kg
VINYLCAPROLACTAM	Ingestion	Rat	LD50 1,049 mg/kg
DIOXAZINE VIOLET	Dermal	Rat	LD50 > 5,000 mg/kg
DIOXAZINE VIOLET	Ingestion	Rat	LD50 > 5,000 mg/kg
SYNTHETIC AMORPHOUS SILICA, FUMED, CRYSTALLINE FREE	Dermal	Rabbit	LD50 > 5,000 mg/kg
SYNTHETIC AMORPHOUS SILICA, FUMED, CRYSTALLINE FREE	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
SYNTHETIC AMORPHOUS SILICA, FUMED, CRYSTALLINE FREE	Ingestion	Rat	LD50 > 5,110 mg/kg
DIETHYLENE GLYCOL ETHYL ETHER ACRYLATE	Dermal		LD50 estimated to be 1,000 - 2,000 mg/kg
DIETHYLENE GLYCOL ETHYL ETHER ACRYLATE	Ingestion	Rat	LD50 1,860 mg/kg
1-BUTANONE, 2-(DIMETHYLAMINO)-1-[4-(4-MORPHOLINYL)PHENYL]-2-(PHENYLMETHYL)-	Dermal	Rat	LD50 > 2,000 mg/kg
1-BUTANONE, 2-(DIMETHYLAMINO)-1-[4-(4-MORPHOLINYL)PHENYL]-2-(PHENYLMETHYL)-	Ingestion	Rat	LD50 > 5,000 mg/kg
1-PROPANONE, 2-METHYL-1-[4-(METHYLTHIO)PHENYL]-2-(4-MORPHOLINYL)-	Dermal	Rat	LD50 > 2,000 mg/kg
1-PROPANONE, 2-METHYL-1-[4-(METHYLTHIO)PHENYL]-2-(4-MORPHOLINYL)-	Ingestion	Rat	LD50 967 mg/kg
2-PHENOXYETHANOL	Dermal	Rabbit	LD50 > 2,000 mg/kg
2-PHENOXYETHANOL	Inhalation-Dust/Mist	Rat	LC50 > 1.5 mg/l
2-PHENOXYETHANOL	Ingestion	Rat	LD50 1,260 mg/kg
TRIMETHYLOLPROPANE ETHOXYLATE TRIACRYLATE	Dermal	Rabbit	LD50 > 13,000 mg/kg
TRIMETHYLOLPROPANE ETHOXYLATE TRIACRYLATE	Ingestion	Rat	LD50 > 2,000 mg/kg
OCTAMETHYLCYCLOTETRASIOXANE	Dermal	Rat	LD50 > 2,400 mg/kg
OCTAMETHYLCYCLOTETRASIOXANE	Inhalation-Dust/Mist (4 hours)	Rat	LC50 36 mg/l
OCTAMETHYLCYCLOTETRASIOXANE	Ingestion	Rat	LD50 > 5,000 mg/kg
ETHYLBENZENE	Dermal	Rabbit	LD50 15,433 mg/kg
ETHYLBENZENE	Inhalation-Vapor (4 hours)	Rat	LC50 17.4 mg/l
ETHYLBENZENE	Ingestion	Rat	LD50 4,769 mg/kg
.ALPHA.,.ALPHA.',.ALPHA."-1,2,3-PROPANETRIYLTRIS[POLYPROPYLENE GLYCOL ACRYLATE]	Dermal	Rabbit	LD50 > 2,000 mg/kg
.ALPHA.,.ALPHA.',.ALPHA."-1,2,3-PROPANETRIYLTRIS[POLYPROPYLENE GLYCOL ACRYLATE]	Ingestion	Rat	LD50 > 2,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
PHENOXY ETHYL ACRYLATE	Rabbit	No significant irritation
VINYLCAPROLACTAM	Rabbit	Minimal irritation
DIOXAZINE VIOLET	Rabbit	Minimal irritation
SYNTHETIC AMORPHOUS SILICA, FUMED, CRYSTALLINE FREE	Rabbit	No significant irritation
DIETHYLENE GLYCOL ETHYL ETHER ACRYLATE	Rabbit	Irritant
1-BUTANONE, 2-(DIMETHYLAMINO)-1-[4-(4-MORPHOLINYL)PHENYL]-2-(PHENYLMETHYL)-	Rabbit	No significant irritation
1-PROPANONE, 2-METHYL-1-[4-(METHYLTHIO)PHENYL]-2-(4-MORPHOLINYL)-	Rabbit	No significant irritation
2-PHENOXYETHANOL	Rabbit	No significant irritation
TRIMETHYLOLPROPANE ETHOXYLATE TRIACRYLATE	Rabbit	Minimal irritation
OCTAMETHYLCYCLOTETRASIOXANE	Rabbit	Minimal irritation
ETHYLBENZENE	Rabbit	Mild irritant
.ALPHA.,.ALPHA.',.ALPHA."-1,2,3-	Rabbit	Minimal irritation

PROPANETRIYLTRIS[POLYPROPYLENE GLYCOL ACRYLATE]		
---	--	--

Serious Eye Damage/Irritation

Name	Species	Value
PHENOXY ETHYL ACRYLATE	Rabbit	No significant irritation
VINYLCAPROLACTAM	Rabbit	Severe irritant
DIOXAZINE VIOLET	Rabbit	Mild irritant
SYNTHETIC AMORPHOUS SILICA, FUMED, CRYSTALLINE FREE	Rabbit	No significant irritation
DIETHYLENE GLYCOL ETHYL ETHER ACRYLATE	Rabbit	Severe irritant
1-BUTANONE, 2-(DIMETHYLAMINO)-1-[4-(4-MORPHOLINYL)PHENYL]-2-(PHENYLMETHYL)-	Rabbit	No significant irritation
1-PROPANONE, 2-METHYL-1-[4-(METHYLTHIO)PHENYL]-2-(4-MORPHOLINYL)-	Rabbit	No significant irritation
2-PHENOXYETHANOL	Rabbit	Corrosive
TRIMETHYLOLPROPANE ETHOXYLATE TRIACRYLATE	Rabbit	Severe irritant
OCTAMETHYLCYCLOTETRASILOXANE	Rabbit	No significant irritation
ETHYLBENZENE	Rabbit	Moderate irritant
.ALPHA.,.ALPHA.',.ALPHA."-1,2,3-PROPANETRIYLTRIS[POLYPROPYLENE GLYCOL ACRYLATE]	Rabbit	Severe irritant

Skin Sensitization

Name	Species	Value
PHENOXY ETHYL ACRYLATE	Guinea pig	Sensitizing
VINYLCAPROLACTAM	Mouse	Sensitizing
SYNTHETIC AMORPHOUS SILICA, FUMED, CRYSTALLINE FREE	Human and animal	Not classified
DIETHYLENE GLYCOL ETHYL ETHER ACRYLATE	Guinea pig	Sensitizing
1-BUTANONE, 2-(DIMETHYLAMINO)-1-[4-(4-MORPHOLINYL)PHENYL]-2-(PHENYLMETHYL)-	Guinea pig	Not classified
2-PHENOXYETHANOL	Guinea pig	Not classified
TRIMETHYLOLPROPANE ETHOXYLATE TRIACRYLATE	Guinea pig	Sensitizing
OCTAMETHYLCYCLOTETRASILOXANE	Human and animal	Not classified
ETHYLBENZENE	Human	Not classified
.ALPHA.,.ALPHA.',.ALPHA."-1,2,3-PROPANETRIYLTRIS[POLYPROPYLENE GLYCOL ACRYLATE]	Mouse	Sensitizing

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
VINYLCAPROLACTAM	In Vitro	Not mutagenic
SYNTHETIC AMORPHOUS SILICA, FUMED, CRYSTALLINE FREE	In Vitro	Not mutagenic
1-BUTANONE, 2-(DIMETHYLAMINO)-1-[4-(4-MORPHOLINYL)PHENYL]-2-(PHENYLMETHYL)-	In Vitro	Not mutagenic
1-BUTANONE, 2-(DIMETHYLAMINO)-1-[4-(4-MORPHOLINYL)PHENYL]-2-(PHENYLMETHYL)-	In vivo	Not mutagenic
OCTAMETHYLCYCLOTETRASILOXANE	In Vitro	Some positive data exist, but the data are not sufficient for classification
ETHYLBENZENE	In vivo	Not mutagenic
ETHYLBENZENE	In Vitro	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
SYNTHETIC AMORPHOUS SILICA, FUMED, CRYSTALLINE FREE	Not Specified	Mouse	Some positive data exist, but the data are not sufficient for classification
ETHYLBENZENE	Inhalation	Multiple animal species	Carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
PHENOXY ETHYL ACRYLATE	Ingestion	Not classified for male reproduction	Rat	NOAEL 800 mg/kg/day	43 days
PHENOXY ETHYL ACRYLATE	Ingestion	Toxic to female reproduction	Rat	NOAEL 300 mg/kg/day	prematuring into lactation
PHENOXY ETHYL ACRYLATE	Ingestion	Toxic to development	Rat	NOAEL 300 mg/kg/day	prematuring into lactation
SYNTHETIC AMORPHOUS SILICA, FUMED, CRYSTALLINE FREE	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
SYNTHETIC AMORPHOUS SILICA, FUMED, CRYSTALLINE FREE	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
SYNTHETIC AMORPHOUS SILICA, FUMED, CRYSTALLINE FREE	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
1-BUTANONE, 2-(DIMETHYLAMINO)-1-[4-(4-MORPHOLINYLPHENYL)-2-(PHENYLMETHYL)-	Ingestion	Not classified for female reproduction	Rat	NOAEL 300 mg/kg/day	1 generation
1-BUTANONE, 2-(DIMETHYLAMINO)-1-[4-(4-MORPHOLINYLPHENYL)-2-(PHENYLMETHYL)-	Ingestion	Not classified for male reproduction	Rat	NOAEL 300 mg/kg/day	1 generation
1-BUTANONE, 2-(DIMETHYLAMINO)-1-[4-(4-MORPHOLINYLPHENYL)-2-(PHENYLMETHYL)-	Ingestion	Toxic to development	Rat	NOAEL 30 mg/kg/day	1 generation
1-PROPANONE, 2-METHYL-1-[4-(METHYLTHIO)PHENYL]-2-(4-MORPHOLINYLPHENYL)-	Ingestion	Toxic to female reproduction	Rat	LOAEL 40 mg/kg/day	1 generation
1-PROPANONE, 2-METHYL-1-[4-(METHYLTHIO)PHENYL]-2-(4-MORPHOLINYLPHENYL)-	Ingestion	Toxic to development	Rat	LOAEL 40 mg/kg/day	1 generation
OCTAMETHYLCYCLOTETRASIOXANE	Inhalation	Not classified for male reproduction	Rat	NOAEL 8.5 mg/l	2 generation
OCTAMETHYLCYCLOTETRASIOXANE	Ingestion	Toxic to female reproduction	Rabbit	NOAEL 50 mg/kg/day	during organogenesis
OCTAMETHYLCYCLOTETRASIOXANE	Inhalation	Toxic to female reproduction	Rat	NOAEL 3.6 mg/l	2 generation
ETHYLBENZENE	Inhalation	Not classified for development	Rat	NOAEL 4.3 mg/l	prematuring & during gestation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
VINYLCAPROLACTAM	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL Not available	
2-PHENOXYETHANOL	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
ETHYLBENZENE	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
ETHYLBENZENE	Inhalation	respiratory irritation	Some positive data exist, but the	Human	NOAEL Not	

			data are not sufficient for classification	and animal	available	
ETHYLBENZENE	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
VINYLCAPROLACTAM	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	NOAEL 0.001 mg/l	28 days
VINYLCAPROLACTAM	Inhalation	blood liver kidney and/or bladder eyes	Not classified	Rat	NOAEL 0.18 mg/l	90 days
VINYLCAPROLACTAM	Ingestion	liver	Not classified	Rat	NOAEL 260 mg/kg/day	3 months
DIOXAZINE VIOLET	Ingestion	blood	Not classified	Rat	NOAEL 500 mg/kg/day	6 weeks
SYNTHETIC AMORPHOUS SILICA, FUMED, CRYSTALLINE FREE	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
1-BUTANONE, 2-(DIMETHYLAMINO)-1-[4-(4-MORPHOLINYL)PHENYL]-2-(PHENYLMETHYL)-	Ingestion	endocrine system hematopoietic system liver kidney and/or bladder	Not classified	Rat	NOAEL 500 mg/kg/day	28 days
1-PROPANONE, 2-METHYL-1-[4-(METHYLTHIO)PHENYL]-2-(4-MORPHOLINYL)-	Ingestion	peripheral nervous system eyes	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 75 mg/kg/day	90 days
OCTAMETHYLCYCLOTETRAILOXANE	Dermal	hematopoietic system	Not classified	Rabbit	NOAEL 960 mg/kg/day	3 weeks
OCTAMETHYLCYCLOTETRAILOXANE	Inhalation	liver	Not classified	Rat	NOAEL 8.5 mg/l	13 weeks
OCTAMETHYLCYCLOTETRAILOXANE	Inhalation	endocrine system immune system kidney and/or bladder	Not classified	Rat	NOAEL 8.5 mg/l	2 generation
OCTAMETHYLCYCLOTETRAILOXANE	Inhalation	hematopoietic system	Not classified	Rat	NOAEL 8.5 mg/l	13 weeks
OCTAMETHYLCYCLOTETRAILOXANE	Ingestion	liver	Not classified	Rat	NOAEL 1,600 mg/kg/day	2 weeks
ETHYLBENZENE	Inhalation	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1.1 mg/l	2 years
ETHYLBENZENE	Inhalation	liver	Some positive data exist, but the data are not sufficient for classification	Mouse	NOAEL 1.1 mg/l	103 weeks
ETHYLBENZENE	Inhalation	hematopoietic system	Not classified	Rat	NOAEL 3.4 mg/l	28 days
ETHYLBENZENE	Inhalation	auditory system	Not classified	Rat	NOAEL 2.4 mg/l	5 days
ETHYLBENZENE	Inhalation	endocrine system	Not classified	Mouse	NOAEL 3.3 mg/l	103 weeks
ETHYLBENZENE	Inhalation	gastrointestinal tract	Not classified	Rat	NOAEL 3.3 mg/l	2 years
ETHYLBENZENE	Inhalation	bone, teeth, nails, and/or hair muscles	Not classified	Multiple animal species	NOAEL 4.2 mg/l	90 days
ETHYLBENZENE	Inhalation	heart immune system respiratory system	Not classified	Multiple animal species	NOAEL 3.3 mg/l	2 years

ETHYLBENZENE	Ingestion	liver kidney and/or bladder	Not classified	Rat	NOAEL 680 mg/kg/day	6 months
--------------	-----------	-------------------------------	----------------	-----	---------------------	----------

Aspiration Hazard

Name	Value
ETHYLBENZENE	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): Not regulated

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:

Physical Hazards

Not applicable

Health Hazards

Carcinogenicity

Reproductive toxicity

Respiratory or Skin Sensitization
Serious eye damage or eye irritation
Specific target organ toxicity (single or repeated exposure)

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

<u>Ingredient</u>	<u>C.A.S. No</u>	<u>% by Wt</u>
PHENOXY ETHYL ACRYLATE (GLYCOL ETHERS)	48145-04-6	30 - 40
DIETHYLENE GLYCOL ETHYL ETHER ACRYLATE (GLYCOL ETHERS)	7328-17-8	1 - 5
2-PHENOXYETHANOL (GLYCOL ETHERS)	122-99-6	1 - 5
ETHYLBENZENE	100-41-4	Trade Secret 0.1 - 1.0

This material contains a chemical which requires export notification under TSCA Section 12[b]:

<u>Ingredient (Category if applicable)</u>	<u>C.A.S. No</u>	<u>Regulation</u>	<u>Status</u>
OCTAMETHYLCYCLOTETRASILOXANE	556-67-2	Toxic Substances Control Act (TSCA) 4 Test Rule Chemicals	Applicable

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 2 **Flammability:** 1 **Instability:** 1 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document Group:	20-7386-4	Version Number:	4.05
Issue Date:	05/21/19	Supersedes Date:	05/21/19

Reason for Reissue

Conversion to GHS format SDS.

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY

OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

3M USA SDSs are available at www.3M.com