



Safety Data Sheet

Copyright, 2023, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group: 20-4172-1
Issue Date: 05/08/23

Version Number: 7.00
Supersedes Date: 10/22/18

SECTION 1: Identification

1.1. Product identifier

3M™ Classic Roofing Granules, Green - 3700W (Wausau, WI)

Product Identification Numbers

98-0111-1217-8

7010399982

1.2. Recommended use and restrictions on use

Recommended use

Industrial use

1.3. Supplier's details

MANUFACTURER: 3M
DIVISION: Industrial Mineral Products
ADDRESS: 3M Center, St. Paul, MN 55144-1000, USA
Telephone: 1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

2.1. Hazard classification

Serious Eye Damage/Irritation: Category 1.

Carcinogenicity: Category 1A.

Specific Target Organ Toxicity (repeated exposure): Category 1.

2.2. Label elements

Signal word

Danger

Symbols

Corrosion | Health Hazard |

Pictograms

**Hazard Statements**

Causes serious eye damage.

May cause cancer.

Causes damage to organs through prolonged or repeated exposure:
respiratory system |

Precautionary Statements**Prevention:**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wear protective gloves and eye/face protection.

Wear protective gloves.

Do not eat, drink or smoke when using this product.

Wash thoroughly after handling.

Response:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Immediately call a POISON CENTER or doctor/physician.

Storage:

Store locked up.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

43% of the mixture consists of ingredients of unknown acute oral toxicity.

43% of the mixture consists of ingredients of unknown acute dermal toxicity.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
Feldspar-Group Minerals	68476-25-5	25 - 60 Trade Secret *
Quartz Silica	14808-60-7	10 - 40 Trade Secret *
Illite	12173-60-3	< 25 Trade Secret *
Mica-Group Minerals	12001-26-2	< 25 Trade Secret *
Chlorite (Mineral)	1318-59-8	< 10 Trade Secret *
Pyroxene-Group Minerals	12174-37-7	< 10 Trade Secret *
Ceramic	66402-68-4	0.5 - 5 Trade Secret *
Dolomite	16389-88-1	< 5 Trade Secret *
Hematite	1317-60-8	< 5 Trade Secret *
Ilmenite	12168-52-4	< 5 Trade Secret *
Magnetite	1309-38-2	< 5 Trade Secret *
Calcite	13397-26-7	< 2 Trade Secret *
Epidote	1318-49-6	< 2 Trade Secret *

Sericite	12174-53-7	< 2 Trade Secret *
Chromium(III) Oxide (Cr2O3)	1308-38-9	< 1 Trade Secret *
Oil	64742-52-5	< 0.5 Trade Secret *
Titanium Dioxide	13463-67-7	< 0.5 Trade Secret *

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Wash with soap and water. If signs/symptoms develop, get medical attention.

Eye Contact:

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Serious damage to the eyes (corneal cloudiness, severe pain, tearing, ulcerations, and significantly impaired or loss of vision). Target organ effects following prolonged or repeated exposure. See Section 11 for additional details.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Non-combustible. Use a fire fighting agent suitable for surrounding fire.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Not applicable.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Use wet sweeping compound or water to avoid dusting. Sweep up.

Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not breathe dust/fume/gas/mist/vapors/spray. Granules are not respirable. Dust generated during handling may contain respirable material. 3M does not recommend material handling methods that could damage the coating or base mineral. In particular, roofing granules should not be conveyed pneumatically, via screw conveyors, or used as a sand blasting media. These uses can cause coating and base mineral attrition which may lead to increased levels of dust generation. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Use personal protective equipment (gloves, respirators, etc.) as required. Solids can generate static electricity charges when transferred and in mixing operations sufficient to be an ignition source. Evaluate the need for precautions, such as grounding and bonding, low energy transfer of material (e.g. low speed, short distance), or inert atmospheres. Do not handle until all safety precautions have been read and understood.

7.2. Conditions for safe storage including any incompatibilities

No special storage requirements.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Mica-Group Minerals	12001-26-2	ACGIH	TWA(respirable fraction):0.1 mg/m3	
Mica-Group Minerals	12001-26-2	OSHA	TWA:20 millions of particles/cu. ft.	
CHROMIUM (II) COMPOUNDS	1308-38-9	OSHA	TWA(as Cr):0.5 mg/m3	
CHROMIUM (III) COMPOUNDS	1308-38-9	ACGIH	TWA(as Cr(III), inhalable fraction):0.003 mg/m3;TWA(as Cr):0.5 mg/m3	A4: Not class. as human carcin
CHROMIUM (III) COMPOUNDS	1308-38-9	OSHA	TWA(as Cr):0.5 mg/m3	
Chromium(3+), soluble salts	1308-38-9	ACGIH	TWA(as Cr(III), inhalable fraction):0.003 mg/m3	A4: Not class. as human carcin, Dermal/Respiratory Sensitizer
Titanium Dioxide	13463-67-7	ACGIH	TWA(Respirable nanoscale particles):0.2 mg/m3;TWA(Respirable finescale particles):2.5 mg/m3	A3: Confirmed animal carcin.
Titanium Dioxide	13463-67-7	OSHA	TWA(as total dust):15 mg/m3	
Quartz Silica	14808-60-7	ACGIH	TWA(respirable fraction):0.025 mg/m3	A2: Suspected human carcin.
Quartz Silica	14808-60-7	OSHA	TWA Table Z-1(respirable):0.05 mg/m3;TWA Table Z-3(respirable):0.1 mg/m3;TWA	

			concentration(respirable):0.1 mg/m ³ (2.4 millions of particles/cu. ft.)	
DUST, INERT OR NUISANCE	16389-88-1	OSHA	TWA(as total dust):15 mg/m ³ ;TWA(as total dust):50 millions of particles/cu. ft.(15 mg/m ³);TWA(respirable fraction):5 mg/m ³ ;TWA(respirable fraction):15 millions of particles/cu. ft.(5 mg/m ³)	
Particles (insoluble or poorly soluble) not otherwise specified, inhalable particles	16389-88-1	ACGIH	TWA(inhalable particulates):10 mg/m ³	
Particles (insoluble or poorly soluble) not otherwise specified, respirable particles	16389-88-1	ACGIH	TWA(respirable particles):3 mg/m ³	
Paraffin oil	64742-52-5	OSHA	TWA(as mist):5 mg/m ³	
PETROLEUM DISTILLATES	64742-52-5	OSHA	TWA:2000 mg/m ³ (500 ppm)	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Provide local exhaust ventilation at transfer points. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full Face Shield

Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

When only incidental contact is anticipated, alternative glove material(s) may be used. If contact with the glove does occur, remove immediately and replace with a set of new gloves. For incidental contact, gloves made of the following material(s) may be used:Nitrile Rubber

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state

Solid

Color

Green

Specific Physical Form:

Granules

Odor

Oily

Odor threshold

No Data Available

pH

No Data Available

Melting point

No Data Available

Boiling Point

No Data Available

Flash Point

No flash point

Evaporation rate

No Data Available

Flammability (solid, gas)

Not Classified

Flammable Limits(LEL)

No Data Available

Flammable Limits(UEL)

No Data Available

Vapor Pressure

No Data Available

Vapor Density

No Data Available

Specific Gravity

2.60 - 2.90 [Ref Std: WATER=1]

Solubility In Water

No Data Available

Solubility- non-water

No Data Available

Partition coefficient: n-octanol/ water

No Data Available

Autoignition temperature

No Data Available

Decomposition temperature

No Data Available

Viscosity

No Data Available

Molecular weight

No Data Available

SECTION 10: Stability and reactivity

10.1. Reactivity

This material is considered to be non reactive under normal use conditions.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

None known.

10.6. Hazardous decomposition products

Substance

Condition

None known.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

Skin Contact:

May be harmful in contact with skin.

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Mechanical Skin irritation: Signs/symptoms may include abrasion, redness, pain, and itching.

Eye Contact:

Corrosive (Eye Burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

Mechanical eye irritation: Signs/symptoms may include pain, redness, tearing and corneal abrasion.

Ingestion:

May be harmful if swallowed.

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Additional Health Effects:

Prolonged or repeated exposure may cause target organ effects:

Silicosis: Signs/symptoms may include breathlessness, weakness, chest pain, persistent cough, increased amounts of sputum, and heart disease.

Pneumoconiosis: Sign/symptoms may include persistent cough, breathlessness, chest pain, increased amounts of sputum, and changes in lung function tests.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Ingredient	CAS No.	Class Description	Regulation
Silica, Crystalline (Respirable Size)	14808-60-7	Known To Be Human Carcinogen.	National Toxicology Program Carcinogens
Silica dust, crystalline, in the form of quartz or cristobalite	14808-60-7	Grp. 1: Carcinogenic to humans	International Agency for Research on Cancer
Titanium dioxide	13463-67-7	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >2,000 - =5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >2,000 - =5,000 mg/kg
Feldspar-Group Minerals	Dermal		LD50 estimated to be 2,000 - 5,000 mg/kg
Feldspar-Group Minerals	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
Quartz Silica	Dermal		LD50 estimated to be > 5,000 mg/kg
Quartz Silica	Ingestion		LD50 estimated to be > 5,000 mg/kg
Mica-Group Minerals	Dermal		LD50 estimated to be > 5,000 mg/kg
Mica-Group Minerals	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
Chlorite (Mineral)	Dermal		LD50 estimated to be > 5,000 mg/kg
Chlorite (Mineral)	Ingestion		LD50 estimated to be > 5,000 mg/kg
Dolomite	Dermal		LD50 estimated to be 2,000 - 5,000 mg/kg
Hematite	Dermal		LD50 estimated to be > 5,000 mg/kg
Magnetite	Dermal		LD50 estimated to be > 5,000 mg/kg
Dolomite	Ingestion	Rat	LD50 > 2,000 mg/kg
Hematite	Ingestion	Rat	LD50 5,500 mg/kg
Magnetite	Ingestion	Rat	LD50 > 10,000 mg/kg
Ceramic	Dermal		LD50 estimated to be > 5,000 mg/kg
Ceramic	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
Calcite	Dermal	Rat	LD50 > 2,000 mg/kg
Calcite	Inhalation-Dust/Mist (4 hours)	Rat	LC50 3 mg/l
Calcite	Ingestion	Rat	LD50 6,450 mg/kg
Chromium(III) Oxide (Cr2O3)	Dermal	Professional judgement	LD50 estimated to be > 5,000 mg/kg
Chromium(III) Oxide (Cr2O3)	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 5.41 mg/l
Chromium(III) Oxide (Cr2O3)	Ingestion	Rat	LD50 > 5,000 mg/kg
Oil	Dermal	Rabbit	LD50 > 2,000 mg/kg
Oil	Ingestion	Rat	LD50 > 5,000 mg/kg
Titanium Dioxide	Dermal	Rabbit	LD50 > 10,000 mg/kg
Titanium Dioxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 6.82 mg/l
Titanium Dioxide	Ingestion	Rat	LD50 > 10,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Feldspar-Group Minerals	Professional judgement	No significant irritation
Quartz Silica	Professional judgement	No significant irritation
Chlorite (Mineral)	Professional judgement	No significant irritation

	nt	
Dolomite	Professional judgement	No significant irritation
Magnetite	Rabbit	No significant irritation
Ceramic	Rabbit	No significant irritation
Calcite	Rabbit	No significant irritation
Chromium(III) Oxide (Cr2O3)	Rabbit	No significant irritation
Oil	Rabbit	Minimal irritation
Titanium Dioxide	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Chlorite (Mineral)	Professional judgement	No significant irritation
Dolomite	Professional judgement	No significant irritation
Ceramic	Rabbit	Mild irritant
Calcite	Rabbit	No significant irritation
Chromium(III) Oxide (Cr2O3)	Rabbit	No significant irritation
Oil	Rabbit	Mild irritant
Titanium Dioxide	Rabbit	No significant irritation

Skin Sensitization

Name	Species	Value
Chromium(III) Oxide (Cr2O3)	similar compounds	Not classified
Oil	Guinea pig	Not classified
Titanium Dioxide	Human and animal	Not classified

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Quartz Silica	In Vitro	Some positive data exist, but the data are not sufficient for classification
Quartz Silica	In vivo	Some positive data exist, but the data are not sufficient for classification
Magnetite	In Vitro	Not mutagenic
Ceramic	In Vitro	Some positive data exist, but the data are not sufficient for classification
Chromium(III) Oxide (Cr2O3)	In vivo	Not mutagenic
Chromium(III) Oxide (Cr2O3)	In Vitro	Some positive data exist, but the data are not sufficient for classification
Titanium Dioxide	In Vitro	Not mutagenic
Titanium Dioxide	In vivo	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Quartz Silica	Inhalation	Human and	Carcinogenic

		animal	
Ceramic	Inhalation	Multiple animal species	Some positive data exist, but the data are not sufficient for classification
Chromium(III) Oxide (Cr2O3)	Ingestion	Rat	Not carcinogenic
Oil	Ingestion	Rat	Not carcinogenic
Oil	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Titanium Dioxide	Ingestion	Multiple animal species	Not carcinogenic
Titanium Dioxide	Inhalation	Rat	Carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
Calcite	Ingestion	Not classified for development	Rat	NOAEL 625 mg/kg/day	premating & during gestation
Chromium(III) Oxide (Cr2O3)	Ingestion	Not classified for female reproduction	Rat	NOAEL 2,000 mg/kg/day	90 days
Chromium(III) Oxide (Cr2O3)	Ingestion	Not classified for male reproduction	Rat	NOAEL 2,000 mg/kg/day	90 days
Chromium(III) Oxide (Cr2O3)	Ingestion	Not classified for development	Rat	NOAEL 2,000 mg/kg/day	90 days

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Calcite	Inhalation	respiratory system	Not classified	Rat	NOAEL 0.812 mg/l	90 minutes
Chromium(III) Oxide (Cr2O3)	Inhalation	respiratory system	Not classified	Rat	NOAEL 40 mg	
Oil	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Quartz Silica	Inhalation	silicosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
Mica-Group Minerals	Inhalation	pneumoconiosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
Magnetite	Inhalation	pneumoconiosis	Not classified	Human	NOAEL Not available	occupational exposure
Ceramic	Inhalation	pulmonary fibrosis	Not classified	Multiple animal species	NOAEL not available	
Ceramic	Inhalation	respiratory system	Not classified	Human	NOAEL not available	occupational exposure
Calcite	Inhalation	respiratory system	Not classified	Human	NOAEL Not available	occupational exposure
Chromium(III) Oxide (Cr2O3)	Inhalation	immune system respiratory system hematopoietic system liver kidney and/or bladder	Not classified	Rat	NOAEL 44 mg/m3	90 days
Titanium Dioxide	Inhalation	respiratory system	Some positive data exist, but the	Rat	LOAEL 0.01	2 years

			data are not sufficient for classification		mg/l	
Titanium Dioxide	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information**Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations**13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility.

EPA Hazardous Waste Number (RCRA): Not regulated

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information**15.1. US Federal Regulations**

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:**Physical Hazards**

Not applicable

Health Hazards

Carcinogenicity

Serious eye damage or eye irritation

Specific target organ toxicity (single or repeated exposure)

15.2. State Regulations

Contact 3M for more information.

California Proposition 65

<u>Ingredient</u>	<u>C.A.S. No.</u>	<u>Listing</u>
Silica, crystalline (airborne particles of respirable size)	None	Carcinogen
Carbon black (airborne, unbound particles of respirable size [= 10 micrometers])	1333-86-4	Carcinogen
Cobalt metal powder	None	Carcinogen
Arsenic	7440-38-2	Carcinogen
CHROMIUM (HEXAVALENT COMPOUNDS)	None	Carcinogen
Lead	7439-92-1	Female reproductive toxin
Lead	7439-92-1	Male reproductive toxin
Lead	7439-92-1	Developmental Toxin
Titanium dioxide (airborne, unbound particles of respirable size)	13463-67-7	Carcinogen
Cadmium and cadmium compounds	None	Carcinogen
Titanium dioxide (airborne, unbound particles of respirable size)	13463-67-7	Carcinogen

15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 3 **Flammability:** 0 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document Group:	20-4172-1	Version Number:	7.00
Issue Date:	05/08/23	Supersedes Date:	10/22/18

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com

