



## Safety Data Sheet

Copyright,2020, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document Group:</b>	41-0602-7	<b>Version Number:</b>	1.03
<b>Issue Date:</b>	09/12/20	<b>Supersedes Date:</b>	01/27/20

### SECTION 1: Identification

#### 1.1. Product identifier

Scotchgard(TM) Fabric Water Shield 4106-PF

#### Product Identification Numbers

ID Number	UPC	ID Number	UPC
70-0070-4903-7	006-38060-66239-7	70-0070-4991-2	006-38060-85057-2
70-0070-5071-2	06-38060-85172-2	70-0070-5261-9	006-38060-65784-3
70-0070-5300-5	006-38060-65783-6		

7100221262, 7100222699, 7100224647, 7100229461, 7100229946

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Water repellent

#### 1.3. Supplier's details

**MANUFACTURER:** 3M  
**DIVISION:** Home Care Division  
**ADDRESS:** 3M Center, St. Paul, MN 55144-1000, USA  
**Telephone:** 1-888-3M HELPS (1-888-364-3577)

#### 1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

### SECTION 2: Hazard identification

#### 2.1. Hazard classification

Flammable Aerosol: Category 1.  
 Gas Under Pressure: Liquefied gas.  
 Simple Asphyxiant.  
 Specific Target Organ Toxicity (single exposure): Category 1.  
 Specific Target Organ Toxicity (single exposure): Category 3.

#### 2.2. Label elements

##### Signal word

Danger

**Symbols**

Flame | Gas cylinder | Exclamation mark | Health Hazard |

**Pictograms**



**Hazard Statements**

Extremely flammable aerosol.  
Contains gas under pressure; may explode if heated.

May cause drowsiness or dizziness.  
May displace oxygen and cause rapid suffocation.

Causes damage to organs:  
cardiovascular system |

**Precautionary Statements**

**General:**

Keep out of reach of children.

**Prevention:**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
Do not spray on an open flame or other ignition source.  
Pressurized container: Do not pierce or burn, even after use.  
Do not breathe dust/fume/gas/mist/vapors/spray.  
Use only outdoors or in a well-ventilated area.  
Do not eat, drink or smoke when using this product.  
Wash thoroughly after handling.

**Response:**

IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
IF exposed: Call a POISON CENTER or doctor/physician.  
Specific treatment (see Notes to Physician on this label).

**Storage:**

Protect from sunlight. Do not expose to temperatures exceeding 50C/122F.  
Store in a well-ventilated place.  
Store locked up.

**Disposal:**

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

**Notes to Physician:**

Exposure may increase myocardial irritability. Do not administer sympathomimetic drugs unless absolutely necessary.

**Supplemental Information:**

Intentional concentration and inhalation may be harmful or fatal.

25% of the mixture consists of ingredients of unknown acute oral toxicity.  
25% of the mixture consists of ingredients of unknown acute dermal toxicity.

**SECTION 3: Composition/information on ingredients**

Ingredient	C.A.S. No.	% by Wt
Hydrotreated Light Petroleum Distillates	64742-47-8	60 - 70 Trade Secret *
Petroleum Gases, Liquified, Sweetened	68476-86-8	23 - 27 Trade Secret *
Silicone Mixture	Trade Secret*	2 - 6
Proprietary Resin	Trade Secret*	1 - 4

\*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

**SECTION 4: First aid measures**

**4.1. Description of first aid measures**

**Inhalation:**

Remove person to fresh air. Get medical attention.

**Skin Contact:**

Wash with soap and water. If signs/symptoms develop, get medical attention.

**Eye Contact:**

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

**If Swallowed:**

Rinse mouth. If you feel unwell, get medical attention.

**4.2. Most important symptoms and effects, both acute and delayed**

See Section 11.1. Information on toxicological effects.

**4.3. Indication of any immediate medical attention and special treatment required**

Exposure may increase myocardial irritability. Do not administer sympathomimetic drugs unless absolutely necessary.

**SECTION 5: Fire-fighting measures**

**5.1. Suitable extinguishing media**

Use a fire fighting agent suitable for the surrounding fire.

**5.2. Special hazards arising from the substance or mixture**

Closed containers exposed to heat from fire may build pressure and explode.

**Hazardous Decomposition or By-Products**

Substance

Formaldehyde  
 Carbon monoxide  
 Carbon dioxide  
 Toxic Vapor, Gas, Particulate

Condition

During Combustion  
 During Combustion  
 During Combustion  
 During Combustion

**5.3. Special protective actions for fire-fighters**

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

If possible, seal leaking container. Place leaking containers in a well-ventilated area, preferably an operating exhaust hood, or if necessary outdoors on an impermeable surface until appropriate packaging for the leaking container or its contents is available. Contain spill. Cover spill area with a fire-extinguishing foam. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Do not use in a confined area with minimal air exchange. Keep out of reach of children. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

### 7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50C/122F. Store away from heat. Store away from acids. Store away from oxidizing agents.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Kerosine (petroleum)	64742-47-8	ACGIH	TWA(as total hydrocarbon vapor, non-aerosol):200 mg/m3	A3: Confirmed animal carcin., SKIN

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

**8.2. Exposure controls**

**8.2.1. Engineering controls**

Do not remain in area where available oxygen may be reduced. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

**8.2.2. Personal protective equipment (PPE)**

**Eye/face protection**

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect Vented Goggles

**Skin/hand protection**

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Nitrile Rubber

**Respiratory protection**

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors

Organic vapor respirators may have short service life.

For questions about suitability for a specific application, consult with your respirator manufacturer.

**SECTION 9: Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

**Appearance**

**Physical state**

Liquid : Aerosol

**Color**

Colorless

**Specific Physical Form:**

Aerosol

**Odor**

Faint Petroleum, Faint Hydrocarbon

**Odor threshold**

*No Data Available*

**pH**

*Not Applicable*

**Melting point**

*Not Applicable*

**Boiling Point**

174 °C

**Flash Point**

103 °F [*Test Method:*Closed Cup] [*Details:*Liquid only; propellant flash point <0 F]

**Evaporation rate**

*No Data Available*

**Flammability (solid, gas)**

Not Applicable

**Flammable Limits(LEL)**

0.8 %

**Flammable Limits(UEL)**

6 %

**Vapor Pressure**

1.1 mmHg [*@* 68 °F]

**Vapor Density**

4.8 [*Ref Std:*AIR=1] [*Details:*Conditions: for CAS 64742-47-8]

Density	0.76 g/cm <sup>3</sup>
Specific Gravity	0.76 [Ref Std: WATER=1]
Solubility in Water	Negligible
Solubility- non-water	No Data Available
Partition coefficient: n-octanol/ water	No Data Available
Autoignition temperature	446 - 600 °F [Details: Conditions: for CAS 64742-47-8]
Decomposition temperature	No Data Available
Viscosity	1 centipoise
Molecular weight	No Data Available
Volatile Organic Compounds	91.8 % weight
VOC Less H <sub>2</sub> O & Exempt Solvents	697 g/l

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

### 10.2. Chemical stability

Stable.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

Heat

### 10.5. Incompatible materials

Strong oxidizing agents

### 10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

### 11.1. Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation:

Simple Asphyxiation: Signs/symptoms may include increased heart rate, rapid respirations, drowsiness, headache, incoordination, altered judgement, nausea, vomiting, lethargy, seizures, coma, and may be fatal.

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and

nose and throat pain.

May cause additional health effects (see below).

**Skin Contact:**

May be harmful in contact with skin.

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.

**Eye Contact:**

Contact with the eyes during product use is not expected to result in significant irritation.

**Ingestion:**

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

**Additional Health Effects:**

**Single exposure may cause target organ effects:**

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Single exposure, above recommended guidelines, may cause:

Cardiac Sensitization: Signs/symptoms may include irregular heartbeat (arrhythmia), faintness, chest pain, and may be fatal.

**Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE 2,000 - 5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Hydrotreated Light Petroleum Distillates	Dermal	Rabbit	LD50 > 3,160 mg/kg
Hydrotreated Light Petroleum Distillates	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 3 mg/l
Hydrotreated Light Petroleum Distillates	Ingestion	Rat	LD50 > 5,000 mg/kg
Petroleum Gases, Liquified, Sweetened	Inhalation-Gas (4 hours)	Rat	LC50 277,000 ppm
Silicone Mixture	Dermal	Rabbit	LD50 > 19,400 mg/kg
Silicone Mixture	Ingestion	Rat	LD50 > 17,000 mg/kg

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

Name	Species	Value
Hydrotreated Light Petroleum Distillates	Rabbit	Mild irritant
Petroleum Gases, Liquified, Sweetened	Professional judgement	No significant irritation
Silicone Mixture	Rabbit	No significant irritation

**Serious Eye Damage/Irritation**

Name	Species	Value
------	---------	-------

Hydrotreated Light Petroleum Distillates	Rabbit	Mild irritant
Petroleum Gases, Liquified, Sweetened	Professional judgement	No significant irritation
Silicone Mixture	Rabbit	No significant irritation

**Skin Sensitization**

Name	Species	Value
Hydrotreated Light Petroleum Distillates	Guinea pig	Not classified

**Respiratory Sensitization**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Germ Cell Mutagenicity**

Name	Route	Value
Hydrotreated Light Petroleum Distillates	In Vitro	Not mutagenic
Petroleum Gases, Liquified, Sweetened	In Vitro	Not mutagenic

**Carcinogenicity**

Name	Route	Species	Value
Hydrotreated Light Petroleum Distillates	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification

**Reproductive Toxicity**

**Reproductive and/or Developmental Effects**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Target Organ(s)**

**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Hydrotreated Light Petroleum Distillates	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Hydrotreated Light Petroleum Distillates	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Hydrotreated Light Petroleum Distillates	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
Petroleum Gases, Liquified, Sweetened	Inhalation	cardiac sensitization	Causes damage to organs	similar compounds	NOAEL Not available	
Petroleum Gases, Liquified, Sweetened	Inhalation	central nervous system depression	May cause drowsiness or dizziness		NOAEL Not available	
Petroleum Gases, Liquified, Sweetened	Inhalation	respiratory irritation	Not classified		NOAEL Not available	

**Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Petroleum Gases, Liquified, Sweetened	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL Not available	



**Aspiration Hazard**

Name	Value
Hydrotreated Light Petroleum Distillates	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

**SECTION 12: Ecological information**

**Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

**Chemical fate information**

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

**SECTION 13: Disposal considerations**

**13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. Facility must be capable of handling aerosol cans. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): D001 (Ignitable)

**SECTION 14: Transport Information**

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

**SECTION 15: Regulatory information**

**15.1. US Federal Regulations**

Contact 3M for more information.

**EPCRA 311/312 Hazard Classifications:**

**Physical Hazards**

Flammable (gases, aerosols, liquids, or solids)

Gas under pressure

**Health Hazards**

Simple Asphyxiant

Specific target organ toxicity (single or repeated exposure)

**15.2. State Regulations**

Contact 3M for more information.

### 15.3. Chemical Inventories

The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information.

The components of this product are in compliance with the new substance notification requirements of CEPA.

The components of this material are in compliance with the China "Measures on Environmental Management of New Chemical Substance". Certain restrictions may apply. Contact the selling division for additional information.

The components of this material are in compliance with the provisions of the Korean Toxic Chemical Control Law. Certain restrictions may apply. Contact the selling division for additional information.

The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information.

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

### 15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

## SECTION 16: Other information

### NFPA Hazard Classification

**Health:** 2 **Flammability:** 3 **Instability:** 0 **Special Hazards:** None  
**Aerosol Storage Code:** 3

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

### HMIS Hazard Classification

**Health:** 4 **Flammability:** 3 **Physical Hazard:** 0 **Personal Protection:** X - See PPE section.

Hazardous Material Identification System (HMIS® IV) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® IV ratings are to be used with a fully implemented HMIS® IV program. HMIS® is a registered mark of the American Coatings Association (ACA).

<b>Document Group:</b>	41-0602-7	<b>Version Number:</b>	1.03
<b>Issue Date:</b>	09/12/20	<b>Supersedes Date:</b>	01/27/20

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

**3M USA SDSs are available at [www.3M.com](http://www.3M.com)**