



Safety Data Sheet

Copyright, 2021, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	07-4243-7	Version Number:	6.01
Issue Date:	05/18/21	Supersedes Date:	07/30/20

Product identifier

3M™ Flexible Foam Adhesive PN 08463

ID Number	UPC	ID Number	UPC
41-0003-6635-5		41-0003-8014-1	
41-3701-2158-8		60-4551-1123-1	
60-4551-1132-2		60-9800-3647-3	
60-9800-4269-5		60-9800-4270-3	
60-9800-4271-1			

7100045768, 7000045731, 7000045732, 7000045733, 7100241758, 7100241812

Recommended use

Automotive, Two Component Flexible Foam

Supplier's details

MANUFACTURER:	3M
DIVISION:	Automotive Aftermarket
ADDRESS:	3M Center, St. Paul, MN 55144-1000, USA
Telephone:	1-888-3M HELPS (1-888-364-3577)

Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet (SDS), Article Information Sheet (AIS), or Article Information Letter (AIL) for each of these components is included. Please do not separate the component documents from this cover page. The document numbers for components of this product are:

07-5569-4, 07-3378-2

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com



Safety Data Sheet

Copyright, 2019, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	07-3378-2	Version Number:	11.03
Issue Date:	10/22/19	Supersedes Date:	04/05/18

SECTION 1: Identification

1.1. Product identifier

3M™ Flexible Foam/Part A, 08463

Product Identification Numbers

ID Number	UPC	ID Number	UPC
LB-K100-0029-6			

1.2. Recommended use and restrictions on use

Recommended use

Automotive, Two Component Flexible Foam

1.3. Supplier's details

MANUFACTURER:	3M
DIVISION:	Automotive Aftermarket
ADDRESS:	3M Center, St. Paul, MN 55144-1000, USA
Telephone:	1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

The label elements below were prepared in accordance with OSHA Hazard Communication Standard, 29 CFR 1910.1200. This information may be different from the actual product label information for labels regulated by other agencies.

2.1. Hazard classification

Serious Eye Damage/Irritation: Category 2A.

Skin Corrosion/Irritation: Category 2.

Respiratory Sensitizer: Category 1.

Skin Sensitizer: Category 1.

Specific Target Organ Toxicity (single exposure): Category 3.

Specific Target Organ Toxicity (repeated exposure): Category 1.

2.2. Label elements

Signal word

Danger

Symbols

Exclamation mark | Health Hazard |

Pictograms**Hazard Statements**

Causes serious eye irritation.

Causes skin irritation.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

May cause respiratory irritation.

Causes damage to organs through prolonged or repeated exposure:

respiratory system |

Precautionary Statements**Prevention:**

Do not breathe dust/fume/gas/mist/vapors/spray.

Use only outdoors or in a well-ventilated area.

In case of inadequate ventilation wear respiratory protection.

Wear protective gloves and eye/face protection.

Do not eat, drink or smoke when using this product.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Response:

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

If eye irritation persists: Get medical advice/attention.

IF ON SKIN: Wash with plenty of soap and water.

If skin irritation or rash occurs: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

Call a POISON CENTER or doctor/physician if you feel unwell.

Storage:

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

Supplemental Information:

Persons previously sensitized to isocyanates may develop a cross-sensitization reaction to other isocyanates.

38% of the mixture consists of ingredients of unknown acute oral toxicity.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
Urethane Prepolymer NJTSRN 04499600-6306	Trade Secret*	30 - 60 Trade Secret *
P,P'-Methylenebis(phenyl isocyanate)	101-68-8	10 - 30 Trade Secret *
Polymethylene Polyphenylene Isocyanate	9016-87-9	10 - 30 Trade Secret *
1,1'-METHYLENEBIS(ISOCYANATOBENZENE)	26447-40-5	< 15 Trade Secret *
Dimethyl Siloxane, Reaction Product With Silica	67762-90-7	1 - 5 Trade Secret *

NJTS or NJTSRN: New Jersey Trade Secret Registry Number.

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures**4.1. Description of first aid measures****Inhalation:**

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures**5.1. Suitable extinguishing media**

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products**Substance**

Isocyanates
Carbon monoxide
Carbon dioxide
Hydrogen Cyanide

Condition

During Combustion
During Combustion
During Combustion
During Combustion

Oxides of Nitrogen

During Combustion

5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Pour isocyanate decontaminant solution (90% water, 8% concentrated ammonia, 2% detergent) on spill and allow to react for 10 minutes. Or pour water on spill and allow to react for more than 30 minutes. Cover with absorbent material. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a container approved for transportation by appropriate authorities, but do not seal the container for 48 hours to avoid pressure build-up. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

For industrial/occupational use only. Not for consumer sale or use. Do not use in a confined area with minimal air exchange. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed to prevent contamination with water or air. If contamination is suspected, do not reseal container. Store away from heat. Store away from amines.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
P,P'-Methylenebis(phenyl isocyanate)	101-68-8	ACGIH	TWA:0.005 ppm	
P,P'-Methylenebis(phenyl isocyanate)	101-68-8	OSHA	CEIL:0.2 mg/m ³ (0.02 ppm)	
SILICA, AMORPHOUS	67762-90-7	OSHA	TWA concentration:0.8	

			mg/m ³ ;TWA:20 millions of particles/cu. ft.	
--	--	--	---------------------------------------------------------	--

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls**8.2.1. Engineering controls**

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)**Eye/face protection**

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Butyl Rubber

Neoprene

Nitrile Rubber

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron – Butyl rubber

Apron - Neoprene

Apron – Nitrile

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties****Appearance****Physical state**

Liquid

Color

Brown

Specific Physical Form:

Paste

Odor	Odorless
Odor threshold	<i>No Data Available</i>
pH	<i>Not Applicable</i>
Melting point	<i>Not Applicable</i>
Boiling Point	>=300 °F
Flash Point	>=300 °F [<i>Test Method</i> :Closed Cup]
Evaporation rate	<i>Not Applicable</i>
Flammability (solid, gas)	Not Applicable
Flammable Limits(LEL)	<i>No Data Available</i>
Flammable Limits(UEL)	<i>No Data Available</i>
Vapor Pressure	<=27 psia [<i>@</i> 131.0000000000 °F] [<i>Details</i> :MITS data]
Vapor Density	8.50 [<i>Ref Std</i> :AIR=1]
Density	1.135 - 1.16 g/ml
Specific Gravity	1.135 - 1.16 [<i>Ref Std</i> :WATER=1]
Solubility In Water	<i>Not Applicable</i>
Solubility- non-water	<i>No Data Available</i>
Partition coefficient: n-octanol/ water	<i>No Data Available</i>
Autoignition temperature	<i>No Data Available</i>
Decomposition temperature	<i>No Data Available</i>
Viscosity	<i>No Data Available</i>
Hazardous Air Pollutants	4.34 lb HAPS/lb solids [<i>Test Method</i> :Calculated]
Molecular weight	<i>No Data Available</i>
Volatile Organic Compounds	0.1 % weight [<i>Test Method</i> :calculated per CARB title 2]
Volatile Organic Compounds	1 g/l [<i>Test Method</i> :calculated SCAQMD rule 443.1]
Percent volatile	0.1 % weight
VOC Less H2O & Exempt Solvents	1 g/l [<i>Test Method</i> :calculated SCAQMD rule 443.1]

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat

10.5. Incompatible materials

Amines

Alcohols

Water

Reaction with water, alcohols, and amines is not hazardous if container can vent to the atmosphere to prevent pressure buildup.

10.6. Hazardous decomposition products

Substance

None known.

Condition

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Allergic Respiratory Reaction: Signs/symptoms may include difficulty breathing, wheezing, cough, and tightness of chest.

May cause additional health effects (see below).

Skin Contact:

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain.

Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Additional Health Effects:

Prolonged or repeated exposure may cause target organ effects:

Respiratory Effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish colored skin (cyanosis), sputum production, changes in lung function tests, and/or respiratory failure.

Additional Information:

Persons previously sensitized to isocyanates may develop a cross-sensitization reaction to other isocyanates.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
P,P'-Methylenebis(phenyl isocyanate)	Dermal	Rabbit	LD50 > 5,000 mg/kg
Polymethylene Polyphenylene Isocyanate	Dermal	Rabbit	LD50 > 5,000 mg/kg
P,P'-Methylenebis(phenyl isocyanate)	Inhalation-Dust/Mist (4 hours)	Rat	LC50 0.368 mg/l

P,P'-Methylenebis(phenyl isocyanate)	Ingestion	Rat	LD50 31,600 mg/kg
Polymethylene Polyphenylene Isocyanate	Inhalation-Dust/Mist (4 hours)	Rat	LC50 0.368 mg/l
Polymethylene Polyphenylene Isocyanate	Ingestion	Rat	LD50 31,600 mg/kg
1,1'-METHYLENEBIS(ISOCYANATOBENZENE)	Dermal	Rabbit	LD50 > 5,000 mg/kg
1,1'-METHYLENEBIS(ISOCYANATOBENZENE)	Inhalation-Dust/Mist (4 hours)	Rat	LC50 0.368 mg/l
1,1'-METHYLENEBIS(ISOCYANATOBENZENE)	Ingestion	Rat	LD50 31,600 mg/kg
Dimethyl Siloxane, Reaction Product With Silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
Dimethyl Siloxane, Reaction Product With Silica	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Dimethyl Siloxane, Reaction Product With Silica	Ingestion	Rat	LD50 > 5,110 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
P,P'-Methylenebis(phenyl isocyanate)	official classification	Irritant
Polymethylene Polyphenylene Isocyanate	official classification	Irritant
1,1'-METHYLENEBIS(ISOCYANATOBENZENE)	official classification	Irritant
Dimethyl Siloxane, Reaction Product With Silica	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
P,P'-Methylenebis(phenyl isocyanate)	official classification	Severe irritant
Polymethylene Polyphenylene Isocyanate	official classification	Severe irritant
1,1'-METHYLENEBIS(ISOCYANATOBENZENE)	official classification	Severe irritant
Dimethyl Siloxane, Reaction Product With Silica	Rabbit	No significant irritation

Skin Sensitization

Name	Species	Value
P,P'-Methylenebis(phenyl isocyanate)	official classification	Sensitizing
Polymethylene Polyphenylene Isocyanate	official classification	Sensitizing
1,1'-METHYLENEBIS(ISOCYANATOBENZENE)	official classification	Sensitizing
Dimethyl Siloxane, Reaction Product With Silica	Human and animal	Not classified

Respiratory Sensitization

Name	Species	Value
P,P'-Methylenebis(phenyl isocyanate)	Human	Sensitizing

Polymethylene Polyphenylene Isocyanate	Human	Sensitizing
1,1'-METHYLENEBIS(ISOCYANATOBENZENE)	Human	Sensitizing

Germ Cell Mutagenicity

Name	Route	Value
P,P'-Methylenebis(phenyl isocyanate)	In Vitro	Some positive data exist, but the data are not sufficient for classification
Polymethylene Polyphenylene Isocyanate	In Vitro	Some positive data exist, but the data are not sufficient for classification
1,1'-METHYLENEBIS(ISOCYANATOBENZENE)	In Vitro	Some positive data exist, but the data are not sufficient for classification
Dimethyl Siloxane, Reaction Product With Silica	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
P,P'-Methylenebis(phenyl isocyanate)	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification
Polymethylene Polyphenylene Isocyanate	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification
1,1'-METHYLENEBIS(ISOCYANATOBENZENE)	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification
Dimethyl Siloxane, Reaction Product With Silica	Not Specified	Mouse	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
P,P'-Methylenebis(phenyl isocyanate)	Inhalation	Not classified for development	Rat	NOAEL 0.004 mg/l	during organogenesis
Polymethylene Polyphenylene Isocyanate	Inhalation	Not classified for development	Rat	NOAEL 0.004 mg/l	during organogenesis
1,1'-METHYLENEBIS(ISOCYANATOBENZENE)	Inhalation	Not classified for development	Rat	NOAEL 0.004 mg/l	during organogenesis
Dimethyl Siloxane, Reaction Product With Silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Dimethyl Siloxane, Reaction Product With Silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Dimethyl Siloxane, Reaction Product With Silica	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
P,P'-Methylenebis(phenyl isocyanate)	Inhalation	respiratory irritation	May cause respiratory irritation	official classification	NOAEL Not available	
Polymethylene Polyphenylene Isocyanate	Inhalation	respiratory irritation	May cause respiratory irritation	official classification	NOAEL Not available	
1,1'-METHYLENEBIS(ISOCYANATOBENZENE)	Inhalation	respiratory irritation	May cause respiratory irritation	official classification	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
P,P'-Methylenebis(phenyl isocyanate)	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.004 mg/l	13 weeks
Polymethylene Polyphenylene Isocyanate	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.004 mg/l	13 weeks
1,1'-METHYLENEBIS(ISOCYANATOBENZENE)	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.004 mg/l	13 weeks
Dimethyl Siloxane, Reaction Product With Silica	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:

Physical Hazards
Not applicable

Health Hazards
Respiratory or Skin Sensitization
Serious eye damage or eye irritation
Skin Corrosion or Irritation
Specific target organ toxicity (single or repeated exposure)

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

<u>Ingredient</u>	<u>C.A.S. No</u>	<u>% by Wt</u>
P,P'-Methylenebis(phenyl isocyanate)	101-68-8	Trade Secret 10 - 30
P,P'-Methylenebis(phenyl isocyanate) (DIISOCYANATES (CERTAIN CHEMICALS ONLY))	101-68-8	10 - 30
Polymethylene Polyphenylene Isocyanate	9016-87-9	Trade Secret 10 - 30
Polymethylene Polyphenylene Isocyanate (DIISOCYANATES (CERTAIN CHEMICALS ONLY))	9016-87-9	10 - 30

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 2 **Flammability:** 1 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document Group: 07-3378-2 **Version Number:** 11.03
Issue Date: 10/22/19 **Supersedes Date:** 04/05/18

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of

which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com



Safety Data Sheet

Copyright,2021, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	07-5569-4	Version Number:	12.01
Issue Date:	05/18/21	Supersedes Date:	07/29/20

SECTION 1: Identification

1.1. Product identifier

3M™ Flexible Foam Adhesive PN 08463, Part B

Product Identification Numbers

ID Number	UPC	ID Number	UPC
LB-K100-0029-7			

1.2. Recommended use and restrictions on use

Recommended use

Automotive, Two Component Flexible Foam

1.3. Supplier's details

MANUFACTURER:	3M
DIVISION:	Automotive Aftermarket
ADDRESS:	3M Center, St. Paul, MN 55144-1000, USA
Telephone:	1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

The label elements below were prepared in accordance with OSHA Hazard Communication Standard, 29 CFR 1910.1200. This information may be different from the actual product label information for labels regulated by other agencies.

2.1. Hazard classification

Serious Eye Damage/Irritation: Category 2A.
 Skin Corrosion/Irritation: Category 2.
 Skin Sensitizer: Category 1B.
 Reproductive Toxicity: Category 1B.
 Germ Cell Mutagenicity: Category 2.
 Specific Target Organ Toxicity (single exposure): Category 1.
 Specific Target Organ Toxicity (repeated exposure): Category 1.

2.2. Label elements

Signal word

Danger

Symbols

Exclamation mark | Health Hazard |

Pictograms**Hazard Statements**

Causes serious eye irritation.

Causes skin irritation.

May cause an allergic skin reaction.

May damage fertility or the unborn child.

Suspected of causing genetic defects.

Causes damage to organs:

immune system |

liver |

nervous system |

kidney/urinary tract |

Causes damage to organs through prolonged or repeated exposure:

immune system |

liver |

Precautionary Statements**Prevention:**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wear protective gloves and eye/face protection.

Do not eat, drink or smoke when using this product.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Response:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

If eye irritation persists: Get medical advice/attention.

IF ON SKIN: Wash with plenty of soap and water.

If skin irritation or rash occurs: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

IF exposed or concerned: Get medical advice/attention.

Get medical advice/attention if you feel unwell.

Storage:

Store locked up.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

51% of the mixture consists of ingredients of unknown acute inhalation toxicity.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
Glycerol Poly(Oxyethylene, Oxypropylene) Ether	9082-00-2	30 - 60 Trade Secret *
Polypropylene Glycol Glycerol Triether	25791-96-2	30 - 60 Trade Secret *
Dimethyl Siloxane, Reaction Product with Silica	67762-90-7	3 - 7 Trade Secret *
Diethylene Glycol	111-46-6	1 - 5 Trade Secret *
Dipropylene Glycol	25265-71-8	1 - 5 Trade Secret *
Water	7732-18-5	1 - 5 Trade Secret *
Dibutyltin Dilaurate	77-58-7	< 2 Trade Secret *
Triethylenediamine	280-57-9	0.5 - 1.5 Trade Secret *

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with detergent and water. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not use in a confined area with minimal air exchange. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Use personal protective equipment (gloves, respirators, etc.) as required.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Store away from heat. Store away from areas where product may come into contact with food or pharmaceuticals.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Diethylene Glycol	111-46-6	AIHA	TWA:10 mg/m ³	
SILICA, AMORPHOUS	67762-90-7	OSHA	TWA:20 millions of particles/cu. ft.;TWA concentration:0.8 mg/m ³	
TIN, ORGANIC COMPOUNDS	77-58-7	ACGIH	TWA(as Sn):0.1 mg/m ³ ;STEL(as Sn):0.2 mg/m ³	A4: Not class. as human carcin, SKIN
TIN, ORGANIC COMPOUNDS	77-58-7	OSHA	TWA(as Sn):0.1 mg/m ³	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Provide appropriate local exhaust ventilation on open containers. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment. Provide appropriate local exhaust ventilation for cutting, grinding, sanding or machining.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Neoprene
Nitrile Rubber

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - Neoprene
Apron - Nitrile

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state

Liquid

Color

Black

Specific Physical Form:

Flexible Foam

Odor

Odorless

Odor threshold

No Data Available

pH

Not Applicable

Melting point

Not Applicable

Boiling Point

Not Applicable

Flash Point

≥ 250 °F [*Test Method: Tagliabue Closed Cup*]

Evaporation rate

Not Applicable

Flammability (solid, gas)

Not Applicable

Flammable Limits(LEL)

No Data Available

Flammable Limits(UEL)

No Data Available

Vapor Pressure

≤ 27 psia [*@ 131.000000000 °F*] [*Details: MITS data*]

Vapor Density	<i>Not Applicable</i>
Density	0.960 - 1.030 g/ml
Specific Gravity	0.960 - 1.030 [<i>Ref Std: WATER=1</i>]
Solubility in Water	Moderate
Solubility- non-water	<i>No Data Available</i>
Partition coefficient: n-octanol/ water	<i>No Data Available</i>
Autoignition temperature	<i>No Data Available</i>
Decomposition temperature	<i>No Data Available</i>
Viscosity	<i>No Data Available</i>
Hazardous Air Pollutants	0.0008 lb HAPS/lb solids [<i>Test Method: Calculated</i>]
Molecular weight	<i>No Data Available</i>
Volatile Organic Compounds	45 g/l [<i>Test Method: calculated SCAQMD rule 443.1</i>]
Volatile Organic Compounds	1.9 % weight [<i>Test Method: calculated per CARB title 2</i>]
Percent volatile	26.3 % weight
VOC Less H ₂ O & Exempt Solvents	57 g/l [<i>Test Method: calculated SCAQMD rule 443.1</i>]

SECTION 10: Stability and reactivity

10.1. Reactivity

This material is considered to be non reactive under normal use conditions.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

None known.

10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
Carbon monoxide	Not Specified
Carbon dioxide	Not Specified
Toxic Vapor, Gas, Particulate	Not Specified

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin Contact:

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain.
Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:

Liver Effects: Signs/symptoms may include loss of appetite, weight loss, fatigue, weakness, abdominal tenderness and jaundice.

Immunological Effects: Signs/symptoms may include alterations in the number of circulating immune cells, allergic skin and /or respiratory reaction, and changes in immune function.

Neurological Effects: Signs/symptoms may include personality changes, lack of coordination, sensory loss, tingling or numbness of the extremities, weakness, tremors, and/or changes in blood pressure and heart rate.

Kidney/Bladder Effects: Signs/symptoms may include changes in urine production, abdominal or lower back pain, increased protein in urine, increased blood urea nitrogen (BUN), blood in urine, and painful urination.

Prolonged or repeated exposure may cause target organ effects:

Liver Effects: Signs/symptoms may include loss of appetite, weight loss, fatigue, weakness, abdominal tenderness and jaundice.

Immunological Effects: Signs/symptoms may include alterations in the number of circulating immune cells, allergic skin and /or respiratory reaction, and changes in immune function.

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Genotoxicity:

Genotoxicity and Mutagenicity: May interact with genetic material and possibly alter gene expression.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Dust/Mist(4 hr)		No data available; calculated ATE >12.5 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Glycerol Poly(Oxyethylene, Oxypropylene) Ether	Dermal	Rabbit	LD50 > 5,000 mg/kg

Glycerol Poly(Oxyethylene, Oxypropylene) Ether	Ingestion	Rat	LD50 > 10,000 mg/kg
Polypropylene Glycol Glycerol Triether	Dermal	Rat	LD50 > 2,000 mg/kg
Polypropylene Glycol Glycerol Triether	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 50 mg/l
Polypropylene Glycol Glycerol Triether	Ingestion	Rat	LD50 4,600 mg/kg
Dimethyl Siloxane, Reaction Product with Silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
Dimethyl Siloxane, Reaction Product with Silica	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Dimethyl Siloxane, Reaction Product with Silica	Ingestion	Rat	LD50 > 5,110 mg/kg
Dipropylene Glycol	Dermal	Rabbit	LD50 > 5,010 mg/kg
Dipropylene Glycol	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 2.34 mg/l
Dipropylene Glycol	Ingestion	Rat	LD50 > 14,800 mg/kg
Dibutyltin Dilaurate	Dermal	Rat	LD50 > 2,000 mg/kg
Dibutyltin Dilaurate	Ingestion	Rat	LD50 1,290 mg/kg
Diethylene Glycol	Ingestion	Human	LD50 estimated to be 300 - 2,000 mg/kg
Diethylene Glycol	Dermal	Rabbit	LD50 13,300 mg/kg
Diethylene Glycol	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 4.6 mg/l
Triethylenediamine	Dermal	Rabbit	LD50 > 3,200 mg/kg
Triethylenediamine	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 5.05 mg/l
Triethylenediamine	Ingestion	Rat	LD50 1,870 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Polypropylene Glycol Glycerol Triether	Rabbit	No significant irritation
Dimethyl Siloxane, Reaction Product with Silica	Rabbit	No significant irritation
Dipropylene Glycol	Rabbit	No significant irritation
Dibutyltin Dilaurate	Rabbit	Corrosive
Diethylene Glycol	Rabbit	No significant irritation
Triethylenediamine	Rabbit	Mild irritant

Serious Eye Damage/Irritation

Name	Species	Value
Polypropylene Glycol Glycerol Triether	Rabbit	Mild irritant
Dimethyl Siloxane, Reaction Product with Silica	Rabbit	No significant irritation
Dipropylene Glycol	Rabbit	No significant irritation
Dibutyltin Dilaurate	Rabbit	Corrosive
Diethylene Glycol	Rabbit	Mild irritant
Triethylenediamine	Rabbit	Corrosive

Skin Sensitization

Name	Species	Value
Dimethyl Siloxane, Reaction Product with Silica	Human and animal	Not classified
Dipropylene Glycol	Guinea pig	Not classified
Dibutyltin Dilaurate	Guinea pig	Sensitizing

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Dimethyl Siloxane, Reaction Product with Silica	In Vitro	Not mutagenic
Dipropylene Glycol	In Vitro	Not mutagenic
Dipropylene Glycol	In vivo	Not mutagenic
Dibutyltin Dilaurate	In Vitro	Some positive data exist, but the data are not sufficient for classification
Dibutyltin Dilaurate	In vivo	Mutagenic

Carcinogenicity

Name	Route	Species	Value
Dimethyl Siloxane, Reaction Product with Silica	Not Specified	Mouse	Some positive data exist, but the data are not sufficient for classification
Dipropylene Glycol	Ingestion	Multiple animal species	Not carcinogenic

Reproductive Toxicity**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test Result	Exposure Duration
Dimethyl Siloxane, Reaction Product with Silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Dimethyl Siloxane, Reaction Product with Silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Dimethyl Siloxane, Reaction Product with Silica	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
Dipropylene Glycol	Ingestion	Not classified for development	Rat	NOAEL 5,000 mg/kg/day	during organogenesis
Dibutyltin Dilaurate	Ingestion	Toxic to female reproduction	Rat	NOAEL 2 mg/kg/day	prematuring into lactation
Dibutyltin Dilaurate	Ingestion	Toxic to development	Rat	NOAEL 2.5 mg/kg/day	during gestation

Target Organ(s)**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Dibutyltin Dilaurate	Ingestion	immune system	Causes damage to organs	Rat	LOAEL 5 mg/kg	
Diethylene Glycol	Ingestion	liver nervous system kidney and/or bladder	Causes damage to organs	Human	NOAEL Not available	poisoning and/or abuse
Diethylene Glycol	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Dimethyl Siloxane, Reaction Product with Silica	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
Dipropylene Glycol	Ingestion	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 470 mg/kg/day	105 weeks
Dipropylene Glycol	Ingestion	heart	Not classified	Rat	NOAEL 470 mg/kg/day	105 weeks
Dipropylene Glycol	Ingestion	endocrine system liver	Not classified	Rat	NOAEL 3,040	105 weeks

					mg/kg/day	
Dipropylene Glycol	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 115 mg/kg/day	105 weeks
Dipropylene Glycol	Ingestion	skin bone, teeth, nails, and/or hair hematopoietic system immune system nervous system vascular system	Not classified	Rat	NOAEL 3,040 mg/kg/day	105 weeks
Dibutyltin Dilaurate	Ingestion	liver	Causes damage to organs through prolonged or repeated exposure	Rat	NOAEL 2 mg/kg/day	2 weeks
Dibutyltin Dilaurate	Ingestion	immune system	Causes damage to organs through prolonged or repeated exposure	Rat	NOAEL 0.3 mg/kg/day	28 days

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information**Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations**13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information**15.1. US Federal Regulations**

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:**Physical Hazards**

Not applicable

Health Hazards
Germ cell mutagenicity
Reproductive toxicity
Respiratory or Skin Sensitization
Serious eye damage or eye irritation
Skin Corrosion or Irritation
Specific target organ toxicity (single or repeated exposure)

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 2 **Flammability:** 1 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document Group:	07-5569-4	Version Number:	12.01
Issue Date:	05/18/21	Supersedes Date:	07/29/20

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com