



Safety Data Sheet

Copyright,2023, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

| | | | |
|------------------------|-----------|-------------------------|----------|
| Document Group: | 08-0531-7 | Version Number: | 22.00 |
| Issue Date: | 04/05/23 | Supersedes Date: | 01/17/23 |

SECTION 1: Identification

1.1. Product identifier

3M™ Black Super Weatherstrip and Gasket Adhesive, 08008, 08008B, 08581

Product Identification Numbers

LB-K000-1071-0, 41-0003-7951-5, 41-3701-2175-2, 60-4550-2996-1, 60-4550-5472-0, 60-4550-5560-2, 60-4550-5843-2, 60-4550-9044-3, 60-4551-0856-7, 60-9800-3122-7
7000045523, 7010328150, 7010308840, 7100210691

1.2. Recommended use and restrictions on use

Recommended use

Automotive, Adhesive

1.3. Supplier's details

| | |
|----------------------|---|
| MANUFACTURER: | 3M |
| DIVISION: | Construction and Home Improvement Markets |
| ADDRESS: | 3M Center, St. Paul, MN 55144-1000, USA |
| Telephone: | 1-888-3M HELPS (1-888-364-3577) |

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

The label elements below were prepared in accordance with OSHA Hazard Communication Standard, 29 CFR 1910.1200. This information may be different from the actual product label information for labels regulated by other agencies.

2.1. Hazard classification

Flammable Liquid: Category 2.
Serious Eye Damage/Irritation: Category 2A.
Skin Corrosion/Irritation: Category 2.
Skin Sensitizer: Category 1A.
Reproductive Toxicity: Category 1B.
Carcinogenicity: Category 2.
Specific Target Organ Toxicity (single exposure): Category 3.
Specific Target Organ Toxicity (repeated exposure): Category 1.

2.2. Label elements

Signal word

Danger

Symbols

Flame | Exclamation mark | Health Hazard |

Pictograms**Hazard Statements**

Highly flammable liquid and vapor.

Causes serious eye irritation.

Causes skin irritation.

May cause an allergic skin reaction.

May cause drowsiness or dizziness.

May damage fertility or the unborn child.

Suspected of causing cancer.

Causes damage to organs through prolonged or repeated exposure:

nervous system |

sensory organs |

Precautionary Statements**General:**

Keep out of reach of children.

Prevention:

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Keep container tightly closed.

Use explosion-proof electrical/ventilating/lighting equipment.

Do not breathe dust/fume/gas/mist/vapors/spray.

Use only outdoors or in a well-ventilated area.

Wear protective gloves and eye/face protection.

Do not eat, drink or smoke when using this product.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Response:

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

If eye irritation persists: Get medical advice/attention.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

IF exposed or concerned: Get medical advice/attention.

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

Storage:

Store in a well-ventilated place. Keep cool.

Keep container tightly closed.

Store locked up.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

8% of the mixture consists of ingredients of unknown acute inhalation toxicity.

SECTION 3: Composition/information on ingredients

| Ingredient | C.A.S. No. | % by Wt |
|--|------------|------------------------|
| Naphtha (petroleum), solvent-refined light | 64741-84-0 | 15 - 40 Trade Secret * |
| HEXANE | 110-54-3 | 7 - 30 Trade Secret * |
| Methyl Ethyl Ketone | 78-93-3 | 10 - 30 Trade Secret * |
| Toluene | 108-88-3 | < 10 Trade Secret * |
| Carbon Black | 1333-86-4 | < 1 Trade Secret * |
| Ethylbenzene | 100-41-4 | < 1 Trade Secret * |
| Methyl isobutyl ketone | 108-10-1 | < 1 Trade Secret * |
| STYRENATED PHENOL | 61788-44-1 | < 0.5 Trade Secret * |

Any remaining components do not contribute to the hazards of this material.

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Allergic skin reaction (redness, swelling, blistering, and itching). Central nervous system depression (headache, dizziness, drowsiness, incoordination, nausea, slurred speech, giddiness, and unconsciousness). Target organ effects following prolonged or repeated exposure. See Section 11 for additional details.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Cover spill area with a fire-extinguishing foam. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. Use personal protective equipment (gloves, respirators, etc.) as required. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapor accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store away from heat. Store away from acids. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

| Ingredient | C.A.S. No. | Agency | Limit type | Additional Comments |
|------------------------|------------|--------|---|---|
| Ethylbenzene | 100-41-4 | ACGIH | TWA:20 ppm | A3: Confirmed animal carcin., Ototoxicant |
| Ethylbenzene | 100-41-4 | OSHA | TWA:435 mg/m ³ (100 ppm) | |
| Methyl isobutyl ketone | 108-10-1 | ACGIH | TWA:20 ppm;STEL:75 ppm | A3: Confirmed animal carcin. |
| Methyl isobutyl ketone | 108-10-1 | OSHA | TWA:410 mg/m ³ (100 ppm) | |
| Toluene | 108-88-3 | ACGIH | TWA:20 ppm | A4: Not class. as human carcin, Ototoxicant |
| Toluene | 108-88-3 | OSHA | TWA:200 ppm;CEIL:300 ppm | |
| HEXANE | 110-54-3 | ACGIH | TWA:50 ppm | Danger of cutaneous absorption |
| HEXANE | 110-54-3 | OSHA | TWA:1800 mg/m ³ (500 ppm) | |
| Carbon Black | 1333-86-4 | ACGIH | TWA(inhalable fraction):3 mg/m ³ | A3: Confirmed animal carcin. |
| Carbon Black | 1333-86-4 | OSHA | TWA:3.5 mg/m ³ | |
| Naphtha | 64741-84-0 | OSHA | TWA:400 mg/m ³ (100 ppm) | |
| Methyl Ethyl Ketone | 78-93-3 | ACGIH | TWA:200 ppm;STEL:300 ppm | |
| Methyl Ethyl Ketone | 78-93-3 | OSHA | TWA:590 mg/m ³ (200 ppm) | |

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective

clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state
Color

Liquid
Black

Odor

Solvent

Odor threshold

No Data Available

pH

Not Applicable

Melting point

No Data Available

Boiling Point

148 - 189 °F

Flash Point

-6.00 °F [Test Method: Tagliabue Closed Cup]

Evaporation rate

>=3.6 [Ref Std: ETHER=1]

Flammability (solid, gas)

Not Applicable

Flammable Limits(LEL)

1.00 % volume

Flammable Limits(UEL)

11.50 % volume

Vapor Pressure

120.0000 mmHg [@ 68 °F]

Vapor Density

3.00 [Ref Std: AIR=1]

Density

0.90 g/ml

Specific Gravity

0.90 [Ref Std: WATER=1]

Solubility in Water

Slight (less than 10%)

Solubility- non-water

No Data Available

Partition coefficient: n-octanol/ water

No Data Available

Autoignition temperature

No Data Available

Decomposition temperature

No Data Available

Viscosity

7,500 - 9,500 centipoise

Hazardous Air Pollutants

0.57 lb HAPS/lb solids [Test Method: Calculated]

Volatile Organic Compounds

64.4 % weight [Test Method: calculated per CARB title 2]

Percent volatile

64.4 % weight

VOC Less H2O & Exempt Solvents

579.7 g/l [Test Method: calculated SCAQMD rule 443.1]

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat

Sparks and/or flames

10.5. Incompatible materials

Strong oxidizing agents

10.6. Hazardous decomposition products**Substance****Condition**

Carbon monoxide

Not Specified

Carbon dioxide

Not Specified

Toxic Vapor, Gas, Particulate

Not Specified

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects**Signs and Symptoms of Exposure**

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

Skin Contact:

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain.
Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

Additional Health Effects:**Single exposure may cause target organ effects:**

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Prolonged or repeated exposure may cause target organ effects:

Ocular Effects: Signs/symptoms may include blurred or significantly impaired vision.

Auditory Effects: Signs/symptoms may include hearing impairment, balance dysfunction and ringing in the ears.

Peripheral Neuropathy: Signs/symptoms may include tingling or numbness of the extremities, incoordination, weakness of the hands and feet, tremors and muscle atrophy.

Olfactory Effects: Signs/symptoms may include decreased ability to detect odors and/or complete loss of smell.

Neurological Effects: Signs/symptoms may include personality changes, lack of coordination, sensory loss, tingling or numbness of the extremities, weakness, tremors, and/or changes in blood pressure and heart rate.

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

| Ingredient | CAS No. | Class Description | Regulation |
|------------------------|----------------|-------------------------------|---|
| Carbon black | 1333-86-4 | Grp. 2B: Possible human carc. | International Agency for Research on Cancer |
| Ethylbenzene | 100-41-4 | Grp. 2B: Possible human carc. | International Agency for Research on Cancer |
| Methyl isobutyl ketone | 108-10-1 | Grp. 2B: Possible human carc. | International Agency for Research on Cancer |

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

| Name | Route | Species | Value |
|--|----------------------------|----------------|--|
| Overall product | Dermal | | No data available; calculated ATE >5,000 mg/kg |
| Overall product | Inhalation-Vapor(4 hr) | | No data available; calculated ATE >50 mg/l |
| Overall product | Ingestion | | No data available; calculated ATE >5,000 mg/kg |
| Naphtha (petroleum), solvent-refined light | Dermal | Rat | LD50 > 2,800 mg/kg |
| Naphtha (petroleum), solvent-refined light | Inhalation-Vapor (4 hours) | Rat | LC50 > 25.2 mg/l |
| Naphtha (petroleum), solvent-refined light | Ingestion | Rat | LD50 > 5,840 mg/kg |
| Methyl Ethyl Ketone | Dermal | Rabbit | LD50 > 8,050 mg/kg |
| Methyl Ethyl Ketone | Inhalation-Vapor (4 hours) | Rat | LC50 34.5 mg/l |
| Methyl Ethyl Ketone | Ingestion | Rat | LD50 2,737 mg/kg |
| HEXANE | Dermal | Rabbit | LD50 > 2,000 mg/kg |
| HEXANE | Inhalation-Vapor (4 hours) | Rat | LC50 170 mg/l |
| HEXANE | Ingestion | Rat | LD50 > 28,700 mg/kg |
| Toluene | Dermal | Rat | LD50 12,000 mg/kg |
| Toluene | Inhalation-Vapor (4 hours) | Rat | LC50 30 mg/l |
| Toluene | Ingestion | Rat | LD50 5,550 mg/kg |
| Ethylbenzene | Dermal | Rabbit | LD50 15,433 mg/kg |
| Ethylbenzene | Inhalation-Vapor (4 hours) | Rat | LC50 17.4 mg/l |
| Ethylbenzene | Ingestion | Rat | LD50 4,769 mg/kg |

| | | | |
|------------------------|----------------------------|--------|---------------------|
| Methyl isobutyl ketone | Dermal | Rabbit | LD50 > 16,000 mg/kg |
| Methyl isobutyl ketone | Inhalation-Vapor (4 hours) | Rat | LC50 11 mg/l |
| Methyl isobutyl ketone | Ingestion | Rat | LD50 3,038 mg/kg |
| STYRENATED PHENOL | Dermal | Rat | LD50 > 2,000 mg/kg |
| STYRENATED PHENOL | Ingestion | Rat | LD50 > 2,000 mg/kg |
| Carbon Black | Dermal | Rabbit | LD50 > 3,000 mg/kg |
| Carbon Black | Ingestion | Rat | LD50 > 8,000 mg/kg |

ATE = acute toxicity estimate

Skin Corrosion/Irritation

| Name | Species | Value |
|--|------------------|---------------------------|
| Naphtha (petroleum), solvent-refined light | Rabbit | Irritant |
| Methyl Ethyl Ketone | Rabbit | Minimal irritation |
| HEXANE | Human and animal | Mild irritant |
| Toluene | Rabbit | Irritant |
| Ethylbenzene | Rabbit | Mild irritant |
| Methyl isobutyl ketone | Rabbit | Mild irritant |
| STYRENATED PHENOL | Rabbit | No significant irritation |
| Carbon Black | Rabbit | No significant irritation |

Serious Eye Damage/Irritation

| Name | Species | Value |
|--|---------|---------------------------|
| Naphtha (petroleum), solvent-refined light | Rabbit | Mild irritant |
| Methyl Ethyl Ketone | Rabbit | Severe irritant |
| HEXANE | Rabbit | Mild irritant |
| Toluene | Rabbit | Moderate irritant |
| Ethylbenzene | Rabbit | Moderate irritant |
| Methyl isobutyl ketone | Rabbit | Mild irritant |
| STYRENATED PHENOL | Rabbit | Mild irritant |
| Carbon Black | Rabbit | No significant irritation |

Skin Sensitization

| Name | Species | Value |
|--|------------|----------------|
| Naphtha (petroleum), solvent-refined light | Guinea pig | Not classified |
| HEXANE | Human | Not classified |
| Toluene | Guinea pig | Not classified |
| Ethylbenzene | Human | Not classified |
| Methyl isobutyl ketone | Guinea pig | Not classified |
| STYRENATED PHENOL | Mouse | Sensitizing |

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

| Name | Route | Value |
|---------------------|----------|--|
| Methyl Ethyl Ketone | In Vitro | Not mutagenic |
| HEXANE | In Vitro | Not mutagenic |
| HEXANE | In vivo | Not mutagenic |
| Toluene | In Vitro | Not mutagenic |
| Toluene | In vivo | Not mutagenic |
| Ethylbenzene | In vivo | Not mutagenic |
| Ethylbenzene | In Vitro | Some positive data exist, but the data are not |

| | | |
|------------------------|----------|--|
| | | sufficient for classification |
| Methyl isobutyl ketone | In Vitro | Not mutagenic |
| Carbon Black | In Vitro | Not mutagenic |
| Carbon Black | In vivo | Some positive data exist, but the data are not sufficient for classification |

Carcinogenicity

| Name | Route | Species | Value |
|------------------------|------------|-------------------------|--|
| Methyl Ethyl Ketone | Inhalation | Human | Not carcinogenic |
| HEXANE | Dermal | Mouse | Not carcinogenic |
| HEXANE | Inhalation | Mouse | Some positive data exist, but the data are not sufficient for classification |
| Toluene | Dermal | Mouse | Some positive data exist, but the data are not sufficient for classification |
| Toluene | Ingestion | Rat | Some positive data exist, but the data are not sufficient for classification |
| Toluene | Inhalation | Mouse | Some positive data exist, but the data are not sufficient for classification |
| Ethylbenzene | Inhalation | Multiple animal species | Carcinogenic |
| Methyl isobutyl ketone | Inhalation | Multiple animal species | Carcinogenic |
| Carbon Black | Dermal | Mouse | Not carcinogenic |
| Carbon Black | Ingestion | Mouse | Not carcinogenic |
| Carbon Black | Inhalation | Rat | Carcinogenic |

Reproductive Toxicity

Reproductive and/or Developmental Effects

| Name | Route | Value | Species | Test Result | Exposure Duration |
|--|------------|--|-------------------------|-----------------------|------------------------------|
| Naphtha (petroleum), solvent-refined light | Ingestion | Toxic to male reproduction | similar compounds | NOAEL not available | not available |
| Naphtha (petroleum), solvent-refined light | Inhalation | Toxic to male reproduction | similar compounds | NOAEL not available | not available |
| Methyl Ethyl Ketone | Inhalation | Not classified for development | Rat | LOAEL 8.8 mg/l | during gestation |
| HEXANE | Ingestion | Not classified for development | Mouse | NOAEL 2,200 mg/kg/day | during organogenesis |
| HEXANE | Inhalation | Not classified for development | Rat | NOAEL 0.7 mg/l | during gestation |
| HEXANE | Ingestion | Toxic to male reproduction | Rat | NOAEL 1,140 mg/kg/day | 90 days |
| HEXANE | Inhalation | Toxic to male reproduction | Rat | LOAEL 3.52 mg/l | 28 days |
| Toluene | Inhalation | Not classified for female reproduction | Human | NOAEL Not available | occupational exposure |
| Toluene | Inhalation | Not classified for male reproduction | Rat | NOAEL 2.3 mg/l | 1 generation |
| Toluene | Ingestion | Toxic to development | Rat | LOAEL 520 mg/kg/day | during gestation |
| Toluene | Inhalation | Toxic to development | Human | NOAEL Not available | poisoning and/or abuse |
| Ethylbenzene | Inhalation | Not classified for development | Rat | NOAEL 4.3 mg/l | premating & during gestation |
| Methyl isobutyl ketone | Inhalation | Not classified for female reproduction | Multiple animal species | NOAEL 8.2 mg/l | 2 generation |
| Methyl isobutyl ketone | Ingestion | Not classified for male reproduction | Rat | NOAEL 1,000 | 13 weeks |

| | | | | mg/kg/day | |
|------------------------|------------|--------------------------------------|-------------------------|-----------------|----------------------|
| Methyl isobutyl ketone | Inhalation | Not classified for male reproduction | Multiple animal species | NOAEL 8.2 mg/l | 2 generation |
| Methyl isobutyl ketone | Inhalation | Not classified for development | Mouse | NOAEL 12.3 mg/l | during organogenesis |

Target Organ(s)

Specific Target Organ Toxicity - single exposure

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|--|------------|-----------------------------------|--|-------------------------|---------------------|------------------------|
| Naphtha (petroleum), solvent-refined light | Inhalation | central nervous system depression | May cause drowsiness or dizziness | similar compounds | NOAEL not available | not available |
| Naphtha (petroleum), solvent-refined light | Ingestion | central nervous system depression | May cause drowsiness or dizziness | similar compounds | NOAEL not available | not available |
| Methyl Ethyl Ketone | Inhalation | central nervous system depression | May cause drowsiness or dizziness | official classification | NOAEL Not available | |
| Methyl Ethyl Ketone | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | Human | NOAEL Not available | |
| Methyl Ethyl Ketone | Ingestion | central nervous system depression | May cause drowsiness or dizziness | Professional judgement | NOAEL Not available | |
| Methyl Ethyl Ketone | Ingestion | liver | Not classified | Rat | NOAEL Not available | not applicable |
| Methyl Ethyl Ketone | Ingestion | kidney and/or bladder | Not classified | Rat | LOAEL 1,080 mg/kg | not applicable |
| HEXANE | Inhalation | central nervous system depression | May cause drowsiness or dizziness | Human | NOAEL Not available | not available |
| HEXANE | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | Rabbit | NOAEL Not available | 8 hours |
| HEXANE | Inhalation | respiratory system | Not classified | Rat | NOAEL 24.6 mg/l | 8 hours |
| Toluene | Inhalation | central nervous system depression | May cause drowsiness or dizziness | Human | NOAEL Not available | |
| Toluene | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | Human | NOAEL Not available | |
| Toluene | Inhalation | immune system | Not classified | Mouse | NOAEL 0.004 mg/l | 3 hours |
| Toluene | Ingestion | central nervous system depression | May cause drowsiness or dizziness | Human | NOAEL Not available | poisoning and/or abuse |
| Ethylbenzene | Inhalation | central nervous system depression | May cause drowsiness or dizziness | Human | NOAEL Not available | |
| Ethylbenzene | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | Human and animal | NOAEL Not available | |
| Ethylbenzene | Ingestion | central nervous system depression | May cause drowsiness or dizziness | Professional judgement | NOAEL Not available | |
| Methyl isobutyl ketone | Inhalation | central nervous system depression | May cause drowsiness or dizziness | Human | LOAEL 0.1 mg/l | 2 hours |
| Methyl isobutyl ketone | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | Human | NOAEL Not available | |
| Methyl isobutyl ketone | Inhalation | vascular system | Not classified | Dog | NOAEL Not available | not available |
| Methyl isobutyl ketone | Ingestion | central nervous | May cause drowsiness or | Rat | LOAEL 900 | not applicable |

| | | | | | | |
|--|--|-------------------|-----------|--|-------|--|
| | | system depression | dizziness | | mg/kg | |
|--|--|-------------------|-----------|--|-------|--|

Specific Target Organ Toxicity - repeated exposure

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|--|------------|--|--|-------------------|-----------------------|------------------------|
| Naphtha (petroleum), solvent-refined light | Inhalation | peripheral nervous system | May cause damage to organs though prolonged or repeated exposure | similar compounds | NOAEL not available | not available |
| Methyl Ethyl Ketone | Dermal | nervous system | Not classified | Guinea pig | NOAEL Not available | 31 weeks |
| Methyl Ethyl Ketone | Inhalation | liver kidney and/or bladder heart endocrine system gastrointestinal tract bone, teeth, nails, and/or hair hematopoietic system immune system muscles | Not classified | Rat | NOAEL 14.7 mg/l | 90 days |
| Methyl Ethyl Ketone | Ingestion | liver | Not classified | Rat | NOAEL Not available | 7 days |
| Methyl Ethyl Ketone | Ingestion | nervous system | Not classified | Rat | NOAEL 173 mg/kg/day | 90 days |
| HEXANE | Inhalation | peripheral nervous system | Causes damage to organs through prolonged or repeated exposure | Human | NOAEL Not available | occupational exposure |
| HEXANE | Inhalation | respiratory system | Some positive data exist, but the data are not sufficient for classification | Mouse | LOAEL 1.76 mg/l | 13 weeks |
| HEXANE | Inhalation | liver | Not classified | Rat | NOAEL Not available | 6 months |
| HEXANE | Inhalation | kidney and/or bladder | Not classified | Rat | LOAEL 1.76 mg/l | 6 months |
| HEXANE | Inhalation | hematopoietic system | Not classified | Mouse | NOAEL 35.2 mg/l | 13 weeks |
| HEXANE | Inhalation | auditory system immune system eyes | Not classified | Human | NOAEL Not available | occupational exposure |
| HEXANE | Inhalation | heart skin endocrine system | Not classified | Rat | NOAEL 1.76 mg/l | 6 months |
| HEXANE | Ingestion | peripheral nervous system | Some positive data exist, but the data are not sufficient for classification | Rat | NOAEL 1,140 mg/kg/day | 90 days |
| HEXANE | Ingestion | endocrine system hematopoietic system liver immune system kidney and/or bladder | Not classified | Rat | NOAEL Not available | 13 weeks |
| Toluene | Inhalation | auditory system eyes olfactory system | Causes damage to organs through prolonged or repeated exposure | Human | NOAEL Not available | poisoning and/or abuse |
| Toluene | Inhalation | nervous system | May cause damage to organs though prolonged or repeated exposure | Human | NOAEL Not available | poisoning and/or abuse |
| Toluene | Inhalation | respiratory system | Some positive data exist, but the data are not sufficient for classification | Rat | LOAEL 2.3 mg/l | 15 months |
| Toluene | Inhalation | heart liver kidney and/or bladder | Not classified | Rat | NOAEL 11.3 mg/l | 15 weeks |
| Toluene | Inhalation | endocrine system | Not classified | Rat | NOAEL 1.1 mg/l | 4 weeks |
| Toluene | Inhalation | immune system | Not classified | Mouse | NOAEL Not available | 20 days |
| Toluene | Inhalation | bone, teeth, nails, and/or hair | Not classified | Mouse | NOAEL 1.1 mg/l | 8 weeks |
| Toluene | Inhalation | hematopoietic system vascular | Not classified | Human | NOAEL Not available | occupational exposure |

| | | | | | | |
|------------------------|------------|---|--|-------------------------|-----------------------|-----------|
| | | system | | | | |
| Toluene | Inhalation | gastrointestinal tract | Not classified | Multiple animal species | NOAEL 11.3 mg/l | 15 weeks |
| Toluene | Ingestion | nervous system | Some positive data exist, but the data are not sufficient for classification | Rat | NOAEL 625 mg/kg/day | 13 weeks |
| Toluene | Ingestion | heart | Not classified | Rat | NOAEL 2,500 mg/kg/day | 13 weeks |
| Toluene | Ingestion | liver kidney and/or bladder | Not classified | Multiple animal species | NOAEL 2,500 mg/kg/day | 13 weeks |
| Toluene | Ingestion | hematopoietic system | Not classified | Mouse | NOAEL 600 mg/kg/day | 14 days |
| Toluene | Ingestion | endocrine system | Not classified | Mouse | NOAEL 105 mg/kg/day | 28 days |
| Toluene | Ingestion | immune system | Not classified | Mouse | NOAEL 105 mg/kg/day | 4 weeks |
| Ethylbenzene | Inhalation | kidney and/or bladder | Some positive data exist, but the data are not sufficient for classification | Rat | NOAEL 1.1 mg/l | 2 years |
| Ethylbenzene | Inhalation | liver | Some positive data exist, but the data are not sufficient for classification | Mouse | NOAEL 1.1 mg/l | 103 weeks |
| Ethylbenzene | Inhalation | hematopoietic system | Not classified | Rat | NOAEL 3.4 mg/l | 28 days |
| Ethylbenzene | Inhalation | auditory system | Not classified | Rat | NOAEL 2.4 mg/l | 5 days |
| Ethylbenzene | Inhalation | endocrine system | Not classified | Mouse | NOAEL 3.3 mg/l | 103 weeks |
| Ethylbenzene | Inhalation | gastrointestinal tract | Not classified | Rat | NOAEL 3.3 mg/l | 2 years |
| Ethylbenzene | Inhalation | bone, teeth, nails, and/or hair muscles | Not classified | Multiple animal species | NOAEL 4.2 mg/l | 90 days |
| Ethylbenzene | Inhalation | heart immune system respiratory system | Not classified | Multiple animal species | NOAEL 3.3 mg/l | 2 years |
| Ethylbenzene | Ingestion | liver kidney and/or bladder | Not classified | Rat | NOAEL 680 mg/kg/day | 6 months |
| Methyl isobutyl ketone | Inhalation | liver | Not classified | Rat | NOAEL 0.41 mg/l | 13 weeks |
| Methyl isobutyl ketone | Inhalation | heart | Not classified | Multiple animal species | NOAEL 0.8 mg/l | 2 weeks |
| Methyl isobutyl ketone | Inhalation | kidney and/or bladder | Not classified | Multiple animal species | NOAEL 0.4 mg/l | 90 days |
| Methyl isobutyl ketone | Inhalation | respiratory system | Not classified | Multiple animal species | NOAEL 4.1 mg/l | 14 weeks |
| Methyl isobutyl ketone | Inhalation | endocrine system hematopoietic system | Not classified | Multiple animal species | NOAEL 0.41 mg/l | 90 days |
| Methyl isobutyl ketone | Inhalation | nervous system | Not classified | Multiple animal species | NOAEL 0.41 mg/l | 13 weeks |
| Methyl isobutyl ketone | Ingestion | endocrine system hematopoietic system liver kidney and/or bladder | Not classified | Rat | NOAEL 1,000 mg/kg/day | 13 weeks |
| Methyl isobutyl ketone | Ingestion | heart immune system muscles nervous system respiratory system | Not classified | Rat | NOAEL 1,040 mg/kg/day | 120 days |

| | | | | | | |
|--------------|------------|----------------|----------------|-------|---------------------|-----------------------|
| Carbon Black | Inhalation | pneumoconiosis | Not classified | Human | NOAEL Not available | occupational exposure |
|--------------|------------|----------------|----------------|-------|---------------------|-----------------------|

Aspiration Hazard

| Name | Value |
|--|--|
| Naphtha (petroleum), solvent-refined light | Aspiration hazard |
| HEXANE | Aspiration hazard |
| Toluene | Aspiration hazard |
| Ethylbenzene | Aspiration hazard |
| Methyl isobutyl ketone | Some positive data exist, but the data are not sufficient for classification |

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate uncured product in a permitted waste incineration facility. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:

| |
|---|
| Physical Hazards |
| Flammable (gases, aerosols, liquids, or solids) |

| |
|-----------------------|
| Health Hazards |
| Carcinogenicity |
| Reproductive toxicity |

| |
|--|
| Respiratory or Skin Sensitization |
| Serious eye damage or eye irritation |
| Skin Corrosion or Irritation |
| Specific target organ toxicity (single or repeated exposure) |

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

| <u>Ingredient</u> | <u>C.A.S. No</u> | <u>% by Wt</u> |
|------------------------|------------------|---------------------|
| Toluene | 108-88-3 | Trade Secret < 10 |
| HEXANE | 110-54-3 | Trade Secret 7 - 30 |
| HEXANE (Hexane) | 110-54-3 | Trade Secret 7 - 30 |
| Ethylbenzene | 100-41-4 | Trade Secret < 1 |
| Methyl isobutyl ketone | 108-10-1 | Trade Secret < 1 |

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 2 **Flammability:** 3 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

HMIS Hazard Classification

Health: *3 **Flammability:** 3 **Physical Hazard:** 0 **Personal Protection:** X - See PPE section.

Hazardous Material Identification System (HMIS® IV) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® IV ratings are to be used with a fully implemented HMIS® IV program. HMIS® is a registered mark of the American Coatings Association (ACA).

| | | | |
|------------------------|-----------|-------------------------|----------|
| Document Group: | 08-0531-7 | Version Number: | 22.00 |
| Issue Date: | 04/05/23 | Supersedes Date: | 01/17/23 |

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable

for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com