



Safety Data Sheet

Copyright, 2021, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

| | | | |
|------------------------|-----------|-------------------------|----------|
| Document Group: | 08-1276-8 | Version Number: | 12.01 |
| Issue Date: | 04/30/21 | Supersedes Date: | 05/21/18 |

SECTION 1: Identification

1.1. Product identifier

3M™ Zinc Spray 16-501

Product Identification Numbers

| | | | |
|----------------|------------------|----------------|-----|
| ID Number | UPC | ID Number | UPC |
| 80-6109-2798-2 | 00-54007-42828-2 | 80-6116-1654-3 | |

7000006136

1.2. Recommended use and restrictions on use

Recommended use

PROTECTIVE COATING, protective coating

Restrictions on use

INDUSTRIAL USE ONLY

1.3. Supplier's details

| | |
|----------------------|---|
| MANUFACTURER: | 3M |
| DIVISION: | Electrical Markets Division |
| ADDRESS: | 3M Center, St. Paul, MN 55144-1000, USA |
| Telephone: | 1-888-3M HELPS (1-888-364-3577) |

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

2.1. Hazard classification

Flammable Aerosol: Category 1.

Gas Under Pressure: Liquefied gas.

Serious Eye Damage/Irritation: Category 2A.

Reproductive Toxicity: Category 1B.

Simple Asphyxiant.

Specific Target Organ Toxicity (single exposure): Category 1.

Specific Target Organ Toxicity (single exposure): Category 3.

Specific Target Organ Toxicity (repeated exposure): Category 1.

2.2. Label elements

Signal word

Danger

Symbols

Flame | Gas cylinder | Exclamation mark | Health Hazard |

Pictograms**Hazard Statements**

Extremely flammable aerosol.

Contains gas under pressure; may explode if heated.

Causes serious eye irritation.

May cause drowsiness or dizziness.

May damage fertility or the unborn child.

May displace oxygen and cause rapid suffocation.

Causes damage to organs:

cardiovascular system |

Causes damage to organs through prolonged or repeated exposure:

nervous system |

sensory organs |

Precautionary Statements**Prevention:**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not spray on an open flame or other ignition source.

Pressurized container: Do not pierce or burn, even after use.

Do not breathe dust/fume/gas/mist/vapors/spray.

Use only outdoors or in a well-ventilated area.

Wear protective gloves and eye/face protection.

Wear eye/face protection.

Wear protective gloves.

Do not eat, drink or smoke when using this product.

Wash thoroughly after handling.

Response:

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

If eye irritation persists: Get medical advice/attention.

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see Notes to Physician on this label).

Storage:

Protect from sunlight. Do not expose to temperatures exceeding 50C/122F.

Store in a well-ventilated place. Keep container tightly closed.
Store locked up.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

Notes to Physician:

Exposure may increase myocardial irritability. Do not administer sympathomimetic drugs unless absolutely necessary.

Supplemental Information:

Intentional concentration and inhalation may be harmful or fatal.

13% of the mixture consists of ingredients of unknown acute oral toxicity.

13% of the mixture consists of ingredients of unknown acute dermal toxicity.

52% of the mixture consists of ingredients of unknown acute inhalation toxicity.

SECTION 3: Composition/information on ingredients

| Ingredient | C.A.S. No. | % by Wt |
|--|------------|------------------------|
| ZINC | 7440-66-6 | 45 - 53 Trade Secret * |
| BUTANE | 106-97-8 | 10 - 15 Trade Secret * |
| PROPANE | 74-98-6 | 10 - 15 Trade Secret * |
| METHYL ETHYL KETONE (MEK) | 78-93-3 | 8 - 13 Trade Secret * |
| HEPTANE | 142-82-5 | 2 - 5 Trade Secret * |
| Resin Epoxy Ester | 66070-75-5 | 1 - 5 Trade Secret * |
| SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC | 64742-89-8 | 2 - 5 Trade Secret * |
| TOLUENE | 108-88-3 | 2 - 5 Trade Secret * |

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures**Inhalation:**

Remove person to fresh air. Get medical attention.

Skin Contact:

Wash with soap and water. If signs/symptoms develop, get medical attention.

Eye Contact:

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Exposure may increase myocardial irritability. Do not administer sympathomimetic drugs unless absolutely necessary.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a carbon dioxide or dry chemical extinguisher to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products**Substance**

Carbon monoxide
Carbon dioxide
Oxides of Lead
Oxides of Zinc

Condition

During Combustion
During Combustion
During Combustion
During Combustion

5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

For industrial/occupational use only. Not for consumer sale or use. Do not use in a confined area with minimal air exchange. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (gloves, respirators, etc.) as required.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Do not expose to temperatures exceeding 50C/122F. Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

| Ingredient | C.A.S. No. | Agency | Limit type | Additional Comments |
|---------------------------|------------|--------|------------------------------|---|
| BUTANE | 106-97-8 | ACGIH | STEL:1000 ppm | |
| TOLUENE | 108-88-3 | ACGIH | TWA:20 ppm | A4: Not class. as human carcin, Ototoxicant |
| TOLUENE | 108-88-3 | OSHA | TWA:200 ppm;CEIL:300 ppm | |
| HEPTANE | 142-82-5 | ACGIH | TWA:400 ppm;STEL:500 ppm | |
| HEPTANE | 142-82-5 | OSHA | TWA:2000 mg/m3(500 ppm) | |
| Naphtha | 64742-89-8 | OSHA | TWA:400 mg/m3(100 ppm) | |
| PROPANE | 74-98-6 | ACGIH | Limit value not established: | simple asphyxiant |
| PROPANE | 74-98-6 | OSHA | TWA:1800 mg/m3(1000 ppm) | |
| METHYL ETHYL KETONE (MEK) | 78-93-3 | ACGIH | TWA:200 ppm;STEL:300 ppm | |
| METHYL ETHYL KETONE (MEK) | 78-93-3 | OSHA | TWA:590 mg/m3(200 ppm) | |

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Do not remain in area where available oxygen may be reduced. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates
 Half facepiece or full facepiece supplied-air respirator
 Organic vapor respirators may have short service life.

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state
 Color

Liquid
 Gray

Specific Physical Form:

Compressed Gas

Odor

Hydrocarbon

Odor threshold

No Data Available

pH

Not Applicable

Melting point

Not Applicable

Boiling Point

-44 - 325 °F

Flash Point

-78 °F [*Test Method*:Closed Cup] [*Details*:Based on butane]

Evaporation rate

>=1 [*Ref Std*:ETHER=1]

Flammability (solid, gas)

Not Applicable

Flammable Limits(LEL)

0.9 %

Flammable Limits(UEL)

Approximately 10 %

Vapor Pressure

No Data Available

Vapor Density

No Data Available

Density

1144 kg/l

Specific Gravity

1.15 [*Ref Std*:WATER=1] [*Details*:Reference standard: Water = 1]

Solubility In Water

No Data Available

Solubility- non-water

No Data Available

Partition coefficient: n-octanol/ water

No Data Available

Autoignition temperature

No Data Available

Decomposition temperature

No Data Available

Viscosity

No Data Available

Volatile Organic Compounds

Approximately 52 g/l *No Data Available*

Percent volatile

Approximately 88 % volume

VOC Less H2O & Exempt Solvents

No Data Available

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat

Sparks and/or flames

10.5. Incompatible materials

Strong acids
Strong bases
Strong oxidizing agents

10.6. Hazardous decomposition products

| <u>Substance</u> | <u>Condition</u> |
|-------------------------------|------------------|
| Hydrocarbons | Normal Use |
| Ketones | Normal Use |
| Toxic Vapor, Gas, Particulate | Normal Use |

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

May be harmful if inhaled. Simple Asphyxiation: Signs/symptoms may include increased heart rate, rapid respirations, drowsiness, headache, incoordination, altered judgement, nausea, vomiting, lethargy, seizures, coma, and may be fatal.

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.

Eye Contact:

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion:

May be harmful if swallowed.

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Single exposure, above recommended guidelines, may cause: Cardiac Sensitization: Signs/symptoms may include irregular

heartbeat (arrhythmia), faintness, chest pain, and may be fatal.

Prolonged or repeated exposure may cause target organ effects:

Ocular Effects: Signs/symptoms may include blurred or significantly impaired vision.

Auditory Effects: Signs/symptoms may include hearing impairment, balance dysfunction and ringing in the ears.

Olfactory Effects: Signs/symptoms may include decreased ability to detect odors and/or complete loss of smell.

Neurological Effects: Signs/symptoms may include personality changes, lack of coordination, sensory loss, tingling or numbness of the extremities, weakness, tremors, and/or changes in blood pressure and heart rate.

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

| Name | Route | Species | Value |
|--|--------------------------------|------------------------|--|
| Overall product | Dermal | | No data available; calculated ATE >5,000 mg/kg |
| Overall product | Inhalation-Dust/Mist(4 hr) | | No data available; calculated ATE5 - 12.5 mg/l |
| Overall product | Ingestion | | No data available; calculated ATE >5,000 mg/kg |
| ZINC | Dermal | Professional judgement | LD50 estimated to be > 5,000 mg/kg |
| ZINC | Inhalation-Dust/Mist (4 hours) | Rat | LC50 > 5.41 mg/l |
| ZINC | Ingestion | Rat | LD50 > 2,000 mg/kg |
| PROPANE | Inhalation-Gas (4 hours) | Rat | LC50 > 200,000 ppm |
| METHYL ETHYL KETONE (MEK) | Dermal | Rabbit | LD50 > 8,050 mg/kg |
| METHYL ETHYL KETONE (MEK) | Inhalation-Vapor (4 hours) | Rat | LC50 34.5 mg/l |
| METHYL ETHYL KETONE (MEK) | Ingestion | Rat | LD50 2,737 mg/kg |
| BUTANE | Inhalation-Gas (4 hours) | Rat | LC50 277,000 ppm |
| TOLUENE | Dermal | Rat | LD50 12,000 mg/kg |
| TOLUENE | Inhalation-Vapor (4 hours) | Rat | LC50 30 mg/l |
| TOLUENE | Ingestion | Rat | LD50 5,550 mg/kg |
| HEPTANE | Dermal | Rabbit | LD50 3,000 mg/kg |
| HEPTANE | Inhalation-Vapor (4 hours) | Rat | LC50 103 mg/l |
| HEPTANE | Ingestion | Rat | LD50 > 15,000 mg/kg |
| SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC | Dermal | Rabbit | LD50 3,000 mg/kg |
| SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC | Inhalation-Vapor (4 hours) | Rat | LC50 > 5.2 mg/l |
| SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC | Ingestion | Rat | LD50 > 5,000 mg/kg |

ATE = acute toxicity estimate

Skin Corrosion/Irritation

| Name | Species | Value |
|--|------------------------|---------------------------|
| PROPANE | Rabbit | Minimal irritation |
| METHYL ETHYL KETONE (MEK) | Rabbit | Minimal irritation |
| BUTANE | Professional judgement | No significant irritation |
| TOLUENE | Rabbit | Irritant |
| HEPTANE | Human | Mild irritant |
| SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC | Rabbit | Irritant |

Serious Eye Damage/Irritation

| Name | Species | Value |
|--|------------------------|---------------------------|
| ZINC | Rabbit | No significant irritation |
| PROPANE | Rabbit | Mild irritant |
| METHYL ETHYL KETONE (MEK) | Rabbit | Severe irritant |
| BUTANE | Rabbit | No significant irritation |
| TOLUENE | Rabbit | Moderate irritant |
| HEPTANE | Professional judgement | Moderate irritant |
| SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC | Rabbit | No significant irritation |

Skin Sensitization

| Name | Species | Value |
|---------|------------|----------------|
| TOLUENE | Guinea pig | Not classified |

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

| Name | Route | Value |
|--|----------|---------------|
| PROPANE | In Vitro | Not mutagenic |
| METHYL ETHYL KETONE (MEK) | In Vitro | Not mutagenic |
| BUTANE | In Vitro | Not mutagenic |
| TOLUENE | In Vitro | Not mutagenic |
| TOLUENE | In vivo | Not mutagenic |
| HEPTANE | In Vitro | Not mutagenic |
| SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC | In Vitro | Not mutagenic |

Carcinogenicity

| Name | Route | Species | Value |
|--|------------|---------|--|
| METHYL ETHYL KETONE (MEK) | Inhalation | Human | Not carcinogenic |
| TOLUENE | Dermal | Mouse | Some positive data exist, but the data are not sufficient for classification |
| TOLUENE | Ingestion | Rat | Some positive data exist, but the data are not sufficient for classification |
| TOLUENE | Inhalation | Mouse | Some positive data exist, but the data are not sufficient for classification |
| SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC | Dermal | Mouse | Some positive data exist, but the data are not sufficient for classification |

Reproductive Toxicity**Reproductive and/or Developmental Effects**

| Name | Route | Value | Species | Test Result | Exposure |
|------|-------|-------|---------|-------------|----------|
|------|-------|-------|---------|-------------|----------|

| | | | | | Duration |
|---------------------------|------------|--|-------|---------------------|------------------------|
| METHYL ETHYL KETONE (MEK) | Inhalation | Not classified for development | Rat | LOAEL 8.8 mg/l | during gestation |
| TOLUENE | Inhalation | Not classified for female reproduction | Human | NOAEL Not available | occupational exposure |
| TOLUENE | Inhalation | Not classified for male reproduction | Rat | NOAEL 2.3 mg/l | 1 generation |
| TOLUENE | Ingestion | Toxic to development | Rat | LOAEL 520 mg/kg/day | during gestation |
| TOLUENE | Inhalation | Toxic to development | Human | NOAEL Not available | poisoning and/or abuse |

Target Organ(s)

Specific Target Organ Toxicity - single exposure

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|--|------------|-----------------------------------|--|-------------------------|---------------------|------------------------|
| PROPANE | Inhalation | cardiac sensitization | Causes damage to organs | Human | NOAEL Not available | |
| PROPANE | Inhalation | central nervous system depression | May cause drowsiness or dizziness | Human | NOAEL Not available | |
| PROPANE | Inhalation | respiratory irritation | Not classified | Human | NOAEL Not available | |
| METHYL ETHYL KETONE (MEK) | Inhalation | central nervous system depression | May cause drowsiness or dizziness | official classification | NOAEL Not available | |
| METHYL ETHYL KETONE (MEK) | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | Human | NOAEL Not available | |
| METHYL ETHYL KETONE (MEK) | Ingestion | central nervous system depression | May cause drowsiness or dizziness | Professional judgement | NOAEL Not available | |
| METHYL ETHYL KETONE (MEK) | Ingestion | liver | Not classified | Rat | NOAEL Not available | not applicable |
| METHYL ETHYL KETONE (MEK) | Ingestion | kidney and/or bladder | Not classified | Rat | LOAEL 1,080 mg/kg | not applicable |
| BUTANE | Inhalation | cardiac sensitization | Causes damage to organs | Human | NOAEL Not available | |
| BUTANE | Inhalation | central nervous system depression | May cause drowsiness or dizziness | Human and animal | NOAEL Not available | |
| BUTANE | Inhalation | heart | Not classified | Dog | NOAEL 5,000 ppm | 25 minutes |
| BUTANE | Inhalation | respiratory irritation | Not classified | Rabbit | NOAEL Not available | |
| TOLUENE | Inhalation | central nervous system depression | May cause drowsiness or dizziness | Human | NOAEL Not available | |
| TOLUENE | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | Human | NOAEL Not available | |
| TOLUENE | Inhalation | immune system | Not classified | Mouse | NOAEL 0.004 mg/l | 3 hours |
| TOLUENE | Ingestion | central nervous system depression | May cause drowsiness or dizziness | Human | NOAEL Not available | poisoning and/or abuse |
| HEPTANE | Inhalation | central nervous system depression | May cause drowsiness or dizziness | Human | NOAEL Not available | |
| HEPTANE | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | Human | NOAEL Not available | |
| HEPTANE | Ingestion | central nervous system depression | May cause drowsiness or dizziness | Human | NOAEL Not available | |
| SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC | Inhalation | central nervous system depression | May cause drowsiness or dizziness | Human and animal | NOAEL Not available | |
| SOLVENT NAPHTHA | Inhalation | respiratory irritation | Some positive data exist, but the | | NOAEL Not | |

| | | | | | | |
|--|-----------|-----------------------------------|--|------------------------|---------------------|--|
| (PETROLEUM), LIGHT ALIPHATIC | | | data are not sufficient for classification | | available | |
| SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC | Ingestion | central nervous system depression | May cause drowsiness or dizziness | Professional judgement | NOAEL Not available | |

Specific Target Organ Toxicity - repeated exposure

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|---------------------------|------------|--|--|-------------------------|-----------------------|------------------------|
| METHYL ETHYL KETONE (MEK) | Dermal | nervous system | Not classified | Guinea pig | NOAEL Not available | 31 weeks |
| METHYL ETHYL KETONE (MEK) | Inhalation | liver kidney and/or bladder heart endocrine system gastrointestinal tract bone, teeth, nails, and/or hair hematopoietic system immune system muscles | Not classified | Rat | NOAEL 14.7 mg/l | 90 days |
| METHYL ETHYL KETONE (MEK) | Ingestion | liver | Not classified | Rat | NOAEL Not available | 7 days |
| METHYL ETHYL KETONE (MEK) | Ingestion | nervous system | Not classified | Rat | NOAEL 173 mg/kg/day | 90 days |
| BUTANE | Inhalation | kidney and/or bladder blood | Not classified | Rat | NOAEL 4,489 ppm | 90 days |
| TOLUENE | Inhalation | auditory system eyes olfactory system | Causes damage to organs through prolonged or repeated exposure | Human | NOAEL Not available | poisoning and/or abuse |
| TOLUENE | Inhalation | nervous system | May cause damage to organs though prolonged or repeated exposure | Human | NOAEL Not available | poisoning and/or abuse |
| TOLUENE | Inhalation | respiratory system | Some positive data exist, but the data are not sufficient for classification | Rat | LOAEL 2.3 mg/l | 15 months |
| TOLUENE | Inhalation | heart liver kidney and/or bladder | Not classified | Rat | NOAEL 11.3 mg/l | 15 weeks |
| TOLUENE | Inhalation | endocrine system | Not classified | Rat | NOAEL 1.1 mg/l | 4 weeks |
| TOLUENE | Inhalation | immune system | Not classified | Mouse | NOAEL Not available | 20 days |
| TOLUENE | Inhalation | bone, teeth, nails, and/or hair | Not classified | Mouse | NOAEL 1.1 mg/l | 8 weeks |
| TOLUENE | Inhalation | hematopoietic system vascular system | Not classified | Human | NOAEL Not available | occupational exposure |
| TOLUENE | Inhalation | gastrointestinal tract | Not classified | Multiple animal species | NOAEL 11.3 mg/l | 15 weeks |
| TOLUENE | Ingestion | nervous system | Some positive data exist, but the data are not sufficient for classification | Rat | NOAEL 625 mg/kg/day | 13 weeks |
| TOLUENE | Ingestion | heart | Not classified | Rat | NOAEL 2,500 mg/kg/day | 13 weeks |
| TOLUENE | Ingestion | liver kidney and/or bladder | Not classified | Multiple animal species | NOAEL 2,500 mg/kg/day | 13 weeks |
| TOLUENE | Ingestion | hematopoietic system | Not classified | Mouse | NOAEL 600 mg/kg/day | 14 days |
| TOLUENE | Ingestion | endocrine system | Not classified | Mouse | NOAEL 105 mg/kg/day | 28 days |
| TOLUENE | Ingestion | immune system | Not classified | Mouse | NOAEL 105 mg/kg/day | 4 weeks |
| HEPTANE | Inhalation | liver nervous system kidney | Not classified | Rat | NOAEL 12 mg/l | 26 weeks |

and/or bladder

Aspiration Hazard

| Name | Value |
|--|-------------------|
| TOLUENE | Aspiration hazard |
| HEPTANE | Aspiration hazard |
| SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC | Aspiration hazard |

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information**Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations**13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): D001 (Ignitable), D035 (Methyl ethyl ketone)

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information**15.1. US Federal Regulations**

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:**Physical Hazards**

Flammable (gases, aerosols, liquids, or solids)

Gas under pressure

Health Hazards

Reproductive toxicity

Serious eye damage or eye irritation

Simple Asphyxiant

Specific target organ toxicity (single or repeated exposure)

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

| <u>Ingredient</u> | <u>C.A.S. No</u> | <u>% by Wt</u> |
|--------------------------|-------------------------|-----------------------|
| TOLUENE | 108-88-3 | Trade Secret 2 - 5 |
| ZINC | 7440-66-6 | Trade Secret 45 - 53 |

This material contains a chemical which requires export notification under TSCA Section 12[b]:**15.2. State Regulations**

Contact 3M for more information.

California Proposition 65

| <u>Ingredient</u> | <u>C.A.S. No.</u> | <u>Listing</u> |
|--------------------------|--------------------------|-----------------------|
| TOLUENE | 108-88-3 | Developmental Toxin |

15.3. Chemical Inventories

The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information.

The components of this product are in compliance with the new substance notification requirements of CEPA.

The components of this material are in compliance with the China "Measures on Environmental Management of New Chemical Substance". Certain restrictions may apply. Contact the selling division for additional information.

The components of this material are in compliance with the provisions of the Korean Toxic Chemical Control Law. Certain restrictions may apply. Contact the selling division for additional information.

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

| |
|--|
| This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200. |
|--|

SECTION 16: Other information**NFPA Hazard Classification****Health: 2 Flammability: 4 Instability: 1 Special Hazards: None**

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

HMIS Hazard Classification**Health: *2 Flammability: 4 Physical Hazard: 0 Personal Protection: X - See PPE section.**

Hazardous Material Identification System (HMIS® IV) hazard ratings are designed to inform employees of chemical hazards

in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® IV ratings are to be used with a fully implemented HMIS® IV program. HMIS® is a registered mark of the American Coatings Association (ACA).

| | | | |
|------------------------|-----------|-------------------------|----------|
| Document Group: | 08-1276-8 | Version Number: | 12.01 |
| Issue Date: | 04/30/21 | Supersedes Date: | 05/21/18 |

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com