



## Safety Data Sheet

Copyright, 2016, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

|                        |           |                         |               |
|------------------------|-----------|-------------------------|---------------|
| <b>Document Group:</b> | 36-9476-7 | <b>Version Number:</b>  | 1.00          |
| <b>Issue Date:</b>     | 11/07/16  | <b>Supersedes Date:</b> | Initial Issue |

### Product identifier

3M™ Scotchcast™ Electrical Resin 9N (A & B)

### ID Number(s):

80-6116-1698-0, 80-6116-1701-2, 80-6116-1704-6

### Recommended use

Electrical, Two Part Curing System For Electronic Components

### Supplier's details

|                      |   |
|----------------------|---|
| <b>MANUFACTURER:</b> | 3M                                      |
| <b>DIVISION:</b>     | Electrical Markets Division             |
| <b>ADDRESS:</b>      | 3M Center, St. Paul, MN 55144-1000, USA |
| <b>Telephone:</b>    | 1-888-3M HELPS (1-888-364-3577)         |

### Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

**This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet (SDS), Article Information Sheet (AIS), or Article Information Letter (AIL) for each of these components is included. Please do not separate the component documents from this cover page. The document numbers for components of this product are:**

36-8589-8, 36-8402-4

**DISCLAIMER:** The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

3M USA SDSs are available at [www.3M.com](http://www.3M.com)



## Safety Data Sheet

Copyright, 2018, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

|                        |           |                         |          |
|------------------------|-----------|-------------------------|----------|
| <b>Document Group:</b> | 36-8402-4 | <b>Version Number:</b>  | 1.02     |
| <b>Issue Date:</b>     | 01/04/18  | <b>Supersedes Date:</b> | 10/24/17 |

### SECTION 1: Identification

#### 1.1. Product identifier

3M™ Scotchcast™ Electrical Resin 9N Part B

#### Product Identification Numbers

LH-A100-2002-8, LH-A100-2002-9, 80-6116-1700-4, 80-6116-1702-0, 80-6116-1705-3

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Electrical, Part B of two part electrical resin

#### 1.3. Supplier's details

|                      |   |
|----------------------|---|
| <b>MANUFACTURER:</b> | 3M                                      |
| <b>DIVISION:</b>     | Electrical Markets Division             |
| <b>ADDRESS:</b>      | 3M Center, St. Paul, MN 55144-1000, USA |
| <b>Telephone:</b>    | 1-888-3M HELPS (1-888-364-3577)         |

#### 1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

### SECTION 2: Hazard identification

#### 2.1. Hazard classification

Serious Eye Damage/Irritation: Category 1.

Skin Corrosion/Irritation: Category 2.

Respiratory Sensitizer: Category 1.

Skin Sensitizer: Category 1A.

Reproductive Toxicity: Category 1B.

#### 2.2. Label elements

##### Signal word

Danger

##### Symbols

Corrosion | Health Hazard |

**Pictograms****Hazard Statements**

Causes serious eye damage.  
 Causes skin irritation.  
 May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
 May cause an allergic skin reaction.  
 May damage fertility or the unborn child.

**Precautionary Statements****Prevention:**

Obtain special instructions before use.  
 Do not handle until all safety precautions have been read and understood.  
 Avoid breathing dust/fume/gas/mist/vapors/spray.  
 In case of inadequate ventilation wear respiratory protection.  
 Wear eye/face protection.  
 Wear protective gloves.  
 Wash thoroughly after handling.  
 Contaminated work clothing must not be allowed out of the workplace.

**Response:**

IF INHALED: If breathing is difficult, remove person to fresh air and keep comfortable for breathing.  
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 IF ON SKIN: Wash with plenty of soap and water.  
 Immediately call a POISON CENTER or doctor/physician.  
 If skin irritation or rash occurs: Get medical advice/attention.  
 Take off contaminated clothing and wash it before reuse.

**Storage:**

Store locked up.

**Disposal:**

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

**Supplemental Information:**

Persons previously sensitized to amines may develop a cross-sensitization reaction to certain other amines.

54% of the mixture consists of ingredients of unknown acute oral toxicity.  
 54% of the mixture consists of ingredients of unknown acute dermal toxicity.

**SECTION 3: Composition/information on ingredients**

| Ingredient                                  | C.A.S. No. | % by Wt                |
|---|------------|------------------------|
| FATTY ACID                                  | 68911-25-1 | 40 - 70 Trade Secret * |
| MICA-GROUP MINERALS                         | 12001-26-2 | 15 - 30 Trade Secret * |
| TALC  | 14807-96-6 | 15 - 30 Trade Secret * |
| Benzene, ethenyl-, homopolymer (oligomeric) | 9003-53-6  | 7 - 15 Trade Secret *  |

|   |           |                        |
|---|-----------|------------------------|
| BIS(3-AMINOPROPYL) ETHER OF DIETHYLENE GLYCOL     | 4246-51-9 | 7 - 15 Trade Secret *  |
| Cashew, nutshell liq. occidentale, Anacardiaceae. | 8007-24-7 | 1 - 5 Trade Secret *   |
| DIETHYLENETRIAMINE                                | 111-40-0  | 0.1 - 1 Trade Secret * |
| Toluene   | 108-88-3  | < 0.5 Trade Secret *   |

\*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

#### Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

#### Eye Contact:

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

#### If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable.

## SECTION 5: Fire-fighting measures

### 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

### 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

### Hazardous Decomposition or By-Products

#### Substance

Carbon monoxide  
Carbon dioxide  
Oxides of Nitrogen

#### Condition

During Combustion  
During Combustion  
During Combustion

### 5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

## SECTION 6: Accidental release measures

**6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

**6.2. Environmental precautions**

Avoid release to the environment.

**6.3. Methods and material for containment and cleaning up**

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

**SECTION 7: Handling and storage**

**7.1. Precautions for safe handling**

For industrial or professional use only. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (gloves, respirators, etc.) as required.

**7.2. Conditions for safe storage including any incompatibilities**

Store away from strong bases. Store away from oxidizing agents.

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

**Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

| Ingredient          | C.A.S. No. | Agency | Limit type                           | Additional Comments            |
|---------------------|------------|--------|--------------------------------------|--------------------------------|
| Toluene             | 108-88-3   | ACGIH  | TWA:20 ppm                           | A4: Not class. as human carcin |
| Toluene             | 108-88-3   | OSHA   | TWA:200 ppm;CEIL:300 ppm             |                                |
| DIETHYLENETRIAMINE  | 111-40-0   | ACGIH  | TWA:1 ppm                            | SKIN                           |
| MICA-GROUP MINERALS | 12001-26-2 | ACGIH  | TWA(respirable fraction):3 mg/m3     |                                |
| MICA-GROUP MINERALS | 12001-26-2 | OSHA   | TWA:20 millions of particles/cu. ft. |                                |
| TALC                | 14807-96-6 | ACGIH  | TWA(respirable fraction):2 mg/m3     | A4: Not class. as human carcin |
| TALC                | 14807-96-6 | OSHA   | TWA:2 mg/m3                          |                                |

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

## 8.2. Exposure controls

### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

### 8.2.2. Personal protective equipment (PPE)

#### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full Face Shield  
Indirect Vented Goggles

#### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

#### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

|                                  |  |
|----------------------------------|--|
| <b>General Physical Form:</b>    | Liquid                                   |
| <b>Specific Physical Form:</b>   | Viscous                                  |
| <b>Odor, Color, Grade:</b>       | Brown viscous liquid with slight odor    |
| <b>Odor threshold</b>            | <i>No Data Available</i>                 |
| <b>pH</b>                        | <i>Not Applicable</i>                    |
| <b>Melting point</b>             | <i>No Data Available</i>                 |
| <b>Boiling Point</b>             | ≥ 356 °F                                 |
| <b>Flash Point</b>               | 180 °C [ <i>Test Method:</i> Closed Cup] |
| <b>Evaporation rate</b>          | <i>No Data Available</i>                 |
| <b>Flammability (solid, gas)</b> | Not Applicable                           |
| <b>Flammable Limits(LEL)</b>     | <i>No Data Available</i>                 |
| <b>Flammable Limits(UEL)</b>     | <i>No Data Available</i>                 |
| <b>Vapor Pressure</b>            | <i>Not Applicable</i>                    |
| <b>Vapor Density</b>             | <i>Not Applicable</i>                    |
| <b>Density</b>                   | 1.26 g/ml - 1.3 g/ml                     |

|  |                                      |
|--|--------------------------------------|
| <b>Specific Gravity</b>                        | 1.26 - 1.3 [Ref Std: WATER=1]        |
| <b>Solubility in Water</b>                     | Nil                                  |
| <b>Solubility- non-water</b>                   | No Data Available                    |
| <b>Partition coefficient: n-octanol/ water</b> | No Data Available                    |
| <b>Autoignition temperature</b>                | No Data Available                    |
| <b>Decomposition temperature</b>               | No Data Available                    |
| <b>Viscosity</b>                               | 9,000 centipoise - 19,000 centipoise |
| <b>Average particle size</b>                   | No Data Available                    |
| <b>Bulk density</b>                            | No Data Available                    |
| <b>Hazardous Air Pollutants</b>                | No Data Available                    |
| <b>Molecular weight</b>                        | No Data Available                    |
| <b>Volatile Organic Compounds</b>              | No Data Available                    |
| <b>Percent volatile</b>                        | Negligible                           |
| <b>Softening point</b>                         | No Data Available                    |
| <b>VOC Less H2O &amp; Exempt Solvents</b>      | No Data Available                    |

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

This material is considered to be non reactive under normal use conditions.

### 10.2. Chemical stability

Stable.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

Not determined

### 10.5. Incompatible materials

Strong oxidizing agents

Strong bases

No Data Available

### 10.6. Hazardous decomposition products

| <u>Substance</u>         | <u>Condition</u>            |
|--------------------------|-----------------------------|
| Aldehydes                | Oxidation, heat or reaction |
| Amine Compounds          | Oxidation, heat or reaction |
| Irritant Vapors or Gases | Oxidation, heat or reaction |

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.



## 11.1. Information on Toxicological effects

### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Allergic Respiratory Reaction: Signs/symptoms may include difficulty breathing, wheezing, cough, and tightness of chest.

May cause additional health effects (see below).

#### Skin Contact:

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain.

Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

#### Eye Contact:

Corrosive (Eye Burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

#### Ingestion:

May be harmful if swallowed.

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

#### Additional Health Effects:

#### Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

#### Additional Information:

Persons previously sensitized to amines may develop a cross-sensitization reaction to certain other amines.

#### Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

#### Acute Toxicity

| Name  | Route                          | Species | Value   |
|---|--------------------------------|---------|---|
| Overall product                               | Dermal                         |         | No data available; calculated ATE >5,000 mg/kg        |
| Overall product                               | Ingestion                      |         | No data available; calculated ATE 2,000 - 5,000 mg/kg |
| MICA-GROUP MINERALS                           | Dermal                         |         | LD50 estimated to be > 5,000 mg/kg                    |
| MICA-GROUP MINERALS                           | Ingestion                      |         | LD50 estimated to be 2,000 - 5,000 mg/kg              |
| TALC  | Dermal                         |         | LD50 estimated to be > 5,000 mg/kg                    |
| TALC  | Ingestion                      |         | LD50 estimated to be > 5,000 mg/kg                    |
| BIS(3-AMINOPROPYL) ETHER OF DIETHYLENE GLYCOL | Dermal                         | Rabbit  | LD50 2,500 mg/kg                                      |
| BIS(3-AMINOPROPYL) ETHER OF DIETHYLENE GLYCOL | Ingestion                      | Rat     | LD50 3,160 mg/kg                                      |
| DIETHYLENETRIAMINE                            | Dermal                         | Rabbit  | LD50 1,045 mg/kg                                      |
| DIETHYLENETRIAMINE                            | Inhalation-Dust/Mist (4 hours) | Rat     | LC50 > 0.07 mg/l                                      |
| DIETHYLENETRIAMINE                            | Ingestion                      | Rat     | LD50 819 mg/kg  |

|         |                            |     |                   |
|---------|----------------------------|-----|-------------------|
| Toluene | Dermal                     | Rat | LD50 12,000 mg/kg |
| Toluene | Inhalation-Vapor (4 hours) | Rat | LC50 30 mg/l      |
| Toluene | Ingestion                  | Rat | LD50 5,550 mg/kg  |

ATE = acute toxicity estimate

### Skin Corrosion/Irritation

| Name  | Species | Value                     |
|---|---------|---------------------------|
| FATTY ACID                                    | Rabbit  | Irritant                  |
| TALC  | Rabbit  | No significant irritation |
| BIS(3-AMINOPROPYL) ETHER OF DIETHYLENE GLYCOL | Rabbit  | Corrosive                 |
| DIETHYLENETRIAMINE                            | Rabbit  | Corrosive                 |
| Toluene                                       | Rabbit  | Irritant                  |

### Serious Eye Damage/Irritation

| Name  | Species                | Value                     |
|---|------------------------|---------------------------|
| FATTY ACID                                    | similar health hazards | Corrosive                 |
| TALC  | Rabbit                 | No significant irritation |
| BIS(3-AMINOPROPYL) ETHER OF DIETHYLENE GLYCOL | similar health hazards | Corrosive                 |
| DIETHYLENETRIAMINE                            | Rabbit                 | Corrosive                 |
| Toluene                                       | Rabbit                 | Moderate irritant         |

### Skin Sensitization

| Name               | Species    | Value          |
|--------------------|------------|----------------|
| FATTY ACID         | Guinea pig | Sensitizing    |
| DIETHYLENETRIAMINE | Guinea pig | Sensitizing    |
| Toluene            | Guinea pig | Not classified |

### Respiratory Sensitization

| Name               | Species | Value          |
|--------------------|---------|----------------|
| TALC               | Human   | Not classified |
| DIETHYLENETRIAMINE | Human   | Sensitizing    |

### Germ Cell Mutagenicity

| Name               | Route    | Value         |
|--------------------|----------|---------------|
| TALC               | In Vitro | Not mutagenic |
| TALC               | In vivo  | Not mutagenic |
| DIETHYLENETRIAMINE | In Vitro | Not mutagenic |
| Toluene            | In Vitro | Not mutagenic |
| Toluene            | In vivo  | Not mutagenic |

### Carcinogenicity

| Name               | Route      | Species                 | Value  |
|--------------------|------------|-------------------------|--|
| TALC               | Inhalation | Rat                     | Some positive data exist, but the data are not sufficient for classification |
| DIETHYLENETRIAMINE | Dermal     | Multiple animal species | Not carcinogenic   |
| Toluene            | Dermal     | Mouse                   | Some positive data exist, but the data are not sufficient for classification |

|         |            |       |  |
|---------|------------|-------|--|
| Toluene | Ingestion  | Rat   | Some positive data exist, but the data are not sufficient for classification |
| Toluene | Inhalation | Mouse | Some positive data exist, but the data are not sufficient for classification |

## Reproductive Toxicity

### Reproductive and/or Developmental Effects

| Name  | Route      | Value                                  | Species | Test Result         | Exposure Duration              |
|---|------------|--|---------|---------------------|--------------------------------|
| TALC  | Ingestion  | Not classified for development         | Rat     | NOAEL 1,600 mg/kg   | during organogenesis           |
| Benzene, ethenyl-, homopolymer (oligomeric) | Ingestion  | Toxic to female reproduction           | Rat     | NOAEL 5 mg/kg/day   | prematuring into lactation     |
| DIETHYLENETRIAMINE                          | Ingestion  | Not classified for male reproduction   | Rat     | NOAEL 300 mg/kg/day | 28 days                        |
| DIETHYLENETRIAMINE                          | Ingestion  | Not classified for development         | Rat     | NOAEL 300 mg/kg/day | prematuring & during gestation |
| DIETHYLENETRIAMINE                          | Ingestion  | Not classified for female reproduction | Rat     | NOAEL 30 mg/kg/day  | prematuring & during gestation |
| Toluene                                     | Inhalation | Not classified for female reproduction | Human   | NOAEL Not available | occupational exposure          |
| Toluene                                     | Inhalation | Not classified for male reproduction   | Rat     | NOAEL 2.3 mg/l      | 1 generation                   |
| Toluene                                     | Ingestion  | Toxic to development                   | Rat     | LOAEL 520 mg/kg/day | during gestation               |
| Toluene                                     | Inhalation | Toxic to development                   | Human   | NOAEL Not available | poisoning and/or abuse         |

## Target Organ(s)

### Specific Target Organ Toxicity - single exposure

| Name  | Route      | Target Organ(s)                   | Value  | Species | Test Result         | Exposure Duration      |
|---|------------|-----------------------------------|--|---------|---------------------|------------------------|
| BIS(3-AMINOPROPYL) ETHER OF DIETHYLENE GLYCOL | Inhalation | respiratory irritation            | Some positive data exist, but the data are not sufficient for classification |         | NOAEL Not available |                        |
| DIETHYLENETRIAMINE                            | Inhalation | respiratory irritation            | Some positive data exist, but the data are not sufficient for classification |         | NOAEL Not available |                        |
| Toluene                                       | Inhalation | central nervous system depression | May cause drowsiness or dizziness  | Human   | NOAEL Not available |                        |
| Toluene                                       | Inhalation | respiratory irritation            | Some positive data exist, but the data are not sufficient for classification | Human   | NOAEL Not available |                        |
| Toluene                                       | Inhalation | immune system                     | Not classified   | Mouse   | NOAEL 0.004 mg/l    | 3 hours                |
| Toluene                                       | Ingestion  | central nervous system depression | May cause drowsiness or dizziness  | Human   | NOAEL Not available | poisoning and/or abuse |

### Specific Target Organ Toxicity - repeated exposure

| Name                | Route      | Target Organ(s)                                  | Value  | Species | Test Result           | Exposure Duration     |
|---------------------|------------|--|--|---------|-----------------------|-----------------------|
| MICA-GROUP MINERALS | Inhalation | pneumoconiosis                                   | Causes damage to organs through prolonged or repeated exposure | Human   | NOAEL Not available   | occupational exposure |
| TALC                | Inhalation | pneumoconiosis                                   | Causes damage to organs through prolonged or repeated exposure | Human   | NOAEL Not available   | occupational exposure |
| TALC                | Inhalation | pulmonary fibrosis   respiratory system          | Not classified   | Rat     | NOAEL 18 mg/m3        | 113 weeks             |
| DIETHYLENETRIAMINE  | Ingestion  | endocrine system   liver   kidney and/or bladder | Not classified   | Rat     | NOAEL 1,210 mg/kg/day | 90 days               |

|         |            |  |  |                         |                       |                        |
|---------|------------|--|--|-------------------------|-----------------------|------------------------|
| Toluene | Inhalation | auditory system   nervous system   eyes   olfactory system | Causes damage to organs through prolonged or repeated exposure               | Human                   | NOAEL Not available   | poisoning and/or abuse |
| Toluene | Inhalation | respiratory system   | Some positive data exist, but the data are not sufficient for classification | Rat                     | LOAEL 2.3 mg/l        | 15 months              |
| Toluene | Inhalation | heart   liver   kidney and/or bladder                      | Not classified   | Rat                     | NOAEL 11.3 mg/l       | 15 weeks               |
| Toluene | Inhalation | endocrine system   | Not classified   | Rat                     | NOAEL 1.1 mg/l        | 4 weeks                |
| Toluene | Inhalation | immune system  | Not classified   | Mouse                   | NOAEL Not available   | 20 days                |
| Toluene | Inhalation | bone, teeth, nails, and/or hair                            | Not classified   | Mouse                   | NOAEL 1.1 mg/l        | 8 weeks                |
| Toluene | Inhalation | hematopoietic system   vascular system                     | Not classified   | Human                   | NOAEL Not available   | occupational exposure  |
| Toluene | Ingestion  | nervous system   | Some positive data exist, but the data are not sufficient for classification | Rat                     | NOAEL 625 mg/kg/day   | 13 weeks               |
| Toluene | Ingestion  | heart  | Not classified   | Rat                     | NOAEL 2,500 mg/kg/day | 13 weeks               |
| Toluene | Ingestion  | liver   kidney and/or bladder                              | Not classified   | Multiple animal species | NOAEL 2,500 mg/kg/day | 13 weeks               |
| Toluene | Ingestion  | hematopoietic system                                       | Not classified   | Mouse                   | NOAEL 600 mg/kg/day   | 14 days                |
| Toluene | Ingestion  | endocrine system   | Not classified   | Mouse                   | NOAEL 105 mg/kg/day   | 28 days                |
| Toluene | Ingestion  | immune system  | Not classified   | Mouse                   | NOAEL 105 mg/kg/day   | 4 weeks                |

**Aspiration Hazard**

| Name    | Value             |
|---------|-------------------|
| Toluene | Aspiration hazard |

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

**SECTION 12: Ecological information**

**Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

**Chemical fate information**

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

**SECTION 13: Disposal considerations**

**13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. If no other disposal options are available, waste product that has been completely cured or polymerized may be placed in a landfill properly designed for industrial waste. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations

classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

**EPA Hazardous Waste Number (RCRA):** D018 (Benzene)

## SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

## SECTION 15: Regulatory information

### 15.1. US Federal Regulations

Contact 3M for more information.

### EPCRA 311/312 Hazard Classifications:

#### Physical Hazards

Not applicable

#### Health Hazards

Reproductive toxicity

Respiratory or Skin Sensitization

Serious eye damage or eye irritation

Skin Corrosion or Irritation

### 15.2. State Regulations

Contact 3M for more information.

### 15.3. Chemical Inventories

The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information.

The components of this product are in compliance with the new substance notification requirements of CEPA.

The components of this material are in compliance with the China "Measures on Environmental Management of New Chemical Substance". Certain restrictions may apply. Contact the selling division for additional information.

The components of this material are in compliance with the provisions of the Korean Toxic Chemical Control Law. Certain restrictions may apply. Contact the selling division for additional information.

The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information.

The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information.

The components of this product are in compliance with the chemical notification requirements of TSCA.

Contact 3M for more information.

### 15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

## SECTION 16: Other information

### NFPA Hazard Classification

**Health:** 3 **Flammability:** 1 **Instability:** 0 **Special Hazards:** None  
**Corrosive:** Yes

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

### HMIS Hazard Classification

**Health:** \*3 **Flammability:** 1 **Physical Hazard:** 0 **Personal Protection:** X - See PPE section.

Hazardous Material Identification System (HMIS® IV) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® IV ratings are to be used with a fully implemented HMIS® IV program. HMIS® is a registered mark of the American Coatings Association (ACA).

|                        |           |                         |          |
|------------------------|-----------|-------------------------|----------|
| <b>Document Group:</b> | 36-8402-4 | <b>Version Number:</b>  | 1.02     |
| <b>Issue Date:</b>     | 01/04/18  | <b>Supersedes Date:</b> | 10/24/17 |

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at [www.3M.com](http://www.3M.com)



## Safety Data Sheet

Copyright, 2018, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

|                        |           |                         |          |
|------------------------|-----------|-------------------------|----------|
| <b>Document Group:</b> | 36-8589-8 | <b>Version Number:</b>  | 2.02     |
| <b>Issue Date:</b>     | 01/04/18  | <b>Supersedes Date:</b> | 12/11/17 |

### SECTION 1: Identification

#### 1.1. Product identifier

3M™ Scotchcast™ Electrical Resin 9N Part A

#### Product Identification Numbers

LH-A100-2005-4, LH-A100-2005-9, 80-6116-1699-8, 80-6116-1703-8

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Electrical, Part A of two part electrical resin curing system

#### 1.3. Supplier's details

|                      |   |
|----------------------|---|
| <b>MANUFACTURER:</b> | 3M                                      |
| <b>DIVISION:</b>     | Electrical Markets Division             |
| <b>ADDRESS:</b>      | 3M Center, St. Paul, MN 55144-1000, USA |
| <b>Telephone:</b>    | 1-888-3M HELPS (1-888-364-3577)         |

#### 1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

### SECTION 2: Hazard identification

#### 2.1. Hazard classification

Serious Eye Damage/Irritation: Category 2B.

Skin Sensitizer: Category 1.

#### 2.2. Label elements

##### Signal word

Warning

##### Symbols

Exclamation mark |

##### Pictograms

**Hazard Statements**

Causes eye irritation.  
May cause an allergic skin reaction.

**Precautionary Statements****Prevention:**

Avoid breathing dust/fume/gas/mist/vapors/spray.  
Wear protective gloves.  
Wash thoroughly after handling.  
Contaminated work clothing must not be allowed out of the workplace.

**Response:**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
If eye irritation persists: Get medical advice/attention.  
IF ON SKIN: Wash with plenty of soap and water.  
If skin irritation or rash occurs: Get medical advice/attention.  
Wash contaminated clothing before reuse.

**Disposal:**

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

### SECTION 3: Composition/information on ingredients

| Ingredient  | C.A.S. No. | % by Wt                |
|---|------------|------------------------|
| 4,4'-ISOPROPYLIDENEDIPHENOL-EPICHLOROHYDRIN POLYMER | 25068-38-6 | 60 - 70 Trade Secret * |
| MICA-GROUP MINERALS                                 | 12001-26-2 | 10 - 20 Trade Secret * |
| TALC  | 14807-96-6 | 10 - 20 Trade Secret * |

\*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

### SECTION 4: First aid measures

**4.1. Description of first aid measures****Inhalation:**

Remove person to fresh air. If you feel unwell, get medical attention.

**Skin Contact:**

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

**Eye Contact:**

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.



**If Swallowed:**

Rinse mouth. If you feel unwell, get medical attention.

**4.2. Most important symptoms and effects, both acute and delayed**

See Section 11.1. Information on toxicological effects.

**4.3. Indication of any immediate medical attention and special treatment required**

Not applicable.

**SECTION 5: Fire-fighting measures**

**5.1. Suitable extinguishing media**

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

**5.2. Special hazards arising from the substance or mixture**

None inherent in this product.

**Hazardous Decomposition or By-Products**

Substance

Aldehydes  
Amine Compounds  
Carbon monoxide  
Carbon dioxide

Condition

During Combustion  
During Combustion  
During Combustion  
During Combustion

**5.3. Special protective actions for fire-fighters**

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

**SECTION 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

**6.2. Environmental precautions**

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

**6.3. Methods and material for containment and cleaning up**

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

**SECTION 7: Handling and storage**

**7.1. Precautions for safe handling**

For industrial or professional use only. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or

on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse.

**7.2. Conditions for safe storage including any incompatibilities**

No special storage requirements.

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

**Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

| Ingredient          | C.A.S. No. | Agency | Limit type                           | Additional Comments            |
|---------------------|------------|--------|--------------------------------------|--------------------------------|
| MICA-GROUP MINERALS | 12001-26-2 | ACGIH  | TWA(respirable fraction):3 mg/m3     |                                |
| MICA-GROUP MINERALS | 12001-26-2 | OSHA   | TWA:20 millions of particles/cu. ft. |                                |
| TALC                | 14807-96-6 | OSHA   | TWA:2 mg/m3                          |                                |
| TALC                | 14807-96-6 | ACGIH  | TWA(respirable fraction):2 mg/m3     | A4: Not class. as human carcin |

ACGIH : American Conference of Governmental Industrial Hygienists  
 AIHA : American Industrial Hygiene Association  
 CMRG : Chemical Manufacturer's Recommended Guidelines  
 OSHA : United States Department of Labor - Occupational Safety and Health Administration  
 TWA: Time-Weighted-Average  
 STEL: Short Term Exposure Limit  
 CEIL: Ceiling

**8.2. Exposure controls**

**8.2.1. Engineering controls**

No engineering controls required.

**8.2.2. Personal protective equipment (PPE)**

**Eye/face protection**

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:  
 Indirect Vented Goggles

**Skin/hand protection**

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

**Respiratory protection**

None required.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

|  |  |
|--|--|
| <b>General Physical Form:</b>                  | Liquid                                   |
| <b>Odor, Color, Grade:</b>                     | Deep rust-red, viscous liquid            |
| <b>Odor threshold</b>                          | <i>No Data Available</i>                 |
| <b>pH</b>                                      | <i>Not Applicable</i>                    |
| <b>Melting point</b>                           | <i>No Data Available</i>                 |
| <b>Boiling Point</b>                           | <i>No Data Available</i>                 |
| <b>Flash Point</b>                             | 356 °F [ <i>Test Method:</i> Closed Cup] |
| <b>Evaporation rate</b>                        | <i>Not Applicable</i>                    |
| <b>Flammability (solid, gas)</b>               | Not Applicable                           |
| <b>Flammable Limits(LEL)</b>                   | <i>No Data Available</i>                 |
| <b>Flammable Limits(UEL)</b>                   | <i>No Data Available</i>                 |
| <b>Vapor Pressure</b>                          | <i>No Data Available</i>                 |
| <b>Vapor Density</b>                           | <i>Not Applicable</i>                    |
| <b>Density</b>                                 | <i>No Data Available</i>                 |
| <b>Specific Gravity</b>                        | 1.43 - 1.47 [ <i>Ref Std:</i> WATER=1]   |
| <b>Solubility in Water</b>                     | Nil                                      |
| <b>Solubility- non-water</b>                   | <i>No Data Available</i>                 |
| <b>Partition coefficient: n-octanol/ water</b> | <i>No Data Available</i>                 |
| <b>Autoignition temperature</b>                | <i>No Data Available</i>                 |
| <b>Decomposition temperature</b>               | <i>No Data Available</i>                 |
| <b>Viscosity</b>                               | 55,000 centipoise - 200,000 centipoise   |
| <b>Average particle size</b>                   | <i>No Data Available</i>                 |
| <b>Bulk density</b>                            | <i>No Data Available</i>                 |
| <b>Hazardous Air Pollutants</b>                | <i>No Data Available</i>                 |
| <b>Molecular weight</b>                        | <i>No Data Available</i>                 |
| <b>Volatile Organic Compounds</b>              | <i>No Data Available</i>                 |
| <b>Percent volatile</b>                        | <i>No Data Available</i>                 |
| <b>Softening point</b>                         | <i>No Data Available</i>                 |
| <b>VOC Less H2O &amp; Exempt Solvents</b>      | <i>No Data Available</i>                 |

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

This material is considered to be non reactive under normal use conditions.

### 10.2. Chemical stability

Stable.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

None known.

### 10.5. Incompatible materials

None known.

No Data Available

**10.6. Hazardous decomposition products**

| <u>Substance</u> | <u>Condition</u> |
|------------------|------------------|
| None known.      |                  |

Refer to section 5.2 for hazardous decomposition products during combustion.

**SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

**11.1. Information on Toxicological effects**

**Signs and Symptoms of Exposure**

Based on test data and/or information on the components, this material may produce the following health effects:

**Inhalation:**

No health effects are expected.

**Skin Contact:**

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

**Eye Contact:**

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

**Ingestion:**

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

**Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

| Name   | Route     | Species | Value  |
|--|-----------|---------|--|
| Overall product                                    | Ingestion |         | No data available; calculated ATE >5,000 mg/kg |
| 4,4'-ISOPROPYLDENEDIPHENOL-EPICHLOROHYDRIN POLYMER | Dermal    | Rat     | LD50 > 1,600 mg/kg                             |
| 4,4'-ISOPROPYLDENEDIPHENOL-EPICHLOROHYDRIN POLYMER | Ingestion | Rat     | LD50 > 1,000 mg/kg                             |
| MICA-GROUP MINERALS                                | Dermal    |         | LD50 estimated to be > 5,000 mg/kg             |
| MICA-GROUP MINERALS                                | Ingestion |         | LD50 estimated to be 2,000 - 5,000 mg/kg       |
| TALC   | Dermal    |         | LD50 estimated to be > 5,000 mg/kg             |
| TALC   | Ingestion |         | LD50 estimated to be > 5,000 mg/kg             |

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

| Name | Species | Value |
|------|---------|-------|
|      |         |       |

|   |        |                           |
|---|--------|---------------------------|
| 4,4'-ISOPROPYLIDENEDIPHENOL-EPICHLOROXYDRIN POLYMER | Rabbit | Mild irritant             |
| TALC  | Rabbit | No significant irritation |

**Serious Eye Damage/Irritation**

| Name  | Species | Value                     |
|---|---------|---------------------------|
| 4,4'-ISOPROPYLIDENEDIPHENOL-EPICHLOROXYDRIN POLYMER | Rabbit  | Moderate irritant         |
| TALC  | Rabbit  | No significant irritation |

**Skin Sensitization**

| Name  | Species          | Value       |
|---|------------------|-------------|
| 4,4'-ISOPROPYLIDENEDIPHENOL-EPICHLOROXYDRIN POLYMER | Human and animal | Sensitizing |

**Respiratory Sensitization**

| Name  | Species | Value          |
|---|---------|----------------|
| 4,4'-ISOPROPYLIDENEDIPHENOL-EPICHLOROXYDRIN POLYMER | Human   | Not classified |
| TALC  | Human   | Not classified |

**Germ Cell Mutagenicity**

| Name  | Route    | Value  |
|---|----------|--|
| 4,4'-ISOPROPYLIDENEDIPHENOL-EPICHLOROXYDRIN POLYMER | In vivo  | Not mutagenic  |
| 4,4'-ISOPROPYLIDENEDIPHENOL-EPICHLOROXYDRIN POLYMER | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| TALC  | In Vitro | Not mutagenic  |
| TALC  | In vivo  | Not mutagenic  |

**Carcinogenicity**

| Name  | Route      | Species | Value  |
|---|------------|---------|--|
| 4,4'-ISOPROPYLIDENEDIPHENOL-EPICHLOROXYDRIN POLYMER | Dermal     | Mouse   | Some positive data exist, but the data are not sufficient for classification |
| TALC  | Inhalation | Rat     | Some positive data exist, but the data are not sufficient for classification |

**Reproductive Toxicity****Reproductive and/or Developmental Effects**

| Name  | Route     | Value                                  | Species | Test Result         | Exposure Duration    |
|---|-----------|--|---------|---------------------|----------------------|
| 4,4'-ISOPROPYLIDENEDIPHENOL-EPICHLOROXYDRIN POLYMER | Ingestion | Not classified for female reproduction | Rat     | NOAEL 750 mg/kg/day | 2 generation         |
| 4,4'-ISOPROPYLIDENEDIPHENOL-EPICHLOROXYDRIN POLYMER | Ingestion | Not classified for male reproduction   | Rat     | NOAEL 750 mg/kg/day | 2 generation         |
| 4,4'-ISOPROPYLIDENEDIPHENOL-EPICHLOROXYDRIN POLYMER | Dermal    | Not classified for development         | Rabbit  | NOAEL 300 mg/kg/day | during organogenesis |
| 4,4'-ISOPROPYLIDENEDIPHENOL-EPICHLOROXYDRIN POLYMER | Ingestion | Not classified for development         | Rat     | NOAEL 750 mg/kg/day | 2 generation         |
| TALC  | Ingestion | Not classified for development         | Rat     | NOAEL 1,600 mg/kg   | during organogenesis |

**Target Organ(s)****Specific Target Organ Toxicity - single exposure**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Specific Target Organ Toxicity - repeated exposure**

| Name   | Route      | Target Organ(s)  | Value  | Species | Test Result           | Exposure Duration     |
|--|------------|--|--|---------|-----------------------|-----------------------|
| 4,4'-ISOPROPYLIDENEDIPH ENOL-EPICHLOROHYDRIN POLYMER | Dermal     | liver  | Not classified   | Rat     | NOAEL 1,000 mg/kg/day | 2 years               |
| 4,4'-ISOPROPYLIDENEDIPH ENOL-EPICHLOROHYDRIN POLYMER | Dermal     | nervous system   | Not classified   | Rat     | NOAEL 1,000 mg/kg/day | 13 weeks              |
| 4,4'-ISOPROPYLIDENEDIPH ENOL-EPICHLOROHYDRIN POLYMER | Ingestion  | auditory system   heart   endocrine system   hematopoietic system   liver   eyes   kidney and/or bladder | Not classified   | Rat     | NOAEL 1,000 mg/kg/day | 28 days               |
| MICA-GROUP MINERALS                                  | Inhalation | pneumoconiosis   | Causes damage to organs through prolonged or repeated exposure | Human   | NOAEL Not available   | occupational exposure |
| TALC   | Inhalation | pneumoconiosis   | Causes damage to organs through prolonged or repeated exposure | Human   | NOAEL Not available   | occupational exposure |
| TALC   | Inhalation | pulmonary fibrosis   respiratory system  | Not classified   | Rat     | NOAEL 18 mg/m3        | 113 weeks             |

#### Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.**

## SECTION 12: Ecological information

### Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

### Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. If no other disposal options are available, waste product that has been completely cured or polymerized may be placed in a landfill properly designed for industrial waste. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

**EPA Hazardous Waste Number (RCRA):** Not regulated

## SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

## SECTION 15: Regulatory information

### 15.1. US Federal Regulations

Contact 3M for more information.

### EPCRA 311/312 Hazard Classifications:

#### Physical Hazards

Not applicable

#### Health Hazards

Respiratory or Skin Sensitization

Serious eye damage or eye irritation

### 15.2. State Regulations

Contact 3M for more information.

### 15.3. Chemical Inventories

The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information.

The components of this product are in compliance with the new substance notification requirements of CEPA.

The components of this material are in compliance with the China "Measures on Environmental Management of New Chemical Substance". Certain restrictions may apply. Contact the selling division for additional information.

The components of this product are in compliance with the chemical notification requirements of TSCA.

Contact 3M for more information.

### 15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

## SECTION 16: Other information

### NFPA Hazard Classification

Health: 2 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document Group: 36-8589-8

Version Number: 2.02

**Issue Date:** 01/04/18

**Supersedes Date:** 12/11/17

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

**3M USA SDSs are available at [www.3M.com](http://www.3M.com)**