



Safety Data Sheet

Copyright, 2024, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group: 36-2082-0
Issue Date: 06/10/24

Version Number: 4.00
Supersedes Date: 01/15/19

SECTION 1: Identification

1.1. Product identifier

3M™ Piezo Inkjet Ink 42795 UV Black

Product Identification Numbers

75-0400-3447-4, 75-3472-9059-7
7010393604, 7100175703

1.2. Recommended use and restrictions on use

Recommended use

Ink

1.3. Supplier's details

MANUFACTURER: 3M
DIVISION: Commercial Branding and Transportation Division
ADDRESS: 3M Center, St. Paul, MN 55144-1000, USA
Telephone: 1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

2.1. Hazard classification

Serious Eye Damage/Irritation: Category 1.
Skin Corrosion/Irritation: Category 2.
Skin Sensitizer: Category 1.
Reproductive Toxicity: Category 1B.
Carcinogenicity: Category 1B.
Specific Target Organ Toxicity (single exposure): Category 3.
Specific Target Organ Toxicity (repeated exposure): Category 2.

2.2. Label elements

Signal word

Danger

Symbols

Corrosion | Exclamation mark | Health Hazard |

Pictograms**Hazard Statements**

Causes serious eye damage.

Causes skin irritation.

May cause an allergic skin reaction.

May cause respiratory irritation.

May damage fertility or the unborn child.

May cause cancer.

May cause damage to organs through prolonged or repeated exposure:

kidney/urinary tract |

skin |

Precautionary Statements**Prevention:**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Do not breathe dust/fume/gas/mist/vapors/spray.

Use only outdoors or in a well-ventilated area.

Wear protective gloves and eye/face protection.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Response:

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

IF ON SKIN: Wash with plenty of soap and water.

Immediately call a POISON CENTER or doctor/physician.

If skin irritation or rash occurs: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

Storage:

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Hazards not otherwise classified

May cause chemical gastrointestinal burns.

22% of the mixture consists of ingredients of unknown acute oral toxicity.

42% of the mixture consists of ingredients of unknown acute dermal toxicity.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
Isobornyl Acrylate	5888-33-5	5 - 30 Trade Secret *
TETRAHYDROFURFURYL ACRYLATE	2399-48-6	< 25 Trade Secret *
ISOOCYL ACRYLATE	29590-42-9	10 - 20 Trade Secret *
2-Propenoic acid, 2-hydroxyethyl ester, polymer with 5-isocyanato-1-(isocyanatomethyl)-1,3,3-trimethylcyclohexane, 2-oxepanone and 2,2'-oxybis[ethanol]	72162-39-1	5 - 15 Trade Secret *
1,6-hexanediol diacrylate	13048-33-4	< 10 Trade Secret *
2-Propenoic acid, 1,6-hexanediyl ester, polymer with 2-aminoethanol	67906-98-3	5 - 10 Trade Secret *
2,4,6-Trimethylbenzoyldiphenylphosphine oxide	75980-60-8	3 - 7 Trade Secret *
BENZOPHENONE	119-61-9	3 - 7 Trade Secret *
Carbon Black	1333-86-4	1 - 5 Trade Secret *
TS Polymer	Trade Secret*	1 - 5 Trade Secret *

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If Swallowed:

Rinse mouth. Do not induce vomiting. Get immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Irritating to the respiratory tract (coughing, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain). Allergic skin reaction (redness, swelling, blistering, and itching). Serious damage to the eyes (corneal cloudiness, severe pain, tearing, ulcerations, and significantly impaired or loss of vision). Target organ effects following prolonged or repeated exposure. See Section 11 for additional details.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

Substance

Carbon monoxide
Carbon dioxide

Condition

During Combustion
During Combustion

5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (gloves, respirators, etc.) as required.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Store away from heat. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
BENZOPHENONE	119-61-9	AIHA	TWA:0.5 mg/m3	
1,6-hexanediol diacrylate	13048-33-4	AIHA	TWA:1 mg/m3(0.11 ppm)	Dermal Sensitizer
Carbon Black	1333-86-4	ACGIH	TWA(inhalable fraction):3 mg/m3	A3: Confirmed animal carcin.

Carbon Black	1333-86-4	OSHA	TWA:3.5 mg/m3	
TETRAHYDROFURFURYL ACRYLATE	2399-48-6	Manufacturer determined	TWA:0.1 ppm(0.64 mg/m3);STEL:0.3 ppm(1.91 mg/m3)	Dermal Sensitizer
ISOOCTYL ACRYLATE	29590-42-9	AIHA	TWA:37.5 mg/m3(5 ppm)	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full Face Shield

Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates, including oily mists

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state

Liquid

Color

Black

Specific Physical Form:	Slurry
Odor	Acrylate
Odor threshold	No Data Available
pH	Not Applicable
Melting point	Not Applicable
Boiling Point	> 200 °F
Flash Point	> 200 °F [Test Method: Closed Cup]
Evaporation rate	No Data Available
Flammability (solid, gas)	Not Applicable
Flammable Limits(LEL)	No Data Available
Flammable Limits(UEL)	No Data Available
Vapor Pressure	< 10 mmHg [@ 20 °C]
Vapor Density	> 1 [Ref Std: AIR=1]
Density	1.04 g/ml
Specific Gravity	1.04 [Ref Std: WATER=1]
Solubility in Water	Negligible
Solubility- non-water	No Data Available
Partition coefficient: n-octanol/ water	No Data Available
Autoignition temperature	No Data Available
Decomposition temperature	No Data Available
Viscosity	No Data Available
Percent volatile	No Data Available

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization may occur. (Upon depletion of inhibitor or exposure to heat)

10.4. Conditions to avoid

Heat

10.5. Incompatible materials

Strong oxidizing agents

10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

Skin Contact:

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain.

Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

May cause additional health effects (see below).

Eye Contact:

Corrosive (Eye Burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

Ingestion:

May be harmful if swallowed.

Gastrointestinal Corrosion: Signs/symptoms may include severe mouth, throat and abdominal pain; nausea; vomiting; and diarrhea; blood in the feces and/or vomitus may also be seen.

May cause additional health effects (see below).

Additional Health Effects:

Prolonged or repeated exposure may cause target organ effects:

Kidney/Bladder Effects: Signs/symptoms may include changes in urine production, abdominal or lower back pain, increased protein in urine, increased blood urea nitrogen (BUN), blood in urine, and painful urination.

Prolonged or repeated exposure by ingestion may cause:

Dermal Effects: Signs/symptoms may include redness, itching, acne, or bumps on the skin.

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Ingredient	CAS No.	Class Description	Regulation
Benzophenone	119-61-9	Grp. 2B: Possible human carc.	International Agency for Research on Cancer
Carbon black	1333-86-4	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >2,000 - =5,000 mg/kg

Isobornyl Acrylate	Dermal	Rabbit	LD50 > 5,000 mg/kg
Isobornyl Acrylate	Ingestion	Rat	LD50 4,350 mg/kg
TETRAHYDROFURFURYL ACRYLATE	Ingestion	Rat	LD50 882 mg/kg
ISOOCTYL ACRYLATE	Dermal	Rabbit	LD50 > 2,000 mg/kg
ISOOCTYL ACRYLATE	Ingestion	Rat	LD50 > 5,000 mg/kg
1,6-hexanediol diacrylate	Dermal	Rabbit	LD50 3,636 mg/kg
1,6-hexanediol diacrylate	Ingestion	Rat	LD50 > 5,000 mg/kg
2,4,6-Trimethylbenzoyldiphenylphosphine oxide	Dermal	Professional judgement	LD50 estimated to be > 5,000 mg/kg
2,4,6-Trimethylbenzoyldiphenylphosphine oxide	Ingestion	Rat	LD50 > 5,000 mg/kg
BENZOPHENONE	Dermal	Rabbit	LD50 3,535 mg/kg
BENZOPHENONE	Ingestion	Rat	LD50 1,900 mg/kg
Carbon Black	Dermal	Rabbit	LD50 > 3,000 mg/kg
Carbon Black	Ingestion	Rat	LD50 > 8,000 mg/kg
TS Polymer	Ingestion	similar compounds	LD50 > 5,000 mg/kg
TS Polymer	Dermal	similar health hazards	LD50 estimated to be > 5,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Overall product	Professional judgement	Irritant
Isobornyl Acrylate	Rabbit	Minimal irritation
TETRAHYDROFURFURYL ACRYLATE	Rabbit	Corrosive
ISOOCTYL ACRYLATE	In vitro data	No significant irritation
2-Propenoic acid, 2-hydroxyethyl ester, polymer with 5-isocyanato-1-(isocyanatomethyl)-1,3,3-trimethylcyclohexane, 2-oxepanone and 2,2'-oxybis[ethanol]	similar compounds	Irritant
2-Propenoic acid, 1,6-hexanediyl ester, polymer with 2-aminoethanol	similar compounds	Irritant
1,6-hexanediol diacrylate	Rabbit	Irritant
2,4,6-Trimethylbenzoyldiphenylphosphine oxide	Rabbit	No significant irritation
BENZOPHENONE	Rabbit	No significant irritation
Carbon Black	Rabbit	No significant irritation
TS Polymer	similar compounds	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Isobornyl Acrylate	Rabbit	Mild irritant
TETRAHYDROFURFURYL ACRYLATE	Rabbit	Corrosive
ISOOCTYL ACRYLATE	similar health hazards	Mild irritant
2-Propenoic acid, 2-hydroxyethyl ester, polymer with 5-isocyanato-1-(isocyanatomethyl)-1,3,3-trimethylcyclohexane, 2-oxepanone and 2,2'-oxybis[ethanol]	similar compounds	Severe irritant
2-Propenoic acid, 1,6-hexanediyl ester, polymer with 2-aminoethanol	similar compounds	Severe irritant
1,6-hexanediol diacrylate	Rabbit	Moderate irritant

2,4,6-Trimethylbenzoyldiphenylphosphine oxide	Rabbit	No significant irritation
BENZOPHENONE	Rabbit	Mild irritant
Carbon Black	Rabbit	No significant irritation
TS Polymer	similar compounds	No significant irritation

Skin Sensitization

Name	Species	Value
Isobornyl Acrylate	Human and animal	Sensitizing
TETRAHYDROFURFURYL ACRYLATE	Professional judgment	Sensitizing
ISOCTYL ACRYLATE	Mouse	Sensitizing
2-Propenoic acid, 1,6-hexanediyl ester, polymer with 2-aminoethanol	similar compounds	Sensitizing
1,6-hexanediol diacrylate	Guinea pig	Sensitizing
2,4,6-Trimethylbenzoyldiphenylphosphine oxide	Mouse	Sensitizing
BENZOPHENONE	Guinea pig	Not classified

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Isobornyl Acrylate	In Vitro	Not mutagenic
TETRAHYDROFURFURYL ACRYLATE	In Vitro	Not mutagenic
ISOCTYL ACRYLATE	In Vitro	Some positive data exist, but the data are not sufficient for classification
1,6-hexanediol diacrylate	In Vitro	Some positive data exist, but the data are not sufficient for classification
2,4,6-Trimethylbenzoyldiphenylphosphine oxide	In Vitro	Not mutagenic
BENZOPHENONE	In Vitro	Not mutagenic
BENZOPHENONE	In vivo	Not mutagenic
Carbon Black	In Vitro	Not mutagenic
Carbon Black	In vivo	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
ISOCTYL ACRYLATE	Dermal	Mouse	Not carcinogenic
1,6-hexanediol diacrylate	Dermal	Mouse	Not carcinogenic
BENZOPHENONE	Dermal	Multiple animal species	Not carcinogenic
BENZOPHENONE	Ingestion	Multiple animal species	Carcinogenic
Carbon Black	Dermal	Mouse	Not carcinogenic
Carbon Black	Ingestion	Mouse	Not carcinogenic
Carbon Black	Inhalation	Rat	Carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure
------	-------	-------	---------	-------------	----------

					Duration
Isobornyl Acrylate	Ingestion	Not classified for male reproduction	Rat	NOAEL 500 mg/kg/day	31 days
Isobornyl Acrylate	Ingestion	Not classified for female reproduction	Rat	NOAEL 100 mg/kg/day	premating into lactation
Isobornyl Acrylate	Ingestion	Not classified for development	Rat	NOAEL 100 mg/kg/day	premating into lactation
TETRAHYDROFURFURYL ACRYLATE	Ingestion	Toxic to female reproduction	Rat	NOAEL 50 mg/kg/day	premating into lactation
TETRAHYDROFURFURYL ACRYLATE	Dermal	Toxic to male reproduction	Rat	NOAEL 100 mg/kg/day	90 days
TETRAHYDROFURFURYL ACRYLATE	Ingestion	Toxic to male reproduction	Rat	NOAEL 35 mg/kg/day	90 days
TETRAHYDROFURFURYL ACRYLATE	Inhalation	Toxic to male reproduction	Rat	NOAEL 0.6 mg/l	90 days
TETRAHYDROFURFURYL ACRYLATE	Ingestion	Toxic to development	Rat	NOAEL 50 mg/kg/day	premating into lactation
ISOOCTYL ACRYLATE	Dermal	Not classified for female reproduction	Rat	NOAEL 57 mg/kg/day	premating & during gestation
ISOOCTYL ACRYLATE	Dermal	Not classified for male reproduction	Rat	NOAEL 57 mg/kg/day	premating & during gestation
ISOOCTYL ACRYLATE	Dermal	Not classified for development	Rat	NOAEL 57 mg/kg/day	premating & during gestation
ISOOCTYL ACRYLATE	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	during organogenesis
1,6-hexanediol diacrylate	Not Specified	Not classified for development	Rat	NOAEL 750 mg/kg/day	during organogenesis
2,4,6-Trimethylbenzoyldiphenylphosphine oxide	Ingestion	Not classified for development	Rat	NOAEL 150 mg/kg/day	during gestation
2,4,6-Trimethylbenzoyldiphenylphosphine oxide	Ingestion	Toxic to female reproduction	Rat	NOAEL 200 mg/kg/day	premating into lactation
2,4,6-Trimethylbenzoyldiphenylphosphine oxide	Ingestion	Toxic to male reproduction	Rat	NOAEL 60 mg/kg/day	85 days
BENZOPHENONE	Ingestion	Not classified for female reproduction	Rat	NOAEL 100 mg/kg/day	2 generation
BENZOPHENONE	Ingestion	Not classified for male reproduction	Rat	NOAEL 80 mg/kg/day	2 generation
BENZOPHENONE	Ingestion	Not classified for development	Rabbit	NOAEL 25 mg/kg/day	during gestation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
TETRAHYDROFURFURYL ACRYLATE	Inhalation	respiratory irritation	May cause respiratory irritation	Human and animal	NOAEL Not available	
ISOOCTYL ACRYLATE	Inhalation	respiratory irritation	Not classified	Human	NOAEL Not available	occupational exposure
ISOOCTYL ACRYLATE	Ingestion	central nervous system depression	Not classified	Rat	NOAEL 5,000 mg/kg	
2-Propenoic acid, 2-hydroxyethyl ester, polymer with 5-isocyanato-1-(isocyanatomethyl)-1,3,3-trimethylcyclohexane, 2-oxepanone and 2,2'-oxybis[ethanol]	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
2-Propenoic acid, 1,6-	Inhalation	respiratory irritation	Some positive data exist, but the	similar	NOAEL Not	

hexanediyl ester, polymer with 2-aminoethanol			data are not sufficient for classification	health hazards	available	
1,6-hexanediol diacrylate	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Isobornyl Acrylate	Ingestion	gastrointestinal tract immune system kidney and/or bladder heart endocrine system hematopoietic system liver nervous system respiratory system	Not classified	Rat	NOAEL 500 mg/kg/day	31 days
ISOOCTYL ACRYLATE	Dermal	heart endocrine system hematopoietic system liver immune system nervous system kidney and/or bladder respiratory system	Not classified	Rat	NOAEL 57 mg/kg/day	prematuring & during gestation
ISOOCTYL ACRYLATE	Ingestion	endocrine system liver kidney and/or bladder heart bone, teeth, nails, and/or hair hematopoietic system immune system muscles nervous system eyes respiratory system vascular system	Not classified	Rat	NOAEL 600 mg/kg/day	90 days
1,6-hexanediol diacrylate	Dermal	skin	May cause damage to organs though prolonged or repeated exposure	Mouse	LOAEL 70 mg/kg/day	80 weeks
2,4,6-Trimethylbenzoyldiphenyl phosphine oxide	Ingestion	skin blood liver kidney and/or bladder nervous system	Not classified	Rat	NOAEL 1,000 mg/kg/day	90 days
BENZOPHENONE	Ingestion	kidney and/or bladder	May cause damage to organs though prolonged or repeated exposure	Rat	LOAEL 75 mg/kg/day	14 weeks
BENZOPHENONE	Ingestion	heart hematopoietic system liver immune system endocrine system bone, teeth, nails, and/or hair nervous system eyes respiratory system	Not classified	Rat	NOAEL 850 mg/kg/day	14 weeks
Carbon Black	Inhalation	pneumoconiosis	Not classified	Human	NOAEL Not available	occupational exposure

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:

Physical Hazards

Not applicable

Health Hazards

Carcinogenicity

Hazard Not Otherwise Classified (HNOC)

Reproductive toxicity

Respiratory or Skin Sensitization

Serious eye damage or eye irritation

Skin Corrosion or Irritation

Specific target organ toxicity (single or repeated exposure)

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA. All required

components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 3 **Flammability:** 1 **Instability:** 1 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document Group: 36-2082-0

Version Number: 4.00

Issue Date: 06/10/24

Supersedes Date: 01/15/19

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com