



## Material Safety Data Sheet

Copyright, 2014, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

**PRODUCT NAME:** 3M™ ESPE™ IMPRINT™ 4 PRELIMINARY Super Quick Economy Pack  
**MANUFACTURER:** 3M  
**DIVISION:** 3M ESPE Dental Products  
**ADDRESS:** 3M Center, St. Paul, MN 55144-1000, USA  
**Telephone:** 1-888-3M HELPS (1-888-364-3577)

**EMERGENCY PHONE: 1-800-364-3577 or (651) 737-6501 (24 hours)**

**Issue Date:** 10/14/14  
**Supersedes Date:** Initial Issue  
**Document Group:** 34-0693-1

### ID Number(s):

70-2011-4254-7

**This product is a kit or a multipart product which consists of multiple, independently packaged components. An SDS for each of these components is included. Please do not separate the component SDSs from this cover page. The document numbers of the SDSs for components of this product are:**

33-4241-7, 33-4256-5

No revision information is available.

**DISCLAIMER:** The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

**3M USA SDSs are available at [www.3M.com](http://www.3M.com)**





## Safety Data Sheet

Copyright,2020, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

|                        |           |                         |          |
|------------------------|-----------|-------------------------|----------|
| <b>Document Group:</b> | 33-4256-5 | <b>Version Number:</b>  | 3.00     |
| <b>Issue Date:</b>     | 03/20/20  | <b>Supersedes Date:</b> | 02/25/16 |

### SECTION 1: Identification

#### 1.1. Product identifier

3M™ Imprint™ 4 Preliminary Super Quick Catalyst

#### Product Identification Numbers

LE-F100-1573-3

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Dental Product, Impression Material

##### Restrictions on use

For use only by dental professionals.

#### 1.3. Supplier's details

|                      |   |
|----------------------|---|
| <b>MANUFACTURER:</b> | 3M                                      |
| <b>DIVISION:</b>     | Oral Care Solutions Division            |
| <b>ADDRESS:</b>      | 3M Center, St. Paul, MN 55144-1000, USA |
| <b>Telephone:</b>    | 1-888-3M HELPS (1-888-364-3577)         |

#### 1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

### SECTION 2: Hazard identification

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

#### 2.1. Hazard classification

Not classified as hazardous according to OSHA Hazard Communication Standard, 29 CFR 1910.1200.

#### 2.2. Label elements

##### Signal word

Not applicable.

##### Symbols

Not applicable.

**Pictograms**

Not applicable.

24% of the mixture consists of ingredients of unknown acute oral toxicity.

### SECTION 3: Composition/information on ingredients

| Ingredient   | C.A.S. No. | % by Wt                |
|--|------------|------------------------|
| Flux calcined diatomaceous earth (cristobalite 1 - <10%)     | 68855-54-9 | 10 - 30 Trade Secret * |
| VINYL-POLYDIMETHYLSILOXANE                                   | 68083-19-2 | 10 - 30 Trade Secret * |
| Siloxanes and Silicones, di-Me, mono(vinyl group)-terminated | 68952-00-1 | 10 - 25 Trade Secret * |
| SODIUM ALUMINUM SILICATE                                     | 37244-96-5 | 10 - 25 Trade Secret * |
| DICHLORODIMETHYLSILANE REACTION PRODUCT WITH SILICA          | 68611-44-9 | 1 - 20 Trade Secret *  |
| POLY(DIMETHYLSILOXANE)                                       | 63148-62-9 | 1 - 20 Trade Secret *  |
| Titanium Dioxide   | 13463-67-7 | < 1.0 Trade Secret *   |

\*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

**Inhalation:**

No need for first aid is anticipated.

**Skin Contact:**

Wash with soap and water. If signs/symptoms develop, get medical attention.

**Eye Contact:**

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

**If Swallowed:**

Rinse mouth. If you feel unwell, get medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

#### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable.

### SECTION 5: Fire-fighting measures

#### 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

#### 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

**Hazardous Decomposition or By-Products**

**Substance**

Carbon monoxide  
Carbon dioxide  
Irritant Vapors or Gases

**Condition**

During Combustion  
During Combustion  
During Combustion

**5.3. Special protective actions for fire-fighters**

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

**SECTION 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Observe precautions from other sections. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

**6.2. Environmental precautions**

Avoid release to the environment.

**6.3. Methods and material for containment and cleaning up**

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

**SECTION 7: Handling and storage**

**7.1. Precautions for safe handling**

Avoid prolonged or repeated skin contact. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

**7.2. Conditions for safe storage including any incompatibilities**

Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidizing agents. Store away from amines.

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

**Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

| Ingredient        | C.A.S. No. | Agency | Limit type   | Additional Comments            |
|-------------------|------------|--------|--|--------------------------------|
| Titanium Dioxide  | 13463-67-7 | ACGIH  | TWA:10 mg/m3   | A4: Not class. as human carcin |
| Titanium Dioxide  | 13463-67-7 | OSHA   | TWA(as total dust):15 mg/m3                                      |                                |
| SILICA, AMORPHOUS | 68611-44-9 | OSHA   | TWA concentration:0.8 mg/m3;TWA:20 millions of particles/cu. ft. |                                |
| Cristobalite      | 68855-54-9 | ACGIH  | TWA(respirable fraction):0.025 mg/m3                             | A2: Suspected human carcin.    |

|                   |            |      |  |  |
|-------------------|------------|------|--|--|
| Cristobalite      | 68855-54-9 | OSHA | TWA concentration(respirable):0.05 mg/m3(1.2 millions of particles/cu. ft.);TWA:0.05 mg/m3 |  |
| SILICA, AMORPHOUS | 68855-54-9 | OSHA | TWA concentration:0.8 mg/m3;TWA:20 millions of particles/cu. ft.                           |  |

ACGIH : American Conference of Governmental Industrial Hygienists  
 AIHA : American Industrial Hygiene Association  
 CMRG : Chemical Manufacturer's Recommended Guidelines  
 OSHA : United States Department of Labor - Occupational Safety and Health Administration  
 TWA: Time-Weighted-Average  
 STEL: Short Term Exposure Limit  
 CEIL: Ceiling

**8.2. Exposure controls**

**8.2.1. Engineering controls**

Use in a well-ventilated area.

**8.2.2. Personal protective equipment (PPE)**

**Eye/face protection**

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

**Skin/hand protection**

See Section 7.1 for additional information on skin protection.

**Respiratory protection**

None required.

**SECTION 9: Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

**Appearance**

**Physical state**

Solid

**Color**

Pink

**Specific Physical Form:**

Paste

**Odor**

Slight Odor, Characteristic Odor

**Odor threshold**

*No Data Available*

**pH**

*No Data Available*

**Melting point**

*No Data Available*

**Boiling Point**

*No Data Available*

**Flash Point**

No flash point

**Evaporation rate**

*No Data Available*

**Flammability (solid, gas)**

Not Classified

**Flammable Limits(LEL)**

*No Data Available*

**Flammable Limits(UEL)**

*No Data Available*

**Vapor Pressure**

*No Data Available*

**Vapor Density**

*No Data Available*

|   |   |
|---|---|
| Density                                     | 1.2 g/cm <sup>3</sup> - 1.4 g/cm <sup>3</sup> |
| Specific Gravity                            | 1.2 - 1.4 [Ref Std: WATER=1]                  |
| Solubility in Water                         | Negligible                                    |
| Solubility- non-water                       | No Data Available                             |
| Partition coefficient: n-octanol/ water     | No Data Available                             |
| Autoignition temperature                    | No Data Available                             |
| Decomposition temperature                   | No Data Available                             |
| Viscosity                                   | No Data Available                             |
| Volatile Organic Compounds                  | Not Applicable                                |
| Percent volatile                            | Not Applicable                                |
| VOC Less H <sub>2</sub> O & Exempt Solvents | Not Applicable                                |

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

### 10.2. Chemical stability

Stable.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

Heat

### 10.5. Incompatible materials

Amines  
Strong acids  
Strong bases  
Strong oxidizing agents

### 10.6. Hazardous decomposition products

| <u>Substance</u> | <u>Condition</u> |
|------------------|------------------|
| None known.      |                  |

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure. The information below represents toxicological information associated with the individual components of the uncured product. Once properly mixed and/or cured, the product is safe for its intended use.

## 11.1. Information on Toxicological effects

### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation:

This product may have a characteristic odor; however, no adverse health effects are anticipated.

#### Skin Contact:

Contact with the skin during product use is not expected to result in significant irritation.

#### Eye Contact:

Contact with the eyes during product use is not expected to result in significant irritation.

#### Ingestion:

May be harmful if swallowed.

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

#### Additional Health Effects:

#### Carcinogenicity:

Exposures needed to cause the following health effect(s) are not expected during normal, intended use:

Contains a chemical or chemicals which can cause cancer.

| Ingredient                  | CAS No.    | Class Description              | Regulation                                  |
|-----------------------------|------------|--------------------------------|---|
| SILICA, CRYSTALLINE AIRRESP | 68855-54-9 | Grp. 1: Carcinogenic to humans | International Agency for Research on Cancer |
| SILICA, CRYSTALLINE AIRRESP | 68855-54-9 | Known human carcinogen         | National Toxicology Program Carcinogens     |
| Titanium Dioxide            | 13463-67-7 | Grp. 2B: Possible human carc.  | International Agency for Research on Cancer |

#### Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

#### Acute Toxicity

| Name   | Route                          | Species                | Value  |
|--|--------------------------------|------------------------|--|
| Overall product  | Ingestion                      |                        | No data available; calculated ATE2,000 - 5,000 mg/kg |
| Flux calcined diatomaceous earth (cristobalite 1 - <10%) | Dermal                         | Professional judgement | LD50 estimated to be > 5,000 mg/kg                   |
| Flux calcined diatomaceous earth (cristobalite 1 - <10%) | Inhalation-Dust/Mist (4 hours) | Rat                    | LC50 > 2.7 mg/l                                      |
| Flux calcined diatomaceous earth (cristobalite 1 - <10%) | Ingestion                      | Rat                    | LD50 > 2,000 mg/kg                                   |
| VINYL-POLYDIMETHYLSILOXANE                               | Dermal                         | Rabbit                 | LD50 > 15,440 mg/kg                                  |
| VINYL-POLYDIMETHYLSILOXANE                               | Ingestion                      | Rat                    | LD50 > 15,440 mg/kg                                  |
| SODIUM ALUMINUM SILICATE                                 | Dermal                         |                        | LD50 estimated to be > 5,000 mg/kg                   |
| SODIUM ALUMINUM SILICATE                                 | Ingestion                      |                        | LD50 estimated to be 2,000 - 5,000 mg/kg             |
| POLY(DIMETHYLSILOXANE)                                   | Dermal                         | Rabbit                 | LD50 > 19,400 mg/kg                                  |
| POLY(DIMETHYLSILOXANE)                                   | Ingestion                      | Rat                    | LD50 > 17,000 mg/kg                                  |
| DICHLORODIMETHYLSILANE REACTION PRODUCT WITH SILICA      | Dermal                         | Rabbit                 | LD50 > 5,000 mg/kg                                   |
| DICHLORODIMETHYLSILANE REACTION PRODUCT WITH SILICA      | Inhalation-Dust/Mist (4 hours) | Rat                    | LC50 > 0.691 mg/l                                    |
| DICHLORODIMETHYLSILANE REACTION PRODUCT WITH SILICA      | Ingestion                      | Rat                    | LD50 > 5,110 mg/kg                                   |
| Titanium Dioxide   | Dermal                         | Rabbit                 | LD50 > 10,000 mg/kg                                  |

|                  |                                |     |                     |
|------------------|--------------------------------|-----|---------------------|
| Titanium Dioxide | Inhalation-Dust/Mist (4 hours) | Rat | LC50 > 6.82 mg/l    |
| Titanium Dioxide | Ingestion                      | Rat | LD50 > 10,000 mg/kg |

ATE = acute toxicity estimate

### Skin Corrosion/Irritation

| Name   | Species                | Value                     |
|--|------------------------|---------------------------|
| Flux calcined diatomaceous earth (cristobalite 1 - <10%) | In vitro data          | No significant irritation |
| VINYL-POLYDIMETHYLSILOXANE                               | Rabbit                 | No significant irritation |
| SODIUM ALUMINUM SILICATE                                 | Professional judgement | No significant irritation |
| POLY(DIMETHYLSILOXANE)                                   | Rabbit                 | No significant irritation |
| DICHLORODIMETHYLSILANE REACTION PRODUCT WITH SILICA      | Rabbit                 | No significant irritation |
| Titanium Dioxide   | Rabbit                 | No significant irritation |

### Serious Eye Damage/Irritation

| Name   | Species                | Value                     |
|--|------------------------|---------------------------|
| Flux calcined diatomaceous earth (cristobalite 1 - <10%) | Rabbit                 | Mild irritant             |
| VINYL-POLYDIMETHYLSILOXANE                               | Rabbit                 | Mild irritant             |
| SODIUM ALUMINUM SILICATE                                 | Professional judgement | Mild irritant             |
| POLY(DIMETHYLSILOXANE)                                   | Rabbit                 | No significant irritation |
| DICHLORODIMETHYLSILANE REACTION PRODUCT WITH SILICA      | Rabbit                 | No significant irritation |
| Titanium Dioxide   | Rabbit                 | No significant irritation |

### Skin Sensitization

| Name   | Species          | Value          |
|--|------------------|----------------|
| Flux calcined diatomaceous earth (cristobalite 1 - <10%) | Mouse            | Not classified |
| DICHLORODIMETHYLSILANE REACTION PRODUCT WITH SILICA      | Human and animal | Not classified |
| Titanium Dioxide   | Human and animal | Not classified |

### Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

### Germ Cell Mutagenicity

| Name   | Route    | Value  |
|--|----------|--|
| Flux calcined diatomaceous earth (cristobalite 1 - <10%) | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| DICHLORODIMETHYLSILANE REACTION PRODUCT WITH SILICA      | In Vitro | Not mutagenic  |
| Titanium Dioxide   | In Vitro | Not mutagenic  |
| Titanium Dioxide   | In vivo  | Not mutagenic  |

### Carcinogenicity

| Name   | Route         | Species          | Value  |
|--|---------------|------------------|--|
| Flux calcined diatomaceous earth (cristobalite 1 - <10%) | Inhalation    | Human and animal | Carcinogenic   |
| DICHLORODIMETHYLSILANE REACTION PRODUCT WITH SILICA      | Not Specified | Mouse            | Some positive data exist, but the data are not sufficient for classification |

|                  |            |                         |                  |
|------------------|------------|-------------------------|------------------|
| Titanium Dioxide | Ingestion  | Multiple animal species | Not carcinogenic |
| Titanium Dioxide | Inhalation | Rat                     | Carcinogenic     |

## Reproductive Toxicity

### Reproductive and/or Developmental Effects

| Name  | Route     | Value                                  | Species | Test Result           | Exposure Duration    |
|---|-----------|--|---------|-----------------------|----------------------|
| DICHLORODIMETHYLSILANE REACTION PRODUCT WITH SILICA | Ingestion | Not classified for female reproduction | Rat     | NOAEL 509 mg/kg/day   | 1 generation         |
| DICHLORODIMETHYLSILANE REACTION PRODUCT WITH SILICA | Ingestion | Not classified for male reproduction   | Rat     | NOAEL 497 mg/kg/day   | 1 generation         |
| DICHLORODIMETHYLSILANE REACTION PRODUCT WITH SILICA | Ingestion | Not classified for development         | Rat     | NOAEL 1,350 mg/kg/day | during organogenesis |

## Target Organ(s)

### Specific Target Organ Toxicity - single exposure

For the component/components, either no data are currently available or the data are not sufficient for classification.

### Specific Target Organ Toxicity - repeated exposure

| Name   | Route      | Target Organ(s)                                     | Value  | Species | Test Result           | Exposure Duration     |
|--|------------|---|--|---------|-----------------------|-----------------------|
| Flux calcined diatomaceous earth (cristobalite 1 - <10%) | Inhalation | silicosis   | Causes damage to organs through prolonged or repeated exposure               | Human   | NOAEL Not available   | occupational exposure |
| Flux calcined diatomaceous earth (cristobalite 1 - <10%) | Ingestion  | hematopoietic system   eyes   kidney and/or bladder | Not classified   | Rat     | NOAEL 3,738 mg/kg/day | 90 days               |
| DICHLORODIMETHYLSILANE REACTION PRODUCT WITH SILICA      | Inhalation | respiratory system   silicosis                      | Not classified   | Human   | NOAEL Not available   | occupational exposure |
| Titanium Dioxide   | Inhalation | respiratory system                                  | Some positive data exist, but the data are not sufficient for classification | Rat     | LOAEL 0.01 mg/l       | 2 years               |
| Titanium Dioxide   | Inhalation | pulmonary fibrosis                                  | Not classified   | Human   | NOAEL Not available   | occupational exposure |

## Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

## SECTION 12: Ecological information

### Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

### Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. If no other disposal options are available, waste product that has been completely cured or polymerized may be placed in a landfill properly designed for industrial waste. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

**EPA Hazardous Waste Number (RCRA):** Not regulated

## SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

## SECTION 15: Regulatory information

### 15.1. US Federal Regulations

Contact 3M for more information.

#### EPCRA 311/312 Hazard Classifications:

##### Physical Hazards

Not applicable

##### Health Hazards

Not applicable

### 15.2. State Regulations

Contact 3M for more information.

### 15.3. Chemical Inventories

The components of this product are in compliance with the new substance notification requirements of CEPA.

The components of this material are in compliance with the China "Measures on Environmental Management of New Chemical Substance". Certain restrictions may apply. Contact the selling division for additional information.

This material contains one or more substances not listed on the TSCA Inventory. Commercial use of this material is regulated by the FDA.

Contact 3M for more information.

### 15.4. International Regulations

Contact 3M for more information.

**This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.**

## SECTION 16: Other information

**NFPA Hazard Classification****Health: 0 Flammability: 1 Instability: 0 Special Hazards: None**

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

|                        |           |                         |          |
|------------------------|-----------|-------------------------|----------|
| <b>Document Group:</b> | 33-4256-5 | <b>Version Number:</b>  | 3.00     |
| <b>Issue Date:</b>     | 03/20/20  | <b>Supersedes Date:</b> | 02/25/16 |

**DISCLAIMER:** The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

**3M USA SDSs are available at [www.3M.com](http://www.3M.com)**



## Safety Data Sheet

Copyright, 2021, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

|                        |           |                         |          |
|------------------------|-----------|-------------------------|----------|
| <b>Document Group:</b> | 33-4241-7 | <b>Version Number:</b>  | 3.01     |
| <b>Issue Date:</b>     | 08/17/21  | <b>Supersedes Date:</b> | 03/20/20 |

### SECTION 1: Identification

#### 1.1. Product identifier

3M™ Imprint™ 4 Preliminary Super Quick Base

#### Product Identification Numbers

LE-F100-1572-2

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Dental Product, Impression Material

##### Restrictions on use

For use only by dental professionals.

#### 1.3. Supplier's details

|                      |   |
|----------------------|---|
| <b>MANUFACTURER:</b> | 3M                                      |
| <b>DIVISION:</b>     | Oral Care Solutions Division            |
| <b>ADDRESS:</b>      | 3M Center, St. Paul, MN 55144-1000, USA |
| <b>Telephone:</b>    | 1-888-3M HELPS (1-888-364-3577)         |

#### 1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

### SECTION 2: Hazard identification

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

#### 2.1. Hazard classification

Not classified as hazardous according to OSHA Hazard Communication Standard, 29 CFR 1910.1200.

#### 2.2. Label elements

##### Signal word

Not applicable.

##### Symbols

Not applicable.

**Pictograms**

Not applicable.

12% of the mixture consists of ingredients of unknown acute oral toxicity.

**SECTION 3: Composition/information on ingredients**

| <b>Ingredient</b>  | <b>C.A.S. No.</b> | <b>% by Wt</b>         |
|--|-------------------|------------------------|
| Flux calcined diatomaceous earth (cristobalite 1 - <10%)   | 68855-54-9        | 20 - 40 Trade Secret * |
| POLY(DIMETHYLSILOXANE)   | 63148-62-9        | 10 - 30 Trade Secret * |
| VINYL-POLYDIMETHYL SILOXANE  | 68083-19-2        | 10 - 30 Trade Secret * |
| DIMETHYL METHYL HYDROGEN SILICONE FLUID  | 68037-59-2        | 1 - 20 Trade Secret *  |
| Siloxanes and Silicones, di-Me, mono(vinyl group)-terminated   | 68952-00-1        | 1 - 20 Trade Secret *  |
| Quartz (14808-60-7), surface modified with silsesquioxanes, methyl, ethoxy-terminated (CAS 104780-78-1), bulk material | None              | 1 - 20 Trade Secret *  |
| DICHLORODIMETHYLSILANE REACTION PRODUCT WITH SILICA  | 68611-44-9        | 1 - 10 Trade Secret *  |
| Titanium Dioxide   | 13463-67-7        | < 1 Trade Secret *     |
| Mentha arvensis, ext.  | 90063-97-1        | < 0.2 Trade Secret *   |

\*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

**SECTION 4: First aid measures****4.1. Description of first aid measures****Inhalation:**

No need for first aid is anticipated.

**Skin Contact:**

No need for first aid is anticipated.

**Eye Contact:**

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

**If Swallowed:**

Rinse mouth. If you feel unwell, get medical attention.

**4.2. Most important symptoms and effects, both acute and delayed**

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

**4.3. Indication of any immediate medical attention and special treatment required**

Not applicable.

**SECTION 5: Fire-fighting measures****5.1. Suitable extinguishing media**

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

**5.2. Special hazards arising from the substance or mixture**

None inherent in this product.

### Hazardous Decomposition or By-Products

#### Substance

Carbon monoxide  
Carbon dioxide  
Irritant Vapors or Gases

#### Condition

During Combustion  
During Combustion  
During Combustion

### 5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Avoid prolonged or repeated skin contact. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

### 7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidizing agents. Store away from amines.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

| Ingredient        | C.A.S. No. | Agency | Limit type   | Additional Comments            |
|-------------------|------------|--------|--|--------------------------------|
| Titanium Dioxide  | 13463-67-7 | ACGIH  | TWA:10 mg/m <sup>3</sup>   | A4: Not class. as human carcin |
| Titanium Dioxide  | 13463-67-7 | OSHA   | TWA(as total dust):15 mg/m <sup>3</sup>                                      |                                |
| SILICA, AMORPHOUS | 68611-44-9 | OSHA   | TWA:20 millions of particles/cu. ft.;TWA concentration:0.8 mg/m <sup>3</sup> |                                |
| CAS NO SEQ117921  | 68855-54-9 | ACGIH  | TWA(inhalable particulates):10 mg/m <sup>3</sup>                             |                                |
| CAS NO SEQ117922  | 68855-54-9 | ACGIH  | TWA(respirable particles):3  |                                |

|                         |            |      |   |  |
|-------------------------|------------|------|---|--|
|                         |            |      | mg/m3   |  |
| DUST, INERT OR NUISANCE | 68855-54-9 | OSHA | TWA(as total dust):15 mg/m3;TWA(as total dust):50 millions of particles/cu. ft.(15 mg/m3);TWA(respirable fraction):5 mg/m3;TWA(respirable fraction):15 millions of particles/cu. ft.(5 mg/m3) |  |
| SILICA, AMORPHOUS       | 68855-54-9 | OSHA | TWA:20 millions of particles/cu. ft.;TWA concentration:0.8 mg/m3  |  |

ACGIH : American Conference of Governmental Industrial Hygienists  
 AIHA : American Industrial Hygiene Association  
 CMRG : Chemical Manufacturer's Recommended Guidelines  
 OSHA : United States Department of Labor - Occupational Safety and Health Administration  
 TWA: Time-Weighted-Average  
 STEL: Short Term Exposure Limit  
 CEIL: Ceiling

**8.2. Exposure controls**

**8.2.1. Engineering controls**

Use in a well-ventilated area.

**8.2.2. Personal protective equipment (PPE)**

**Eye/face protection**

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

**Skin/hand protection**

See Section 7.1 for additional information on skin protection.

**Respiratory protection**

None required.

**SECTION 9: Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

**Appearance**

**Physical state**

Solid

**Color**

White

**Specific Physical Form:**

Paste

**Odor**

Minty

**Odor threshold**

*No Data Available*

**pH**

*Not Applicable*

**Melting point**

*Not Applicable*

**Boiling Point**

*Not Applicable*

**Flash Point**

No flash point

**Evaporation rate**

*No Data Available*

**Flammability (solid, gas)**

Not Classified

**Flammable Limits(LEL)**

*Not Applicable*

|   |                              |
|---|------------------------------|
| Flammable Limits(UEL)                       | <i>Not Applicable</i>        |
| Vapor Pressure                              | <i>No Data Available</i>     |
| Vapor Density                               | <i>No Data Available</i>     |
| Density                                     | 1.2 - 1.4 g/cm <sup>3</sup>  |
| Specific Gravity                            | 1.2 - 1.4 [Ref Std: WATER=1] |
| Solubility in Water                         | Negligible                   |
| Solubility- non-water                       | <i>No Data Available</i>     |
| Partition coefficient: n-octanol/ water     | <i>No Data Available</i>     |
| Autoignition temperature                    | <i>Not Applicable</i>        |
| Decomposition temperature                   | <i>No Data Available</i>     |
| Viscosity                                   | <i>No Data Available</i>     |
| Volatile Organic Compounds                  | <i>Not Applicable</i>        |
| Percent volatile                            | <i>Not Applicable</i>        |
| VOC Less H <sub>2</sub> O & Exempt Solvents | <i>Not Applicable</i>        |

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

This material is considered to be non reactive under normal use conditions. This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

### 10.2. Chemical stability

Stable.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

Heat

### 10.5. Incompatible materials

Amines  
Strong acids  
Strong bases  
Strong oxidizing agents

### 10.6. Hazardous decomposition products

| <u>Substance</u> | <u>Condition</u> |
|------------------|------------------|
| None known.      |                  |

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure. The information below represents toxicological information associated with the individual components of the uncured

product. Once properly mixed and/or cured, the product is safe for its intended use.

### 11.1. Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation:

This product may have a characteristic odor; however, no adverse health effects are anticipated.

#### Skin Contact:

Contact with the skin during product use is not expected to result in significant irritation.

#### Eye Contact:

Contact with the eyes during product use is not expected to result in significant irritation.

#### Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

#### Additional Health Effects:

#### Carcinogenicity:

Exposures needed to cause the following health effect(s) are not expected during normal, intended use:

Contains a chemical or chemicals which can cause cancer.

| Ingredient       | CAS No.    | Class Description             | Regulation                                  |
|------------------|------------|-------------------------------|---|
| Titanium Dioxide | 13463-67-7 | Grp. 2B: Possible human carc. | International Agency for Research on Cancer |

#### Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

#### Acute Toxicity

| Name   | Route                          | Species               | Value  |
|--|--------------------------------|-----------------------|--|
| Overall product  | Ingestion                      |                       | No data available; calculated ATE >5,000 mg/kg |
| Flux calcined diatomaceous earth (cristobalite 1 - <10%)   | Dermal                         | Professional judgment | LD50 estimated to be > 5,000 mg/kg             |
| Flux calcined diatomaceous earth (cristobalite 1 - <10%)   | Inhalation-Dust/Mist (4 hours) | Rat                   | LC50 > 2.7 mg/l                                |
| Flux calcined diatomaceous earth (cristobalite 1 - <10%)   | Ingestion                      | Rat                   | LD50 > 2,000 mg/kg                             |
| POLY(DIMETHYLSILOXANE)   | Dermal                         | Rabbit                | LD50 > 19,400 mg/kg                            |
| POLY(DIMETHYLSILOXANE)   | Ingestion                      | Rat                   | LD50 > 17,000 mg/kg                            |
| VINYL-POLYDIMETHYL SILOXANE  | Dermal                         | Rabbit                | LD50 > 15,440 mg/kg                            |
| VINYL-POLYDIMETHYL SILOXANE  | Ingestion                      | Rat                   | LD50 > 15,440 mg/kg                            |
| DIMETHYL METHYL HYDROGEN SILICONE FLUID  | Dermal                         | Rabbit                | LD50 > 2,000 mg/kg                             |
| DIMETHYL METHYL HYDROGEN SILICONE FLUID  | Ingestion                      | Rat                   | LD50 > 2,000 mg/kg                             |
| Quartz (14808-60-7), surface modified with silsesquioxanes, methyl, ethoxy-terminated (CAS 104780-78-1), bulk material | Dermal                         |                       | LD50 estimated to be > 5,000 mg/kg             |
| Quartz (14808-60-7), surface modified with silsesquioxanes, methyl, ethoxy-terminated (CAS 104780-78-1), bulk material | Ingestion                      |                       | LD50 estimated to be > 5,000 mg/kg             |
| DICHLORODIMETHYLSILANE REACTION PRODUCT WITH SILICA  | Dermal                         | Rabbit                | LD50 > 5,000 mg/kg                             |
| DICHLORODIMETHYLSILANE REACTION PRODUCT WITH SILICA  | Inhalation-Dust/Mist (4 hours) | Rat                   | LC50 > 0.691 mg/l                              |

|   |                                |        |                     |
|---|--------------------------------|--------|---------------------|
| DICHLORODIMETHYLSILANE REACTION PRODUCT WITH SILICA | Ingestion                      | Rat    | LD50 > 5,110 mg/kg  |
| Titanium Dioxide                                    | Dermal                         | Rabbit | LD50 > 10,000 mg/kg |
| Titanium Dioxide                                    | Inhalation-Dust/Mist (4 hours) | Rat    | LC50 > 6.82 mg/l    |
| Titanium Dioxide                                    | Ingestion                      | Rat    | LD50 > 10,000 mg/kg |
| Mentha arvensis, ext.                               | Dermal                         | Rabbit | LD50 > 5,000 mg/kg  |
| Mentha arvensis, ext.                               | Ingestion                      | Rat    | LD50 1,240 mg/kg    |

ATE = acute toxicity estimate

### Skin Corrosion/Irritation

| Name   | Species       | Value                     |
|--|---------------|---------------------------|
| Flux calcined diatomaceous earth (cristobalite 1 - <10%)   | In vitro data | No significant irritation |
| POLY(DIMETHYLSILOXANE)   | Rabbit        | No significant irritation |
| VINYL-POLYDIMETHYL SILOXANE  | Rabbit        | No significant irritation |
| DIMETHYL METHYL HYDROGEN SILICONE FLUID  | Rabbit        | No significant irritation |
| Quartz (14808-60-7), surface modified with silsesquioxanes, methyl, ethoxy-terminated (CAS 104780-78-1), bulk material |               | No significant irritation |
| DICHLORODIMETHYLSILANE REACTION PRODUCT WITH SILICA  | Rabbit        | No significant irritation |
| Titanium Dioxide   | Rabbit        | No significant irritation |
| Mentha arvensis, ext.  | Rabbit        | Mild irritant             |

### Serious Eye Damage/Irritation

| Name   | Species       | Value                     |
|--|---------------|---------------------------|
| Flux calcined diatomaceous earth (cristobalite 1 - <10%) | Rabbit        | Mild irritant             |
| POLY(DIMETHYLSILOXANE)                                   | Rabbit        | No significant irritation |
| VINYL-POLYDIMETHYL SILOXANE                              | Rabbit        | Mild irritant             |
| DIMETHYL METHYL HYDROGEN SILICONE FLUID                  | Rabbit        | Mild irritant             |
| DICHLORODIMETHYLSILANE REACTION PRODUCT WITH SILICA      | Rabbit        | No significant irritation |
| Titanium Dioxide   | Rabbit        | No significant irritation |
| Mentha arvensis, ext.                                    | In vitro data | Severe irritant           |

### Skin Sensitization

| Name   | Species          | Value          |
|--|------------------|----------------|
| Flux calcined diatomaceous earth (cristobalite 1 - <10%) | Mouse            | Not classified |
| DIMETHYL METHYL HYDROGEN SILICONE FLUID                  | Guinea pig       | Not classified |
| DICHLORODIMETHYLSILANE REACTION PRODUCT WITH SILICA      | Human and animal | Not classified |
| Titanium Dioxide   | Human and animal | Not classified |
| Mentha arvensis, ext.                                    | Guinea pig       | Sensitizing    |

### Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

### Germ Cell Mutagenicity

| Name   | Route    | Value  |
|--|----------|--|
| Flux calcined diatomaceous earth (cristobalite 1 - <10%)   | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| DIMETHYL METHYL HYDROGEN SILICONE FLUID  | In Vitro | Not mutagenic  |
| Quartz (14808-60-7), surface modified with silsesquioxanes, methyl, ethoxy-terminated (CAS 104780-78-1), bulk material | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| Quartz (14808-60-7), surface modified with silsesquioxanes, methyl, ethoxy-  | In vivo  | Some positive data exist, but the data are not                               |

|   |          |                               |
|---|----------|-------------------------------|
| terminated (CAS 104780-78-1), bulk material         |          | sufficient for classification |
| DICHLORODIMETHYLSILANE REACTION PRODUCT WITH SILICA | In Vitro | Not mutagenic                 |
| Titanium Dioxide                                    | In Vitro | Not mutagenic                 |
| Titanium Dioxide                                    | In vivo  | Not mutagenic                 |

### Carcinogenicity

| Name   | Route         | Species                 | Value  |
|--|---------------|-------------------------|--|
| Flux calcined diatomaceous earth (cristobalite 1 - <10%)   | Inhalation    | Human and animal        | Carcinogenic   |
| Quartz (14808-60-7), surface modified with silsesquioxanes, methyl, ethoxy-terminated (CAS 104780-78-1), bulk material | Inhalation    | Human and animal        | Carcinogenic   |
| DICHLORODIMETHYLSILANE REACTION PRODUCT WITH SILICA  | Not Specified | Mouse                   | Some positive data exist, but the data are not sufficient for classification |
| Titanium Dioxide   | Ingestion     | Multiple animal species | Not carcinogenic   |
| Titanium Dioxide   | Inhalation    | Rat                     | Carcinogenic   |

### Reproductive Toxicity

#### Reproductive and/or Developmental Effects

| Name  | Route     | Value                                  | Species | Test Result           | Exposure Duration    |
|---|-----------|--|---------|-----------------------|----------------------|
| DICHLORODIMETHYLSILANE REACTION PRODUCT WITH SILICA | Ingestion | Not classified for female reproduction | Rat     | NOAEL 509 mg/kg/day   | 1 generation         |
| DICHLORODIMETHYLSILANE REACTION PRODUCT WITH SILICA | Ingestion | Not classified for male reproduction   | Rat     | NOAEL 497 mg/kg/day   | 1 generation         |
| DICHLORODIMETHYLSILANE REACTION PRODUCT WITH SILICA | Ingestion | Not classified for development         | Rat     | NOAEL 1,350 mg/kg/day | during organogenesis |

### Target Organ(s)

#### Specific Target Organ Toxicity - single exposure

For the component/components, either no data are currently available or the data are not sufficient for classification.

#### Specific Target Organ Toxicity - repeated exposure

| Name   | Route      | Target Organ(s)                                     | Value  | Species | Test Result           | Exposure Duration     |
|--|------------|---|--|---------|-----------------------|-----------------------|
| Flux calcined diatomaceous earth (cristobalite 1 - <10%)   | Inhalation | silicosis   | Causes damage to organs through prolonged or repeated exposure               | Human   | NOAEL Not available   | occupational exposure |
| Flux calcined diatomaceous earth (cristobalite 1 - <10%)   | Ingestion  | hematopoietic system   eyes   kidney and/or bladder | Not classified   | Rat     | NOAEL 3,738 mg/kg/day | 90 days               |
| Quartz (14808-60-7), surface modified with silsesquioxanes, methyl, ethoxy-terminated (CAS 104780-78-1), bulk material | Inhalation | silicosis   | Causes damage to organs through prolonged or repeated exposure               | Human   | NOAEL Not available   | occupational exposure |
| DICHLORODIMETHYLSILANE REACTION PRODUCT WITH SILICA  | Inhalation | respiratory system   silicosis                      | Not classified   | Human   | NOAEL Not available   | occupational exposure |
| Titanium Dioxide   | Inhalation | respiratory system                                  | Some positive data exist, but the data are not sufficient for classification | Rat     | LOAEL 0.01 mg/l       | 2 years               |
| Titanium Dioxide   | Inhalation | pulmonary fibrosis                                  | Not classified   | Human   | NOAEL Not available   | occupational exposure |

**Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.**

**SECTION 12: Ecological information**

**Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

**Chemical fate information**

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

**SECTION 13: Disposal considerations**

**13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Prior to disposal, consult all applicable authorities and regulations to insure proper classification. Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. If no other disposal options are available, waste product may be placed in a landfill properly designed for industrial waste.

**EPA Hazardous Waste Number (RCRA):** Not regulated

**SECTION 14: Transport Information**

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

**SECTION 15: Regulatory information**

**15.1. US Federal Regulations**

Contact 3M for more information.

**EPCRA 311/312 Hazard Classifications:**

**Physical Hazards**

Not applicable

**Health Hazards**

Not applicable

**15.2. State Regulations**

Contact 3M for more information.

**15.3. Chemical Inventories**

The components of this product are in compliance with the new substance notification requirements of CEPA.

The components of this material are in compliance with the China "Measures on Environmental Management of New Chemical Substance". Certain restrictions may apply. Contact the selling division for additional information.

This material contains one or more substances not listed on the TSCA Inventory. Commercial use of this material is regulated by the FDA.

Contact 3M for more information.

#### 15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

### SECTION 16: Other information

#### NFPA Hazard Classification

**Health:** 0 **Flammability:** 1 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

|                        |           |                         |          |
|------------------------|-----------|-------------------------|----------|
| <b>Document Group:</b> | 33-4241-7 | <b>Version Number:</b>  | 3.01     |
| <b>Issue Date:</b>     | 08/17/21  | <b>Supersedes Date:</b> | 03/20/20 |

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at [www.3M.com](http://www.3M.com)