

Safety Data Sheet

Copyright, 2022, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document Group:
 39-0698-9
 Version Number:
 1.01

 Issue Date:
 10/25/22
 Supercedes Date:
 06/03/21

Product identifier

3M Scotch-WeldTM EC-9356 B/A FST - Structural Adhesive

Recommended use

Adhesive, Industrial use

Supplier's details

MANUFACTURER: 3M

DIVISION: 3M France

Automotive and Aerospace Solutions Division

ADDRESS: 3M Center, St. Paul, MN 55144-1000, USA

Telephone: 1-888-3M HELPS (1-888-364-3577)

Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet (SDS), Article Information Sheet (AIS), or Article Information Letter (AIL) for each of these components is included. Please do not separate the component documents from this cover page. The document numbers for components of this product are:

38-9216-3, 38-9217-1

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com



Safety Data Sheet

Copyright, 2021, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group: 38-9216-3 **Version Number:** 1.00

Issue Date: 06/03/21 **Supercedes Date:** Initial Issue

SECTION 1: Identification

1.1. Product identifier

3M Scotch-Weld™ EC-9356 B/A FST Part A - Structural Adhesive

1.2. Recommended use and restrictions on use

Recommended use

Adhesive

1.3. Supplier's details

MANUFACTURER: 3M

DIVISION: 3M France

Automotive and Aerospace Solutions Division

ADDRESS: 3M Center, St. Paul, MN 55144-1000, USA

Telephone: 1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

2.1. Hazard classification

Acute Toxicity (oral): Category 4.

Serious Eye Damage/Irritation: Category 1.

Skin Corrosion/Irritation: Category 1B.

Skin Sensitizer: Category 1A.

Specific Target Organ Toxicity (single exposure): Category 1.

Specific Target Organ Toxicity (single exposure): Category 3.

2.2. Label elements

Signal word

Danger

Symbols

Corrosion | Exclamation mark | Health Hazard |

Pictograms



Hazard Statements

Harmful if swallowed. Causes severe skin burns and eye damage. May cause an allergic skin reaction. May cause drowsiness or dizziness.

Causes damage to organs: blood or blood-forming organs

Precautionary Statements

Prevention:

Do not breathe dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area.

Wear protective gloves, protective clothing, and eye/face protection.

Do not eat, drink or smoke when using this product.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Response:

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Immediately call a POISON CENTER or doctor/physician.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

Specific treatment (see Notes to Physician on this label).

Call a POISON CENTER or doctor/physician if you feel unwell.

Storage:

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

Notes to Physician:

Overexposure to this product may result in methemoglobinemia. Methemoglobinemia may be clinically suspected by the presence of clinical "cyanosis" in the presence of a normal PaO2 (as obtained by arterial blood gases). Routine pulse oximetry may be inaccurate for monitoring oxygen saturation in the presence of methemoglobinemia, and should not be used to make the diagnosis of this disorder. If the patient is symptomatic or if the methemoglobin level is >20%, specific therapy with methylene blue should be considered as part of the medical management.

2.3. Hazards not otherwise classified

May cause chemical gastrointestinal burns.

Supplemental Information:

Persons previously sensitized to amines may develop a cross-sensitization reaction to certain other amines.

30% of the mixture consists of ingredients of unknown acute oral toxicity.

30% of the mixture consists of ingredients of unknown acute dermal toxicity.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
Alumina Trihydrate	21645-51-2	15 - 40
BIS(3-AMINOPROPYL) ETHER OF DIETHYLENE	4246-51-9	1 - 35 Trade Secret *
GLYCOL		
Amine Terminated Adduct	Trade Secret*	5 - 30
FATTY ACIDS, C18-UNSATD., DIMERS,	68911-25-1	1 - 25 Trade Secret *
POLYMERS WITH 3,3'-[OXYBIS(2,1-		
ETHANEDIYLOXY)]BIS[1-PROPANAMINE]		
Nitric acid, calcium salt, tetrahydrate	13477-34-4	1 - 15 Trade Secret *
Siloxanes and Silicones, di-Me, reaction products with	67762-90-7	1 - 10
silica		
Titanium Dioxide	13463-67-7	<= 3 Trade Secret *

^{*}The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact

Immediately flush with large amounts of water for at least 15 minutes. Remove contaminated clothing. Get immediate medical attention. Wash clothing before reuse.

Eye Contact:

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If Swallowed:

Rinse mouth. Do not induce vomiting. Get immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Skin burns (localized redness, swelling, itching, intense pain, blistering, and tissue destruction). Allergic skin reaction (redness, swelling, blistering, and itching). Serious damage to the eyes (corneal cloudiness, severe pain, tearing, ulcerations, and significantly impaired or loss of vision). Central nervous system depression (headache, dizziness, drowsiness, incoordination, nausea, slurred speech, giddiness, and unconsciousness). Target organ effects. See Section 11 for additional details.

4.3. Indication of any immediate medical attention and special treatment required

Overexposure to this product may result in methemoglobinemia. Methemoglobinemia may be clinically suspected by the presence of clinical "cyanosis" in the presence of a normal PaO2 (as obtained by arterial blood gases). Routine pulse oximetry may be inaccurate for monitoring oxygen saturation in the presence of methemoglobinemia, and should not be used to make the diagnosis of this disorder. If the patient is symptomatic or if the methemoglobin level is >20%, specific therapy with methylene blue should be considered as part of the medical management.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

SubstanceConditionCarbon monoxideDuring CombustionCarbon dioxideDuring CombustionHydrogen ChlorideDuring Combustion

5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a metal container approved for use in transportation by appropriate authorities. The container must be lined with polyethylene plastic or contain a plastic drum liner made of polyethylene. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Store away from acids.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

particles/cu. ft.;TWA concentration:0.8 mg/m3

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient C.A.S. No. Limit type **Additional Comments** Agency Titanium Dioxide 13463-67-7 ACGIH TWA:10 mg/m3 A4: Not class, as human carcin Titanium Dioxide 13463-67-7 OSHA TWA(as total dust):15 mg/m³ Aluminum, insoluble compounds 21645-51-2 ACGIH TWA(respirable fraction):1 A4: Not class. as human mg/m3 carcin DUST, INERT OR NUISANCE 21645-51-2 OSHA TWA(as total dust):15 mg/m3;TWA(as total dust):50 millions of particles/cu. ft.(15 mg/m3);TWA(respirable fraction):5 mg/m3;TWA(respirable fraction):15 millions of particles/cu. ft.(5 mg/m3) SILICA, AMORPHOUS 67762-90-7 **OSHA** TWA:20 millions of

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CMRG: Chemical Manufacturer's Recommended Guidelines

OSHA: United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full Face Shield

Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state Liquid Color White

Specific Physical Form: Paste **Odor** Amine

Odor thresholdNo Data AvailablepHNo Data AvailableMelting pointNo Data AvailableBoiling PointNot Applicable

Flash Point > 200 °F [Test Method:Closed Cup]

Evaporation rateNot ApplicableFlammability (solid, gas)Not ApplicableFlammable Limits(LEL)Not ApplicableFlammable Limits(UEL)Not ApplicableVapor PressureNot ApplicableVapor DensityNot Applicable

Density 1.1 - 1.5 g/cm3 [*Ref Std*:WATER=1]

Specific Gravity 1.3 [Ref Std: WATER=1]

Solubility in WaterNot ApplicableSolubility- non-waterNegligiblePartition coefficient: n-octanol/ waterNo Data AvailableAutoignition temperatureNo Data AvailableDecomposition temperatureNo Data AvailableViscosityNo Data Available

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

Not determined

10.6. Hazardous decomposition products

<u>Substance</u> <u>Condition</u>

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin Contact:

May be harmful in contact with skin.

Corrosive (Skin Burns): Signs/symptoms may include localized redness, swelling, itching, intense pain, blistering, ulceration, and tissue destruction.

Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eve Contact:

Corrosive (Eye Burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

Ingestion:

Harmful if swallowed. Gastrointestinal Corrosion: Signs/symptoms may include severe mouth, throat and abdominal pain; nausea; vomiting; and diarrhea; blood in the feces and/or vomitus may also be seen.

May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:

Methemoglobinemia: Signs/symptoms may include headache, dizziness, nausea, difficulty breathing, and generalized weakness.

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Carcinogenicity:

Ingredient	CAS No.	Class Description	Regulation
Titanium Dioxide	13463-67-7	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

Additional Information:

Persons previously sensitized to amines may develop a cross-sensitization reaction to certain other amines.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE2,000 - 5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE300 - 2,000 mg/kg
Alumina Trihydrate	Dermal		LD50 estimated to be > 5,000 mg/kg
Alumina Trihydrate	Ingestion	Rat	LD50 > 5,000 mg/kg
BIS(3-AMINOPROPYL) ETHER OF DIETHYLENE GLYCOL	Dermal	Rabbit	LD50 2,500 mg/kg
BIS(3-AMINOPROPYL) ETHER OF DIETHYLENE GLYCOL	Ingestion	Rat	LD50 3,160 mg/kg
FATTY ACIDS, C18-UNSATD., DIMERS, POLYMERS WITH 3,3'-[OXYBIS(2,1-ETHANEDIYLOXY)]BIS[1-PROPANAMINE]	Dermal	Rat	LD50 > 2,000 mg/kg
FATTY ACIDS, C18-UNSATD., DIMERS, POLYMERS WITH 3,3'-[OXYBIS(2,1-ETHANEDIYLOXY)]BIS[1-PROPANAMINE]	Ingestion	Rat	LD50 > 2,000 mg/kg
Nitric acid, calcium salt, tetrahydrate	Ingestion	Rat	LD50 >300, <2000 mg/kg
Nitric acid, calcium salt, tetrahydrate	Dermal	similar compoun ds	LD50 > 2,000 mg/kg
Siloxanes and Silicones, di-Me, reaction products with silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
Siloxanes and Silicones, di-Me, reaction products with silica	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Rat	LD50 > 5,110 mg/kg
Titanium Dioxide	Dermal	Rabbit	LD50 > 10,000 mg/kg
Titanium Dioxide	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 6.82 mg/l
Titanium Dioxide	Ingestion	Rat	LD50 > 10,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Alumina Trihydrate	Rabbit	No significant irritation
BIS(3-AMINOPROPYL) ETHER OF DIETHYLENE GLYCOL	Rabbit	Corrosive
FATTY ACIDS, C18-UNSATD., DIMERS, POLYMERS WITH 3,3'-	Rat	Irritant
[OXYBIS(2,1-ETHANEDIYLOXY)]BIS[1-PROPANAMINE]		
Nitric acid, calcium salt, tetrahydrate	similar	No significant irritation
	compoun	
	ds	
Siloxanes and Silicones, di-Me, reaction products with silica	Rabbit	No significant irritation
Titanium Dioxide	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Alumina Trihydrate	Rabbit	No significant irritation
BIS(3-AMINOPROPYL) ETHER OF DIETHYLENE GLYCOL	similar	Corrosive
	health	
	hazards	
FATTY ACIDS, C18-UNSATD., DIMERS, POLYMERS WITH 3,3'-	In vitro	Severe irritant
[OXYBIS(2,1-ETHANEDIYLOXY)]BIS[1-PROPANAMINE]	data	
Nitric acid, calcium salt, tetrahydrate	Rabbit	Corrosive
Siloxanes and Silicones, di-Me, reaction products with silica	Rabbit	No significant irritation
Titanium Dioxide	Rabbit	No significant irritation

Skin Sensitization

Name	Species	Value
Alumina Trihydrate	Guinea	Not classified
	pig	
FATTY ACIDS, C18-UNSATD., DIMERS, POLYMERS WITH 3,3'-	Guinea	Sensitizing
[OXYBIS(2,1-ETHANEDIYLOXY)]BIS[1-PROPANAMINE]	pig	
Nitric acid, calcium salt, tetrahydrate	similar	Not classified
	compoun	
	ds	
Siloxanes and Silicones, di-Me, reaction products with silica	Human	Not classified
	and	
	animal	
Titanium Dioxide	Human	Not classified
	and	
	animal	

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
FATTY ACIDS, C18-UNSATD., DIMERS, POLYMERS WITH 3,3'-	In Vitro	Not mutagenic
[OXYBIS(2,1-ETHANEDIYLOXY)]BIS[1-PROPANAMINE]		
Nitric acid, calcium salt, tetrahydrate	In Vitro	Not mutagenic
Siloxanes and Silicones, di-Me, reaction products with silica	In Vitro	Not mutagenic
Titanium Dioxide	In Vitro	Not mutagenic
Titanium Dioxide	In vivo	Not mutagenic

Carcinogenicity

eur emogement j			
Name	Route	Species	Value
Alumina Trihydrate	Not	Multiple	Not carcinogenic
	Specified	animal	
		species	
Siloxanes and Silicones, di-Me, reaction products with silica	Not Specified	Mouse	Some positive data exist, but the data are not sufficient for classification
Titanium Dioxide	Ingestion	Multiple animal species	Not carcinogenic
Titanium Dioxide	Inhalation	Rat	Carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
Alumina Trihydrate	Ingestion	Not classified for development	Rat	NOAEL 768 mg/kg/day	during organogenesi s
FATTY ACIDS, C18-UNSATD., DIMERS, POLYMERS WITH 3,3'-[OXYBIS(2,1- ETHANEDIYLOXY)]BIS[1- PROPANAMINE]	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	premating into lactation
FATTY ACIDS, C18-UNSATD., DIMERS, POLYMERS WITH 3,3'-[OXYBIS(2,1- ETHANEDIYLOXY)]BIS[1- PROPANAMINE]	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	29 days
FATTY ACIDS, C18-UNSATD., DIMERS, POLYMERS WITH 3,3'-[OXYBIS(2,1- ETHANEDIYLOXY)]BIS[1- PROPANAMINE]	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	premating into lactation
Nitric acid, calcium salt, tetrahydrate	Ingestion	Not classified for female reproduction	similar compoun ds	NOAEL 1,500 mg/kg/day	premating into lactation
Nitric acid, calcium salt, tetrahydrate	Ingestion	Not classified for male reproduction	similar	NOAEL 1,500	28 days

Page 9 of

		/2.1	

			compoun ds	mg/kg/day	
Nitric acid, calcium salt, tetrahydrate	Ingestion	Not classified for development	similar compoun ds	NOAEL 1,500 mg/kg/day	premating into lactation
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesi s

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
BIS(3-AMINOPROPYL) ETHER OF DIETHYLENE GLYCOL	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
FATTY ACIDS, C18- UNSATD., DIMERS, POLYMERS WITH 3,3'- [OXYBIS(2,1- ETHANEDIYLOXY)]BIS[1-PROPANAMINE]	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	Irritation Positive	
FATTY ACIDS, C18- UNSATD., DIMERS, POLYMERS WITH 3,3'- [OXYBIS(2,1- ETHANEDIYLOXY)]BIS[1-PROPANAMINE]	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Rat	NOAEL Not available	
Nitric acid, calcium salt, tetrahydrate	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
Nitric acid, calcium salt, tetrahydrate	Ingestion	methemoglobinemi a	Causes damage to organs	Human	NOAEL Not available	environmental exposure

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
FATTY ACIDS, C18- UNSATD., DIMERS, POLYMERS WITH 3,3'- [OXYBIS(2,1- ETHANEDIYLOXY)]BIS [1-PROPANAMINE]	Ingestion	heart skin endocrine system gastrointestinal tract bone, teeth, nails, and/or hair hematopoietic system liver immune system muscles nervous system eyes kidney and/or bladder respiratory system vascular system	Not classified	Rat	NOAEL 1,000 mg/kg/day	29 days
Nitric acid, calcium salt, tetrahydrate	Ingestion	heart skin endocrine system bone, teeth, nails, and/or hair hematopoietic system liver immune system nervous system eyes kidney and/or bladder respiratory system vascular	Not classified	similar compoun ds	NOAEL 1,500 mg/kg/day	28 days

Page 10 **of** 12

		system				
Siloxanes and Silicones, di-Me, reaction products with silica	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
Titanium Dioxide	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.01 mg/l	2 years
Titanium Dioxide	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): D002 (Corrosive)

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:

Not applicable

Page 11 of 12

Health Hazards

Acute toxicity

Hazard Not Otherwise Classified (HNOC)

Respiratory or Skin Sensitization

Serious eye damage or eye irritation

Skin Corrosion or Irritation

Specific target organ toxicity (single or repeated exposure)

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 3 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document Group:38-9216-3Version Number:1.00Issue Date:06/03/21Supercedes Date:Initial Issue

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com



Safety Data Sheet

Copyright, 2022, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document Group:
 38-9217-1
 Version Number:
 3.00

 Issue Date:
 07/22/22
 Supercedes Date:
 12/07/21

SECTION 1: Identification

1.1. Product identifier

3M Scotch-Weld™ EC-9356 B/A FST Part B - Structural Adhesive

1.2. Recommended use and restrictions on use

Recommended use

Adhesive

1.3. Supplier's details

MANUFACTURER: 3M

DIVISION: 3M France

Automotive and Aerospace Solutions Division

ADDRESS: 3M Center, St. Paul, MN 55144-1000, USA

Telephone: 1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

2.1. Hazard classification

Serious Eye Damage/Irritation: Category 2B. Skin Corrosion/Irritation: Category 2. Skin Sensitizer: Category 1A.

2.2. Label elements

Signal word

Warning

Symbols

Exclamation mark |

Pictograms



Hazard Statements

Causes eye irritation.

Causes skin irritation.

May cause an allergic skin reaction.

Precautionary Statements

Prevention:

Avoid breathing dust/fume/gas/mist/vapors/spray.

Wear protective gloves.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Response:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

If eye irritation persists: Get medical advice/attention. IF ON SKIN: Wash with plenty of soap and water.

If skin irritation or rash occurs: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

11% of the mixture consists of ingredients of unknown acute oral toxicity.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
Alumina Trihydrate	21645-51-2	25 - 35
Bisphenol A Diglycidyl Ether	1675-54-3	25 - 35 Trade Secret *
1,4-BIS[(2,3-	14228-73-0	5 - 15 Trade Secret *
EPOXYPROPOXY)METHYL]CYCLOHEXANE		
Acrylic copolymer	Trade Secret*	7 - 13
EPICHLOROHYDRIN-PHENOL-FORMALDEHYDE	9003-36-5	< 10 Trade Secret *
RESIN		
Red Phosphorus	7723-14-0	3 - 7 Trade Secret *
Titanium Dioxide	13463-67-7	3 - 7 Trade Secret *
Oxide glass chemicals	65997-17-3	0.5 - 1.5
Siloxanes and Silicones, di-Me, reaction products with	67762-90-7	0.5 - 1.5
silica		

^{*}The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get

medical attention.

Eve Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Allergic skin reaction (redness, swelling, blistering, and itching).

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance	Condition
Aldehydes	During Combustion
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Hydrogen Chloride	During Combustion

5.3. Special protective actions for fire-fighters

When fire fighting conditions are severe and total thermal decomposition of the product is possible, wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Contain spill. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid breathing dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage including any incompatibilities

Store away from amines.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Titanium Dioxide	13463-67-7	ACGIH	TWA:10 mg/m3	A4: Not class. as human
				carcin
Titanium Dioxide	13463-67-7	OSHA	TWA(as total dust):15 mg/m3	
Aluminum, insoluble compounds	21645-51-2	ACGIH	TWA(respirable fraction):1	A4: Not class. as human
			mg/m3	carcin
DUST, INERT OR NUISANCE	21645-51-2	OSHA	TWA(as total dust):15	
			mg/m3;TWA(as total dust):50	
			millions of particles/cu. ft.(15	
			mg/m3);TWA(respirable	
			fraction):5	
			mg/m3;TWA(respirable	
			fraction):15 millions of	
			particles/cu. ft.(5 mg/m3)	
Oxide glass chemicals	65997-17-3	Manufacturer	TWA(as non-fibrous,	
		determined	respirable)(8 hours):3	
			mg/m3;TWA(as non-fibrous,	
			inhalable fraction)(8 hours):10	
			mg/m3	
SILICA, AMORPHOUS	67762-90-7	OSHA	TWA:20 millions of	
			particles/cu. ft.;TWA	
			concentration:0.8 mg/m3	
Phosphorus, mol. (P4)	7723-14-0	ACGIH	TWA:0.1 mg/m3	
Red Phosphorus	7723-14-0	OSHA	TWA:0.1 mg/m3	

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CMRG: Chemical Manufacturer's Recommended Guidelines

OSHA: United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect Vented Goggles

No Data Available

No Data Available

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Percent volatile

Physical stateSolidColorPink

Specific Physical Form:Paste
Odor
Epoxy

Odor threshold No Data Available рH Not Applicable **Melting point** Not Applicable **Boiling Point** Not Applicable Flash Point No flash point Not Applicable **Evaporation rate** Flammability (solid, gas) Not Classified Flammable Limits(LEL) Not Applicable Not Applicable Flammable Limits(UEL) **Vapor Pressure** Not Applicable Not Applicable Vapor Density Density 1.1 - 1.5 g/cm3 **Specific Gravity** No Data Available Solubility in Water Not Applicable **Solubility- non-water** Negligible Partition coefficient: n-octanol/ water Not Applicable **Autoignition temperature** Not Applicable Not Applicable **Decomposition temperature** Viscosity No Data Available **Volatile Organic Compounds** No Data Available

SECTION 10: Stability and reactivity

VOC Less H2O & Exempt Solvents

Page 5 **of** 12

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

None known

10.5. Incompatible materials

Amines

10.6. Hazardous decomposition products

Substance

Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin Contact:

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eve Contact:

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Carcinogenicity:

<u>Ingredient</u>	CAS No.	Class Description	Regulation
Titanium dioxide	13463-67-7	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

Page 6 of

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Bisphenol A Diglycidyl Ether	Dermal	Rat	LD50 > 1,600 mg/kg
Bisphenol A Diglycidyl Ether	Ingestion	Rat	LD50 > 1,000 mg/kg
Alumina Trihydrate	Dermal		LD50 estimated to be > 5,000 mg/kg
Alumina Trihydrate	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 2.3 mg/l
Alumina Trihydrate	Ingestion	Rat	LD50 > 5,000 mg/kg
EPICHLOROHYDRIN-PHENOL-FORMALDEHYDE RESIN	Dermal	Rat	LD50 > 2,000 mg/kg
EPICHLOROHYDRIN-PHENOL-FORMALDEHYDE RESIN	Ingestion	Rat	LD50 > 5,000 mg/kg
Titanium Dioxide	Dermal	Rabbit	LD50 > 10,000 mg/kg
Titanium Dioxide	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 6.82 mg/l
Titanium Dioxide	Ingestion	Rat	LD50 > 10,000 mg/kg
1,4-BIS[(2,3-EPOXYPROPOXY)METHYL]CYCLOHEXANE	Dermal	Rabbit	LD50 > 2,000 mg/kg
1,4-BIS[(2,3-EPOXYPROPOXY)METHYL]CYCLOHEXANE	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 5.19 mg/l
1,4-BIS[(2,3-EPOXYPROPOXY)METHYL]CYCLOHEXANE	Ingestion	Rat	LD50 1,098 mg/kg
Red Phosphorus	Dermal		LD50 estimated to be > 5,000 mg/kg
Red Phosphorus	Inhalation- Dust/Mist (4 hours)	Rat	LC50 1.1 mg/l
Red Phosphorus	Ingestion	Rat	LD50 > 15,000 mg/kg
Oxide glass chemicals	Dermal		LD50 estimated to be > 5,000 mg/kg
Oxide glass chemicals	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
Siloxanes and Silicones, di-Me, reaction products with silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
Siloxanes and Silicones, di-Me, reaction products with silica	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Rat	LD50 > 5,110 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Bisphenol A Diglycidyl Ether	Rabbit	Mild irritant
Alumina Trihydrate	Rabbit	No significant irritation
EPICHLOROHYDRIN-PHENOL-FORMALDEHYDE RESIN	Rabbit	Irritant
Titanium Dioxide	Rabbit	No significant irritation
1,4-BIS[(2,3-EPOXYPROPOXY)METHYL]CYCLOHEXANE	In vitro	Irritant
	data	
Oxide glass chemicals	Professio	No significant irritation
	nal	
	judgeme	
	nt	
Siloxanes and Silicones, di-Me, reaction products with silica	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Serious Lyc Damage/Hittation		
Name	Species	Value
Bisphenol A Diglycidyl Ether	Rabbit	Moderate irritant
Alumina Trihydrate	Rabbit	No significant irritation
EPICHLOROHYDRIN-PHENOL-FORMALDEHYDE RESIN	Rabbit	No significant irritation
Titanium Dioxide	Rabbit	No significant irritation

Page 7 **of** 12

1,4-BIS[(2,3-EPOXYPROPOXY)METHYL]CYCLOHEXANE	In vitro	No significant irritation
	data	
Oxide glass chemicals	Professio	No significant irritation
	nal	
	judgeme	
	nt	
Siloxanes and Silicones, di-Me, reaction products with silica	Rabbit	No significant irritation

Skin Sensitization

Name	Species	Value
Bisphenol A Diglycidyl Ether	Human	Sensitizing
	and	
	animal	
Alumina Trihydrate	Guinea	Not classified
	pig	
EPICHLOROHYDRIN-PHENOL-FORMALDEHYDE RESIN	Multiple	Sensitizing
	animal	
	species	
Titanium Dioxide	Human	Not classified
	and	
	animal	
1,4-BIS[(2,3-EPOXYPROPOXY)METHYL]CYCLOHEXANE	Mouse	Sensitizing
Siloxanes and Silicones, di-Me, reaction products with silica	Human	Not classified
•	and	
	animal	

Respiratory Sensitization

Name	Species	Value
Bisphenol A Diglycidyl Ether	Human	Not classified

Germ Cell Mutagenicity

Name	Route	Value			
Bisphenol A Diglycidyl Ether	In vivo	Not mutagenic			
Bisphenol A Diglycidyl Ether	In Vitro	Some positive data exist, but the data are not sufficient for classification			
EPICHLOROHYDRIN-PHENOL-FORMALDEHYDE RESIN	In vivo	Not mutagenic			
EPICHLOROHYDRIN-PHENOL-FORMALDEHYDE RESIN	In Vitro	Some positive data exist, but the data are not			
		sufficient for classification			
Titanium Dioxide	In Vitro	Not mutagenic			
Titanium Dioxide	In vivo	Not mutagenic			
1,4-BIS[(2,3-EPOXYPROPOXY)METHYL]CYCLOHEXANE	In vivo	Not mutagenic			
1,4-BIS[(2,3-EPOXYPROPOXY)METHYL]CYCLOHEXANE	In Vitro	Some positive data exist, but the data are not sufficient for classification			
Oxide glass chemicals	In Vitro	Some positive data exist, but the data are not			
		sufficient for classification			
Siloxanes and Silicones, di-Me, reaction products with silica	In Vitro	Not mutagenic			

Carcinogenicity

Name	Route	Species	Value
Bisphenol A Diglycidyl Ether	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Alumina Trihydrate	Not Specified	Multiple animal species	Not carcinogenic
Titanium Dioxide	Ingestion	Multiple animal species	Not carcinogenic
Titanium Dioxide	Inhalation	Rat	Carcinogenic
Oxide glass chemicals	Inhalation	Multiple animal species	Some positive data exist, but the data are not sufficient for classification
Siloxanes and Silicones, di-Me, reaction products with silica	Not	Mouse	Some positive data exist, but the data are not

Page 8 **of** 12

~ .~ .	000 1 0 1 100 1
Specified	sufficient for classification
Soccinca	Sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
Bisphenol A Diglycidyl Ether	Ingestion	Not classified for female reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
Bisphenol A Diglycidyl Ether	Ingestion	Not classified for male reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
Bisphenol A Diglycidyl Ether	Dermal	Not classified for development	Rabbit	NOAEL 300 mg/kg/day	during organogenesi s
Bisphenol A Diglycidyl Ether	Ingestion	Not classified for development	Rat	NOAEL 750 mg/kg/day	2 generation
Alumina Trihydrate	Ingestion	Not classified for development	Rat	NOAEL 768 mg/kg/day	during organogenesi s
1,4-BIS[(2,3- EPOXYPROPOXY)METHYL]CYCLOHE XANE	Ingestion	Not classified for female reproduction	Rat	NOAEL 300 mg/kg/day	premating into lactation
1,4-BIS[(2,3- EPOXYPROPOXY)METHYL]CYCLOHE XANE	Ingestion	Not classified for male reproduction	Rat	NOAEL 300 mg/kg/day	33 days
1,4-BIS[(2,3- EPOXYPROPOXY)METHYL]CYCLOHE XANE	Ingestion	Not classified for development	Rat	NOAEL 300 mg/kg/day	premating into lactation
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesi s

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
EPICHLOROHYDRIN- PHENOL- FORMALDEHYDE RESIN	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL not available	
1,4-BIS[(2,3- EPOXYPROPOXY)MET HYL]CYCLOHEXANE	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Bisphenol A Diglycidyl Ether	Dermal	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	2 years
Bisphenol A Diglycidyl Ether	Dermal	nervous system	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
Bisphenol A Diglycidyl Ether	Ingestion	auditory system heart endocrine system hematopoietic system liver eyes kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days

Page 9 of

EPICHLOROHYDRIN- PHENOL- FORMALDEHYDE RESIN	Ingestion	heart endocrine system gastrointestinal tract bone, teeth, nails, and/or hair hematopoietic system liver immune system nervous system eyes kidney and/or bladder respiratory system vascular system	Not classified	Rat	NOAEL 250 mg/kg/day	13 weeks
Titanium Dioxide	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.01 mg/l	2 years
Titanium Dioxide	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure
1,4-BIS[(2,3- EPOXYPROPOXY)MET HYL]CYCLOHEXANE	Ingestion	endocrine system gastrointestinal tract liver heart hematopoietic system immune system nervous system kidney and/or bladder	Not classified	Rat	NOAEL 300 mg/kg/day	33 days
Oxide glass chemicals	Inhalation	respiratory system	Not classified	Human	NOAEL not available	occupational exposure
Siloxanes and Silicones, di-Me, reaction products with silica	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:

Physical Hazards

Not applicable

Health Hazards

Respiratory or Skin Sensitization

Serious eye damage or eye irritation

Skin Corrosion or Irritation

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

Ingredient C.A.S. No % by Wt

Red Phosphorus (Phosphorus, mol. (P4)) 7723-14-0 Trade Secret 3 - 7

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 2 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

 Document Group:
 38-9217-1
 Version Number:
 3.00

 Issue Date:
 07/22/22
 Supercedes Date:
 12/07/21

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com