

# Safety Data Sheet

Copyright, 2023, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:38-2424-0Version Number:4.06Issue Date:11/30/23Supercedes Date:08/02/23

# **SECTION 1: Identification**

### 1.1. Product identifier

3M<sup>™</sup> Heavy Duty 20CA Clear

### **Product Identification Numbers**

62-4863-4920-2, 62-4863-4925-1 7100166355, 7100152617

#### 1.2. Recommended use and restrictions on use

### Recommended use

Aerosol Spray Adhesive

1.3. Supplier's details

MANUFACTURER: 3M

**DIVISION:** Industrial Adhesives and Tapes Division ADDRESS: 3M Center, St. Paul, MN 55144-1000, USA

**Telephone:** 1-888-3M HELPS (1-888-364-3577)

#### 1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

# **SECTION 2: Hazard identification**

### 2.1. Hazard classification

Flammable Aerosol: Category 1. Gas Under Pressure: Dissolved gas.

Serious Eye Damage/Irritation: Category 2B.

Reproductive Toxicity: Category 1B.

Simple Asphyxiant.

Specific Target Organ Toxicity (single exposure): Category 1. Specific Target Organ Toxicity (single exposure): Category 3.

#### 2.2. Label elements

# Signal word

Danger

### **Symbols**

Flame | Gas cylinder | Exclamation mark | Health Hazard |

# **Pictograms**



#### **Hazard Statements**

Extremely flammable aerosol.

Contains gas under pressure; may explode if heated.

Causes eye irritation.

May cause drowsiness or dizziness.

May damage fertility or the unborn child.

May displace oxygen and cause rapid suffocation.

Causes damage to organs:

cardiovascular system

May cause damage to organs:

respiratory system

# **Precautionary Statements**

#### **Prevention:**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not spray on an open flame or other ignition source.

Pressurized container: Do not pierce or burn, even after use.

Do not breathe dust/fume/gas/mist/vapors/spray.

Use only outdoors or in a well-ventilated area.

Wear protective gloves and eye/face protection.

Do not eat, drink or smoke when using this product.

Wash thoroughly after handling.

# **Response:**

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

If eye irritation persists: Get medical advice/attention.

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see Notes to Physician on this label).

# Storage:

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Keep container tightly closed.

Store locked up in a well-ventilated place.

#### Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

# Notes to Physician:

Exposure may increase myocardial irritability. Do not administer sympathomimetic drugs unless absolutely necessary.

\_\_\_\_\_

#### 2.3. Hazards not otherwise classified

Repeated exposure may cause skin dryness or cracking.

### **Supplemental Information:**

Intentional concentration and inhalation may be harmful or fatal.

# **SECTION 3: Composition/information on ingredients**

Ingredient	C.A.S. No.	% by Wt
Methyl Acetate	79-20-9	35 - 45 Trade Secret *
Non-hazardous components (NJTS Reg. No. 0449960-6850)	Trade Secret*	15 - 30 Trade Secret *
Dimethyl ether	115-10-6	5 - 15 Trade Secret *
Propane	74-98-6	5 - 15 Trade Secret *
1,1-Difluoroethane	75-37-6	< 10 Trade Secret *
Hexamethyldisiloxane	107-46-0	3 - 10 Trade Secret *
Tackifier	Trade Secret*	5 - 10 Trade Secret *
Cyclohexane	110-82-7	1 - 5 Trade Secret *
n-Butyl acetate	123-86-4	< 2 Trade Secret *
Hexane	110-54-3	< 1 Trade Secret *
Toluene	108-88-3	< 1 Trade Secret *
MORPHOLINE	110-91-8	< 0.5 Trade Secret *

NJTS or NJTSRN: New Jersey Trade Secret Registry Number.

# **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

#### Inhalation:

Remove person to fresh air. Get medical attention.

### **Skin Contact:**

Wash with soap and water. If signs/symptoms develop, get medical attention.

#### **Eye Contact:**

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

#### If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

Irritating to the respiratory tract (coughing, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain). Central nervous system depression (headache, dizziness, drowsiness, incoordination, nausea, slurred speech, giddiness, and unconsciousness). Target organ effects. See Section 11 for additional details.

# 4.3. Indication of any immediate medical attention and special treatment required

Exposure may increase myocardial irritability. Do not administer sympathomimetic drugs unless absolutely necessary.

<sup>\*</sup>The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

# **SECTION 5: Fire-fighting measures**

# 5.1. Suitable extinguishing media

Use a fire fighting agent suitable for the surrounding fire.

### 5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode. Exposure to extreme heat can give rise to thermal decomposition.

### **Hazardous Decomposition or By-Products**

<b>Substance</b>	<b>Condition</b>
Aldehydes	<b>During Combustion</b>
Hydrocarbons	<b>During Combustion</b>
Carbon monoxide	<b>During Combustion</b>
Carbon dioxide	<b>During Combustion</b>
Hydrogen Chloride	During Combustion
Hydrogen Fluoride	<b>During Combustion</b>
Ketones	<b>During Combustion</b>
Toxic Vapor, Gas, Particulate	During Combustion

### 5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

# **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

### 6.2. Environmental precautions

For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

### 6.3. Methods and material for containment and cleaning up

If possible, seal leaking container. Place leaking containers in a well-ventilated area, preferably an operating exhaust hood, or if necessary outdoors on an impermeable surface until appropriate packaging for the leaking container or its contents is available. Contain spill. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

# **SECTION 7: Handling and storage**

# 7.1. Precautions for safe handling

Do not breathe thermal decomposition products. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (gloves, respirators, etc.) as required.

### 7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store away from heat. Store away from acids. Store away from oxidizing agents.

# **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

# Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Toluene	108-88-3	ACGIH	TWA:20 ppm	A4: Not class. as human
				carcin, Ototoxicant
Toluene	108-88-3	OSHA	TWA:200 ppm;CEIL:300 ppm	
Hexane	110-54-3	ACGIH	TWA:50 ppm	Danger of cutaneous
				absorption
Hexane	110-54-3	OSHA	TWA:1800 mg/m3(500 ppm)	
Cyclohexane	110-82-7	ACGIH	TWA:100 ppm	
Cyclohexane	110-82-7	OSHA	TWA:1050 mg/m3(300 ppm)	
MORPHOLINE	110-91-8	ACGIH	TWA:20 ppm	A4: Not class. as human
				carcin, Danger of
				cutaneous absorption
MORPHOLINE	110-91-8	OSHA	TWA:70 mg/m3(20 ppm)	SKIN
Dimethyl ether	115-10-6	AIHA	TWA:1880 mg/m3(1000 ppm)	
n-Butyl acetate	123-86-4	ACGIH	TWA:50 ppm;STEL:150 ppm	
n-Butyl acetate	123-86-4	OSHA	TWA:710 mg/m3(150 ppm)	
Propane	74-98-6	ACGIH	Limit value not established:	simple asphyxiant
Propane	74-98-6	OSHA	TWA:1800 mg/m3(1000 ppm)	
1,1-Difluoroethane	75-37-6	AIHA	TWA:2700 mg/m3(1000 ppm)	
Methyl Acetate	79-20-9	ACGIH	TWA:200 ppm;STEL:250 ppm	
Methyl Acetate	79-20-9	OSHA	TWA:610 mg/m3(200 ppm)	

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CMRG: Chemical Manufacturer's Recommended Guidelines

OSHA: United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

# 8.2. Exposure controls

### 8.2.1. Engineering controls

For those situations where the material might be exposed to extreme overheating due to misuse or equipment failure, use with appropriate local exhaust ventilation sufficient to maintain levels of thermal decomposition products below their exposure guidelines. Do not remain in area where available oxygen may be reduced. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

### 8.2.2. Personal protective equipment (PPE)

# Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields Indirect Vented Goggles

### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended: Polymer laminate

# Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

For those situations where the material might be exposed to extreme overheating due to misuse or equipment failure, use a positive pressure supplied-air respirator.

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates Half facepiece or full facepiece supplied-air respirator

For questions about suitability for a specific application, consult with your respirator manufacturer.

# **SECTION 9: Physical and chemical properties**

# 9.1. Information on basic physical and chemical properties

**Appearance** 

Physical stateLiquidColorAmber

Specific Physical Form:AerosolOdorMild SolventOdor thresholdNo Data AvailablepHNot Applicable

Melting pointNo Data AvailableBoiling PointNo Data AvailableFlash PointApproximately -40 °F

Evaporation rate 1

Flammability (solid, gas)

Flammable Limits(LEL)

Flammable Limits(UEL)

Vapor Pressure

No Data Available

No Data Available

<=4137 mmHg

Vapor Density 2

**Density** 0.863 g/ml

Specific Gravity Approximately 0.88 [Ref Std:WATER=1]

Solubility in Water Nil

Solubility- non-waterNo Data AvailablePartition coefficient: n-octanol/ waterNo Data AvailableAutoignition temperatureNo Data AvailableDecomposition temperatureNo Data AvailableViscosity100 centipoiseHazardous Air Pollutants0 % weightMolecular weightNo Data Available

**Volatile Organic Compounds** < 25 % [Test Method: calculated per CARB title 2]

**Volatile Organic Compounds** <= 424.2 g/l [*Test Method*:calculated SCAQMD rule 443.1]

# **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

# 10.2. Chemical stability

Stable.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

Heat

### 10.5. Incompatible materials

Strong oxidizing agents

### 10.6. Hazardous decomposition products

### **Substance**

Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

Extreme heat arising from situations such as misuse or equipment failure can generate hydrogen fluoride as a decomposition product.

# **SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

### 11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation:

Simple Asphyxiation: Signs/symptoms may include increased heart rate, rapid respirations, drowsiness, headache, incoordination, altered judgement, nausea, vomiting, lethargy, seizures, coma, and may be fatal.

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

### **Skin Contact:**

Prolonged or repeated exposure may cause: Dermal Defatting: Signs/symptoms may include localized redness, itching, drying and cracking of skin.

### **Eye Contact:**

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

### **Ingestion:**

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

# **Additional Health Effects:**

#### Single exposure may cause target organ effects:

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Respiratory Effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish colored skin (cyanosis), sputum production, changes in lung function tests, and/or respiratory failure.

Single exposure, above recommended guidelines, may cause: Cardiac Sensitization: Signs/symptoms may include irregular heartbeat (arrhythmia), faintness, chest pain, and may be fatal.

### Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

### **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

### Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation- Vapor(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Methyl Acetate	Dermal	Rat	LD50 > 2,000 mg/kg
Methyl Acetate	Inhalation- Vapor (4 hours)	Rat	LC50 > 49 mg/l
Methyl Acetate	Ingestion	Rat	LD50 > 5,000 mg/kg
Propane	Inhalation- Gas (4 hours)	Rat	LC50 > 200,000 ppm
Non-hazardous components (NJTS Reg. No. 0449960-6850)	Dermal	Not available	LD50 > 2,000 mg/kg
Non-hazardous components (NJTS Reg. No. 0449960-6850)	Ingestion	Not available	LD50 > 2,000 mg/kg
Dimethyl ether	Inhalation- Gas (4 hours)	Rat	LC50 164,000 ppm
Hexamethyldisiloxane	Dermal	Rabbit	LD50 > 2,000 mg/kg
Hexamethyldisiloxane	Inhalation- Vapor (4 hours)	Rat	LC50 106 mg/l
Hexamethyldisiloxane	Ingestion	Rat	LD50 > 5,000 mg/kg
Tackifier	Dermal	Professio nal judgeme nt	LD50 estimated to be > 5,000 mg/kg
Tackifier	Ingestion	Rat	LD50 > 2,000 mg/kg
1,1-Difluoroethane	Inhalation- Gas (4 hours)	Rat	LC50 > 437,000 ppm
Cyclohexane	Dermal	Rat	LD50 > 2,000 mg/kg

Cyclohexane	Inhalation-	Rat	LC50 > 32.9  mg/l
	Vapor (4		8
	hours)		
Cyclohexane	Ingestion	Rat	LD50 6,200 mg/kg
Hexane	Dermal	Rabbit	LD50 > 2,000 mg/kg
Hexane	Inhalation-	Rat	LC50 170 mg/l
	Vapor (4		
	hours)		
Hexane	Ingestion	Rat	LD50 > 28,700 mg/kg
n-Butyl acetate	Dermal	Rabbit	LD50 > 5,000 mg/kg
n-Butyl acetate	Inhalation-	Rat	LC50 1.4 mg/l
	Dust/Mist		
	(4 hours)		
n-Butyl acetate	Inhalation-	Rat	LC50 > 20 mg/l
	Vapor (4		
	hours)		
n-Butyl acetate	Ingestion	Rat	LD50 > 8,800 mg/kg
Toluene	Dermal	Rat	LD50 12,000 mg/kg
Toluene	Inhalation-	Rat	LC50 30 mg/l
	Vapor (4		
	hours)		
Toluene	Ingestion	Rat	LD50 5,550 mg/kg
MORPHOLINE	Dermal	Rabbit	LD50 500 mg/kg
MORPHOLINE	Inhalation-	Rat	LC50 estimated to be 10 - 20 mg/l
	Vapor		
MORPHOLINE	Ingestion	Rat	LD50 1,680 mg/kg

ATE = acute toxicity estimate

# Skin Corrosion/Irritation

Name	Species	Value
Methyl Acetate	Rabbit	No significant irritation
Propane	Rabbit	Minimal irritation
Non-hazardous components (NJTS Reg. No. 0449960-6850)	Professio	No significant irritation
	nal	
	judgeme	
	nt	
Hexamethyldisiloxane	Rabbit	No significant irritation
Tackifier	In vitro	No significant irritation
	data	
Cyclohexane	Rabbit	Mild irritant
Hexane	Human	Mild irritant
	and	
	animal	
n-Butyl acetate	Rabbit	Minimal irritation
Toluene	Rabbit	Irritant
MORPHOLINE	Rabbit	Corrosive

Serious Eye Damage/Irritation

Name	Species	Value
Methyl Acetate	Rabbit	Moderate irritant
Propane	Rabbit	Mild irritant
Non-hazardous components (NJTS Reg. No. 0449960-6850)	Professio nal judgeme nt	No significant irritation
Hexamethyldisiloxane	Rabbit	Mild irritant
Tackifier	In vitro data	No significant irritation
Cyclohexane	Rabbit	Mild irritant
Hexane	Rabbit	Mild irritant
n-Butyl acetate	Rabbit	Moderate irritant
Toluene	Rabbit	Moderate irritant

**Page** 9 **of** 17

MORPHOLINE	Rabbit	Corrosive

# **Skin Sensitization**

Name	Species	Value
Methyl Acetate	Human	Not classified
Non-hazardous components (NJTS Reg. No. 0449960-6850)		Not classified
Hexamethyldisiloxane	Guinea	Not classified
	pig	
Tackifier	Multiple	Not classified
	animal	
	species	
Hexane	Human	Not classified
n-Butyl acetate	Multiple	Not classified
	animal	
	species	
Toluene	Guinea	Not classified
	pig	
MORPHOLINE	Guinea	Not classified
	pig	

**Respiratory Sensitization**For the component/components, either no data are currently available or the data are not sufficient for classification.

**Germ Cell Mutagenicity** 

Name	Route	Value
Methyl Acetate	In Vitro	Not mutagenic
3		
Methyl Acetate	In vivo	Not mutagenic
Propane	In Vitro	Not mutagenic
Dimethyl ether	In Vitro	Not mutagenic
Dimethyl ether	In vivo	Not mutagenic
Hexamethyldisiloxane	In Vitro	Not mutagenic
Hexamethyldisiloxane	In vivo	Not mutagenic
Tackifier	In Vitro	Not mutagenic
1,1-Difluoroethane	In Vitro	Some positive data exist, but the data are not
		sufficient for classification
1,1-Difluoroethane	In vivo	Some positive data exist, but the data are not
		sufficient for classification
Cyclohexane	In Vitro	Not mutagenic
Cyclohexane	In vivo	Some positive data exist, but the data are not
•		sufficient for classification
Hexane	In Vitro	Not mutagenic
Hexane	In vivo	Not mutagenic
n-Butyl acetate	In Vitro	Not mutagenic
Toluene	In Vitro	Not mutagenic
Toluene	In vivo	Not mutagenic
MORPHOLINE	In Vitro	Some positive data exist, but the data are not
		sufficient for classification
MORPHOLINE	In vivo	Some positive data exist, but the data are not
		sufficient for classification

Carcinogenicity

Name	Route	Species	Value
Dimethyl ether	Inhalation	Rat	Not carcinogenic
Hexamethyldisiloxane	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification
1,1-Difluoroethane	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification
Hexane	Dermal	Mouse	Not carcinogenic
Hexane	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification
Toluene	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification

Page 10 of 17

Toluene	Ingestion	Rat	Some positive data exist, but the data are not
			sufficient for classification
Toluene	Inhalation	Mouse	Some positive data exist, but the data are not
			sufficient for classification
MORPHOLINE	Ingestion	Multiple	Not carcinogenic
		animal	
		species	
MORPHOLINE	Inhalation	Rat	Not carcinogenic

# Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
Dimethyl ether	Inhalation	Not classified for development	Rat	NOAEL 40,000 ppm	during organogenesi s
Hexamethyldisiloxane	Inhalation	Not classified for male reproduction	Rat	NOAEL 33 mg/l	13 weeks
1,1-Difluoroethane	Inhalation	Not classified for development	Rat	NOAEL 50,000 ppm	during organogenesi s
Cyclohexane	Inhalation	Not classified for female reproduction	Rat	NOAEL 24 mg/l	2 generation
Cyclohexane	Inhalation	Not classified for male reproduction	Rat	NOAEL 24 mg/l	2 generation
Cyclohexane	Inhalation	Not classified for development	Rat	NOAEL 6.9 mg/l	2 generation
Hexane	Ingestion	Not classified for development	Mouse	NOAEL 2,200 mg/kg/day	during organogenesi s
Hexane	Inhalation	Not classified for development	Rat	NOAEL 0.7 mg/l	during gestation
Hexane	Ingestion	Toxic to male reproduction	Rat	NOAEL 1,140 mg/kg/day	90 days
Hexane	Inhalation	Toxic to male reproduction	Rat	LOAEL 3.52 mg/l	28 days
n-Butyl acetate	Inhalation	Not classified for female reproduction	Rat	NOAEL 7.1 mg/l	premating & during gestation
n-Butyl acetate	Inhalation	Not classified for development	Rat	NOAEL 7.1 mg/l	premating & during gestation
Toluene	Inhalation	Not classified for female reproduction	Human	NOAEL Not available	occupational exposure
Toluene	Inhalation	Not classified for male reproduction	Rat	NOAEL 2.3 mg/l	1 generation
Toluene	Ingestion	Toxic to development	Rat	LOAEL 520 mg/kg/day	during gestation
Toluene	Inhalation	Toxic to development	Human	NOAEL Not available	poisoning and/or abuse
MORPHOLINE	Ingestion	Not classified for development		NA	
MORPHOLINE	Ingestion	Toxic to male reproduction	similar compoun ds	NOAEL 60 mg/kg/day	2 generation

# Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Methyl Acetate	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	

Page 11 of 17

Methyl Acetate	Inhalation	recniretory imitation	May cause recoireters imitation	Нитоп	NOAEL Not	
Methyl Acetate	iiiiaiation	respiratory irritation	May cause respiratory irritation	Human and animal	available	
Methyl Acetate	Inhalation	blindness	Not classified		NOAEL Not available	
Methyl Acetate	Ingestion	central nervous system depression	May cause drowsiness or dizziness		NOAEL Not available	
Propane	Inhalation	cardiac sensitization	Causes damage to organs	Human	NOAEL Not available	
Propane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Propane	Inhalation	respiratory irritation	Not classified	Human	NOAEL Not available	
Dimethyl ether	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Rat	LOAEL 10,000 ppm	30 minutes
Dimethyl ether	Inhalation	cardiac sensitization	Some positive data exist, but the data are not sufficient for classification	Dog	NOAEL 100,000 ppm	5 minutes
Hexamethyldisiloxane	Inhalation	respiratory irritation	Not classified	Rat	NOAEL 33 mg/l	6 hours
Hexamethyldisiloxane	Ingestion	central nervous system depression	Not classified	Guinea pig	LOAEL 22,900 mg/kg	not applicable
1,1-Difluoroethane	Inhalation	cardiac sensitization	Causes damage to organs	Human and animal	NOAEL Not available	poisoning and/or abuse
1,1-Difluoroethane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL 100,000 ppm	
1,1-Difluoroethane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Not available	NOAEL Not available	not available
Cyclohexane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Cyclohexane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human and animal	NOAEL Not available	
Cyclohexane	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professio nal judgeme nt	NOAEL Not available	
Hexane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	not available
Hexane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Rabbit	NOAEL Not available	8 hours
Hexane	Inhalation	respiratory system	Not classified	Rat	NOAEL 24.6 mg/l	8 hours
n-Butyl acetate	Inhalation	respiratory system	May cause damage to organs	Rat	LOAEL 2.6 mg/l	4 hours
n-Butyl acetate	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	not available
n-Butyl acetate	Inhalation	respiratory irritation	May cause respiratory irritation	Human	NOAEL Not available	not available
n-Butyl acetate	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professio nal judgeme nt	NOAEL Not available	
Toluene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Toluene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Toluene	Inhalation	immune system	Not classified	Mouse	NOAEL 0.004 mg/l	3 hours
Toluene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse

**Page** 12 **of** 17

MORPHOLINE	Inhalation	respiratory irritation	Some positive data exist, but the	similar	NOAEL Not	
			data are not sufficient for	health	available	
			classification	hazards		

**Specific Target Organ Toxicity - repeated exposure** 

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Methyl Acetate	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1.1 mg/l	28 days
Methyl Acetate	Inhalation	endocrine system   hematopoietic system   liver   immune system   kidney and/or bladder	Not classified	Rat	NOAEL 6.1 mg/l	28 days
Dimethyl ether	Inhalation	hematopoietic system	Not classified	Rat	NOAEL 25,000 ppm	2 years
Dimethyl ether	Inhalation	liver	Not classified	Rat	NOAEL 20,000 ppm	30 weeks
Hexamethyldisiloxane	Dermal	liver   kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Hexamethyldisiloxane	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 4 mg/l	13 weeks
Hexamethyldisiloxane	Inhalation	hematopoietic system	Not classified	Rat	NOAEL 33 mg/l	13 weeks
Hexamethyldisiloxane	Inhalation	liver	Not classified	Multiple animal species	NOAEL 29 mg/l	15 days
Hexamethyldisiloxane	Inhalation	heart   endocrine system   immune system   nervous system   respiratory system	Not classified	Rat	NOAEL 33 mg/l	13 weeks
Tackifier	Ingestion	heart   gastrointestinal tract   hematopoietic   system   liver   nervous system   eyes   kidney and/or bladder	Not classified	Rat	NOAEL 331 mg/kg/day	90 days
1,1-Difluoroethane	Inhalation	hematopoietic system   kidney and/or bladder   respiratory system	Not classified	Rat	NOAEL 25,000 ppm	2 years
Cyclohexane	Inhalation	liver	Not classified	Rat	NOAEL 24 mg/l	90 days
Cyclohexane	Inhalation	auditory system	Not classified	Rat	NOAEL 1.7 mg/l	90 days
Cyclohexane	Inhalation	kidney and/or bladder	Not classified	Rabbit	NOAEL 2.7 mg/l	10 weeks
Cyclohexane	Inhalation	hematopoietic system	Not classified	Mouse	NOAEL 24 mg/l	14 weeks
Cyclohexane	Inhalation	peripheral nervous system	Not classified	Rat	NOAEL 8.6 mg/l	30 weeks
Hexane	Inhalation	peripheral nervous system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
Hexane	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Mouse	LOAEL 1.76 mg/l	13 weeks
Hexane	Inhalation	liver	Not classified	Rat	NOAEL Not available	6 months
Hexane	Inhalation	kidney and/or bladder	Not classified	Rat	LOAEL 1.76 mg/l	6 months
Hexane	Inhalation	hematopoietic system	Not classified	Mouse	NOAEL 35.2 mg/l	13 weeks

**Page** 13 **of** 17

11	1111	1.7	N 4 1 'C' 1	LTT	NOAEL N. 4	1 (* 1
Hexane	Inhalation	auditory system   immune system   eyes	Not classified	Human	NOAEL Not available	occupational exposure
Hexane	Inhalation	heart   skin   endocrine system	Not classified	Rat	NOAEL 1.76 mg/l	6 months
Hexane	Ingestion	peripheral nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1,140 mg/kg/day	90 days
Hexane	Ingestion	endocrine system   hematopoietic system   liver   immune system   kidney and/or bladder	Not classified	Rat	NOAEL Not available	13 weeks
n-Butyl acetate	Inhalation	olfactory system	Not classified	Rat	NOAEL 2.4 mg/l	14 weeks
n-Butyl acetate	Inhalation	liver   kidney and/or bladder	Not classified	Rabbit	NOAEL 7.26 mg/l	13 days
Toluene	Inhalation	auditory system   nervous system   eyes   olfactory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
Toluene	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 2.3 mg/l	15 months
Toluene	Inhalation	heart   liver   kidney and/or bladder	Not classified	Rat	NOAEL 11.3 mg/l	15 weeks
Toluene	Inhalation	endocrine system	Not classified	Rat	NOAEL 1.1 mg/l	4 weeks
Toluene	Inhalation	immune system	Not classified	Mouse	NOAEL Not available	20 days
Toluene	Inhalation	bone, teeth, nails, and/or hair	Not classified	Mouse	NOAEL 1.1 mg/l	8 weeks
Toluene	Inhalation	hematopoietic system   vascular system	Not classified	Human	NOAEL Not available	occupational exposure
Toluene	Inhalation	gastrointestinal tract	Not classified	Multiple animal species	NOAEL 11.3 mg/l	15 weeks
Toluene	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 625 mg/kg/day	13 weeks
Toluene	Ingestion	heart	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
Toluene	Ingestion	liver   kidney and/or bladder	Not classified	Multiple animal species	NOAEL 2,500 mg/kg/day	13 weeks
Toluene	Ingestion	hematopoietic system	Not classified	Mouse	NOAEL 600 mg/kg/day	14 days
Toluene	Ingestion	endocrine system	Not classified	Mouse	NOAEL 105 mg/kg/day	28 days
Toluene	Ingestion	immune system	Not classified	Mouse	NOAEL 105 mg/kg/day	4 weeks
MORPHOLINE	Dermal	liver   kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Guinea pig	LOAEL 900 mg/kg/day	13 days
MORPHOLINE	Dermal	hematopoietic system	Not classified	Guinea pig	NOAEL 900 mg/kg/day	13 days
MORPHOLINE	Inhalation	eyes	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
MORPHOLINE	Inhalation	pulmonary fibrosis	May cause damage to organs though prolonged or repeated exposure	Rat	NOAEL 0.09 mg/l	13 weeks
MORPHOLINE	Inhalation	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 64 mg/l	5 days

**Page** 14 **of** 17

MORPHOLINE	Inhalation	liver	Not classified	Rat	LOAEL 64 mg/l	5 days
MORPHOLINE	Inhalation	heart   endocrine system	Not classified	Rat	NOAEL 0.9 mg/l	13 weeks
MORPHOLINE	Inhalation	gastrointestinal tract   nervous system	Not classified	Rat	NOAEL 0.53 mg/l	104 weeks
MORPHOLINE	Ingestion	kidney and/or bladder	May cause damage to organs though prolonged or repeated exposure	Rat	LOAEL 160 mg/kg/day	30 days
MORPHOLINE	Ingestion	liver   respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 160 mg/kg/day	30 days
MORPHOLINE	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 800 mg/kg/day	30 days
MORPHOLINE	Ingestion	endocrine system	Not classified	Rat	NOAEL 323 mg/kg/day	4 weeks

**Aspiration Hazard** 

Name	Value
Cyclohexane	Aspiration hazard
Hexane	Aspiration hazard
Toluene	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

# **SECTION 12: Ecological information**

# **Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

# **Chemical fate information**

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

# **SECTION 13: Disposal considerations**

### 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Facility must be capable of handling aerosol cans. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): D001 (Ignitable)

# **SECTION 14: Transport Information**

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

# **SECTION 15: Regulatory information**

**Page** 15 **of** 17

# 15.1. US Federal Regulations

Contact 3M for more information.

### **EPCRA 311/312 Hazard Classifications:**

### Physical Hazards

Flammable (gases, aerosols, liquids, or solids)

Gas under pressure

#### Health Hazards

Hazard Not Otherwise Classified (HNOC)

Reproductive toxicity

Serious eye damage or eye irritation

Simple Asphyxiant

Specific target organ toxicity (single or repeated exposure)

### Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

**Ingredient** 

<u>C.A.S. No</u>

% by W

Cyclohexane

110-82-7

Trade Secret 1 - 5

# 15.2. State Regulations

Contact 3M for more information.

# 15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

# 15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

# **SECTION 16: Other information**

### NFPA Hazard Classification

Health: 3 Flammability: 4 Instability: 0 Special Hazards: None

**Aerosol Storage Code:** 3

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

The NFPA Health code of 3 is due to emergency situations where the material may thermally decompose and release Hydrogen Fluoride. During normal use conditions, please reference Section 2 and Section 11 of the SDS for additional health hazard information.

 Document Group:
 38-2424-0
 Version Number:
 4.06

 Issue Date:
 11/30/23
 Supercedes Date:
 08/02/23

**Page** 16 **of** 17

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com