



## Safety Data Sheet

Copyright, 2022, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document Group:</b>	32-7451-1	<b>Version Number:</b>	2.00
<b>Issue Date:</b>	07/27/22	<b>Supersedes Date:</b>	07/07/21

### SECTION 1: Identification

#### 1.1. Product identifier

3M™ Scotch-Weld™ Metal Primer EC-3901

#### Product Identification Numbers

87-3300-0031-3, 87-3300-0032-1  
7100039750

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Metal Primer

This chemical/product is not and cannot be distributed in commerce (as defined in TSCA section 3(5)) or processed (as defined in TSCA section 3(13)) for consumer paint or coating removal.

#### 1.3. Supplier's details

<b>MANUFACTURER:</b>	3M
<b>DIVISION:</b>	Automotive and Aerospace Solutions Division
<b>ADDRESS:</b>	3M Center, St. Paul, MN 55144-1000, USA
<b>Telephone:</b>	1-888-3M HELPS (1-888-364-3577)

#### 1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

### SECTION 2: Hazard identification

#### 2.1. Hazard classification

Flammable Liquid: Category 2.  
Acute Toxicity (oral): Category 3.  
Acute Toxicity (dermal): Category 4.  
Acute Toxicity (inhalation): Category 4.  
Serious Eye Damage/Irritation: Category 2B.  
Skin Sensitizer: Category 1.  
Reproductive Toxicity: Category 2.  
Specific Target Organ Toxicity (single exposure): Category 1.  
Specific Target Organ Toxicity (single exposure): Category 3.

#### 2.2. Label elements

**Signal word**

Danger

**Symbols**

Flame | Skull and crossbones | Exclamation mark | Health Hazard |

**Pictograms****Hazard Statements**

Highly flammable liquid and vapor.

Toxic if swallowed.

Harmful in contact with skin.

Causes eye irritation.

May cause an allergic skin reaction.

Harmful if inhaled.

May cause drowsiness or dizziness.

Suspected of damaging fertility or the unborn child.

Causes damage to organs:  
sensory organs |**Precautionary Statements****Prevention:**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Keep container tightly closed.

Use explosion-proof electrical/ventilating/lighting equipment.

Do not breathe dust/fume/gas/mist/vapors/spray.

Use only outdoors or in a well-ventilated area.

Wear protective gloves, protective clothing, and eye/face protection.

Do not eat, drink or smoke when using this product.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

**Response:**

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

If eye irritation persists: Get medical advice/attention.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

Rinse mouth.

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see Notes to Physician on this label).

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

**Storage:**

Store in a well-ventilated place. Keep container tightly closed.

Keep cool.

Store locked up.

**Disposal:**

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

**Notes to Physician:**

This product contains methanol. If there is a reasonable suspicion of methanol poisoning, intravenous (IV) administration with either fomepizole (preferred) or ethanol (if fomepizole is unavailable) should be considered as part of the medical management.

**Supplemental Information:**

Persons previously sensitized to amines may develop a cross-sensitization reaction to certain other amines.

### SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
METHYL ALCOHOL	67-56-1	99 - 99.9 Trade Secret *
AMINO SILANE	1760-24-3	< 1 Trade Secret *
DCM	75-09-2	< 0.01

\*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

### SECTION 4: First aid measures

**4.1. Description of first aid measures**

**Inhalation:**

Remove person to fresh air. If you feel unwell, get medical attention.

**Skin Contact:**

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

**Eye Contact:**

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

**If Swallowed:**

Rinse mouth. Get immediate medical attention.

**4.2. Most important symptoms and effects, both acute and delayed**

Allergic skin reaction (redness, swelling, blistering, and itching). Toxic if swallowed. Central nervous system depression (headache, dizziness, drowsiness, incoordination, nausea, slurred speech, giddiness, and unconsciousness). Target organ effects. See Section 11 for additional details.

**4.3. Indication of any immediate medical attention and special treatment required**

This product contains methanol. If there is a reasonable suspicion of methanol poisoning, intravenous (IV) administration with either

fomepizole (preferred) or ethanol (if fomepizole is unavailable) should be considered as part of the medical management.

## SECTION 5: Fire-fighting measures

### 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

### 5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

### Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Formaldehyde	During Combustion
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion

### 5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

### 6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

### 6.3. Methods and material for containment and cleaning up

Contain spill. Cover spill area with a fire-extinguishing foam. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. Use personal protective equipment

(gloves, respirators, etc.) as required. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapor accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

**7.2. Conditions for safe storage including any incompatibilities**

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store away from acids. Store away from oxidizing agents.

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

**Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
METHYL ALCOHOL	67-56-1	ACGIH	TWA:200 ppm;STEL:250 ppm	Danger of cutaneous absorption
METHYL ALCOHOL	67-56-1	OSHA	TWA:260 mg/m3(200 ppm)	
DCM	75-09-2	ACGIH	TWA:50 ppm	A3: Confirmed animal carcin.
DCM	75-09-2	OSHA	TWA:25 ppm;STEL:125 ppm	29 CFR 1910.1052, SKIN

ACGIH : American Conference of Governmental Industrial Hygienists  
 AIHA : American Industrial Hygiene Association  
 CMRG : Chemical Manufacturer's Recommended Guidelines  
 OSHA : United States Department of Labor - Occupational Safety and Health Administration  
 TWA: Time-Weighted-Average  
 STEL: Short Term Exposure Limit  
 CEIL: Ceiling

**8.2. Exposure controls**

**8.2.1. Engineering controls**

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

**8.2.2. Personal protective equipment (PPE)**

**Eye/face protection**

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

- Full Face Shield
- Indirect Vented Goggles

**Skin/hand protection**

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then

use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

Half facepiece or full facepiece supplied-air respirator

For questions about suitability for a specific application, consult with your respirator manufacturer.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

#### Appearance

Physical state

Liquid

Color

Red

Odor

Strong Solvent

Odor threshold

*No Data Available*

pH

*Not Applicable*

Melting point

*Not Applicable*

Boiling Point

148 °F

Flash Point

52 °F [*Test Method*:Closed Cup]

Evaporation rate

5.9 [*Ref Std*:ETHER=1]

Flammability (solid, gas)

Not Applicable

Flammable Limits(LEL)

6 % volume

Flammable Limits(UEL)

36.5 % volume

Vapor Pressure

94 mmHg [*@* 68 °F]

Vapor Density

1.1 [*Ref Std*:AIR=1]

Density

0.8 g/ml

Specific Gravity

0.8 [*Ref Std*:WATER=1]

Solubility in Water

Negligible

Solubility- non-water

*No Data Available*

Partition coefficient: n-octanol/ water

*No Data Available*

Autoignition temperature

*No Data Available*

Decomposition temperature

*No Data Available*

Viscosity

3 - 8 centipoise [*@* 73.4 °F ]

Volatile Organic Compounds

<=796 g/l [*Test Method*:calculated SCAQMD rule 443.1]

Percent volatile

99 - 99.5 % weight [*Test Method*:Estimated]

VOC Less H2O & Exempt Solvents

<=796 g/l [*Test Method*:calculated SCAQMD rule 443.1]

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

### 10.2. Chemical stability

Stable.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

**10.4. Conditions to avoid**

Sparks and/or flames

**10.5. Incompatible materials**

Strong oxidizing agents

**10.6. Hazardous decomposition products****Substance****Condition**

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

**SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

**11.1. Information on Toxicological effects****Signs and Symptoms of Exposure**

**Based on test data and/or information on the components, this material may produce the following health effects:**

**Inhalation:**

Harmful if inhaled.

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

**Skin Contact:**

Harmful in contact with skin. Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

May cause additional health effects (see below).

**Eye Contact:**

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

**Ingestion:**

Toxic if swallowed. Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

**Additional Health Effects:****Single exposure may cause target organ effects:**

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

May cause blindness.

### Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

### Carcinogenicity:

Ingredient	CAS No.	Class Description	Regulation
Dichloromethane (methylene chloride)	75-09-2	Grp. 2A: Probable human carc.	International Agency for Research on Cancer
Dichloromethane (Methylene Chloride)	75-09-2	Anticipated human carcinogen	National Toxicology Program Carcinogens
METHYLENE CHLORIDE	75-09-2	Cancer hazard	OSHA Carcinogens

### Additional Information:

Persons previously sensitized to amines may develop a cross-sensitization reaction to certain other amines.

### Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

### Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >1,000 - =2,000 mg/kg
Overall product	Inhalation-Vapor(4 hr)		No data available; calculated ATE >10 - =20 mg/l
Overall product	Ingestion		No data available; calculated ATE >50 - =300 mg/kg
METHYL ALCOHOL	Dermal		LD50 estimated to be 1,000 - 2,000 mg/kg
METHYL ALCOHOL	Inhalation-Vapor		LC50 estimated to be 10 - 20 mg/l
METHYL ALCOHOL	Ingestion		LD50 estimated to be 50 - 300 mg/kg
AMINO SILANE	Dermal	Rabbit	LD50 > 2,000 mg/kg
AMINO SILANE	Inhalation-Dust/Mist (4 hours)	Rat	LC50 >1.49, <2.44 mg/l
AMINO SILANE	Ingestion	Rat	LD50 1,897 mg/kg
DCM	Dermal	Rat	LD50 > 2,000 mg/kg
DCM	Inhalation-Vapor (4 hours)	Rat	LC50 63.7 mg/l
DCM	Ingestion	Rat	LD50 1,410 mg/kg

ATE = acute toxicity estimate

### Skin Corrosion/Irritation

Name	Species	Value
METHYL ALCOHOL	Rabbit	Mild irritant
AMINO SILANE	Rabbit	Mild irritant
DCM	Rabbit	Irritant

### Serious Eye Damage/Irritation

Name	Species	Value
METHYL ALCOHOL	Rabbit	Moderate irritant
AMINO SILANE	Rabbit	Corrosive
DCM	Rabbit	Severe irritant

### Skin Sensitization

Name	Species	Value
METHYL ALCOHOL	Guinea pig	Not classified



AMINO SILANE	Multiple animal species	Sensitizing
--------------	-------------------------	-------------

### Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

### Germ Cell Mutagenicity

Name	Route	Value
METHYL ALCOHOL	In Vitro	Some positive data exist, but the data are not sufficient for classification
METHYL ALCOHOL	In vivo	Some positive data exist, but the data are not sufficient for classification
DCM	In vivo	Not mutagenic
DCM	In Vitro	Some positive data exist, but the data are not sufficient for classification

### Carcinogenicity

Name	Route	Species	Value
METHYL ALCOHOL	Inhalation	Multiple animal species	Not carcinogenic
DCM	Inhalation	Multiple animal species	Carcinogenic

### Reproductive Toxicity

#### Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
METHYL ALCOHOL	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,600 mg/kg/day	21 days
METHYL ALCOHOL	Ingestion	Toxic to development	Mouse	LOAEL 4,000 mg/kg/day	during organogenesis
METHYL ALCOHOL	Inhalation	Toxic to development	Mouse	NOAEL 1.3 mg/l	during organogenesis
DCM	Inhalation	Not classified for female reproduction	Rat	NOAEL 5.2 mg/l	2 generation
DCM	Inhalation	Not classified for male reproduction	Rat	NOAEL 5.2 mg/l	2 generation
DCM	Inhalation	Not classified for development	Multiple animal species	NOAEL 4.3 mg/l	during gestation

### Target Organ(s)

#### Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
METHYL ALCOHOL	Inhalation	blindness	Causes damage to organs	Human	NOAEL Not available	occupational exposure
METHYL ALCOHOL	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	not available
METHYL ALCOHOL	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL Not available	6 hours
METHYL ALCOHOL	Ingestion	blindness	Causes damage to organs	Human	NOAEL Not available	poisoning and/or abuse
METHYL ALCOHOL	Ingestion	central nervous	May cause drowsiness or	Human	NOAEL Not	poisoning

		system depression	dizziness		available	and/or abuse
DCM	Dermal	blood	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL Not available	4 hours
DCM	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	occupational exposure
DCM	Inhalation	blood	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
DCM	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	

### Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
METHYL ALCOHOL	Inhalation	liver	Not classified	Rat	NOAEL 6.55 mg/l	4 weeks
METHYL ALCOHOL	Inhalation	respiratory system	Not classified	Rat	NOAEL 13.1 mg/l	6 weeks
METHYL ALCOHOL	Ingestion	liver   nervous system	Not classified	Rat	NOAEL 2,500 mg/kg/day	90 days
AMINO SILANE	Inhalation	respiratory system	May cause damage to organs though prolonged or repeated exposure	Rat	NOAEL 0.015 mg/l	90 days
DCM	Inhalation	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 6.95 mg/l	2 years
DCM	Inhalation	liver	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 0.17 mg/l	2 years
DCM	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Multiple animal species	LOAEL 35 mg/l	8 weeks
DCM	Inhalation	heart	Not classified	Human	NOAEL Not available	
DCM	Inhalation	immune system	Not classified	Rat	NOAEL 18 mg/l	28 days
DCM	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 1,200 mg/kg/day	3 months
DCM	Ingestion	blood	Not classified	Rat	NOAEL 249 mg/kg/day	2 years
DCM	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 1,469 mg/kg/day	3 months
DCM	Ingestion	eyes	Not classified	Rat	NOAEL 249 mg/kg/day	104 weeks

### Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

## SECTION 12: Ecological information

### Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

### Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): D001 (Ignitable)

## SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

## SECTION 15: Regulatory information

### 15.1. US Federal Regulations

Contact 3M for more information.

#### EPCRA 311/312 Hazard Classifications:

##### Physical Hazards

Flammable (gases, aerosols, liquids, or solids)

##### Health Hazards

Acute toxicity

Reproductive toxicity

Respiratory or Skin Sensitization

Serious eye damage or eye irritation

Specific target organ toxicity (single or repeated exposure)

#### Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

<u>Ingredient</u>	<u>C.A.S. No</u>	<u>% by Wt</u>
METHYL ALCOHOL	67-56-1	Trade Secret 99 - 99.9

#### This material contains a chemical which requires export notification under TSCA Section 12[b]:

<u>Ingredient (Category if applicable)</u>	<u>C.A.S. No</u>	<u>Regulation</u>	<u>Status</u>
DCM	75-09-2	Toxic Substances Control Act (TSCA) 6 Banned or Restricted Use Chemicals	Applicable

#### Additional TSCA Information

This chemical/product is not and cannot be distributed in commerce (as defined in TSCA section 3(5)) or processed (as defined in TSCA section 3(13)) for consumer paint or coating removal.

## 15.2. State Regulations

Contact 3M for more information.

## 15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

## 15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

## SECTION 16: Other information

### NFPA Hazard Classification

**Health:** 2 **Flammability:** 3 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

<b>Document Group:</b>	32-7451-1	<b>Version Number:</b>	2.00
<b>Issue Date:</b>	07/27/22	<b>Supersedes Date:</b>	07/07/21

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at [www.3M.com](http://www.3M.com)