



Safety Data Sheet

Copyright, 2021, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group: 32-0253-8
Issue Date: 04/30/21

Version Number: 4.01
Supersedes Date: 05/18/18

SECTION 1: Identification

1.1. Product identifier

3M™ Solar Encapsulant Film EVA9100

Product Identification Numbers

70-0066-8774-6
7010312383

1.2. Recommended use and restrictions on use

Recommended use

Film

1.3. Supplier's details

MANUFACTURER: 3M
DIVISION: Electrical Markets Division
ADDRESS: 3M Center, St. Paul, MN 55144-1000, USA
Telephone: 1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

2.1. Hazard classification

Carcinogenicity: Category 2.

2.2. Label elements

Signal word

Warning

Symbols

Health Hazard |

Pictograms

**Hazard Statements**

Suspected of causing cancer.

Precautionary Statements**Prevention:**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Wear protective gloves.

Response:

IF exposed or concerned: Get medical advice/attention.

Storage:

Store locked up.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

Supplemental Information:

May cause thermal burns.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
Carbonoperoxoic acid, OO-(1,1-dimethylethyl) O-(2-ethylhexyl) ester	34443-12-4	0.1 - 1 Trade Secret *
OCTABENZONE	1843-05-6	< 0.5 Trade Secret *
TRIMETHYLOLPROPANE TRIACRYLATE	15625-89-5	< 0.5 Trade Secret *
VINYL ACETATE	108-05-4	0 - 0.5 Trade Secret *
ETHYLENE-VINYL ACETATE POLYMER	24937-78-8	> 90 Trade Secret *

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures**4.1. Description of first aid measures****Inhalation:**

Remove person to fresh air. If you are concerned, get medical advice.

Skin Contact:

Immediately flush skin with large amounts of cold water for at least 15 minutes. DO NOT ATTEMPT TO REMOVE MOLTEN MATERIAL. Cover affected area with a clean dressing. Get immediate medical attention.

Eye Contact:

Immediately flush eyes with large amounts of water for at least 15 minutes. DO NOT ATTEMPT TO REMOVE MOLTEN MATERIAL. Get immediate medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable.

SECTION 5: Fire-fighting measures**5.1. Suitable extinguishing media**

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Keep away from reactive metals (eg. Aluminum, zinc etc.) to avoid the formation of hydrogen gas that could create an explosion hazard. Use personal protective equipment (gloves, respirators, etc.) as required.

7.2. Conditions for safe storage including any incompatibilities

Protect from sunlight. Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
VINYL ACETATE	108-05-4	ACGIH	TWA:10 ppm;STEL:15 ppm	A3: Confirmed animal carcin.
TRIMETHYLOLPROPANE TRIACRYLATE	15625-89-5	AIHA	TWA:1 mg/m3	SKIN

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Provide appropriate local exhaust when product is heated. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full Face Shield

Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Thermal hazards

Wear heat insulating gloves when handling hot material to prevent thermal burns.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state
Color

Solid
White

Specific Physical Form:

Film

Odor

Mild Odor

Odor threshold

No Data Available

pH

Not Applicable

Melting point

No Data Available

Boiling Point

No Data Available

Flash Point

500 °F [*Test Method:*Closed Cup]

Evaporation rate

Not Applicable

Flammability (solid, gas)

Not Classified

Flammable Limits(LEL)

No Data Available

Flammable Limits(UEL)

No Data Available

Vapor Pressure

No Data Available

Vapor Density

No Data Available

Density

0.93 - 0.97 g/ml

Specific Gravity

0.93 - 0.97 [*Ref Std:*WATER=1]

Solubility In Water

No Data Available

Solubility- non-water

No Data Available

Partition coefficient: n-octanol/ water

No Data Available

Autoignition temperature

No Data Available

Decomposition temperature

No Data Available

Viscosity

No Data Available

Average particle size

No Data Available

Bulk density

No Data Available

Hazardous Air Pollutants

No Data Available

Molecular weight

No Data Available

Volatile Organic Compounds

No Data Available

Percent volatile

No Data Available

Percent volatile

No Data Available

Softening point

No Data Available

VOC Less H2O & Exempt Solvents

No Data Available

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Sparks and/or flames

Light

10.5. Incompatible materials

Strong acids

Strong bases

Strong oxidizing agents

Reactive metals

No Data Available

10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
Carbon monoxide	Oxidation, heat or reaction
Carbon dioxide	Oxidation, heat or reaction

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Vapors from heated material may cause irritation of the respiratory system. Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

Skin Contact:

During heating: Thermal Burns: Signs/symptoms may include intense pain, redness and swelling, and tissue destruction.

Eye Contact:

During heating: Thermal Burns: Signs/symptoms may include severe pain, redness and swelling, and tissue destruction.

Ingestion:

Physical Blockage: Signs/symptoms may include cramping, abdominal pain, and constipation.

May cause additional health effects (see below).

Additional Health Effects:

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

<u>Ingredient</u>	<u>CAS No.</u>	<u>Class Description</u>	<u>Regulation</u>
VINYL ACETATE	108-05-4	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

<u>Name</u>	<u>Route</u>	<u>Species</u>	<u>Value</u>
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
ETHYLENE-VINYL ACETATE POLYMER	Dermal		LD50 estimated to be > 5,000 mg/kg

ETHYLENE-VINYL ACETATE POLYMER	Ingestion	Rat	LD50 > 1,000 mg/kg
VINYL ACETATE	Dermal	Rabbit	LD50 2,320 mg/kg
VINYL ACETATE	Inhalation-Vapor (4 hours)	Rat	LC50 11.3 mg/l
VINYL ACETATE	Ingestion	Rat	LD50 2,920 mg/kg
TRIMETHYLOLPROPANE TRIACRYLATE	Dermal	Rabbit	LD50 5,170 mg/kg
TRIMETHYLOLPROPANE TRIACRYLATE	Ingestion	Rat	LD50 > 5,000 mg/kg
OCTABENZONE	Dermal	Rabbit	LD50 > 10,000 mg/kg
OCTABENZONE	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 20 mg/l
OCTABENZONE	Ingestion	Rat	LD50 > 10,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
ETHYLENE-VINYL ACETATE POLYMER	Professional judgement	No significant irritation
VINYL ACETATE	Rabbit	Minimal irritation
TRIMETHYLOLPROPANE TRIACRYLATE	Rabbit	Mild irritant
OCTABENZONE	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
ETHYLENE-VINYL ACETATE POLYMER	Professional judgement	No significant irritation
VINYL ACETATE	Rabbit	Mild irritant
TRIMETHYLOLPROPANE TRIACRYLATE	Rabbit	Corrosive
OCTABENZONE	Rabbit	No significant irritation

Skin Sensitization

Name	Species	Value
VINYL ACETATE	Guinea pig	Not classified
TRIMETHYLOLPROPANE TRIACRYLATE	Guinea pig	Sensitizing
OCTABENZONE	Guinea pig	Sensitizing

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
VINYL ACETATE	In Vitro	Some positive data exist, but the data are not sufficient for classification
VINYL ACETATE	In vivo	Some positive data exist, but the data are not sufficient for classification
TRIMETHYLOLPROPANE TRIACRYLATE	In vivo	Not mutagenic
TRIMETHYLOLPROPANE TRIACRYLATE	In Vitro	Some positive data exist, but the data are not sufficient for classification
OCTABENZONE	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
VINYL ACETATE	Ingestion	Multiple animal species	Carcinogenic
VINYL ACETATE	Inhalation	Rat	Carcinogenic
TRIMETHYLOLPROPANE TRIACRYLATE	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
VINYL ACETATE	Ingestion	Not classified for female reproduction	Rat	NOAEL 140 mg/kg/day	2 generation
VINYL ACETATE	Ingestion	Not classified for male reproduction	Rat	NOAEL 140 mg/kg/day	2 generation
VINYL ACETATE	Ingestion	Not classified for development	Rat	NOAEL 700 mg/kg/day	2 generation
VINYL ACETATE	Inhalation	Not classified for development	Rat	NOAEL 0.7 mg/l	during organogenesis
OCTABENZONE	Ingestion	Not classified for female reproduction	Rat	NOAEL 614 mg/kg/day	4 generation
OCTABENZONE	Ingestion	Not classified for male reproduction	Rat	NOAEL 524 mg/kg/day	4 generation
OCTABENZONE	Ingestion	Not classified for development	Rat	NOAEL 614 mg/kg/day	4 generation

Lactation

Name	Route	Species	Value
OCTABENZONE	Ingestion	Rat	Not classified for effects on or via lactation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
VINYL ACETATE	Inhalation	respiratory irritation	May cause respiratory irritation	Human and animal	NOAEL Not available	
VINYL ACETATE	Inhalation	central nervous system depression	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
ETHYLENE-VINYL ACETATE POLYMER	Ingestion	liver	Not classified	Rat	NOAEL 4,000 mg/kg/day	90 days
VINYL ACETATE	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Multiple animal species	NOAEL 0.2 mg/l	104 weeks
VINYL ACETATE	Inhalation	heart hematopoietic system liver kidney and/or bladder	Not classified	Rat	NOAEL 2.1 mg/l	104 weeks
VINYL ACETATE	Inhalation	endocrine system	Not classified	Rat	NOAEL 0.07 mg/l	120 days
VINYL ACETATE	Inhalation	immune system	Not classified	Multiple animal	NOAEL 3.5 mg/l	3 months

				species		
VINYL ACETATE	Inhalation	nervous system	Not classified	Multiple animal species	NOAEL 2.1 mg/l	104 weeks
VINYL ACETATE	Inhalation	gastrointestinal tract	Not classified	Mouse	NOAEL 3.5 mg/l	3 months
VINYL ACETATE	Ingestion	liver	Not classified	Rat	LOAEL 684 mg/kg/day	3 months
VINYL ACETATE	Ingestion	hematopoietic system nervous system kidney and/or bladder	Not classified	Rat	NOAEL 235 mg/kg/day	104 weeks
VINYL ACETATE	Ingestion	immune system respiratory system	Not classified	Mouse	NOAEL 950 mg/kg/day	3 months
VINYL ACETATE	Ingestion	heart	Not classified	Rat	NOAEL 235 mg/kg/day	104 weeks
TRIMETHYLOLPROPANE TRIACRYLATE	Dermal	immune system	May cause damage to organs though prolonged or repeated exposure	Mouse	NOAEL 50 mg/kg/day	16 days
TRIMETHYLOLPROPANE TRIACRYLATE	Dermal	heart hematopoietic system kidney and/or bladder respiratory system	Not classified	Mouse	NOAEL 12 mg/kg/day	28 weeks
OCTABENZONE	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 80 mg/kg/day	90 days
OCTABENZONE	Ingestion	endocrine system hematopoietic system	Not classified	Rat	NOAEL 2,000 mg/kg/day	90 days
OCTABENZONE	Ingestion	liver	Not classified	Dog	NOAEL 300 mg/kg/day	2 years

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): Not regulated

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:

Physical Hazards

Not applicable

Health Hazards

Carcinogenicity

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

<u>Ingredient</u>	<u>C.A.S. No</u>	<u>% by Wt</u>
VINYL ACETATE	108-05-4	Trade Secret 0 - 0.5

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

This product is an article as defined by TSCA regulations, and is exempt from TSCA Inventory listing requirements.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 0 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document Group: 32-0253-8

Issue Date: 04/30/21

Version Number: 4.01

Supersedes Date: 05/18/18

Reason for Reissue

Conversion to GHS format SDS.

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com