



Safety Data Sheet

Copyright,2020, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	32-1840-1	Version Number:	7.00
Issue Date:	11/23/20	Supersedes Date:	10/26/20

SECTION 1: Identification

1.1. Product identifier

3M™ Screen Print UV Gloss Clear 9740i

Product Identification Numbers

75-0400-3343-5, 75-0400-3386-4, 75-3472-5444-5, 75-3472-5445-2
7100041500, 7000148701, 7100175319, 7100175688

1.2. Recommended use and restrictions on use

Recommended use

UV Clear Coat for Graphic Applications, Ink

1.3. Supplier's details

MANUFACTURER:	3M
DIVISION:	Commercial Solutions Division
ADDRESS:	3M Center, St. Paul, MN 55144-1000, USA
Telephone:	1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

2.1. Hazard classification

Acute Toxicity (oral): Category 4.
Serious Eye Damage/Irritation: Category 1.
Skin Corrosion/Irritation: Category 2.
Skin Sensitizer: Category 1A.
Reproductive Toxicity: Category 1B.
Carcinogenicity: Category 2.
Specific Target Organ Toxicity (repeated exposure): Category 1.

2.2. Label elements

Signal word

Danger

Symbols

Corrosion | Exclamation mark | Health Hazard |

Pictograms**Hazard Statements**

Harmful if swallowed.

Causes serious eye damage.

Causes skin irritation.

May cause an allergic skin reaction.

May damage fertility or the unborn child.

Suspected of causing cancer.

Causes damage to organs through prolonged or repeated exposure:
respiratory system |

May cause damage to organs through prolonged or repeated exposure:
gastrointestinal tract |
immune system |
skin |

Precautionary Statements**Prevention:**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wear protective gloves and eye/face protection.

Do not eat, drink or smoke when using this product.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Response:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF ON SKIN: Wash with plenty of soap and water.

Immediately call a POISON CENTER or doctor/physician.

If skin irritation or rash occurs: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

Rinse mouth.

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

Storage:

Keep container tightly closed.

Keep cool.

Store locked up in a well-ventilated place.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

50% of the mixture consists of ingredients of unknown acute oral toxicity.

53% of the mixture consists of ingredients of unknown acute dermal toxicity.

90% of the mixture consists of ingredients of unknown acute inhalation toxicity.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
Urethane acrylate oligomer	72162-39-1	30 - 40 Trade Secret *
Vinylcaprolactam	2235-00-9	10 - 20 Trade Secret *
Amine modified acrylic oligomer	67906-98-3	5 - 15 Trade Secret *
1,6-HEXANEDIOL DIACRYLATE	13048-33-4	3 - 7 Trade Secret *
2-Ethylhexyl Acrylate	103-11-7	3 - 7 Trade Secret *
CURING AGENT (NJTSRN 04499600-6673)	Trade Secret*	3 - 7 Trade Secret *
TETRAHYDROFURFURYL ACRYLATE	2399-48-6	1 - 5 Trade Secret *
DIETHYLENE GLYCOL ETHYL ETHER ACRYLATE	7328-17-8	1 - 3 Trade Secret *
N,N'-BIS(2,2,6,6-TETRAMETHYL-4-PIPERIDINYL)-1,6-HEXANEDIAMINE, POLYMERS W/MORPHOLINE-2,4,6-TRICHLORO-1,3,5-TRIAZINE RCTN PROD, METHYLATED	193098-40-7	1 - 3 Trade Secret *
POLY(DIMETHYLSILOXANE)	63148-62-9	1 - 3 Trade Secret *
TRIAZINE DERIVATIVE	Trade Secret*	1 - 3 Trade Secret *
UV ABSORBERS (NJTSRN 04499600-6672)	Trade Secret*	1 - 3 Trade Secret *
2,4,6-Trimethylbenzoyldiphenylphosphine oxide	75980-60-8	< 1 Trade Secret *
N,N'-BIS(2,6-DIISOPROPYLPHENYL)CARBODIIMIDE	2162-74-5	< 1 Trade Secret *
PHENOXY ETHYL ACRYLATE	48145-04-6	<= 1 Trade Secret *
Acrylic Acid	79-10-7	< 0.2 Trade Secret *
Toluene	108-88-3	< 0.2 Trade Secret *

NJTS or NJTSRN: New Jersey Trade Secret Registry Number.

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable.

SECTION 5: Fire-fighting measures**5.1. Suitable extinguishing media**

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products**Substance**

Formaldehyde
Carbon monoxide
Carbon dioxide

Condition

During Combustion
During Combustion
During Combustion

5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with detergent and water. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (gloves, respirators, etc.) as required.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Protect from sunlight. Store away from

heat. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Toluene	108-88-3	ACGIH	TWA:20 ppm	A4: Not class. as human carcin, Ototoxicant
Toluene	108-88-3	OSHA	TWA:200 ppm;CEIL:300 ppm	
1,6-HEXANEDIOL DIACRYLATE	13048-33-4	AIHA	TWA:1 mg/m3(0.11 ppm)	Dermal Sensitizer
Vinylcaprolactam	2235-00-9	Manufacturer determined	TWA:0.1 ppm(0.57 mg/m3)	
TETRAHYDROFURFURYL ACRYLATE	2399-48-6	Manufacturer determined	TWA:0.1 ppm(0.64 mg/m3);STEL:0.3 ppm(1.91 mg/m3)	Dermal Sensitizer
Acrylic Acid	79-10-7	ACGIH	TWA:2 ppm	A4: Not class. as human carcin, Danger of cutaneous absorption

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full Face Shield

Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an

exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates, including oily mists

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state

Liquid

Color

Colorless

Odor

Acrylate

Odor threshold

No Data Available

pH

Not Applicable

Melting point

Not Applicable

Boiling Point

≥ 200 °F

Flash Point

≥ 200 °F [*Test Method: Closed Cup*]

Evaporation rate

≤ 1 [*Ref Std: BUOAC=1*]

Flammability (solid, gas)

Not Applicable

Flammable Limits(LEL)

No Data Available

Flammable Limits(UEL)

No Data Available

Vapor Pressure

≤ 10 mmHg [*@ 20 °C*]

Vapor Density

≥ 1 [*Ref Std: AIR=1*]

Density

1.3 g/ml

Specific Gravity

1.3 [*Test Method: Tested per ASTM protocol*] [*Ref Std: WATER=1*]

Solubility in Water

Moderate

Solubility- non-water

No Data Available

Partition coefficient: n-octanol/ water

No Data Available

Autoignition temperature

No Data Available

Decomposition temperature

No Data Available

Viscosity

1,000 - 5,000 Pa-s [*Test Method: Tested per ASTM protocol*]

Volatile Organic Compounds

< 10 g/l

VOC Less H2O & Exempt Solvents

< 10 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization may occur. upon depletion of inhibitor or exposure to heat.

10.4. Conditions to avoid

Heat

10.5. Incompatible materials

Strong oxidizing agents

10.6. Hazardous decomposition products**Substance****Condition**

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects**Signs and Symptoms of Exposure**

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

May be harmful if inhaled. Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

Skin Contact:

May be harmful in contact with skin.

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

May cause additional health effects (see below).

Eye Contact:

Corrosive (Eye Burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

Ingestion:

Harmful if swallowed. Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

Additional Health Effects:**Prolonged or repeated exposure may cause target organ effects:**

Immunological Effects: Signs/symptoms may include alterations in the number of circulating immune cells, allergic skin and/or respiratory reaction, and changes in immune function.

Gastrointestinal Effects: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Respiratory Effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish colored skin (cyanosis), sputum production, changes in lung function tests, and/or respiratory failure.

Dermal Effects: Signs/symptoms may include redness, itching, acne, or bumps on the skin.

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Ingredient	CAS No.	Class Description	Regulation
2-Ethylhexyl Acrylate	103-11-7	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE2,000 - 5,000 mg/kg
Overall product	Inhalation-Dust/Mist(4 hr)		No data available; calculated ATE5 - 12.5 mg/l
Overall product	Ingestion		No data available; calculated ATE300 - 2,000 mg/kg
Vinylcaprolactam	Dermal	Rabbit	LD50 1,700 mg/kg
Vinylcaprolactam	Ingestion	Rat	LD50 1,049 mg/kg
2-Ethylhexyl Acrylate	Dermal	Rabbit	LD50 > 10,000 mg/kg
2-Ethylhexyl Acrylate	Ingestion	Rat	LD50 4,430 mg/kg
1,6-HEXANEDIOL DIACRYLATE	Dermal	Rabbit	LD50 3,636 mg/kg
1,6-HEXANEDIOL DIACRYLATE	Ingestion	Rat	LD50 > 5,000 mg/kg
CURING AGENT (NJTSRN 04499600-6673)	Dermal	Rat	LD50 > 5,000 mg/kg
CURING AGENT (NJTSRN 04499600-6673)	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 1 mg/l
CURING AGENT (NJTSRN 04499600-6673)	Ingestion	Rat	LD50 2,500 mg/kg
TETRAHYDROFURFURYL ACRYLATE	Ingestion	Rat	LD50 882 mg/kg
DIETHYLENE GLYCOL ETHYL ETHER ACRYLATE	Dermal		LD50 estimated to be 1,000 - 2,000 mg/kg
DIETHYLENE GLYCOL ETHYL ETHER ACRYLATE	Ingestion	Rat	LD50 1,860 mg/kg
N,N'-BIS(2,2,6,6-TETRAMETHYL-4-PIPERIDINYL)-1,6-HEXANEDIAMINE, POLYMERS W/MORPHOLINE-2,4,6-TRICHLORO-1,3,5-TRIAZINE RCTN PROD, METHYLATED	Dermal	Rat	LD50 > 2,000 mg/kg
N,N'-BIS(2,2,6,6-TETRAMETHYL-4-PIPERIDINYL)-1,6-HEXANEDIAMINE, POLYMERS W/MORPHOLINE-2,4,6-TRICHLORO-1,3,5-TRIAZINE RCTN PROD, METHYLATED	Ingestion	Rat	LD50 > 500, < 2,000 mg/kg
N,N'-BIS(2,2,6,6-TETRAMETHYL-4-PIPERIDINYL)-1,6-HEXANEDIAMINE, POLYMERS W/MORPHOLINE-2,4,6-TRICHLORO-1,3,5-TRIAZINE RCTN PROD, METHYLATED	Inhalation-Dust/Mist (4 hours)	similar compounds	LC50 2.8 mg/l
TRIAZINE DERIVATIVE	Dermal	Rat	LD50 > 2,000 mg/kg
TRIAZINE DERIVATIVE	Ingestion	Rat	LD50 > 2,000 mg/kg
POLY(DIMETHYLSILOXANE)	Dermal	Rabbit	LD50 > 19,400 mg/kg
POLY(DIMETHYLSILOXANE)	Ingestion	Rat	LD50 > 17,000 mg/kg
PHENOXY ETHYL ACRYLATE	Dermal	Rat	LD50 > 2,000 mg/kg
PHENOXY ETHYL ACRYLATE	Ingestion	Rat	LD50 > 5,000 mg/kg
N,N'-BIS(2,6-DIISOPROPYLPHENYL)CARBODIIMIDE	Dermal	Rat	LD50 > 2,000 mg/kg
N,N'-BIS(2,6-DIISOPROPYLPHENYL)CARBODIIMIDE	Ingestion	Rat	LD50 > 300, < 2000 mg/kg
2,4,6-Trimethylbenzoyldiphenylphosphine oxide	Dermal	Professional judgement	LD50 estimated to be > 5,000 mg/kg
2,4,6-Trimethylbenzoyldiphenylphosphine oxide	Ingestion	Rat	LD50 > 5,000 mg/kg
Toluene	Dermal	Rat	LD50 12,000 mg/kg

Toluene	Inhalation-Vapor (4 hours)	Rat	LC50 30 mg/l
Toluene	Ingestion	Rat	LD50 5,550 mg/kg
Acrylic Acid	Dermal	Rabbit	LD50 > 2,000 mg/kg
Acrylic Acid	Inhalation-Dust/Mist (4 hours)	Rat	LC50 3.8 mg/l
Acrylic Acid	Ingestion	Rat	LD50 1,250 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Urethane acrylate oligomer	similar compounds	Irritant
Vinylcaprolactam	Rabbit	Minimal irritation
Amine modified acrylic oligomer	similar compounds	Irritant
2-Ethylhexyl Acrylate	Rabbit	Irritant
1,6-HEXANEDIOL DIACRYLATE	Rabbit	Irritant
CURING AGENT (NJTSRN 04499600-6673)	Rabbit	No significant irritation
TETRAHYDROFURFURYL ACRYLATE	Rabbit	Corrosive
DIETHYLENE GLYCOL ETHYL ETHER ACRYLATE	Rabbit	Irritant
N,N'-BIS(2,2,6,6-TETRAMETHYL-4-PIPERIDINYL)-1,6-HEXANEDIAMINE, POLYMERS W/MORPHOLINE-2,4,6-TRICHLORO-1,3,5-TRIAZINE RCTN PROD, METHYLATED	Rabbit	No significant irritation
TRIAZINE DERIVATIVE	Rabbit	No significant irritation
POLY(DIMETHYLSILOXANE)	Rabbit	No significant irritation
PHENOXY ETHYL ACRYLATE	Rabbit	No significant irritation
N,N'-BIS(2,6-DIISOPROPYLPHENYL)CARBODIIMIDE	Rat	Minimal irritation
2,4,6-Trimethylbenzoyldiphenylphosphine oxide	Rabbit	No significant irritation
Toluene	Rabbit	Irritant
Acrylic Acid	Rabbit	Corrosive

Serious Eye Damage/Irritation

Name	Species	Value
Urethane acrylate oligomer	similar compounds	Severe irritant
Vinylcaprolactam	Rabbit	Severe irritant
Amine modified acrylic oligomer	similar compounds	Severe irritant
2-Ethylhexyl Acrylate	Rabbit	No significant irritation
1,6-HEXANEDIOL DIACRYLATE	Rabbit	Moderate irritant
CURING AGENT (NJTSRN 04499600-6673)	Rabbit	Mild irritant
TETRAHYDROFURFURYL ACRYLATE	Rabbit	Corrosive
DIETHYLENE GLYCOL ETHYL ETHER ACRYLATE	Rabbit	Severe irritant
N,N'-BIS(2,2,6,6-TETRAMETHYL-4-PIPERIDINYL)-1,6-HEXANEDIAMINE, POLYMERS W/MORPHOLINE-2,4,6-TRICHLORO-1,3,5-TRIAZINE RCTN PROD, METHYLATED	Rabbit	Severe irritant
TRIAZINE DERIVATIVE	Rabbit	No significant irritation
POLY(DIMETHYLSILOXANE)	Rabbit	No significant irritation
PHENOXY ETHYL ACRYLATE	Rabbit	No significant irritation
N,N'-BIS(2,6-DIISOPROPYLPHENYL)CARBODIIMIDE	Rabbit	Mild irritant
2,4,6-Trimethylbenzoyldiphenylphosphine oxide	Rabbit	No significant irritation
Toluene	Rabbit	Moderate irritant
Acrylic Acid	Rabbit	Corrosive

Skin Sensitization

Name	Species	Value
Vinylcaprolactam	Mouse	Sensitizing
Amine modified acrylic oligomer	similar compounds	Sensitizing
2-Ethylhexyl Acrylate	Human and animal	Sensitizing
1,6-HEXANEDIOL DIACRYLATE	Guinea pig	Sensitizing
CURING AGENT (NJTSRN 04499600-6673)	Guinea pig	Not classified
TETRAHYDROFURFURYL ACRYLATE	Professional judgement	Sensitizing
DIETHYLENE GLYCOL ETHYL ETHER ACRYLATE	Guinea pig	Sensitizing
N,N'-BIS(2,2,6,6-TETRAMETHYL-4-PIPERIDINYL)-1,6-HEXANEDIAMINE, POLYMERS W/MORPHOLINE-2,4,6-TRICHLORO-1,3,5-TRIAZINE RCTN PROD, METHYLATED	Guinea pig	Not classified
TRIAZINE DERIVATIVE	Mouse	Not classified
PHENOXY ETHYL ACRYLATE	Guinea pig	Sensitizing
N,N'-BIS(2,6-DIISOPROPYLPHENYL)CARBODIIMIDE	Guinea pig	Not classified
2,4,6-Trimethylbenzoyldiphenylphosphine oxide	Mouse	Sensitizing
Toluene	Guinea pig	Not classified
Acrylic Acid	Guinea pig	Not classified

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Vinylcaprolactam	In Vitro	Not mutagenic
2-Ethylhexyl Acrylate	In vivo	Not mutagenic
2-Ethylhexyl Acrylate	In Vitro	Some positive data exist, but the data are not sufficient for classification
1,6-HEXANEDIOL DIACRYLATE	In Vitro	Some positive data exist, but the data are not sufficient for classification
CURING AGENT (NJTSRN 04499600-6673)	In Vitro	Not mutagenic
CURING AGENT (NJTSRN 04499600-6673)	In vivo	Not mutagenic
TETRAHYDROFURFURYL ACRYLATE	In Vitro	Not mutagenic
N,N'-BIS(2,2,6,6-TETRAMETHYL-4-PIPERIDINYL)-1,6-HEXANEDIAMINE, POLYMERS W/MORPHOLINE-2,4,6-TRICHLORO-1,3,5-TRIAZINE RCTN PROD, METHYLATED	In Vitro	Not mutagenic
TRIAZINE DERIVATIVE	In Vitro	Not mutagenic
N,N'-BIS(2,6-DIISOPROPYLPHENYL)CARBODIIMIDE	In Vitro	Not mutagenic
2,4,6-Trimethylbenzoyldiphenylphosphine oxide	In Vitro	Not mutagenic
Toluene	In Vitro	Not mutagenic
Toluene	In vivo	Not mutagenic
Acrylic Acid	In vivo	Not mutagenic
Acrylic Acid	In Vitro	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
2-Ethylhexyl Acrylate	Dermal	Mouse	Carcinogenic
1,6-HEXANEDIOL DIACRYLATE	Dermal	Mouse	Not carcinogenic
Toluene	Dermal	Mouse	Some positive data exist, but the data are not

			sufficient for classification
Toluene	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification
Toluene	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification
Acrylic Acid	Ingestion	Rat	Not carcinogenic
Acrylic Acid	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
2-Ethylhexyl Acrylate	Inhalation	Not classified for development	Rat	NOAEL 0.75 mg/l	during gestation
1,6-HEXANEDIOL DIACRYLATE	Not Specified	Not classified for development	Rat	NOAEL 750 mg/kg/day	during organogenesis
CURING AGENT (NJTSRN 04499600-6673)	Ingestion	Not classified for development	Rat	NOAEL 900 mg/kg/day	during gestation
TETRAHYDROFURFURYL ACRYLATE	Ingestion	Toxic to female reproduction	Rat	NOAEL 50 mg/kg/day	prematuring into lactation
TETRAHYDROFURFURYL ACRYLATE	Dermal	Toxic to male reproduction	Rat	NOAEL 100 mg/kg/day	90 days
TETRAHYDROFURFURYL ACRYLATE	Ingestion	Toxic to male reproduction	Rat	NOAEL 35 mg/kg/day	90 days
TETRAHYDROFURFURYL ACRYLATE	Inhalation	Toxic to male reproduction	Rat	NOAEL 0.6 mg/l	90 days
TETRAHYDROFURFURYL ACRYLATE	Ingestion	Toxic to development	Rat	NOAEL 50 mg/kg/day	prematuring into lactation
PHENOXY ETHYL ACRYLATE	Ingestion	Not classified for male reproduction	Rat	NOAEL 800 mg/kg/day	43 days
PHENOXY ETHYL ACRYLATE	Ingestion	Toxic to female reproduction	Rat	NOAEL 300 mg/kg/day	prematuring into lactation
PHENOXY ETHYL ACRYLATE	Ingestion	Toxic to development	Rat	NOAEL 300 mg/kg/day	prematuring into lactation
N,N'-BIS(2,6-DIISOPROPYLPHENYL)CARBODIIMIDE	Ingestion	Not classified for development	Rat	NOAEL 3 mg/kg/day	prematuring into lactation
N,N'-BIS(2,6-DIISOPROPYLPHENYL)CARBODIIMIDE	Ingestion	Not classified for male reproduction	Rat	NOAEL 3 mg/kg/day	28 days
N,N'-BIS(2,6-DIISOPROPYLPHENYL)CARBODIIMIDE	Ingestion	Toxic to female reproduction	Rat	NOAEL 1 mg/kg/day	prematuring into lactation
2,4,6-Trimethylbenzoyldiphenylphosphine oxide	Ingestion	Not classified for development	Rat	NOAEL 150 mg/kg/day	during gestation
2,4,6-Trimethylbenzoyldiphenylphosphine oxide	Ingestion	Toxic to female reproduction	Rat	NOAEL 200 mg/kg/day	prematuring into lactation
2,4,6-Trimethylbenzoyldiphenylphosphine oxide	Ingestion	Toxic to male reproduction	Rat	NOAEL 60 mg/kg/day	85 days
Toluene	Inhalation	Not classified for female reproduction	Human	NOAEL Not available	occupational exposure
Toluene	Inhalation	Not classified for male reproduction	Rat	NOAEL 2.3 mg/l	1 generation
Toluene	Ingestion	Toxic to development	Rat	LOAEL 520 mg/kg/day	during gestation
Toluene	Inhalation	Toxic to development	Human	NOAEL Not available	poisoning and/or abuse
Acrylic Acid	Ingestion	Not classified for female reproduction	Rat	NOAEL 460 mg/kg/day	2 generation
Acrylic Acid	Ingestion	Not classified for male reproduction	Rat	NOAEL 460 mg/kg/day	2 generation
Acrylic Acid	Inhalation	Not classified for development	Rat	NOAEL 1.1 mg/l	during organogenesis

Acrylic Acid	Ingestion	Not classified for development	Rat	NOAEL 53 mg/kg/day	s 2 generation
--------------	-----------	--------------------------------	-----	--------------------	-------------------

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Urethane acrylate oligomer	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
Vinylcaprolactam	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL Not available	
Amine modified acrylic oligomer	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
2-Ethylhexyl Acrylate	Inhalation	respiratory irritation	May cause respiratory irritation	Rat	NOAEL Not available	
1,6-HEXANEDIOL DIACRYLATE	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
TETRAHYDROFURFURYL ACRYLATE	Inhalation	respiratory irritation	May cause respiratory irritation	Human and animal	NOAEL Not available	
N,N'-BIS(2,2,6,6-TETRAMETHYL-4-PIPERIDINYL)-1,6-HEXANEDIAMINE, POLYMERS W/MORPHOLINE-2,4,6-TRICHLORO-1,3,5-TRIAZINE RCTN PROD, METHYLATED	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
Toluene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Toluene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Toluene	Inhalation	immune system	Not classified	Mouse	NOAEL 0.004 mg/l	3 hours
Toluene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
Acrylic Acid	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Vinylcaprolactam	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	NOAEL 0.001 mg/l	28 days
Vinylcaprolactam	Inhalation	blood liver kidney and/or bladder eyes	Not classified	Rat	NOAEL 0.18 mg/l	90 days
Vinylcaprolactam	Ingestion	liver	Not classified	Rat	NOAEL 260 mg/kg/day	3 months
2-Ethylhexyl Acrylate	Inhalation	endocrine system liver	Not classified	Rat	NOAEL 0.75 mg/l	90 days
2-Ethylhexyl Acrylate	Inhalation	olfactory system	Not classified	Rat	NOAEL 0.08 mg/l	90 days
2-Ethylhexyl Acrylate	Inhalation	respiratory system	Not classified	Rat	NOAEL 0.75 mg/l	90 days
1,6-HEXANEDIOL DIACRYLATE	Dermal	skin	May cause damage to organs though prolonged or repeated	Mouse	LOAEL 70 mg/kg/day	80 weeks

			exposure			
CURING AGENT (NJTSRN 04499600-6673)	Ingestion	endocrine system liver kidney and/or bladder heart blood immune system nervous system	Not classified	Rat	NOAEL 1,000 mg/kg/day	90 days
N,N'-BIS(2,2,6,6- TETRAMETHYL-4- PIPERIDINYL)-1,6- HEXANEDIAMINE, POLYMERS W/MORPHOLINE-2,4,6- TRICHLORO-1,3,5- TRIAZINE RCTN PROD, METHYLATED	Ingestion	gastrointestinal tract immune system	May cause damage to organs though prolonged or repeated exposure	Rat	NOAEL 15 mg/kg/day	28 days
N,N'-BIS(2,6- DIISOPROPYLPHENYL) CARBODIIMIDE	Ingestion	heart endocrine system immune system kidney and/or bladder	Causes damage to organs through prolonged or repeated exposure	Rat	NOAEL 4 mg/kg/day	28 days
N,N'-BIS(2,6- DIISOPROPYLPHENYL) CARBODIIMIDE	Ingestion	bone, teeth, nails, and/or hair hematopoietic system liver nervous system	Not classified	Rat	NOAEL 16 mg/kg/day	28 days
2,4,6- Trimethylbenzoyldiphenyl phosphine oxide	Ingestion	skin blood liver kidney and/or bladder nervous system	Not classified	Rat	NOAEL 1,000 mg/kg/day	90 days
Toluene	Inhalation	auditory system eyes olfactory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
Toluene	Inhalation	nervous system	May cause damage to organs though prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
Toluene	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 2.3 mg/l	15 months
Toluene	Inhalation	heart liver kidney and/or bladder	Not classified	Rat	NOAEL 11.3 mg/l	15 weeks
Toluene	Inhalation	endocrine system	Not classified	Rat	NOAEL 1.1 mg/l	4 weeks
Toluene	Inhalation	immune system	Not classified	Mouse	NOAEL Not available	20 days
Toluene	Inhalation	bone, teeth, nails, and/or hair	Not classified	Mouse	NOAEL 1.1 mg/l	8 weeks
Toluene	Inhalation	hematopoietic system vascular system	Not classified	Human	NOAEL Not available	occupational exposure
Toluene	Inhalation	gastrointestinal tract	Not classified	Multiple animal species	NOAEL 11.3 mg/l	15 weeks
Toluene	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 625 mg/kg/day	13 weeks
Toluene	Ingestion	heart	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
Toluene	Ingestion	liver kidney and/or bladder	Not classified	Multiple animal species	NOAEL 2,500 mg/kg/day	13 weeks
Toluene	Ingestion	hematopoietic system	Not classified	Mouse	NOAEL 600 mg/kg/day	14 days
Toluene	Ingestion	endocrine system	Not classified	Mouse	NOAEL 105 mg/kg/day	28 days
Toluene	Ingestion	immune system	Not classified	Mouse	NOAEL 105 mg/kg/day	4 weeks

Aspiration Hazard

Name	Value
Toluene	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information**Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations**13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. If no other disposal options are available, waste product that has been completely cured or polymerized may be placed in a landfill properly designed for industrial waste. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): D018 (Benzene)

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information**15.1. US Federal Regulations**

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:**Physical Hazards**

Not applicable

Health Hazards

Acute toxicity

Carcinogenicity

Reproductive toxicity

Respiratory or Skin Sensitization
Serious eye damage or eye irritation
Skin Corrosion or Irritation
Specific target organ toxicity (single or repeated exposure)

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 3 **Flammability:** 1 **Instability:** 1 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document Group:	32-1840-1	Version Number:	7.00
Issue Date:	11/23/20	Supersedes Date:	10/26/20

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com