



## Safety Data Sheet

Copyright, 2018, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document Group:</b>	32-1802-1	<b>Version Number:</b>	2.01
<b>Issue Date:</b>	01/08/18	<b>Supersedes Date:</b>	09/23/15

### SECTION 1: Identification

#### 1.1. Product identifier

3M(TM) Piezo Inkjet Ink 1596v2 Cyan

#### Product Identification Numbers

75-3472-5459-3

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Ink

#### 1.3. Supplier's details

<b>MANUFACTURER:</b>	3M
<b>DIVISION:</b>	Commercial Solutions Division
<b>ADDRESS:</b>	3M Center, St. Paul, MN 55144-1000, USA
<b>Telephone:</b>	1-888-3M HELPS (1-888-364-3577)

#### 1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

### SECTION 2: Hazard identification

#### 2.1. Hazard classification

Flammable Liquid: Category 4.  
Acute Toxicity (inhalation): Category 4.  
Serious Eye Damage/Irritation: Category 2A.  
Skin Corrosion/Irritation: Category 2.  
Specific Target Organ Toxicity (repeated exposure): Category 2.

#### 2.2. Label elements

##### Signal word

Warning

##### Symbols

Exclamation mark | Health Hazard |

**Pictograms****Hazard Statements**

Combustible liquid.

Causes serious eye irritation.

Causes skin irritation.

Harmful if inhaled.

May cause damage to organs through prolonged or repeated exposure:  
blood or blood-forming organs |

**Precautionary Statements****Prevention:**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not breathe dust/fume/gas/mist/vapors/spray.

Use only outdoors or in a well-ventilated area.

Wear protective gloves and eye/face protection.

Wash thoroughly after handling.

**Response:**

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

If eye irritation persists: Get medical advice/attention.

IF ON SKIN: Wash with plenty of soap and water.

If skin irritation occurs: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

Get medical advice/attention if you feel unwell.

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

**Storage:**

Keep container tightly closed.

Keep cool.

Store locked up in a well-ventilated place.

**Disposal:**

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

3% of the mixture consists of ingredients of unknown acute oral toxicity.

3% of the mixture consists of ingredients of unknown acute dermal toxicity.

5% of the mixture consists of ingredients of unknown acute inhalation toxicity.

**SECTION 3: Composition/information on ingredients**

Ingredient	C.A.S. No.	% by Wt
2-BUTOXYETHYL ACETATE	112-07-2	70 - 90 Trade Secret *
CYCLOHEXANONE	108-94-1	5 - 15 Trade Secret *

ETHYL LACTATE	97-64-3	1 - 10 Trade Secret *
PIGMENT	Trade Secret*	1 - 10 Trade Secret *
TRICRESYL PHOSPHATE	1330-78-5	0.1 - 2 Trade Secret *

\*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

**Inhalation:**

Remove person to fresh air. If you feel unwell, get medical attention.

**Skin Contact:**

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

**Eye Contact:**

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

**If Swallowed:**

Rinse mouth. If you feel unwell, get medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable.

## SECTION 5: Fire-fighting measures

### 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

### 5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

### Hazardous Decomposition or By-Products

**Substance**

Carbon monoxide  
Carbon dioxide

**Condition**

During Combustion  
During Combustion

### 5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or

exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

**6.2. Environmental precautions**

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

**6.3. Methods and material for containment and cleaning up**

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with detergent and water. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

**SECTION 7: Handling and storage**

**7.1. Precautions for safe handling**

For industrial or professional use only. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

**7.2. Conditions for safe storage including any incompatibilities**

Store in a well-ventilated place. Keep cool. Protect from sunlight. Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidizing agents.

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

**Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
CYCLOHEXANONE	108-94-1	ACGIH	TWA:20 ppm;STEL:50 ppm	A3: Confirmed animal carcin., SKIN
CYCLOHEXANONE	108-94-1	OSHA	TWA:200 mg/m3(50 ppm)	
2-BUTOXYETHYL ACETATE	112-07-2	ACGIH	TWA:20 ppm	A3: Confirmed animal carcin.

ACGIH : American Conference of Governmental Industrial Hygienists  
 AIHA : American Industrial Hygiene Association  
 CMRG : Chemical Manufacturer's Recommended Guidelines  
 OSHA : United States Department of Labor - Occupational Safety and Health Administration  
 TWA: Time-Weighted-Average  
 STEL: Short Term Exposure Limit  
 CEIL: Ceiling

**8.2. Exposure controls**

**8.2.1. Engineering controls**

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

**8.2.2. Personal protective equipment (PPE)**

**Eye/face protection**

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect Vented Goggles

**Skin/hand protection**

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Butyl Rubber

**Respiratory protection**

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

<b>General Physical Form:</b>	Liquid
<b>Specific Physical Form:</b>	Liquid
<b>Odor, Color, Grade:</b>	Solvent Odor, Cyan Color
<b>Odor threshold</b>	<i>No Data Available</i>
<b>pH</b>	<i>Not Applicable</i>
<b>Melting point</b>	<i>Not Applicable</i>
<b>Boiling Point</b>	> 380 °F
<b>Flash Point</b>	142 °F [ <i>Test Method: Closed Cup</i> ]
<b>Evaporation rate</b>	<i>No Data Available</i>
<b>Flammability (solid, gas)</b>	Not Applicable
<b>Flammable Limits(LEL)</b>	0.88 %
<b>Flammable Limits(UEL)</b>	12.75 %
<b>Vapor Pressure</b>	<i>No Data Available</i>
<b>Vapor Density</b>	<i>No Data Available</i>
<b>Density</b>	0.968 g/ml
<b>Specific Gravity</b>	0.968 [ <i>Ref Std: WATER=1</i> ]
<b>Solubility in Water</b>	Moderate
<b>Solubility- non-water</b>	<i>No Data Available</i>
<b>Partition coefficient: n-octanol/ water</b>	<i>No Data Available</i>
<b>Autoignition temperature</b>	> 600 °F
<b>Decomposition temperature</b>	<i>No Data Available</i>
<b>Viscosity</b>	<i>No Data Available</i>
<b>Volatile Organic Compounds</b>	880 g/l
<b>Percent volatile</b>	85 - 95 %
<b>VOC Less H<sub>2</sub>O &amp; Exempt Solvents</b>	880 g/l

**SECTION 10: Stability and reactivity**

### 10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

### 10.2. Chemical stability

Stable.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

Sparks and/or flames

Heat

### 10.5. Incompatible materials

Strong oxidizing agents

Strong bases

Strong acids

Reducing agents

### 10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

### 11.1. Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation:

Harmful if inhaled.

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

#### Skin Contact:

May be harmful in contact with skin.

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain.

#### Eye Contact:

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

**Ingestion:**

May be harmful if swallowed.

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

**Additional Health Effects:****Prolonged or repeated exposure may cause target organ effects:**

Blood Effects: Signs/symptoms may include generalized weakness and fatigue, skin pallor, changes in blood clotting time, internal bleeding, and/or hemoglobinemia.

**Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE2,000 - 5,000 mg/kg
Overall product	Inhalation-Vapor(4 hr)		No data available; calculated ATE10 - 20 mg/l
Overall product	Ingestion		No data available; calculated ATE2,000 - 5,000 mg/kg
2-BUTOXYETHYL ACETATE	Inhalation-Vapor	official classification	LC50 estimated to be 10 - 20 mg/l
2-BUTOXYETHYL ACETATE	Dermal	Rabbit	LD50 > 4,766 mg/kg
2-BUTOXYETHYL ACETATE	Ingestion	Rat	LD50 2,400 mg/kg
CYCLOHEXANONE	Dermal	Rabbit	LD50 >794, <3160 mg/kg
CYCLOHEXANONE	Inhalation-Vapor (4 hours)	Rat	LC50 > 6.2 mg/l
CYCLOHEXANONE	Ingestion	Rat	LD50 1,296 mg/kg
ETHYL LACTATE	Dermal	Rabbit	LD50 > 5,000 mg/kg
ETHYL LACTATE	Ingestion	Rat	LD50 > 5,000 mg/kg
TRICRESYL PHOSPHATE	Dermal	Rabbit	LD50 > 10,000 mg/kg
TRICRESYL PHOSPHATE	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 5.2 mg/l
TRICRESYL PHOSPHATE	Ingestion	Rat	LD50 > 4,640 mg/kg

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

Name	Species	Value
2-BUTOXYETHYL ACETATE	Rabbit	Minimal irritation
CYCLOHEXANONE	Rabbit	Irritant

**Serious Eye Damage/Irritation**

Name	Species	Value
2-BUTOXYETHYL ACETATE	Rabbit	Mild irritant
CYCLOHEXANONE	Rabbit	Severe irritant

**Skin Sensitization**

Name	Species	Value
CYCLOHEXANONE	Guinea pig	Not classified

**Respiratory Sensitization**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Germ Cell Mutagenicity**

Name	Route	Value
CYCLOHEXANONE	In vivo	Not mutagenic
CYCLOHEXANONE	In Vitro	Some positive data exist, but the data are not sufficient for classification

**Carcinogenicity**

Name	Route	Species	Value
CYCLOHEXANONE	Ingestion	Multiple animal species	Some positive data exist, but the data are not sufficient for classification

**Reproductive Toxicity****Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test Result	Exposure Duration
CYCLOHEXANONE	Inhalation	Not classified for female reproduction	Rat	NOAEL 4 mg/l	2 generation
CYCLOHEXANONE	Inhalation	Not classified for male reproduction	Rat	NOAEL 2 mg/l	2 generation
CYCLOHEXANONE	Ingestion	Not classified for development	Mouse	LOAEL 1,100 mg/kg/day	during organogenesis
CYCLOHEXANONE	Inhalation	Not classified for development	Rat	NOAEL 2 mg/l	2 generation

**Target Organ(s)****Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
2-BUTOXYETHYL ACETATE	Dermal	kidney and/or bladder	Not classified	Rabbit	NOAEL Not available	24 hours
2-BUTOXYETHYL ACETATE	Dermal	blood	Not classified	Rabbit	LOAEL 3,191 mg/kg	24 hours
2-BUTOXYETHYL ACETATE	Dermal	heart   endocrine system   hematopoietic system   liver   nervous system	Not classified	Rabbit	NOAEL 10,000 mg/kg	24 hours
2-BUTOXYETHYL ACETATE	Inhalation	central nervous system depression	Some positive data exist, but the data are not sufficient for classification	similar compounds	NOAEL Not available	
2-BUTOXYETHYL ACETATE	Inhalation	blood   heart   endocrine system   hematopoietic system   liver   nervous system   kidney and/or bladder   respiratory system	Not classified	Multiple animal species	NOAEL 2.6 mg/l	4 hours
2-BUTOXYETHYL ACETATE	Ingestion	blood	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 2,400 mg/kg	not applicable
2-BUTOXYETHYL ACETATE	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 2,400 mg/kg	not applicable
2-BUTOXYETHYL ACETATE	Ingestion	kidney and/or bladder	Not classified	Rat	LOAEL 2,400 mg/kg	not applicable
2-BUTOXYETHYL	Ingestion	heart   liver	Not classified	Rat	NOAEL	not applicable

ACETATE		nervous system			3,000 mg/kg	
CYCLOHEXANONE	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Guinea pig	LOAEL 16.1 mg/l	6 hours
CYCLOHEXANONE	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
CYCLOHEXANONE	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	

#### Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
2-BUTOXYETHYL ACETATE	Inhalation	blood	May cause damage to organs though prolonged or repeated exposure	Multiple animal species	NOAEL 0.7 mg/l	10 months
2-BUTOXYETHYL ACETATE	Inhalation	kidney and/or bladder	Not classified	Multiple animal species	LOAEL 0.7 mg/l	10 months
2-BUTOXYETHYL ACETATE	Inhalation	heart   endocrine system   hematopoietic system   liver   nervous system   respiratory system	Not classified	Multiple animal species	NOAEL 0.7 mg/l	10 months
CYCLOHEXANONE	Inhalation	liver   kidney and/or bladder	Not classified	Rabbit	NOAEL 0.76 mg/l	50 days
CYCLOHEXANONE	Ingestion	liver	Not classified	Mouse	NOAEL 4,800 mg/kg/day	90 days

#### Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

## SECTION 12: Ecological information

#### Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

#### Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

## SECTION 13: Disposal considerations

#### 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): D001 (Ignitable)

**SECTION 14: Transport Information**

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

**SECTION 15: Regulatory information**

**15.1. US Federal Regulations**

Contact 3M for more information.

**EPCRA 311/312 Hazard Classifications:**

**Physical Hazards**

Flammable (gases, aerosols, liquids, or solids)

**Health Hazards**

Acute toxicity

Serious eye damage or eye irritation

Skin Corrosion or Irritation

Specific target organ toxicity (single or repeated exposure)

**Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):**

<b>Ingredient</b>	<b>C.A.S. No</b>	<b>% by Wt</b>
2-BUTOXYETHYL ACETATE (GLYCOL ETHERS)	112-07-2	70 - 90
PIGMENT (Copper compounds except copper phthalocyanine compounds substituted with only H and/or Cl and/or Br (C32R16CuN8, R=any combination of H,Cl,Br))	Trade Secret	1 - 10

**15.2. State Regulations**

Contact 3M for more information.

**15.3. Chemical Inventories**

The components of this product are in compliance with the chemical notification requirements of TSCA.

Contact 3M for more information.

**15.4. International Regulations**

Contact 3M for more information.

**This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.**

**SECTION 16: Other information**

**NFPA Hazard Classification**

**Health: 2 Flammability: 2 Instability: 0 Special Hazards: None**

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

<b>Document Group:</b>	32-1802-1	<b>Version Number:</b>	2.01
<b>Issue Date:</b>	01/08/18	<b>Supersedes Date:</b>	09/23/15

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

**3M USA SDSs are available at [www.3M.com](http://www.3M.com)**